

PATUAKHALI SCIENCE AND TECHNOLOGY UNIVERSITY

COURSE CODE CIT-112

SUBMITTED TO:

Md. Mahbubur Rahman

**Department of Computer Science and Information
Technology**

Faculty of Computer Science and Engineering

SUBMITTED BY:

Md. Sharafat Karim

ID: 2102024,

Registration No: 10151

Faculty of Computer Science and Engineering

Assignment: 08

Table of Contents

1 Write a function exchange to interchange the values of two variables, say x and y. Illustrate the use of this function, in a calling function. Assume that x and y are defined as global variables.....	4
2 Write a function space(x) that can be used to provide a space of x positions between two output numbers. Demonstrate its application.....	5
3 Use recursive function calls to evaluate.....	6
4 Write a function to evaluate the polynomial, using an array variable.....	7
5 Write a function that will generate and print the first n Fibonacci numbers. Test the function for n = 5, 10, and 15.....	9
6 Write a function that will round a floating-point number to an indicated decimal place. For example the number 17.457 would yield the value 17.46 when it is rounded off to two decimal places.....	10
7 Write a function prime that returns 1 if its argument is a prime number and returns zero otherwise.....	11
8 Write a function that will scan a character string passed as an argument and convert all lowercase characters into their uppercase equivalents.....	12
9 Develop a top_down modular program to implement a calculator. The program should request the user to input two numbers and display one of the following as per the desire of the user:.....	13
10 Develop a modular interactive program using functions that reads the values of three sides of a triangle and displays either its area or its perimeter as per the request of the user. Given the three sides a, b and c.....	15
11 Write a function that can be called to find the largest element of an m by n matrix.....	17
12 Write a function that can be called to compute the product of two matrices of size m by n and n by m. The main function provides the values for m and n and two matrices.....	19

13 Design and code an interactive modular program that will use functions to a matrix of m by n size, compute column averages and row averages, and then print the entire matrix with averages shown in respective rows and columns.....	22
14 modular program of array.....	25
15 string operation.....	28
16 Write a program that invokes a function called find() to perform the following tasks:.....	30
17 Design a function locate () that takes two character arrays s1 and s2 and one integer value m as parameters and inserts the string s2 into s1 immediately after the index m . Write a program to test the function using a real-life situation. (Hint: s2 may be a missing word in s1 that represents a line of text).....	31
18 Write a function that takes an integer parameter m representing the month number of the year and returns the corresponding name of the month. For instance, if m = 3, the month is March. Test your program.....	33
19 In preparing the calendar for a year we need to know whether that particular year is leap year or not. Design a function leap() that receives the year as a parameter and returns an appropriate message. What modifications are required if we want to use the function in preparing the actual calendar?.....	34
20 Write a function that receives a floating point value x and returns it as a value rounded to two nearest decimal places. For example, the value 123.4567 will be rounded to 123.46 (Hint: Seek help of one of the math functions available in math library).....	36


1 Write a function exchange to interchange the values of two variables, say x and y. Illustrate the use of this function, in a calling function. Assume that x and y are defined as global variables.

```
#include<stdio.h>

int a = 10, b = 20;

void swap (void)
{
    b = a + b ;
    a = b - a ;
    b = b - a ;
}

int main()
{
    printf("Before swap: a = %d, b = %d\n", a, b);
    swap();
    printf("After swap: a = %d, b = %d\n", a, b);
    return 0;
}
```



```
python-docx/input git:main*
(venv) > cl 1.c
compiling 1
0.05s user 0.04s system 68% cpu 0.132 total

) Before swap: a = 10, b = 20
After swap: a = 20, b = 10


python-docx/input git:main*
(venv) > 
```

2 Write a function space(x) that can be used to provide a space of x positions between two output numbers. Demonstrate its application.

```
#include <stdio.h>
```

```
void space(int x) {  
    for (int i = 0; i < x; i++) {  
        printf(" ");  
    }  
}
```

```
int main() {  
    printf("123");  
    space(3);  
    printf("456\n");  
    return 0;  
}
```



```
python-docx/input git:main*  
(venv) > cl 2.c  
compiling 2  
0.04s user 0.02s system 90% cpu 0.066 total  
  
123    456  
  
python-docx/input git:main*  
(venv) > 
```

The screenshot shows a terminal window with a dark background. The prompt is 'python-docx/input git:main*'. The user enters '(venv) > cl 2.c'. The terminal shows 'compiling 2' and a progress bar. Below the progress bar, it shows '0.04s user 0.02s system 90% cpu 0.066 total'. The output of the program is '123 456'. The prompt is 'python-docx/input git:main*'. The user enters '(venv) > '.


3 Use recursive function calls to evaluate

```
#include <stdio.h>
#include <math.h>

int factorial(int n)
{
    if (n == 1)
        return 1;
    else
        return n * factorial(n - 1);
}

float evaluate(int x, int n, int i)
{
    if (n >= 10)
        return 0;
    else if (i % 2 == 0)
        return -pow(x, n) / factorial(n) + evaluate(x, n + 2, i+1);
    else
        return pow(x, n) / factorial(n) + evaluate(x, n + 2, i+1);
}

int main()
{
    int n;
    scanf("%d", &n);
    printf("%f\n", evaluate(n, 1, 1));
}
```



```
python-docx/input git:main*
(venv) > cl 3.c
compiling 3
0.10s user 0.03s system 98% cpu 0.131 total

) 2
0.909347

python-docx/input git:main*
(venv) > 
```

The screenshot shows a terminal window with a dark background. The prompt is `python-docx/input git:main*`. The user enters `(venv) > cl 3.c`, which triggers a compilation process. The output shows `compiling 3` and timing information: `0.10s user 0.03s system 98% cpu 0.131 total`. Below this, the user enters `) 2`, and the program outputs `0.909347`. The prompt returns to `python-docx/input git:main*`, and the user enters `(venv) >` .

4 Write a function to evaluate the polynomial, using an array variable.

```
// n order polinoial
// Generated with AI

#include <stdio.h>
#include <math.h>

int factorial(int n)
{
    if (n == 1)
        return 1;
    else
        return n * factorial(n - 1);
}

float evaluate(int x, int n, int i)
{
    if (n >= 11)
        return 0;
    else if (i % 2 == 0)
        return -pow(x, n) / factorial(n) + evaluate(x, n + 2, i+1);
    else
        return pow(x, n) / factorial(n) + evaluate(x, n + 2, i+1);
}

int main()
{
    int n;
    scanf("%d", &n);
    printf("%f\n", evaluate(n, 1, 1));
}
```

```
python-docx/input git:main*  
(venv) > cl 4.c  
compiling 4  
0.13s user 0.03s system 86% cpu 0.181 total
```

```
) 1  
0.841471
```


```
python-docx/input git:main*  
(venv) > 
```


5 Write a function that will generate and print the first n Fibonacci numbers. Test the function for n = 5, 10, and 15.

```
#include <stdio.h>
```

```
void fibonacci(int n)
{
    int i, a = 0, b = 1, c;
    for (i = 0; i < n; i++)
    {
        printf("%d ", a);
        c = a + b;
        a = b;
        b = c;
    }
}
```

```
int main()
{
    int n;
    printf("Enter number to generate fibonacci series: ");
    scanf("%d", &n);
    fibonacci(n);
    printf("\n");
}
```



```
python-docx/input git:main*
(venv) > cl 5.c
compiling 5
    0.04s user 0.02s system 97% cpu 0.057 total

) Enter number to generate fibonacci series: 15
0 1 1 2 3 5 8 13 21 34 55 89 144 233 377

python-docx/input git:main*
(venv) > 
```

6 Write a function that will round a floating-point number to an indicated decimal place. For example the number 17.457 would yield the value 17.46 when it is rounded off to two decimal places.


```
#include <stdio.h>

void rounded(float num, int round)
{
    printf("%.*f\n", round, num);
}

int main()
{
    float num;
    int round;

    printf("Enter number to round: ");
    scanf("%f", &num);
    printf("Enter number of decimal places to round to: ");
    scanf("%d", &round);

    rounded(num, round);
}
```



```
(venv) > cl 6.c
compiling 6
0.05s user 0.02s system 94% cpu 0.074 total

Enter number to round: 12.5932
Enter number of decimal places to round to: 2
12.59

python-docx/input git:main* 6s
(venv) > 
```


7 Write a function prime that returns 1 if its argument is a prime number and returns zero otherwise.

```
#include <stdio.h>

int check_prime(int number_to_check_prime)
{
    int i;
    for (i = 2; i < number_to_check_prime; i++)
    {
        if (number_to_check_prime % i == 0)
            return 0;
    }
    return 1;
}

int main()
{
    int number_to_check_prime;
    printf("Enter number to check prime: ");
    scanf("%d", &number_to_check_prime);

    if (check_prime(number_to_check_prime))
        printf("%d is prime\n", number_to_check_prime);
    else
        printf("%d is not prime\n", number_to_check_prime);
}
```



```
python-docx/input git:main* 6s
(venv) > cl 7.c
compiling 7
    0.05s user 0.03s system 73% cpu 0.105 total

) Enter number to check prime: 235
235 is not prime

python-docx/input git:main*
(venv) > 
```


8 Write a function that will scan a character string passed as an argument and convert all lowercase characters into their uppercase equivalents.

```
#include <stdio.h>

void to_uppercase(char *string)
{
    int i;
    for (i = 0; string[i] != '\0'; i++)
    {
        if (string[i] >= 'a' && string[i] <= 'z')
            string[i] -= 32;
    }
}

int main()
{
    char string[100];
    printf("Enter string: ");
    scanf("%s", string);

    to_uppercase(string);
    printf("Your uppercase string : \n");
    printf("%s\n", string);
    return 0;
}
```



```
(venv) > cl 8.c
compiling 8
0.05s user 0.02s system 95% cpu 0.067 total

Enter string: sharafat
Your uppercase string : SHARAFAT

python-docx/input git:main*
(venv) >
```

9 Develop a top_down modular program to implement a calculator. The program should request the user to input two numbers and display one of the following as per the desire of the user:

```
#include <stdio.h>
```

```
int sum(int a, int b)
{
    return a + b;
}
```

```
int difference(int a, int b)
{
    return a - b;
}
```

```
int product(int a, int b)
{
    return a * b;
}
```

```
int division(int a, int b)
{
    return a / b;
}
```

```
int main()
{
    int a, b;
    char operation;


    printf("Enter first number: ");
    scanf("%d", &a);
    printf("Enter second number: ");
    scanf("%d", &b);
```

```

printf("Enter one of the followings: ");
printf("\n(a) Sum of the numbers ");
printf("\n(b) Difference of the numbers ");
printf("\n(c) Product of the numbers ");
printf("\n(d) Division of the numbers ");
printf("\n");

scanf(" %c", &operation);
switch (operation)
{
    case 'a':
        printf("Result -> %d\n", sum(a, b));
        break;
    case 'b':
        printf("Result -> %d\n", difference(a, b));
        break;
    case 'c':
        printf("Result -> %d\n", product(a, b));
        break;
    case 'd':
        printf("Result -> %d\n", division(a, b));
        break;
    default:
        printf("Invalid operation\n");
}
}

```



```

(venv) > cl 9.c
compiling 9
0.05s user 0.01s system 94% cpu 0.060 total

Enter first number: 52
Enter second number: 2
Enter one of the followings:
(a) Sum of the numbers
(b) Difference of the numbers
(c) Product of the numbers
(d) Division of the numbers
c
Result -> 104

```

10 Develop a modular interactive program using functions that reads the values of three sides of a triangle and displays either its area or its perimeter as per the request of the user. Given the three sides a, b and c.

```
#include <stdio.h>
#include <math.h>

float perimeter(float a, float b, float c)
{
    return a + b + c;
}


float area(float a, float b, float c)
{
    float s = (a + b + c) / 2;
    return sqrt((s - a) * (s - b) * (s - c));
}

int main()
{
    float a, b, c;
    char operation;

    printf("Enter first side: ");
    scanf("%f", &a);
    printf("Enter second side: ");
    scanf("%f", &b);
    printf("Enter third side: ");
    scanf("%f", &c);

    printf("Enter one of the followings: ");
    printf("\n(a) Perimeter of the triangle ");
    printf("\n(b) Area of the triangle ");
    printf("\n");
```

```
scanf(" %c", &operation);
switch (operation)
{
    case 'a':
        printf("Result -> %f\n", perimeter(a, b, c));
        break;
    case 'b':
        printf("Result -> %f\n", area(a, b, c));
        break;
    default:
        printf("Invalid operation\n");
}
}
```

A terminal window with a dark background. At the top, it shows the file path 'python-docx/input' and 'git:main*' with a green '6s' indicator. Below that, it shows '(venv) > cl 10.c' with 'English (US)' in parentheses. Then, it says 'compiling 10' followed by '0.11s user 0.02s system 98% cpu 0.133 total'. A horizontal line separates this from the next section. The next section shows the program's prompts: 'Enter first side: 1', 'Enter second side: 2', 'Enter third side: 3', and 'Enter one of the followings:'. Below these are two options: '(a) Perimeter of the triangle' and '(b) Area of the triangle'. The user has entered 'a'. The final line shows 'Result -> 6.000000'.

```
python-docx/input git:main* 6s
(venv) > cl 10.c English (US)
compiling 10
0.11s user 0.02s system 98% cpu 0.133 total

Enter first side: 1
Enter second side: 2
Enter third side: 3
Enter one of the followings:
(a) Perimeter of the triangle
(b) Area of the triangle
a
Result -> 6.000000
```


11 Write a function that can be called to find the largest element of an m by n matrix.

```
#include <stdio.h>

int find_largest(int *matrix, int rows, int cols) {
    int i, j, largest = *matrix;
    for (i = 0; i < rows; i++) {
        for (j = 0; j < cols; j++) {
            if (*(matrix + i * cols + j) > largest) {
                largest = *(matrix + i * cols + j);
            }
        }
    }
    return largest;
}

int main() {
    int m, n, i, j;
    printf("Enter number of rows and columns: ");
    scanf("%d %d", &m, &n);

    int matrix[m][n];
    printf("Enter matrix elements: \n");
    for (i = 0; i < m; i++) {
        for (j = 0; j < n; j++) {
            scanf("%d", &matrix[i][j]);
        }
    }

    int largest = find_largest(&matrix[0][0], m, n);
    printf("Largest element in the matrix is %d\n", largest);

    return 0;
}
```

Result → 6.000000

python-docx/input git:main*

(venv) > cl 11.c

compiling 11

0.07s user 0.02s system 93% cpu 0.088 total

Enter number of rows and columns: 2

2

Enter matrix elements:

1 2

3 4

Largest element in the matrix is 4

12 Write a function that can be called to compute the product of two matrices of size m by n and n by m. The main function provides the values for m and n and two matrices.

```
#include <stdio.h>
```

```
void multiply_matrices(int *matrix_one, int *matrix_two, int m, int n)
```

```
{
```

```
    int i, j, k;
```

```
    int result[m][m];
```

```
    for (i = 0; i < m; i++)
```

```
    {
```

```
        for (j = 0; j < m; j++)
```

```
        {
```

```
            result[i][j] = 0;
```

```
            for (k = 0; k < n; k++)
```

```
            {
```

```
                result[i][j] += *(matrix_one + i * n + k) * *(matrix_two + k * m + j);
```

```
            }
```

```
        }
```

```
    }
```

```
    printf("Resultant matrix: \n");
```

```
    for (i = 0; i < m; i++)
```

```
    {
```

```
        printf("[");
```

```
        for (j = 0; j < m; j++)
```

```
        {
```

```
            printf(" %d ", result[i][j]);
```

```
        }
```

```
        printf("]\n");
```

```
    }
```

```
}
```

```

int main()
{
    int m, n;
    printf("Enter m and n (mxn) (nxm): ");
    scanf("%d %d", &m, &n);

    int matrix_one[m][n];
    int matrix_two[n][m];
    int i, j;

    printf("Enter matrix one elements: \n");
    for (i = 0; i < m; i++)
    {
        for (j = 0; j < n; j++)
        {
            printf("Enter element at (%d, %d): ", i, j);
            scanf("%d", &matrix_one[i][j]);
        }
    }

    printf("Enter matrix two elements: \n");
    for (i = 0; i < n; i++)
    {
        for (j = 0; j < m; j++)
        {
            printf("Enter element at (%d, %d): ", i, j);
            scanf("%d", &matrix_two[i][j]);
        }
    }

    multiply_matrices((int *)matrix_one, (int *)matrix_two, m, n);
}

```

Enter m and n (mxn) (nxm): 2 2

Enter matrix one elements:

Enter element at (0, 0): 1

Enter element at (0, 1): 2

Enter element at (1, 0): 3

Enter element at (1, 1): 4

Enter matrix two elements:

Enter element at (0, 0): 5

Enter element at (0, 1): 6


Enter element at (1, 0): 7

Enter element at (1, 1): 8

Resultant matrix:

[19 22]

[43 50]

Zoom: 

13 Design and code an interactive modular program that will use functions to a matrix of m by n size, compute column averages and row averages, and then print the entire matrix with averages shown in respective rows and columns.

```
#include <stdio.h>
```

```
void input_matrix(int *matrix, int rows, int cols)
{
    int i, j;
    printf("Enter matrix elements: \n");
    for (i = 0; i < rows; i++)
    {
        for (j = 0; j < cols; j++)
            scanf("%d", &matrix[i * cols + j]);
    }
}
```

```
void print_matrix(int *matrix, int rows, int cols)
{
    int i, j;
    printf("Matrix: \n");
    for (i = 0; i < rows; i++)
    {
        printf("[");
        for (j = 0; j < cols; j++)
            printf(" %d ", matrix[i * cols + j]);
        printf("]\n");
    }
}
```

```
void print_row_averages(int *matrix, int rows, int cols)
{
    int i, j;
    printf("Row averages: \n");
```

```

    for (i = 0; i < rows; i++)
    {
        int sum = 0;
        for (j = 0; j < cols; j++)
            sum += matrix[i * cols + j];
        printf("%d\n", sum / cols);
    }
}

void print_col_averages(int *matrix, int rows, int cols)
{
    int i, j;
    printf("Column averages: \n");
    for (i = 0; i < cols; i++)
    {
        int sum = 0;
        for (j = 0; j < rows; j++)
            sum += matrix[j * cols + i];
        printf("%d\n", sum / rows);
    }
}

int main()
{
    int m, n;
    printf("Enter number of rows and columns: ");
    scanf("%d %d", &m, &n);

    int matrix[m][n];
    input_matrix(&matrix[0][0], m, n);

    print_matrix(&matrix[0][0], m, n);
    print_row_averages(&matrix[0][0], m, n);
    print_col_averages(&matrix[0][0], m, n);

    return 0;
}

```

}

```
Enter number of rows and columns: 2 2
Enter matrix elements:
1 2 3 4
Matrix:
[ 1  2 ]
[ 3  4 ]
Row averages:
1
3
Column averages:
2
3
```

Zoom: 

14 modular program of array

```
// Develop a top-down modular program that will perform the following tasks:  
// ""  
// (a) Read two integer arrays with unsorted elements.  
// (b) Sort them in ascending order  
// (c) Merge the sorted arrays  
// (d) Print the sorted list  
// ""  
// Use functions for carrying out each of the above tasks. The main function should  
have only function calls.
```

```
#include <stdio.h>
```

```
void input_array(int *array, int size)  
{  
    int i;  
    printf("Enter array elements: \n");  
    for (i = 0; i < size; i++)  
        scanf("%d", &array[i]);  
}
```

```
void print_array(int *array, int size)  
{  
    int i;  
    printf("Array: \n");  
    for (i = 0; i < size; i++)  
        printf("%d ", array[i]);  
    printf("\n");  
}
```

```
void sort_array(int *array, int size)  
{  
    int i, j;  
    for (i = 0; i < size; i++)
```

```

{
    int min = array[i], min_index = i;
    for (j = i + 1; j < size; j++)
    {
        if (array[j] < min)
        {
            min = array[j];
            min_index = j;
        }
    }
    int temp = array[i];
    array[i] = array[min_index];
    array[min_index] = temp;
}
}

```

```

void merge_arrays(int *array_one, int *array_two, int *result, int size_one, int
size_two)

```

```

{
    int i, j;
    for (i = 0; i < size_one; i++)
        result[i] = array_one[i];
    for (j = 0; j < size_two; j++)
        result[i + j] = array_two[j];
}

```

```

void operations(void)

```

```

{
    int m, n;
    printf("Enter size of array one and array two: ");
    scanf("%d %d", &m, &n);
    int array_one[m], array_two[n];
    input_array(array_one, m);
    input_array(array_two, n);


    sort_array(array_one, m);
    sort_array(array_two, n);
}

```

```
int result[m + n];
merge_arrays(array_one, array_two, result, m, n);
sort_array(result, m+n);

print_array(result, m + n);
}

int main()
{
    operations();
    return 0;
}
```



A terminal window with a dark background. The top line shows the file path 'python-docx/input' in blue, followed by 'git:main*' and '8s' in orange. The next line shows '(venv) > cl 14.c' with 'cl' in green and '14.c' in blue. This is followed by 'compiling 14' and a performance summary: '0.04s user 0.02s system 97% cpu 0.061 total'. A horizontal line separates this from the execution output. The output starts with 'Enter size of array one and array two: 2', followed by '1' on the next line. Then 'Enter array elements:' is shown, followed by '1 2' on the next line. This is repeated: 'Enter array elements:' followed by '2 4'. Finally, 'Array:' is shown, followed by '1 2 2' on the next line. A 'Zoom:' slider is visible in the bottom right corner.

```
python-docx/input git:main* 8s
(venv) > cl 14.c
compiling 14
0.04s user 0.02s system 97% cpu 0.061 total

Enter size of array one and array two: 2
1
Enter array elements:
1 2
Enter array elements:
2 4
Array:
1 2 2
```

15 string operation

```
#include <stdio.h>
```

```
void copy_string(char *one, char *two)
{
    int i;
    for (i=0; one[i] != '\0'; i++)
        two[i] = one[i];
    two[i] = '\0';
    return;
}
```

```
void compare_string(char *one, char *two)
{
    int i;
    for (i=0; one[i] != '\0'; i++)
        if (one[i] != two[i])
            break;
    if (one[i] == '\0' && two[i] == '\0')
        printf("Strings are equal\n");
    else
        printf("Strings are not equal\n");
    return;
}
```

```
void concat_string(char *one, char *two)
{
    int i, j;
    for (i=0; one[i] != '\0'; i++);
    for (j=0; two[j] != '\0'; j++)
        one[i+j] = two[j];
    one[i+j] = '\0';
    return;
}
```

```

int main()
{
    char string_one[100], string_two[200];
    printf("Enter your string: ");
    fgets(string_one, 100, stdin);

    copy_string(string_one, string_two);
    printf("Your second string is: %s", string_two);

    compare_string(string_one, string_two);

    concat_string(string_one, string_two);
    printf("Your concatenated string is: %s", string_one);

    return 0;
}

```

```

Array:
1 2 2

python-docx/input git:main* 10s
(venv) > cl 15.c
compiling 15
0.04s user 0.04s system 66% cpu 0.127 total

Enter your string: hello
Your second string is: hello
Strings are equal
Your concatenated string is: hello
hello

```

16 Write a program that invokes a function called find() to perform the following tasks:


```
#include <stdio.h>
```

```
int char_search_inside_string(char *string, char c)
{
    int i;
    for (i=0; string[i] != '\0'; i++)
        if (string[i] == c)
            return i;
    return -1;
}
```

```
int main()
{
    char string[100], c;
    printf("Enter your string: ");
    fgets(string, 100, stdin);
    printf("Enter your character: ");
    scanf("%c", &c);

    int index = char_search_inside_string(string, c);
    if (index == -1)
        printf("Character not found\n");
    else
        printf("Character found at index %d\n", index);
```

```
return
0;
}
```



The terminal screenshot shows the following output and commands:

```
Your second string is: hello
Strings are equal
Your concatenated string is: hello
hello

python-docx/input git:main*
(venv) > cl 16.c
compiling 16
0.05s user 0.02s system 77% cpu 0.085 total

Enter your string: hello
Enter your character: e
Character found at index 1
```

17 Design a function locate () that takes two character arrays s1 and s2 and one integer value m as parameters and inserts the string s2 into s1 immediately after the index m . Write a program to test the function using a real-life situation. (Hint: s2 may be a missing word in s1 that represents a line of text).

```
#include <stdio.h>

char* locate(char *s1, char *s2, int m)
{
    int i, j;
    static char temp[100];
    for (i=0; i< m; i++)
        temp[i] = s1[i];
    for (j=0; s2[j] != '\0'; j++)
        temp[i+j] = s2[j];
    for (; s1[i] != '\0'; i++)
        temp[i+j] = s1[i];
    return temp;
}

int main()
{
    char s1[100], s2[100];
    int m;
    printf("Enter your string: ");
    scanf("%[^\n]s", s1);

    printf("Enter your string: ");
    scanf(" %[^\n]s", s2);

    printf("Enter your index: ");
    scanf("%d", &m);

    char *updated_string;
```

```
updated_string = locate(s1, s2, m);  
printf("Your string is: %s", updated_string);  
  
return 0;  
}
```

compiler didn't create an executable file!

python-docx/input git:main*

(venv) > cl 17.c

compiling 17

0.05s user 0.01s system 98% cpu 0.068 total

Enter your string: hello

Enter your string: oka

Enter your index: 2

Your string is: heokallo%

18 Write a function that takes an integer parameter *m* representing the month number of the year and returns the corresponding name of the month. For instance, if *m* = 3, the month is March. Test your program.

```
#include <stdio.h>
```

```
char *month_name(int m)
```

```
{
```

```
    char *months[] = {
```

```
        "January", "February", "March", "April", "May", "June", "July", "August",
```

```
        "September", "October", "November", "December"};
```

```
    return months[m - 1];
```

```
}
```

```
int main()
```

```
{
```

```
    int m;
```

```
    printf("Enter month number: ");
```

```
    scanf("%d", &m);
```

```
    printf("Month name: %s\n", month_name(m));
```

```
    return 0;
```

```
}
```

```
18.c:7:33: warning: ISO C++ forbids converting  
gs]
```

```
7 |         "September", "October", "Novem  
|                                         ^~~~~~
```

```
18.c:7:45: warning: ISO C++ forbids converting  
gs]
```

```
7 |         "September", "October", "Novem  
|                                         ^~~~~~
```

```
0.05s user 0.02s system 76% cpu 0.092 total
```

```
Enter month number: 2
```

```
Month name: February
```

19 In preparing the calendar for a year we need to know whether that particular year is leap year or not. Design a function leap() that receives the year as a parameter and returns an appropriate message. What modifications are required if we want to use the function in preparing the actual calendar?

```
#include <stdio.h>

int leap(int year)
{
    if (year % 400 == 0)
        return 1;
    else if (year % 100 == 0)
        return 0;
    else if (year % 4 == 0)
        return 1;
    else
        return 0;
}

int main()
{
    int year;

    printf("Enter year: ");
    scanf("%d", &year);

    if (leap(year))
        printf("%d is a leap year.\n", year);
    else
        printf("%d is not a leap year.\n", year);

    return 0;
}
```

0.05s user 0.02s system 76% cpu 0.092 total

Enter month number: 2

Month name: February

python-docx/input git:main*


(venv) > cl 19.c

compiling 19

0.05s user 0.02s system 73% cpu 0.097 total

Enter year: 2002

2002 is not a leap year.

Zoom: 

20 Write a function that receives a floating point value x and returns it as a value rounded to two nearest decimal places. For example, the value 123.4567 will be rounded to 123.46 (Hint: Seek help of one of the math functions available in math library).

```
#include <stdio.h>
#include <math.h>


double round2(double x)
{
    return round(x * 100) / 100;
}

int main()
{
    double x;

    printf("Enter a floating point value: ");
    scanf("%lf", &x);

    printf("Rounded value: %.2lf\n", round2(x));

    return 0;
}
```



```
0.11s user 0.04s system 88% cpu 0.169 total

Enter a floating point value: 12.6549
Rounded value: 12.65

python-docx/input git:main*
(venv) > cl 20.c
compiling 20
0.11s user 0.02s system 96% cpu 0.140 total

Enter a floating point value: 12.6666
Rounded value: 12.67
```