

PATUAKHALI SCIENCE AND TECHNOLOGY UNIVERSITY

COURSE CODE CIT-112

SUBMITTED TO:

Md. Mahbubur Rahman

**Department of Computer Science and Information
Technology**

Faculty of Computer Science and Engineering

SUBMITTED BY:

Md. Sharafat Karim

ID: 2102024,

Registration No: 10151

Faculty of Computer Science and Engineering

Assignment: 07

Table of Contents

1 Write a program, which reads your name from the keyboard and outputs a list of ASCII codes, which represent your name.....	4
2 Write a program to do string processing.....	5
.....	5
3 Write a program to extract a portion of a character string and print the extracted string. Assume that m characters are extracted, starting with the nth character.....	7
4 Write a program which will read a text and count all occurrences of a particular word.....	9
5 Write a program which will read a string and rewrite it in the alphabetical order. For example, the word STRING should be written as GINRST.....	11
6 Write a program to replace a particular word by another word in a given string. For example, the word “PASCAL” should be replaced by “C” in the text “It is good to program in PASCAL language.”	13
8 Write a program that reads a string from the keyboard and determines whether the string is a palindrome or not. (A string is a palindrome if it can be read from left and right with the same meaning. For example, Madam and Anna are palindrome strings. Ignore capitalization).....	16
9 Write program that reads the cost of an item in the form RRRR.PP (Where RRRR denotes Rupees and PP denotes Paise) and converts the value to a string of words that expresses the numeric value in words. For example, if we input 125.75, the output should be “ONE HUNDRED TWENTY FIVE AND PAISE SEVENTY FIVE”	18
10 Develop a program that will read and store the details of a list of students in the format.....	22
11 Write a program to read two strings and compare them using the function strcmp() and print a message that the first string is equal, less, or greater than the second one.....	26


12 Write a program to read a line of text from the keyboard and print out the number of occurrences of a given substring using the function strstr ().....	28
13 Write a program that will copy m consecutive characters from a string s1 beginning at position n into another string s2.....	30
14 Write a program to create a directory of students with roll numbers. The program should display the roll number for a specified name and vice-versa.....	32
15 Given a string make a pyramid out of it.....	35
16 Write a C program to compare two strings without using any string function..	37
17 Write a C program to find the largest and smallest sized word in a string.....	39
18 Write a C program to replace all the white spaces in a string with double white spaces.....	42
19 Write a C program to enter multiple strings and display them in lexicographical order.....	44
20 Write a C program to concatenate two strings without using any string function.....	46

1 Write a program, which reads your name from the keyboard and outputs a list of ASCII codes, which represent your name.

```
#include<stdio.h>

int main()
{
    char name[32];
    scanf("%s", name);

    for (int i=0; name[i] != '\0'; i++)
    {
        printf("%c - %d\n", name[i], name[i]);
    }
}
```



2 Write a program to do string processing

```
#include <stdio.h>
#include <string.h>

int main()
{
    char answer[64];
    int attemp = 3;
    while (attemp-->0)
    {
        printf("Who is the inventor of C? \n");
        scanf("%s", answer);
        if (strcmp(answer, "Dennis Ritchie") == 0)
        {
            printf("Good\n");
            break;
        }
        else
        {
            printf("try again\nCorrect answer: Dennis Ritchie\n");
        }
    }
}
```

```
sharafat karim
s - 115
h - 104
a - 97
r - 114
a - 97
f - 102
a - 97
t - 116
- 32
k - 107
a - 97
r - 114
i - 105
m - 109

python-docx/input git:main* 33s
(venv) > cl 2.c
compiling 2
0.06s user 0.03s system 73% cpu 0.114 total

Who is the inventor of C?
Dennis Ritchie
Good

python-docx/input git:main* 12s
(venv) > 
```

3 Write a program to extract a portion of a character string and print the extracted string. Assume that m characters are extracted, starting with the nth character.

```
#include<stdio.h>

#define init 2
#define end 6

int main()
{
    char string[32], modified_string[32];
    scanf("%[^\\n]", string);

    for (int i= init-1; i < end; i++)
    {
        modified_string[i-init+1] = string[i];
    }

    printf("%s\\n", modified_string);
}
```

t - 116
- 32
k - 107
a - 97
r - 114
i - 105
m - 109

python-docx/input git:main* 33s
(venv) > cl 2.c
compiling 2
0.06s user 0.03s system 73% cpu 0.114 total

Who is the inventor of C?
Dennis Ritchie
Good

python-docx/input git:main* 12s
(venv) > cl 3.c
compiling 3
0.05s user 0.03s system 66% cpu 0.111 total

Hello world, how is it going?
ello

python-docx/input git:main* 15s
(venv) >

4 Write a program which will read a text and count all occurrences of a particular word.

```
#include<stdio.h>

#define occurrence 'a'

int main()
{
    char string[32];
    scanf("%[^\\n]", string);
    int i=0, count = 0;
    while (string[i] != '\\0')
    {
        if (string[i++] == occurrence)
        {
            count++;
        }
    }
    printf("Total occurrence of %c = %d\\n", occurrence, count);
}
```

input : 4 — Konsole

```
(venv) > cl 2.c
compiling 2
0.06s user 0.03s system 73% cpu 0.114 total
```

```
Who is the inventor of C?
Dennis Ritchie
Good
```

python-docx/input git:main* 12s

```
(venv) > cl 3.c
compiling 3
0.05s user 0.03s system 66% cpu 0.111 total
```

```
Hello world, how is it going?
ello
```

python-docx/input git:main* 15s

```
(venv) > cl 4.c
compiling 4
0.04s user 0.02s system 93% cpu 0.068 total
```

```
hi there, I'm gonna find all occurrences
Total occurrence of a = 3
```

python-docx/input git:main* 10s

```
(venv) > 
```

5 Write a program which will read a string and rewrite it in the alphabetical order. For example, the word STRING should be written as GINRST.

```
#include<stdio.h>
#include<string.h>

int main()
{
    char name[32];
    scanf("%s", name);

    int size = strlen(name);
    int i, j;
    for (i=0; i < size; i++)
    {
        for (j=0; j < size-i-1; j++)
        {
            if (name[j] > name[j+1])
            {
                char temp = name[j];
                name[j] = name[j+1];
                name[j+1] = temp;
            }
        }
    }
    printf("%s", name);
}
```

input : zsh — Konsole

python-docx/input git:main* 15s

(venv) > cl 4.c

compiling 4

0.04s user 0.02s system 93% cpu 0.068 total

hi there, I'm gonna find all occurances
Total occurrence of a = 3

python-docx/input git:main* 10s

(venv) > cl 5.c

compiling 5

0.05s user 0.03s system 75% cpu 0.105 total

alphabetic order
◆◆ aabcdeehiloprtr

python-docx/input git:main* 45s

(venv) > cl 5.c

compiling 5

0.04s user 0.02s system 98% cpu 0.060 total

STRING
GINRST

python-docx/input git:main*

(venv) >

6 Write a program to replace a particular word by another word in a given string. For example, the word “PASCAL” should be replaced by “C” in the text “It is good to program in PASCAL language.”

```
#include<stdio.h>
#include<string.h>

int main()
{
    char str[64], modified_str[64];
    printf("Enter the string: ");
    scanf("%[^\n]", str);
    char replace_from[16];
    printf("Enter the string to replace: ");
    scanf("%s", replace_from);
    char replace_with[16];
    printf("Enter the string to replace with: ");
    scanf("%s", replace_with);
    int size = strlen(str);

    printf("-----\n");

    int i, temp;
    for (i=0, temp=0; i<size; i++)
    {
        if (str[i] == replace_from[0])
        {
            for (int j=0; j<strlen(replace_from);j++)
            {
                if (str[i-j] != replace_from[j])
                    break;
            }
            else
            {
                for (int k=0; k<strlen(replace_with); k++)
                {
```

```
        modified_str[temp++] = replace_with[k];
        i += strlen(replace_from);
    }
}
}
}
modified_str[temp++] = str[i];
}
modified_str[temp] = '\0';

printf("%s\n", str);
printf("%s", modified_str);
}
```

```
input : 6 — Konsole

1 alphabetic order
1 *** aabcdeehiloprtr

python-docx/input git:main* 45s
(venv) > cl 5.c
compiling 5
0.04s user 0.02s system 98% cpu 0.060 total

STRING
GINRST

python-docx/input git:main*
(venv) > cl 6.c
compiling 6
0.05s user 0.03s system 73% cpu 0.114 total

Enter the string: PASCAL
Enter the string to replace: C
Enter the string to replace with: K

PASCAL
PASKAL%

python-docx/input git:main* 16s
(venv) > 
```

8 Write a program that reads a string from the keyboard and determines whether the string is a palindrome or not. (A string is a palindrome if it can be read from left and right with the same meaning. For example, Madam and Anna are palindrome strings. Ignore capitalization).

```
#include<stdio.h>
#include<string.h>

int main()
{
    char string[64];
    scanf("%[^\n]", string);
    int size = strlen(string);

    for (int i=0, j=size-1; i < size/2; i++, j--)
    {
        if (string[i] != string[j])
        {
            printf("Not a palindrome");
            return 0;
        }
    }
    printf("A palindrome");
    return 0;
}
```



```
input : zsh — Konsole

STRING
GINRST

python-docx/input git:main*
(venv) > cl 6.c
compiling 6
0.05s user 0.03s system 73% cpu 0.114 total

Enter the string: PASCAL
Enter the string to replace: C
Enter the string to replace with: K

PASCAL
PASKAL%

python-docx/input git:main* 16s
(venv) > cl 8.c
compiling 8
0.04s user 0.03s system 73% cpu 0.084 total

eye
A palindrome%

python-docx/input git:main* 7s
(venv) >
```

9 Write program that reads the cost of an item in the form RRRR.PP (Where RRRR denotes Rupees and PP denotes Paise) and converts the value to a string of words that expresses the numeric value in words. For example, if we input 125.75, the output should be “ONE HUNDRED TWENTY FIVE AND PAISE SEVENTY FIVE”.

// Write program that reads the cost of an item in the form RRRR.PP (Where RRRR denotes Rupees and PP denotes Paise) and converts the value to a string of words that expresses the numeric value in words.

// For example, if we input 125.75, the output should be “ONE HUNDRED TWENTY FIVE AND PAISE SEVENTY FIVE”.

```
#include<stdio.h>
```

```
#include<string.h>
```

```
char* get_first_nine_number(int num)
```

```
{
```

```
    switch(num)
```

```
    {
```

```
        case 0: return "ZERO";
```

```
        case 1: return "ONE";
```

```
        case 2: return "TWO";
```

```
        case 3: return "THREE";
```

```
        case 4: return "FOUR";
```

```
        case 5: return "FIVE";
```

```
        case 6: return "SIX";
```

```
        case 7: return "SEVEN";
```

```
        case 8: return "EIGHT";
```

```
        case 9: return "NINE";
```

```
        case 10: return "TEN";
```

```
        case 11: return "ELEVEN";
```

```
        case 12: return "TWELVE";
```

```
        case 13: return "THIRTEEN";
```

```
        case 14: return "FOURTEEN";
```

```
        case 15: return "FIFTEEN";
```

```

        case 16: return "SIXTEEN";
        case 17: return "SEVENTEEN";
        case 18: return "EIGHTEEN";
        case 19: return "NINETEEN";
        case 20: return "TWENTY";
        case 30: return "THIRTY";
        case 40: return "FOURTY";
        case 50: return "FIFTY";
        case 60: return "SIXTY";
        case 70: return "SEVENTY";
        case 80: return "EIGHTY";
        case 90: return "NINETY";
    }
}

```

```

char* get_number(int num)
{
    char string[50];
    if (num <= 20 )
        return get_first_nine_number(num);
    else
    {
        strcpy(string, "");
        strcat(string, get_first_nine_number((num/10)*10));
        strcat(string, " ");
        strcat(string, get_first_nine_number(num%10));
        char *string2 = string;
        return(string2);
    }
}

```

```

int main()
{
    float cost;
    printf("Enter the cost: ");
    scanf("%f", &cost);
}

```

```

int rupees = (int)cost;
int paise = (int)((cost - rupees) * 100);


char rupees_string[100];
strcpy(rupees_string, "");


if ( rupees >= 1000 )
{
    int thousands = rupees / 1000;
    strcat(strcat(rupees_string, get_number(thousands)), " THOUSAND ");
    rupees = rupees % 1000;
}
if ( rupees >= 100 )
{
    int hundreds = rupees / 100;
    strcat(strcat(rupees_string, get_number(hundreds)), " HUNDRED ");
    rupees = rupees % 100;
}
if ( rupees >= 1 )
{
    strcat(strcat(rupees_string, get_number(rupees)), " AND PAISE ");
}
if ( paise >= 1 )
{
    strcat(rupees_string, get_number(paise));
}


printf("%s", rupees_string);
printf("\n%d", rupees);
}

```

```
input : zsh — Konsole
9.c:35:25: warning: ISO C++ forbids converting a string constant
gs]
35 |         case 60: return "SIXTY";
9.c:36:25: warning: ISO C++ forbids converting a string constant
gs]
36 |         case 70: return "SEVENTY";
9.c:37:25: warning: ISO C++ forbids converting a string constant
gs]
37 |         case 80: return "EIGHTY";
9.c:38:25: warning: ISO C++ forbids converting a string constant
gs]
38 |         case 90: return "NINETY";
9.c:40:1: warning: control reaches end of non-void function [-Wreturn-type]
40 |     }
0.05s user 0.02s system 79% cpu 0.083 total

Enter the cost: 123
ONE HUNDRED TWENTY THREE AND PAISE
23%

python-docx/input git:main*
(venv) >
```

10 Develop a program that will read and store the details of a list of students in the format

```
#include<stdio.h>

struct student
{
    int roll_no;
    char name[50];
    int marks;
};

void sorting_array_with_index(int main[], int sorted_index[])
{
    int n = sizeof(main)/sizeof(main[0]);

    for (int i = 0; i < n; i++)
    {
        sorted_index[i] = i;
    }

    for (int i = 0; i < n; i++)
    {
        for (int j = i; j < n-1; j++)
        {
            if (main[sorted_index[j]] > main[sorted_index[j+1]])
            {
                int temp = sorted_index[j];
                sorted_index[j] = sorted_index[j+1];
                sorted_index[j+1] = temp;
            }
        }
    }
}
```

```

int main()
{
    int n;
    printf("Enter the number of students: ");
    scanf("%d", &n);
    struct student students[n];
    for (int i = 0; i < n; i++)
    {
        printf("Enter the roll number of student %d: ", i+1);
        scanf("%d", &students[i].roll_no);
        printf("Enter the name of student %d: ", i+1);
        scanf("%s", students[i].name);
        printf("Enter the marks of student %d: ", i+1);
        scanf("%d", &students[i].marks);
    }

    printf("\n\n");
    printf("Table of students (alphabetic list)\n");
    printf("Roll No\t\tName\t\tMarks\n");
    for (int i = 0; i < n; i++)
    {
        printf("%d\t\t%s\t\t%d\n", students[i].roll_no, students[i].name,
students[i].marks);
    }

    printf("\n\n");
    printf("Table of students (sorted on roll numbers)\n");
    int sorted_roll_no_index[n];
    int students_roll_no[n];
    for (int i = 0; i < n; i++)
    {
        students_roll_no[i] = students[i].roll_no;
    }
    sorting_array_with_index(students_roll_no, sorted_roll_no_index);
    printf("Roll No\t\tName\t\tMarks\n");
    for (int i = 0; i < n; i++)
    {

```

```

        printf("%d\t\t%s\t\t%d\n", students[sorted_roll_no_index[i]].roll_no,
students[sorted_roll_no_index[i]].name, students[sorted_roll_no_index[i]].marks);
    }
    printf("\n\n");
    printf("Table of students (sorted on marks)\n");
    int sorted_marks_index[n];
    int students_marks[n];
    for (int i = 0; i < n; i++)
    {
        students_marks[i] = students[i].marks;
    }
    sorting_array_with_index(students_marks, sorted_marks_index);
    printf("Roll No\t\tName\t\tMarks\n");
    for (int i = 0; i < n; i++)
    {
        printf("%d\t\t%s\t\t%d\n", students[sorted_marks_index[i]].roll_no,
students[sorted_marks_index[i]].name, students[sorted_marks_index[i]].marks);
    }
    printf("\n\n");
    return 0;
}

```


input : zsh — Konsole

```
Enter the roll number of student 1: 1
Enter the name of student 1: sharafat
Enter the marks of student 1: 10
Enter the roll number of student 2: 2
Enter the name of student 2: monir
Enter the marks of student 2: 100
```

Table of students (alphabetic list)

Roll No	Name	Marks
1	sharafat	10
2	monir	100

Table of students (sorted on roll numbers)

Roll No	Name	Marks
1	sharafat	10
2	monir	100

Table of students (sorted on marks)

Roll No	Name	Marks
1	sharafat	10
2	monir	100

python-docx/input git:main* 58s
(venv) >

11 Write a program to read two strings and compare them using the function `strncmp()` and print a message that the first string is equal, less, or greater than the second one.

```
#include<stdio.h>
#include<string.h>

int main()
{
    char str1[100], str2[100];
    printf("Enter the first string: ");
    scanf("%s", str1);
    printf("Enter the second string: ");
    scanf("%s", str2);

    int result = strncmp(str1, str2, 100);
    if (result == 0)
    {
        printf("The first string is equal to the second one.\n");
    }
    else if (result < 0)
    {
        printf("The first string is less than the second one.\n");
    }
    else
    {
        printf("The first string is greater than the second one.\n");
    }
}
```

```
input : zsh — Konsole

1 sharafat 100 10
2 monir 100 10

Table of students (sorted on roll numbers)
Roll No      Name      Marks
1            sharafat    10
2            monir      100

Table of students (sorted on marks)
Roll No      Name      Marks
1            sharafat    10
2            monir      100

python-docx/input git:main* 58s
(venv) > cl 11.c
compiling 11
0.06s user 0.03s system 83% cpu 0.101 total

Enter the first string: hello
Enter the second string: hollo
The first string is less than the second one.

python-docx/input git:main* 6s
(venv) > 
```

12 Write a program to read a line of text from the keyboard and print out the number of occurrences of a given substring using the function strstr ().

```
#include <stdio.h>
#include <string.h>

int main()
{
    char str[100], substr[100];
    printf("Enter the string: ");
    scanf("%[^\n]%*c", str);
    printf("Enter the substring: ");
    scanf("%[^\n]%*c", substr);

    int count = 0;
    char *ptr = strstr(str, substr);
    printf("%s\n", ptr+1);
    while (ptr != NULL)
    {
        count++;
        ptr = strstr(ptr+1, substr);
    }

    printf("The substring %s occurs %d times in the string %s.\n", substr, count, str);
}
```

```
input : zsh — Konsole

Roll No      Name      Marks
1            sharafat  10
2            monir     100

python-docx/input git:main* 58s
(venv) > cl 11.c
compiling 11
0.06s user 0.03s system 83% cpu 0.101 total

Enter the first string: hello
Enter the second string: hollo
The first string is less than the second one.

python-docx/input git:main* 6s
(venv) > cl 12.c
compiling 12
0.04s user 0.03s system 78% cpu 0.091 total

Enter the string: hello
Enter the substring: el
llo
The substring el occurs 1 times in the string hello.

python-docx/input git:main* 6s
(venv) > 
```

13 Write a program that will copy m consecutive characters from a string s1 beginning at position n into another string s2.

```
#include<stdio.h>
#include<string.h>

int main()
{
    char s1[100], s2[100];
    int m, n;
    printf("Enter the string: ");
    scanf("%[^\\n]*c", s1);
    printf("Enter the new string: ");
    scanf("%[^\\n]*c", s2);
    printf("Enter the value of m: ");
    scanf("%d", &m);
    printf("Enter the value of n: ");
    scanf("%d", &n);

    strncpy(s2+n, s1, m);
    printf("The string s2 is: %s\\n", s2);
}
```

```
Enter the first string: hello
Enter the second string: hollo
The first string is less than the second one.
```

```
python-docx/input git:main* 6s
(venv) > cl 12.c
compiling 12
0.04s user 0.03s system 78% cpu 0.091 total
```

```
Enter the string: hello
Enter the substring: el
llo
The substring el occurs 1 times in the string hello.
```

```
python-docx/input git:main* 6s
(venv) > cl 13.c
compiling 13
0.04s user 0.03s system 78% cpu 0.083 total
```

```
Enter the string: sharafat
Enter the new string: karim
Enter the value of m: 3
Enter the value of n: 4
The string s2 is: karisha
```

```
python-docx/input git:main* 9s
(venv) > 
```

14 Write a program to create a directory of students with roll numbers. The program should display the roll number for a specified name and vice-versa.

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>

struct student
{
    int roll_no;
    char name[50];
};

int main()
{
    struct student students[100];
    int n;
    printf("Enter the number of students: ");
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
    {
        printf("Enter the roll number of student %d: ", i+1);
        scanf("%d", &students[i].roll_no);
        printf("Enter the name of student %d: ", i+1);
        scanf("%s", students[i].name);
    }

    printf("\n\n");
    printf("Type student name or roll number to search: \n");
    char search[50];
    scanf("%s", search);

    int found = 0;
```



```
for (int i = 0; i < n; i++)
{
    if (students[i].roll_no == atoi(search) || strcmp(students[i].name, search) == 0)
    {
        printf("Roll No: %d\n", students[i].roll_no);
        printf("Name: %s\n", students[i].name);
        found = 1;
        break;
    }
}
}
```

```
input : zsh — Konsole
0.04s user 0.03s system 78% cpu 0.083 total

1 Enter the string: sharafat
Enter the new string: karim
Enter the value of m: 3
Enter the value of n: 4
The string s2 is: karisha

python-docx/input git:main* 9s
(venv) > cl 14.c
compiling 14
0.05s user 0.02s system 74% cpu 0.094 total

Enter the number of students: 2
Enter the roll number of student 1: 1
Enter the name of student 1: somehting
Enter the roll number of student 2: 2
Enter the name of student 2: interesting

Type student name or roll number to search:
2
Roll No: 2
Name: interesting

python-docx/input git:main* 19s
(venv) > 
```

15 Given a string make a pyramid out of it

```
// Given a string
// ""
//      char str [ ] = "123456789" ;
// ""
// Write a program that displays the following:
// ""
//      1
//      2 3 2
//      3 4 5 4 3
//      4 5 6 7 6 5 4
//      5 6 7 8 9 8 7 6 5
// ""
```

```
#include <stdio.h>
```

```
int main()
{
    char str[] = "123456789";
    int n = 5;
    for (int i = 0; i < n; i++)
    {
        for (int j = n-i; j > 0; j--)
        {
            printf(" ");
        }
        for (int j = i+1; j < 2*i+2; j++)
        {
            printf("%c ", str[j-1]);
        }
        for (int j = 2*i; j > i; j--)
        {
            printf("%c ", str[j-1]);
        }
        printf("\n");
    }
}
```

```
}  
}
```

```
input: zsh — Konsole  
0.05s user 0.02s system 74% cpu 0.094 total  
1 Enter the number of students: 2  
Enter the roll number of student 1: 1  
Enter the name of student 1: somehting  
Enter the roll number of student 2: 2  
Enter the name of student 2: interesting  
  
Type student name or roll number to search:  
2  
Roll No: 2  
Name: interesting  
  
python-docx/input git:main* 19s  
(venv) > cl 15.c  
compiling 15  
0.04s user 0.02s system 77% cpu 0.074 total  
  
1  
2 3 2  
3 4 5 4 3  
4 5 6 7 6 5 4  
5 6 7 8 9 8 7 6 5  
  
python-docx/input git:main*  
(venv) > 
```

16 Write a C program to compare two strings without using any string function.

// Write a C program to compare two strings without using any string function.

```
#include <stdio.h>

int main()
{
    char str1[100], str2[100];
    printf("Enter the first string: ");
    scanf("%[^\n]%*c", str1);
    printf("Enter the second string: ");
    scanf("%[^\n]%*c", str2);

    int i = 0;
    while (str1[i] != '\0' && str2[i] != '\0')
    {
        if (str1[i] != str2[i])
        {
            printf("The strings are not equal.\n");
            return 0;
        }
        i++;
    }
    if (str1[i] == '\0' && str2[i] == '\0')
    {
        printf("The strings are equal.\n");
    }
    else
    {
        printf("The strings are not equal.\n");
    }
}
```

input : zsh — Konsole

Type student name or roll number to search:

2

Roll No: 2

Name: interesting

python-docx/input git:main* 19s

(venv) > cl 15.c

compiling 15

0.04s user 0.02s system 77% cpu 0.074 total

```
      1
     2 3 2
    3 4 5 4 3
   4 5 6 7 6 5 4
  5 6 7 8 9 8 7 6 5
```

python-docx/input git:main*

(venv) > cl 16.c

compiling 16

0.04s user 0.02s system 87% cpu 0.067 total

Enter the first string: helo

Enter the second string: hello

The strings are not equal.

python-docx/input git:main*

(venv) >

17 Write a C program to find the largest and smallest sized word in a string.

// Write a C program to find the largest and smallest sized word in a string.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    char str[100];
```

```
    printf("Enter the string: ");
```

```
    scanf("%[^\n]%*c", str);
```

```
    int i = 0;
```

```
    int min = 100, max = 0;
```

```
    int min_index = 0, max_index = 0;
```

```
    while (str[i] != '\0')
```

```
    {
```

```
        int count = 0;
```

```
        while (str[i] != ' ' && str[i] != '\0')
```

```
        {
```

```
            count++;
```

```
            i++;
```

```
        }
```

```
        if (count < min)
```

```
        {
```

```
            min = count;
```

```
            min_index = i - count;
```

```
        }
```

```
        if (count > max)
```

```
        {
```

```
            max = count;
```

```
            max_index = i - count;
```

```
        }
```

```
        if (str[i] == '\0')
```

```
    {  
        break;  
    }  
    i++;  
}  
  
printf("The smallest word is: ");  
for (int j = min_index; j < min_index + min; j++)  
{  
    printf("%c", str[j]);  
}  
printf("\n");  
  
printf("The largest word is: ");  
for (int j = max_index; j < max_index + max; j++)  
{  
    printf("%c", str[j]);  
}  
}
```



```
python-docx/input git:main*
(venv) > cl 16.c
compiling 16
0.04s user 0.02s system 87% cpu 0.067 total

Enter the first string: helo
Enter the second string: hello
The strings are not equal.

python-docx/input git:main*
(venv) > cl 17.c
compiling 17
0.05s user 0.03s system 80% cpu 0.091 total

Enter the string: hi there, sharafat
The smallest word is: hi
The largest word is: sharafat%

python-docx/input git:main* 6s
(venv) >
```

18 Write a C program to replace all the white spaces in a string with double white spaces.

// Write a C program to replace all the white spaces in a string with double white spaces.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    char str[100];
```

```
    printf("Enter the string: ");
```

```
    scanf("%[^\n]%*c", str);
```

```
    char white_space_doubled_str[200];
```

```
    int i = 0, j = 0;
```

```
    while (str[i] != '\0')
```

```
    {
```

```
        if (str[i] == ' ')
```

```
        {
```

```
            white_space_doubled_str[j] = ' ';
```

```
            white_space_doubled_str[j+1] = ' ';
```

```
            j += 2;
```

```
        }
```

```
    else
```

```
    {
```

```
        white_space_doubled_str[j] = str[i];
```

```
        j++;
```

```
    }
```


```
    i++;
```

```
}
```

```
white_space_doubled_str[j] = '\0';
```

```
printf("The string with double white spaces is: %s\n", white_space_doubled_str);
```

```
return 0;  
}
```



A terminal window titled "input : zsh — Konsole" showing the compilation and execution of three C programs. The first program (16.c) compares two strings. The second (17.c) finds the smallest and largest words in a sentence. The third (18.c) counts double white spaces in a string. Each program is compiled with 'cc' and its execution is shown with user input.

```
compiling 16  
0.04s user 0.02s system 87% cpu 0.067 total  
  
Enter the first string: helo  
Enter the second string: hello  
The strings are not equal.  
  
python-docx/input git:main*  
(venv) > cl 17.c  
compiling 17  
0.05s user 0.03s system 80% cpu 0.091 total  
  
Enter the string: hi there, sharafat  
The smallest word is: hi  
The largest word is: sharafat%  
  
python-docx/input git:main* 6s  
(venv) > cl 18.c  
compiling 18  
0.04s user 0.02s system 80% cpu 0.083 total  
  
Enter the string: hello world  
The string with double white spaces is: hello  world  
  
python-docx/input git:main*  
(venv) > 
```

19 Write a C program to enter multiple strings and display them in lexicographical order.

// Write a C program to enter multiple strings and display them in lexicographical order.

```
#include <stdio.h>
#include <string.h>

int main()
{
    int n;
    printf("Enter the number of strings: ");
    scanf("%d%c", &n);
    char str[n][100];
    for (int i = 0; i < n; i++)
    {
        printf("Enter the string: ");
        scanf("%[^\n]*c", &str[i]);
    }

    for (int i = 0; i < n; i++)
    {
        for (int j = i+1; j < n; j++)
        {
            if (strcmp(str[i], str[j]) > 0)
            {
                char temp[100];
                strcpy(temp, str[i]);
                strcpy(str[i], str[j]);
                strcpy(str[j], temp);
            }
        }
    }
}
```

```

printf("The strings in lexicographical order are:\n");
for (int i = 0; i < n; i++)
{
    printf("\t%s\n", str[i]);
}
}

```

```

input: 19 — Konsole
0.04s user 0.02s system 97% cpu 0.062 total

1 Enter the number of strings: it's a bit weird
Enter the string: Enter the string: why
Enter the string: wdf
Enter the string: ds
Enter the string: df
Enter the string: df
Enter the string: d
Enter the string: dsgf
Enter the string: sd^C%

python-docx/input git:main* 12s
Invalid number of options.
(venv) > cl 19.c
compiling 19
0.05s user 0.02s system 97% cpu 0.072 total

Enter the number of strings: 2
Enter the string: abcd
Enter the string: abccc
The strings in lexicographical order are:
    abccc
    abcd

python-docx/input git:main* 9s
(venv) >

```

20 Write a C program to concatenate two strings without using any string function.

// Write a C program to concatenate two strings without using any string function.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    char str1[100], str2[100];
```

```
    printf("Enter the first string: ");
```

```
    scanf("%[^\\n]%*c", str1);
```

```
    printf("Enter the second string: ");
```

```
    scanf("%[^\\n]%*c", str2);
```

```
    int i = 0;
```

```
    while (str1[i] != '\\0')
```

```
    {
```

```
        i++;
```

```
    }
```

```
    int j = 0;
```

```
    while (str2[j] != '\\0')
```

```
    {
```

```
        str1[i] = str2[j];
```

```
        i++;
```

```
        j++;
```

```
    }
```

```
    str1[i] = '\\0';
```

```
    printf("The concatenated string is: %s\\n", str1);
```

```
}
```

input : zsh — Konsole

Enter the string: dsgf
Enter the string: sd^C%

```
1 python-docx/input git:main* 12s  
Invalid number of options.  
(venv) > cl 19.c  
compiling 19  
0.05s user 0.02s system 97% cpu 0.072 total
```

```
Enter the number of strings: 2  
Enter the string: abcd  
Enter the string: abccc  
The strings in lexicographical order are:  
    abccc  
    abcd
```

```
python-docx/input git:main* 9s  
(venv) > cl 20.c  
compiling 20  
0.04s user 0.03s system 70% cpu 0.095 total
```

```
Enter the first string: hello  
Enter the second string: world  
The concatenated string is: helloworld
```

```
python-docx/input git:main*  
(venv) > 
```