Linux 10 Commands

```
sharanteja2211@SharanTeja:~$ cd Day15/
sharanteja2211@SharanTeja:~/Day15$ lscpu
Architecture:                x86_64
  CPU op-mode(s):            32-bit, 64-bit
  Address sizes:             48 bits physical, 48 bits virtual
  Byte Order:                Little Endian
CPU(s):                      16
  On-line CPU(s) list:       0-15
Vendor ID:                   AuthenticAMD
  Model name:                AMD Ryzen AI 7 350 w/ Radeon 860M
    CPU family:              26
    Model:                   96
    Thread(s) per core:      2
    Core(s) per socket:      8
    Socket(s):               1
    Stepping:                0
    BogoMIPS:                3992.35
    Flags:                   fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht sys
                             call nx mmxext fxsr_opt pdpe1gb rdtscp lm constant_tsc rep_good nopl xtopology tsc_reliable nonstop_tsc
                             cpuid extd_apicid tsc_known_freq pni pclmulqdq ssse3 fma cx16 sse4_1 sse4_2 movbe popcnt aes xsave avx f
                             16c rdrand hypervisor lahf_lm cmp_legacy svm cr8_legacy abm sse4a misalignsse 3dnowprefetch osvw topoext
                              perfctr_core ssbd ibrs ibpb stibp vmmcall fsgsbase bmi1 avx2 smep bmi2 erms invpcid avx512f avx512dq rd
                             seed adx smap avx512ifma clflushopt clwb avx512cd sha_ni avx512bw avx512vl xsaveopt xsavec xgetbv1 xsave
                             s avx_vnni avx512_bf16 clzero xsaveerptr arat npt nrip_save tsc_scale vmcb_clean flushbyasid decodeassis
                             ts pausefilter pfthreshold v_vmsave_vmload avx512vbmi umip avx512_vbmi2 gfni vaes vpclmulqdq avx512_vnni
                              avx512_bitalg avx512_vpopcntdq rdpid fsrm avx512_vp2intersect
Virtualization features:
  Virtualization:            AMD-V
  Hypervisor vendor:         Microsoft
  Virtualization type:       full
Caches (sum of all):
```

```
sharanteja2211@SharanTeja:~/Day15$ nproc
16
sharanteja2211@SharanTeja:~/Day15$ sudo lshw -short
[sudo: authenticate] Password:
H/W path    Device    Class      Description
=========================================
                      system     Computer
/0                    bus        Motherboard
/0/0                  memory     11GiB System memory
/0/1                  processor  AMD Ryzen AI 7 350 w/ Radeon 860M
/0/2                  display    Microsoft Corporation
/0/3                  display    Basic Render Driver
/0/4                  storage    Virtio 1.0 console
/0/4/0                generic    Virtual I/O device
/0/5                  generic    Virtio 1.0 file system
/0/5/0                generic    Virtual I/O device
/0/6                  system     PnP device PNP0b00
/0/7        scsi0     storage
/0/7/0.0.0  /dev/sda  volume     356MiB Virtual Disk
/0/7/0.0.1  /dev/sdb  volume     159MiB Virtual Disk
/0/7/0.0.2  /dev/sdc  volume     3GiB Virtual Disk
/0/7/0.0.3  /dev/sdd  volume     1TiB Virtual Disk
/1          eth0      network    Ethernet interface
sharanteja2211@SharanTeja:~/Day15$ sudo lshw -class memory
  *-memory
       description: System memory
       physical id: 0
       size: 11GiB
```

```
sharanteja2211@SharanTeja:~/Day15$ which lsusb
/usr/bin/lsusb
sharanteja2211@SharanTeja:~/Day15$ lsusb
sharanteja2211@SharanTeja:~/Day15$ lsusb -v
```

```
sharanteja2211@SharanTeja:~/Day15$ lspci
1cf1:00:00.0 3D controller: Microsoft Corporation Device 008a
5096:00:00.0 3D controller: Microsoft Corporation Basic Render Driver
5582:00:00.0 SCSI storage controller: Red Hat, Inc. Virtio 1.0 console (rev 01)
d585:00:00.0 System peripheral: Red Hat, Inc. Virtio 1.0 file system (rev 01)
sharanteja2211@SharanTeja:~/Day15$ lspci -v
1cf1:00:00.0 3D controller: Microsoft Corporation Device 008a
        Physical Slot: 3499642906
        Flags: bus master, fast devsel, latency 0, NUMA node 0
        Capabilities: <access denied>
        Kernel driver in use: dxgkrnl
        Kernel modules: dxgkrnl

5096:00:00.0 3D controller: Microsoft Corporation Basic Render Driver
        Physical Slot: 81602241
        Flags: bus master, fast devsel, latency 0, NUMA node 0
        Capabilities: <access denied>
        Kernel driver in use: dxgkrnl
        Kernel modules: dxgkrnl
```

```
sharanteja2211@SharanTeja:~/Day15$ lspci | grep -i network
sharanteja2211@SharanTeja:~/Day15$ lsblk
NAME MAJ:MIN RM   SIZE RO TYPE MOUNTPOINTS
sda    8:0    0 356.9M  1 disk
sdb    8:16   0 159.4M  1 disk
sdc    8:32   0     3G  0 disk [SWAP]
sdd    8:48   0     1T  0 disk /mnt/wslg/distro
                            /
sharanteja2211@SharanTeja:~/Day15$ lsblk -f
NAME FSTYPE FSVER LABEL UUID                                 FSAVAIL FSUSE% MOUNTPOINTS
sda  ext4   1.0
sdb  ext4   1.0
sdc  swap   1           a324552a-51d3-46d9-add5-4afe736c767a                [SWAP]
sdd  ext4   1.0         83a64a0e-8393-443f-b194-b3260a132af8  953.8G     0% /mnt/wslg/distro
                                                                           /
sharanteja2211@SharanTeja:~/Day15$ lsblk -o NAME,SIZE,TYPE,FSTYPE,MOUNTPOINTS
NAME   SIZE TYPE FSTYPE MOUNTPOINTS
sda  356.9M disk ext4
sdb  159.4M disk ext4
sdc      3G disk swap   [SWAP]
sdd      1T disk ext4   /mnt/wslg/distro
                        /
sharanteja2211@SharanTeja:~/Day15$ sudo fdisk -l
Disk /dev/ram0: 4 MiB, 4194304 bytes, 8192 sectors
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 4096 bytes
I/O size (minimum/optimal): 4096 bytes / 4096 bytes


Disk /dev/ram1: 4 MiB, 4194304 bytes, 8192 sectors
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 4096 bytes
I/O size (minimum/optimal): 4096 bytes / 4096 bytes


Disk /dev/ram2: 4 MiB, 4194304 bytes, 8192 sectors
```

```
sharanteja2211@SharanTeja:~/Day15$ sudo dmidecode -t system
# dmidecode 3.6
Scanning /dev/mem for entry point.
# No SMBIOS nor DMI entry point found, sorry.
sharanteja2211@SharanTeja:~/Day15$ sudo dmidecode -t bios
# dmidecode 3.6
Scanning /dev/mem for entry point.
# No SMBIOS nor DMI entry point found, sorry.
sharanteja2211@SharanTeja:~/Day15$ sudo dmidecode -t processor
# dmidecode 3.6
Scanning /dev/mem for entry point.
# No SMBIOS nor DMI entry point found, sorry.
sharanteja2211@SharanTeja:~/Day15$ sudo dmidecode -t memory
# dmidecode 3.6
Scanning /dev/mem for entry point.
# No SMBIOS nor DMI entry point found, sorry.
sharanteja2211@SharanTeja:~/Day15$ uname
Linux
sharanteja2211@SharanTeja:~/Day15$ uname -a
Linux SharanTeja 6.18.33.2-microsoft-standard-WSL2 #1 SMP PREEMPT_DYNAMIC Thu Jun 18 21:54:43 UTC 2026 x86_64 GNU/Linux
sharanteja2211@SharanTeja:~/Day15$ uname -r
6.18.33.2-microsoft-standard-WSL2
sharanteja2211@SharanTeja:~/Day15$ dmesg
[    0.000000] Linux version 6.18.33.2-microsoft-standard-WSL2 (root@f1bbfb02316b) (gcc (GCC) 13.2.0, GNU ld (GNU Binutils) 2.41) #1
SMP PREEMPT_DYNAMIC Thu Jun 18 21:54:43 UTC 2026
[    0.000000] Command line: initrd=\initrd.img WSL_ROOT_INIT=1 panic=-1 nr_cpus=16 hv_utils.timesync_implicit=1 console=hvc0 debug p
ty.legacy_count=0 WSL_ENABLE_CRASH_DUMP=1
[    0.000000] KERNEL supported cpus:
[    0.000000]   Intel GenuineIntel
[    0.000000]   AMD AuthenticAMD
[    0.000000] BIOS-provided physical RAM map:
[    0.000000] BIOS-e820: [mem 0x0000000000000000-0x000000000009ffff] usable
[    0.000000] BIOS-e820: [mem 0x00000000000e0000-0x00000000000e0fff] reserved
[    0.000000] BIOS-e820: [mem 0x0000000000100000-0x00000000001fffff] ACPI data
[    0.000000] BIOS-e820: [mem 0x0000000000200000-0x00000000f7ffffff] usable
[    0.000000] BIOS-e820: [mem 0x0000000100000000-0x00000002f0bfffff] usable
```