

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 322, y: 208

Time: 00:14:00

Automatically Choose Connection Type

Switch0

IOS Command Line Interface

```
10 Data active Gig0/2
20 voice active Fa0/1
1002 fddi-default active Fa0/1
1003 token-ring-default active
1004 fddinet-default active
1005 trnet-default active
Switch#show interfaces FastEthernet0/1 switchport
Name: Fa0/1
Switchport: Enabled
Administrative Mode: static access
Operational Mode: static access
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: native
Negotiation of Trunking: Off
Access Mode VLAN: 10 (Data)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: 20
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: All
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Switch#
Switch#
```

Copy Paste

Toggle PDU List Window