Configure static IP addresses, modify MAC addresses, and verify network connectivity using ping and ifconfig commands.

PC1 — □ ✕

Physical   Config   Desktop   Programming   Attributes

IP Configuration   X

Interface   FastEthernet0   ∨

IP Configuration

○ DHCP   ● Static

IPv4 Address   192.168.1.20

Subnet Mask   255.255.255.0

Default Gateway   192.168.1.1

DNS Server   0.0.0.0

IPv6 Configuration

○ Automatic   ● Static

IPv6 Address   /

Link Local Address FE80::20B:BEFF:FEE0:CEAA

Default Gateway

DNS Server

802.1X

☐ Use 802.1X Security

Authentication   MD5   ∨

Username

Password

☐ Top

Physical   Config   **Desktop**   Programming   Attributes

Command Prompt   X

```
        IPv6 Address.....................: ::
        IPv4 Address.....................: 192.168.1.10
        Subnet Mask......................: 255.255.255.0
        Default Gateway..................: ::
                                           192.168.1.1

Bluetooth Connection:

        Connection-specific DNS Suffix..:
        Link-local IPv6 Address.........: ::
        IPv6 Address.....................: ::
        IPv4 Address.....................: 0.0.0.0
        Subnet Mask......................: 0.0.0.0
        Default Gateway..................: ::
                                           0.0.0.0

C:\>ipconfig /all

FastEthernet0 Connection:(default port)

        Connection-specific DNS Suffix..:
        Physical Address.................: 0003.E473.7C0C
        Link-local IPv6 Address.........: FE80::203:E4FF:FE73:7C0C
        IPv6 Address.....................: ::
        IPv4 Address.....................: 192.168.1.10
        Subnet Mask......................: 255.255.255.0
        Default Gateway..................: ::
                                           192.168.1.1
        DHCP Servers.....................: 0.0.0.0
        DHCPv6 IAID......................:
        DHCPv6 Client DUID..............: 00-01-00-01-BD-A7-B9-A7-00-03-E4-73-7C-0C
        DNS Servers......................: ::
                                           0.0.0.0

Bluetooth Connection:

        Connection-specific DNS Suffix..:
        Physical Address.................: 0030.A3A7.5997
        Link-local IPv6 Address.........: ::

C:\>clear
Invalid Command.

C:\>
```

☐ Top

Now, Changing the MAC address for PC0

Ping to PC1 to check whether its working

```
Invalid Command.

C:\>ping 192.168.1.20

Pinging 192.168.1.20 with 32 bytes of data:

Reply from 192.168.1.20: bytes=32 time<1ms TTL=128
Reply from 192.168.1.20: bytes=32 time<1ms TTL=128
Reply from 192.168.1.20: bytes=32 time<1ms TTL=128
Reply from 192.168.1.20: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.1.20:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```

☐ Top