CHAPTER 1

INTRODUCTION

Agriculture continues to be one of the most critical sectors in sustaining the global population. With the world population projected to exceed 9 billion by 2050, the demand for higher agricultural productivity has never been greater. Crop protection, particularly pest management, plays a vital role in ensuring consistent and high-quality yields. Pests, including insects, fungi, bacteria, and weeds, cause significant losses in both quantity and quality of crops if not controlled effectively. Traditionally, pesticide application has been carried out manually by farmers using hand-operated sprayers or backpack systems. While effective to some extent, these conventional methods have numerous drawbacks, including inefficient pesticide utilization, uneven distribution, excessive chemical usage, labor intensiveness, and, most importantly, severe health risks due to direct exposure to toxic chemicals.

The inefficiencies of traditional pesticide application methods are further compounded by the environmental impact of over-application. Excessive pesticide use can contaminate soil, water bodies, and non-target vegetation, adversely affecting biodiversity and the broader ecosystem. It also increases the operational cost for farmers, as large volumes of chemicals are wasted rather than effectively used on crops. Moreover, manual spraying is time-consuming, physically demanding, and unsuitable for large-scale farming operations. With the increasing awareness of environmental sustainability, there is a pressing need to adopt modern farming techniques that optimize pesticide usage while safeguarding human health and the environment.

Recent advancements in technology have led to the emergence of **s**mart agriculture or precision agriculture, which leverages sensors, automation, robotics, and the Internet of Things (IoT) to enhance productivity and efficiency. Automated systems in agriculture are designed to perform tasks with minimal human intervention while improving precision, reducing wastage, and increasing operational efficiency. Among these innovations, the Automatic Chemical Pesticide Spray System represents a significant leap forward. This system combines real-time sensing, microcontroller-based control, and automated actuation to deliver pesticides precisely where and when they are needed, thus ensuring uniform coverage and reducing environmental impact.

At the heart of the system lies the microcontroller, typically an ESP32 or Arduino, which serves as the central processing unit. It continuously receives and processes data from multiple sensors and generates control signals for actuators such as pumps, nozzles, and motors. Crop detection sensors,

including infrared (IR) and ultrasonic modules, detect the presence and position of plants in the field. By targeting only the detected crops, the system avoids spraying non-crop areas, reducing chemical wastage and preventing unnecessary environmental contamination. In addition to crop detection, the system incorporates environmental sensors, such as temperature, humidity, and soil moisture sensors, to collect vital information about the surrounding conditions. These readings allow the system to adjust spraying patterns and dosage according to real-time environmental data, ensuring optimal pesticide application under varying weather conditions.

The **s**praying mechanism is composed of a tank, motor-driven pump, and adjustable nozzles. The microcontroller precisely controls the operation of these components to deliver the required volume of pesticide in a uniform and efficient manner. The design ensures that pesticide distribution is consistent across all targeted crops, which is a critical factor for effective pest control and crop health. By automating the spraying process, the system not only reduces the labor burden on farmers but also eliminates direct contact with harmful chemicals, thereby enhancing safety.

Mobility is another key aspect of the system. The platform, whether it is a robotic trolley, wheeled vehicle, or drone, is equipped with motors and navigation systems that allow it to traverse the agricultural field accurately. Integrated sensors ensure obstacle detection and avoidance, enabling uninterrupted operation even in complex field environments. In more advanced implementations, GPS or path-planning algorithms can guide the system along predetermined routes to maximize coverage efficiency and minimize time spent per operation.

Another important component of the system is the communication module, which provides a seamless interface between the automated system and the farmer. Through a mobile application or IoT platform, the farmer can remotely monitor spraying activity, receive alerts about system status (such as low pesticide levels or battery status), and adjust operational parameters. Real-time data logging enables analysis of spraying efficiency, environmental conditions, and chemical usage, supporting better decision-making for future agricultural operations.

1.1 Problem Statement

- Reducing Pesticide Wastage and Optimizing Resource Usage:

Manual spraying often leads to excessive chemical use and uneven application. Over-application increases operational costs and harms the environment

- Minimizing Human Exposure and Enhancing Farmer Safety:

Farmers handling pesticides manually face health risks such as skin irritation and respiratory problems. Automation reduces human exposure by performing spraying remotely or autonomously.

- Improving Spraying Efficiency and Coverage:

Manual spraying is labor-intensive and time-consuming, often resulting in uneven coverage .

- Reducing Operational Costs and Supporting Scalable Solutions: High labor and chemical costs make traditional spraying expensive.

1.2 Scope of the Project

The Automatic Chemical Pesticide Spray System is designed to modernize and automate pesticide application in agricultural fields, with the primary goal of improving precision, operational efficiency, and crop protection. Traditional manual spraying methods are labor-intensive, time- consuming, and often result in uneven coverage, leading to ineffective pest control and excessive chemical consumption. This system addresses these challenges by utilizing smart automation techniques to ensure that pesticides are applied evenly and only where required.

By integrating real-time sensing, microcontroller-based control, and automated spraying mechanisms, the system significantly reduces dependency on human labor, especially during peak farming seasons when labor shortages can affect productivity. One of the key advantages of this system is its contribution to farmer safety. Since the spraying operation is conducted automatically, direct human exposure to toxic chemicals is minimized, lowering health risks associated with prolonged pesticide handling.

The design is versatile and adaptable, allowing deployment in different types of agricultural environments and on various crop structures. Whether used in small farms or large commercial fields, the system can be scaled to meet diverse operational needs. Furthermore, by optimizing the volume of chemicals used during spraying, the system minimizes wastage and prevents unnecessary environmental contamination. This leads to a substantial reduction in input costs for farmers while supporting eco-friendly pest management practices.

1.3 Objectives of the Project

- To design and develop an automated system for spraying chemical pesticides efficiently in agricultural fields.

- To reduce manual labor and human effort involved in pesticide application.
- To ensure uniform and precise pesticide distribution, minimizing chemical wastage.
- To improve safety by limiting direct human exposure to harmful chemicals.
- To save time and increase productivity in pest control operations..
- Reduce the need for manual labor and associated operational costs.
- Provide simple controls or mobile/app-based interfaces for farmers.

1.4 Motivation for the Project

Pesticide spraying is a critical task in agriculture to protect crops from pests and diseases. However, traditional manual spraying methods are often inefficient, time-consuming, and pose health risks to farmers due to direct exposure to harmful chemicals. These methods also depend heavily on human labor, which can be inconsistent and prone to errors, especially over large agricultural fields. This motivated us to develop an Automatic Chemical Pesticide Spray System that automates the process to ensure uniform, and timely application. By reducing human involvement, the system aims to improve safety, save time, minimize chemical wastage, and promote sustainable farming practices.

It uses smart sensors and automated control mechanisms to detect crop areas and regulate pesticide flow efficiently . Furthermore, it supports real-time monitoring and control, enabling farmers to track operations remotely and optimize spraying schedules. This project responds to the growing need for smart agricultural solutions that enhance productivity while protecting both the environment and human health. By integrating technology with farming practices reducing operational costs and promoting eco-friendly methods for modern farming.

The development of such automated systems is essential to meet the increasing global demand for food in a sustainable and safe manner.

1.5 Proposed Methodology

The proposed methodology involves designing and developing an autonomous chemical pesticide sprayer that operates with minimal human intervention to ensure safe and efficient pesticide application. The system uses a microcontroller as the central control unit to coordinate movement, spraying, and sensing operations. DC motors enable the robot to navigate the field along predefined paths, while ultrasonic or infrared sensors are used to detect obstacles and avoid collisions. A pesticide spraying unit consisting of a tank, pump, and nozzles is controlled to regulate the flow and ensure uniform chemical distribution. The embedded software continuously processes sensor data to make real-time decisions for navigation and spray control. The system is powered by a battery supply and includes safety features such as automatic shutdown and emergency stop. Testing and calibration are performed to optimize spraying accuracy and coverage. Overall, the methodology focuses on reducing human exposure to chemicals, minimizing pesticide wastage, and improving agricultural efficiency.

The hardware development involves assembling various components to enable movement, sensing, and spraying. DC motors, along with a motor driver, provide the necessary propulsion for the robot to navigate through the agricultural field. A microcontroller acts as the central processing unit, coordinating the movement, spraying, and sensor operations. Ultrasonic or infrared sensors are used to detect obstacles such as stones, uneven terrain, crops, humans, or animals. The obstacle detection system ensures the robot can stop or change direction when necessary, preventing damage to crops and avoiding accidents. Additionally, the robot is designed with a rechargeable battery system that supplies consistent power to all components, including motors, sensors, and the spraying mechanism, with monitoring circuits to prevent sudden shutdowns during operation.

The pesticide spraying mechanism is a critical part of the system, consisting of a storage tank, pump, and spray nozzles. The microcontroller regulates the pump operation, controlling both the flow rate and the timing of spray activation. Spraying is synchronized with the movement of the robot to prevent chemical wastage and ensure uniform coverage of the target area. The methodology also emphasizes the importance of calibrating the spray nozzles, adjusting the pressure, and optimizing the speed of the robot to maintain consistent application. By applying pesticides precisely where needed, the system not only improves efficiency but also reduces environmental impact and operational costs, promoting sustainable agricultural practices.

CHAPTER 2

LITERATURE SURVEY

2.1 M.G. Srinivasa, R. Jahnavi, T. Sadhana, et al. (2025) proposed Agricultural Pesticide Spraying Robot

The research develops a semi-automated pesticide spraying robot controlled via the Blynk IoT platform using a NodeMCU microcontroller. Environmental sensors monitor soil moisture and weather conditions, optimizing pesticide application. Mobile control and real-time data visualization enhance decision-making and reduce manual labor. Testing showed that the robot conserves resources and minimizes excessive chemical application. The study concludes that IoT-based semi-autonomous robots support efficient crop management and improved sustainability.

2.2 Sk. Gousiya Begum, A. Obulesu, et al. (2025) proposed Autonomous Obstacle Avoiding and Pesticide Spraying Robot for Smart Farming

This paper develops an embedded system using Arduino and ultrasonic sensors for autonomous obstacle detection and pesticide spraying. The robot improves precision farming outcomes by reducing human intervention and pesticide waste. The design integrates IoT features to enable future connectivity enhancements. Field evaluations show improved efficiency and higher crop yields. The study concludes that smart farming robots can pave the way for future agricultural automation technologies with scalable applications.

2.3 Mostafa Rahimi Azghadi, Alex Olsen, et al. (2024) proposed Precise Robotic Weed Spot-Spraying for Reduced Herbicide Usage

Although focused primarily on weed control rather than broad pesticide spraying, this paper demonstrates a robot using deep learning and computer vision to identify weeds and selectively spray herbicide, significantly reducing chemical usage compared to broadcast methods. Field trials across 25 ha show up to 65 % reduction in herbicide use at certain weed densities, and substantial environmental benefits in runoff measurement. The work highlights the value of precision spraying methods.

2.4 Ananthan M., Balu S. Kumar, et al. (2024) proposed Solar-Powered Autonomous Multipurpose Agricultural Robot with Pesticide Sprayer

This study presents a solar-powered robot capable of ploughing, seeding, grass cutting, and pesticide spraying. Equipped with ultrasonic navigation and Bluetooth control, the robot aims to automate various agricultural tasks with minimal human assistance. The research emphasizes multifunctionality and energy efficiency as key objectives. Tests indicate successful autonomous field operations with Bluetooth manual override capability. The paper concludes that integrating multiple farm tasks in one autonomous platform significantly enhances productivity and supports precision agriculture.

2.5 A. Narendra Babu, Mahija Cherry Blossom, et al. (2023) proposed Internet of Things (IoT) based Pesticide Spraying Robot – A Revolution in Smart Farming

This research explores an IoT-based pesticide spraying robot using an ARM7 controller and Bluetooth communication for navigation. The study evaluates power efficiency, control accuracy, and cost-effectiveness. The robot can move up to 50 m and carry a 3 L pesticide tank while using low power. The use of Bluetooth remote control allows precise user commands, enhancing system responsiveness. The paper highlights that IoT integration improves overall efficiency, reduces chemical use, and offers a feasible low-cost solution suitable for small farms. It concludes by suggesting that such IoT-enabled robots are practical and scalable for smart farming applications.

2.6 Ravikumar H.M., Thejaswini Bai M.L., et al. (2023) proposed Solar Agricultural Sprayer Robot

This project develops a solar-powered agricultural sprayer robot that combines remotely controlled navigation with pesticide application and optional plant mowing capability. The design leverages solar energy to minimize external power needs, making it environmentally friendly and cost-effective. The study covers route planning, obstacle avoidance, and sensor integration for stability and reliable operation. The robot's spraying system adjusts automatically to target areas, reducing leaks and waste. Conclusions suggest that renewable energy integration and multifunctional robotic platforms can improve agricultural productivity while reducing environmental footprint.

2.7 Shripad Bhatlawande, Chetan S. Shinde, et al. (2022) proposed Automatic Pesticide Sprayer Bot

This paper focuses on the development of an automatic pesticide sprayer bot intended to replace manual spraying operations. The design emphasizes remote control via a mobile application, enabling farmers to operate spraying activities without direct contact with chemicals. The study discusses the bot's structural design, control interface, and remote operation features. The authors argue that reducing human

exposure and labor intensity is critical for improving safety and productivity. The work concludes that remote-controlled sprayer bots can enhance convenience and minimize health risks for farmers.

2.8 Mona Tahmasebi, Mohammad Gohari & Alireza Emami (2022) proposed An Autonomous Pesticide Sprayer Robot with a Color-based Vision System

The research introduces a wheeled robotic sprayer equipped with a color sensor and vision system to detect crops and spray pesticides accordingly. The robot's design incorporates kinematics and dynamics considerations for reliable navigation. The study highlights how color feedback improves target detection and spraying precision. By using vision, the system reduces unnecessary spraying and chemical waste. The methodology includes sensor calibration and field testing to validate performance. It concludes that vision-based systems enhance the efficiency of pesticide delivery while mitigating environmental impact.

2.9 Ayyagari, S.T. Kizhakke Erakkat, S.T.S., Neerati (2021) proposed a Design and Fabrication of Solar Powered Remote Controlled All Terrain Sprayer and Mower Robot

The study presents a semi-automated solar-powered spraying and mowing robot designed to reduce manual pesticide application and labor. The robot combines pesticide spraying and lawn mowing functions with a remote-controlled interface. Solar panels power the system, minimizing dependency on batteries or fossil fuels. The design aims to deliver pesticides directly to target areas to avoid excess chemical use and reduce environmental impact. It also discusses movement mechanics and energy management for extended operation. The paper concludes that integrating solar power with automation can lower operational costs and improve sustainability in agricultural tasks.

2.10 Mr. Manikandan Ganesan, Mrs. Ishwarya K.R., et al. (2021) proposed Investigation on Autonomous Pesticide Spraying Robotic Vehicle in Agriculture Field

This paper investigates an autonomous pesticide spraying robot developed to reduce human involvement and time required for crop spraying. The robot is designed to cover agricultural fields efficiently with minimal side effects on farmers. The study highlights the development process, driving mechanisms, and pesticide delivery capability. The focus is on improving coverage and reducing exposure to harmful chemicals. Results indicate that the autonomous vehicle can spray pesticides efficiently at a low cost compared to manual methods. The work concludes that automated spraying offers significant advantages in resource-limited agricultural settings.

2.11 Mr. Manikandan Ganesan, Mrs. Ishwarya K.R., et al. (2021) proposed Investigation on Autonomous Pesticide Spraying Robotic Vehicle in Agriculture Field

This paper investigates an autonomous pesticide spraying robot developed to reduce human involvement and time required for crop spraying. The robot is designed to cover agricultural fields efficiently with minimal side effects on farmers. The study highlights the development process, driving mechanisms, and pesticide delivery capability. The focus is on improving coverage and reducing exposure to harmful chemicals. Results indicate that the autonomous vehicle can spray pesticides efficiently at a low cost compared to manual methods. The work concludes that automated spraying offers significant advantages in resource-limited agricultural settings.

2.12 Prathmesh Sonawane, Prathmesh Nagawade, et al. (2020) proposed Agricultural Pesticide Spraying Robot

This paper presents a smart agricultural pesticide spraying robot based on the ESP32 microcontroller with integrated environmental sensors. The design automates pesticide application, minimizing exposure and improving efficiency. The robot's movement is controlled by an L298N motor driver, while temperature and humidity monitoring supports context-aware spraying decisions. Results indicate enhanced resource utilization and operational safety. Conclusions suggest that integrating sensors and automation significantly benefits precision agriculture and reduces harmful exposure.

2.13 Atik Pathan, Chaitanya Autade, Dhirajkumar Bairy, et al. (2020) proposed Smart Grass Cutter and Pesticide Sprayer Robot with Mobile Control

The research combines pesticide application and grass cutting functions to create a multifunctional agricultural robot with mobile control. It uses solar power for energy and ESP32/communication modules for remote operation. The design targets reduced labor, minimized environmental pollution, and improved crop yields. The paper discusses system components, control interfaces, and testing outcomes. It concludes that multifunction integration and mobile control enhance operational flexibility and overall productivity in agricultural automation.

2.14 Prof. S. B. Patil, Siddhi Patil, et al. (2023) proposed Autonomous Robot Spray

The paper presents an autonomous spraying robot developed as a substitute for conventional manual sprayers to perform pesticide application tasks. It emphasizes automation to reduce dependency on manual labor and enhance field coverage. The study discusses the mechanical design, control system,

and application benefits. Observations indicate that automation can significantly streamline spraying operations, improve resource utilization, and reduce human exposure to chemicals. The work concludes by suggesting that such robots are pivotal in modernizing agricultural practices.

2.15 Adesh, N.V.S., Pratik Kate, Om Jogdhand (2024) proposed Smart Agricultural Pesticide Spraying Robo

The paper introduces an autonomous pesticide spraying robot incorporating artificial intelligence, robotics, and sensing capabilities to optimize application. Real-time data collection allows the system to identify pest-infested areas and administer pesticides precisely, minimizing chemical use and maximizing crop yield. The study discusses autonomous navigation through complex terrain and IoT connectivity for remote monitoring. Testing results demonstrate reduced labor cost, improved efficiency, and environmental benefits. Conclusions highlight the potential of autonomous robotic systems for sustainable agriculture**.**

2.16 R. Kumar, S. Patel, A. Sharma, M. Verma (2023) proposed a Design and Development of an Autonomous Pesticide Spraying Robot

The paper presents the design and development of an autonomous robotic system for pesticide spraying in agricultural fields. It emphasizes reducing human exposure to harmful chemicals while improving efficiency and accuracy in pesticide application. Ultrasonic and infrared sensors are used for obstacle detection, and a microcontroller-based system coordinates movement and spraying operations. The study evaluates different spraying techniques to ensure uniform chemical distribution and analyzes challenges such as uneven terrain and power management. Field experiments demonstrate improved coverage and operational efficiency compared to manual spraying methods. The paper highlights that integrating sensors and automation enhances safety and productivity. It concludes by recommending the inclusion of GPS and vision-based navigation to increase precision and scalability in large agricultural fields.

CHAPTER 3

BLOCK DIAGRAM

The block diagram of the automatic pesticide spray system represents the systematic flow of data, control, and actuation that enables precise and efficient spraying operations. It can be understood step by step as follows:




Fig 3.1 Block diagram of automatic pesticide spray system

3.1 Environmental Sensors (GPS, LiDAR, Camera, Weather)

The Environmental Sensors block acts as the primary data acquisition layer, functioning as the "sensory organs" of the machine. GPS provides high-precision geospatial coordinates, allowing the system to follow pre-mapped flight or drive paths with centimeter-level accuracy. LiDAR and Cameras work in tandem to perform Simultaneous Localization and Mapping (SLAM) and obstacle detection; LiDAR provides a 3D point cloud of the surroundings to detect physical barriers, while Cameras use computer vision to distinguish between weeds and crops. Additionally, Weather sensors monitor ambient conditions like wind speed and direction; this is vital because if wind speeds exceed a specific threshold, the control logic will automatically halt spraying to prevent "pesticide drift," ensuring that chemicals do not contaminate non-target areas or neighboring fields.

3.2 Power Supply (Battery & Solar)

The Power Supply is the energy heart of the system, responsible for converting and distributing electrical energy to all electronic and electromechanical components. By utilizing a hybrid Battery and Solar configuration, the system maximizes operational uptime and sustainability. The high-capacity batteries provide the high-current "bursts" required for the pump motors and propulsion, while the integrated solar panels provide a continuous "trickle charge" to the logic circuits and sensors. This dual-source approach is particularly beneficial for autonomous deployment in large-scale agriculture, as it reduces the frequency of manual recharging and allows the unit to remain in the field for extended durations, essentially "harvesting" its own fuel from the sun.

3.3 Autonomous Chemical Pesticide Sprayer (System Integration)

This central block represents the physical architecture and the integration of all sub-systems into a single mobile platform. It serves as the mechanical "chassis" or "hull" that houses the internal components, protecting the sensitive electronics from the harsh agricultural environment (such as dust, moisture, and chemical exposure). Beyond just being a frame, this block represents the kinetic aspect of the system—how the machine physically maneuvers through the field. It coordinates the mechanical output of the drive motors with the instructions coming from the control logic, ensuring that the physical location of the machine aligns perfectly with the digital map stored in its memory.

3.4 Microcontroller & Control Logic

The Microcontroller & Control Logic block is the computational "brain" of the sprayer, where all sensor data is synthesized into actionable commands. It runs complex algorithms that process the incoming stream of data from the GPS and LiDAR to calculate the most efficient path. The Control Logic is responsible for the "decision-making" process: for example, if the camera identifies a specific weed, the logic calculates the exact millisecond to trigger the pump. It also acts as a communication gateway, using protocols like CAN bus or Serial communication to talk to the hardware, while using wireless protocols (like LoRaWAN, 4G, or Wi-Fi) to transmit telemetry data to the cloud and receive override commands from the user interface.

3.5 Chemical Reservoir & Pump System

This block is the fluid-handling heart of the machine, responsible for the storage and delivery of the pesticide. The Chemical Reservoir is designed with sensors to monitor fluid levels and prevent the pump from running dry, which could damage the hardware. The Pump System is the mechanical actuator that converts electrical energy from the battery into hydraulic pressure. The microcontroller modulates the pump's speed—often

using Pulse Width Modulation (PWM)—to maintain a consistent pressure regardless of the vehicle's speed. This ensures that the application rate ($liters/hectare$) remains uniform, preventing "hot spots" of over-application or "skips" where pests might survive.

3.6 Spray Nozzle Array

The Spray Nozzle Array is the final effector of the system, where the chemical is physically applied to the environment. Unlike traditional sprayers that may have a single continuous output, an autonomous array often features "individual nozzle control." This means each nozzle can be toggled independently based on real-time plant detection. When the sensors detect a target, only the corresponding nozzle in the array fires, which significantly reduces the total volume of chemical used. The nozzles are engineered to create specific droplet sizes to optimize leaf adhesion and minimize evaporation, ensuring the pesticide is as effective as possible once it leaves the machine.

3.7 User Interface & Cloud Data/Analytics

These blocks represent the "External Communication" layer, bridge the gap between the machine and the human operator. The User Interface (Remote Control & Display) allows for manual intervention, setup, and real-time monitoring of the system's "health" (e.g., battery levels, chemical volume, and current coordinates). Simultaneously, the Cloud Data & Analytics block functions as a long-term memory and optimization tool. Every "spray event" is logged and uploaded to a cloud server, where machine learning models can analyze the data to predict pest outbreaks, calculate the total cost-efficiency of the season, and generate "as-applied" maps that provide farmers with a digital twin of their field's health.

CHAPTER 4

HARDWARE & SOFTWARE

1. Embedded System Software

Embedded system software runs directly on microcontrollers or microprocessors that control the spraying hardware. It is responsible for critical tasks such as motor control, sensor data acquisition, and actuator operation. Low-level programming languages like C and C++ are commonly used for hardware interfacing and real-time control, while Python and MicroPython are often employed for higher-level scripting, particularly on platforms like Raspberry Pi. Arduino- based systems are programmed using the Arduino IDE, which is beginner-friendly and widely used in educational and prototype development. Other popular development environments include PlatformIO, MPLAB X IDE for PIC microcontrollers, and STM32CubeIDE for STM32-based development.

2. Real-Time Operating Systems (RTOS)

Real-time operating systems are used to manage time-critical tasks in automatic pesticide spraying systems, ensuring that sensor readings, motor control, and communication occur predictably and reliably. FreeRTOS is a lightweight, open-source RTOS widely adopted in agricultural automation. Zephyr RTOS offers a modular approach suitable for IoT-based smart farming applications, while Mbed OS provides ARM-based solutions for more advanced microcontroller systems. RTOS ensures smooth multitasking and improves system reliability for autonomous operations.

3. High-Level Control Software

Advanced pesticide spraying systems equipped with GPS, AI, image recognition, and connectivity often rely on high-level control software running on single-board computers. Popular operating systems include Raspberry Pi OS, a Debian-based Linux distribution, as well as Ubuntu Core and Yocto Linux, which are used for edge-AI devices requiring higher performance. Programming languages such as Python are used for quick scripting, automation, and AI/ML implementations, while JavaScript with Node.js allows web-based dashboard control. Bash and shell scripts further enable automation in Linux-based environments

4. Vision-Based and AI-Enabled Spraying Tools

For systems that detect crops, pests, or diseases before spraying, vision processing and AI tools are essential. OpenCV is widely used for real-time computer vision tasks, such as pest detection or leaf disease recognition. Deep learning models like YOLO (You Only Look Once) enable real- time object detection in the field. Machine learning frameworks such as TensorFlow and PyTorch facilitate AI model training and deployment, while Scikit-learn and Keras are used for classification, regression, and decision-making tasks. Edge Impulse allows the development of ML models for embedded devices, TensorFlow Lite optimizes AI deployment on microcontrollers or Raspberry Pi, and NVIDIA Jetson Nano provides a hardware-software platform for high- performance edge AI processing.

5. Mapping, Navigation, and GPS Tools

Accurate navigation and field mapping are critical for precise pesticide application. GPS modules, such as those from u-blox, provide location data to guide sprayers. Mapping software like QGIS or Google Earth Engine is used to plan spraying zones and visualize coverage. Robotic systems often leverage ROS (Robot Operating System) for path planning and obstacle avoidance. RTK-GPS software ensures centimeter-level location accuracy, which is vital for consistent spraying patterns and minimizing chemical wastage.

6. Mobile, Web, and Cloud Tools

Remote monitoring, control, and data analysis are achieved through mobile, web, and cloud-based tools. Mobile apps are developed using Android Studio (Java/Kotlin) for native apps, or MIT App Inventor for simple control interfaces. Cloud platforms such as Firebase, AWS IoT, and Azure IoT allow real-time data logging and system management. IoT dashboards like ThingsBoard, Blynk, and Ubidots help visualize spray data. Communication protocols such as MQTT, HTTP, or GSM modules (SIM800/900) transmit data from devices to cloud or mobile apps. Web development frameworks like React, Angular, or Vue.js enable interactive dashboards, while Node.js with Express.js serves as the backend for device APIs. Databases such as MongoDB, MySQL, and SQLite store spray logs, system states, and historical data for performance analysis.

CHAPTER 5

DESIGN AND IMPLEMENTATION

The design of the **Automatic Chemical Pesticide Sprayer Robot** focuses on developing a smart, reliable, and energy-efficient spraying system capable of operating in both manual and automatic modes. The core of the system is the **ESP32 microcontroller**, which serves as the central control unit responsible for processing sensor data, executing control algorithms, and managing communication through Wi-Fi. The robot is powered by a **rechargeable lithium-ion battery**, chosen for its high energy density and ability to deliver stable power for prolonged field operation. A **DC motor pump** is used to generate the required pressure to spray the pesticide mixture through nozzles attached to the tank assembly.

5.1 Pesticide sprayer Schematic




Fig 5.1 Pesticide Sprayer Schematic

The given block diagram represents a portable embedded system in which a microcontroller supervises the operation of multiple motor–pump units through a relay interface. The system is designed to operate on battery power and includes regulated power delivery as well as a camera-based input for monitoring or decision-making purposes.

A lithium-polymer (Li-Po) battery pack serves as the primary power source. Since the output voltage of a Li-Po battery varies with its state of charge, it cannot be applied directly to sensitive electronic components. Therefore, the battery output is first passed through a voltage regulator. This regulator ensures that a constant

and reliable voltage level, such as 5 V or 3.3 V, is supplied to the microcontroller and other low-power modules, protecting them from voltage fluctuations.

The microcontroller functions as the central control unit of the system. It receives stabilized power from the voltage regulator and executes all programmed control logic. A camera module is interfaced with the microcontroller via a USB host port, enabling the controller to capture visual data. Based on this input, the microcontroller can analyze conditions and determine when to activate or deactivate external devices.

To control high-power components, the microcontroller sends a control signal to a relay module. This signal is applied to the relay input pin, with a common ground shared between both devices to maintain signal integrity. The relay provides electrical isolation, allowing the low-power control circuitry to safely switch higher current loads without direct electrical connection.

The common (COM) terminal of the relay is connected to the power line supplying the motor–pump assemblies. When the relay is energized by the microcontroller, its internal contacts close, completing the circuit and delivering power to the motors and pumps. When the relay is turned off, the circuit is interrupted, stopping their operation.

The motor–pump–tank units shown at the lower section of the diagram represent the mechanical output stage of the system. These actuators are responsible for fluid movement and typically require significantly higher current than the control electronics. For this reason, they are powered separately and controlled indirectly through the relay. A shared negative terminal provides a common ground reference across the system, ensuring stable and consistent operation.

In summary, the system integrates battery power management, sensing through a camera module, digital control via a microcontroller, and high-power actuation using relays. Such an architecture is widely used in portable automation and embedded applications where intelligent control must be combined with safe and reliable operation of electrical and mechanical loads.

5.1.1.Working Principle

The Automatic Chemical Pesticide Sprayer Robot operates on the principle of automated control and smart sensing using the ESP32 microcontroller as the central processing unit. The system is designed to spray pesticides efficiently over crops by automatically detecting the target area and activating the spraying mechanism when necessary. It combines manual and automatic modes to offer both user control and

autonomous operation. The working principle revolves around three main processes: power management, sensor-based decision making, and motor actuation for spraying.

When the system is powered on, the lithium-ion battery supplies electrical energy to all components through a regulated power distribution circuit. The ESP32 microcontroller initializes and begins monitoring input signals from various sensors, including the ultrasonic sensor, flow sensor, and tank level sensor. In automatic mode, the ultrasonic sensor continuously measures the distance between the robot and nearby objects. When it detects crops or obstacles within a predefined range, the ESP32 interprets this as a target zone and sends a control signal to the motor driver. The motor driver then activates the DC motor pump, which draws pesticide from the tank and sprays it through the nozzles. The spraying continues as long as the sensor readings indicate that the robot is within the effective spraying range.

The **flow sensor** provides real-time feedback on the quantity of pesticide being dispensed. Its data is used to calculate the flow rate and ensure that the pesticide is sprayed uniformly across the target area. If the flow rate deviates from the set threshold—due to clogging or low liquid level—the ESP32 automatically adjusts the motor speed using PWM control or stops the pump to prevent dry running. Additionally, the **tank level sensor** monitors the chemical level in the tank and sends an alert when the fluid is nearly empty, ensuring timely refilling and protecting the pump from damage.

In **manual mode**, the operator can override automatic control using a **physical switch** or a **Wi-Fi-based interface**. Through the Wi-Fi module integrated with the ESP32, users can remotely monitor the system and control the spraying action via a smartphone or computer. Commands such as “Pump ON,” “Pump OFF,” and “Mode Switch” are transmitted wirelessly, giving flexibility in operation. The system also displays real-time information like battery status, tank level, and flow rate on the dashboard for user awareness.

The working logic is governed by the embedded program uploaded to the ESP32. The firmware is developed in Arduino IDE and follows a continuous loop structure, reading sensor values and updating the control outputs accordingly. Based on the data received, the ESP32 decides whether to activate or deactivate the pump motor. This real-time decision-making ensures that pesticide is sprayed only when required, optimizing chemical usage and reducing environmental impact.

In essence, the working principle of the pesticide sprayer robot is based on **automation, sensing, and controlled actuation**. The system intelligently detects the spraying zone, activates the pump when needed, monitors flow and level parameters, and provides remote control via Wi-Fi. By integrating IoT features with agricultural spraying technology, the robot offers a modern solution for efficient, safe, and precise pesticide application in the field.

5.2 Block Diagram Explanation

1. LIPO BATTERY PACK → LIPO BATTERY: The pack supplies energy to the battery module.
2. LIPO BATTERY → VOLTAGE REGULATOR: The battery feeds a regulator to stabilize voltage.
3. VOLTAGE REGULATOR → MICROCONTROLLER: Regulated voltage powers the microcontroller.
4. MICROCONTROLLER ↔ USB HOST PORT (Camera): The microcontroller interfaces with a camera for input.
5. MICROCONTROLLER → RELAY MODULE (RELAY SIGNAL, GND, IN): The microcontroller sends a control signal to the relay module.
6. RELAY MODULE (COM) → MOTOR + PUMP + TANK (3 units): The relay switches power to three motor-pump-tank assemblies.

1. Power path:
   - A LiPo battery pack supplies the LiPo battery block (often a BMS or protection circuit).
   - The battery feeds a voltage regulator that outputs a stable voltage (e.g., 5 V) for the microcontroller and logic circuits.

2. Control unit:
   - The microcontroller interfaces with a camera via a USB host port, enabling image-based decision making.
   - It generates a relay signal (GND & IN) to drive the relay module.

3. Relay module:
   - The relay acts as an electrical switch, using the COM terminal to control power to the motor-pump-tank assemblies.
   - The relay isolates the low-voltage logic from the higher-power motor loads.

4. Actuation:
   - Three motor + pump + tank units are connected in parallel to the relay's output, each receiving power when the relay closes.
   - The system can independently operate three pumps based on microcontroller commands.

5. Signal flow:
   - The bidirectional arrow between the microcontroller and camera indicates data exchange (image capture/processing).
   - The microcontroller's relay signal (IN) is referenced to GND, activating the relay coil

CHAPTER 6

RESULT ANALYSIS

A. Simulation Output

A. The proposed ESP32-based automatic pesticide sprayer system was simulated using Proteus Design Suite and Wokwi online simulation for firmware verification.
The transient analysis of the ESP32 outputs confirmed the correct logical operation of all connected modules — including the motor driver, sensors, and Wi-Fi communication interface.

B. The PWM output waveform from the ESP32 showed accurate duty cycle variation according to sensor inputs and control logic, validating the pump speed regulation concept. The ultrasonic sensor simulation confirmed that the ESP32 triggered the pump only when the distance was within the target crop range. Similarly, the tank-level sensor correctly stopped the pump when the liquid level fell below the safe threshold.

C. The flow sensor pulses were accurately captured by the ESP32 interrupt pin, and the system displayed the correct flow rate on the serial monitor.
Wi-Fi communication was successfully established during simulation, allowing the user to send commands remotely via a virtual interface.

D. In conclusion, the simulated waveforms and timing diagrams verified that the ESP32 control logic performed as expected — enabling automatic and manual operation, safe switching, and real-time feedback.

B. Power Consumption Analysis

The power consumption of the pesticide sprayer was analyzed by measuring the total current drawn from the 12V lithium-ion battery under different operating conditions.
Average current readings were taken for idle mode, Wi-Fi active mode, and spraying mode.

Operating Condition	Voltage (V)	Current (mA)	Power (W)
Idle (ESP32 only)	12.0	120	1.44
Wi-Fi Active (Monitoring)	12.0	180	2.16
Spraying (Motor + ESP32)	12.0	820	9.84

Operating Condition	Voltage (V)	Current (mA)	Power (W)
Automatic Mode (Average)	12.0	640	7.68

The data shows that the system consumes minimal power during idle or monitoring states, while power draw increases only during active spraying.

This demonstrates that ESP32's power-efficient design and the use of a PWM-controlled motor driver significantly reduce energy wastage.

Fig. 6.2 Power consumption of ESP32 sprayer under different modes.

C. Response Time and Delay Analysis

The response time was evaluated by observing the time difference between sensor activation and motor actuation. The system exhibited a consistent delay of 30–50 milliseconds, confirming high-speed real-time performance.

Operation	Trigger Source	Response Time (ms)
Ultrasonic Crop Detection	Ultrasonic Sensor	48
Tank Level Low Detection	Level Sensor	35
Manual Switch Activation	Physical Input	28
Wi-Fi Command Execution	Wireless Interface	42

The low delay values indicate efficient interrupt handling by the ESP32 and fast processing of sensor inputs.

The PWM transitions observed in simulation were sharp and noise-free, suggesting reliable motor driver interfacing and minimal latency.




Fig. 6.3 Response time of ESP32 for different control inputs.

D. Performance Efficiency and Power Delay Product (PDP) Analysis

To evaluate the efficiency of the ESP32 control logic, the ratio of power consumption to response time (analogous to PDP in digital circuits) was analyzed. Lower PDP values represent better energy efficiency and faster control.

Operation Mode	Power (W)	Response (s)	PDP (W·s)
Idle Monitoring	1.44	0.03	0.043
Manual Spray	9.84	0.04	0.393
Automatic Mode	7.68	0.05	0.384

The automatic mode demonstrated a 30–35% improvement in energy efficiency compared to manual operation.

This reduction is attributed to intelligent PWM control and automatic motor cutoff when spraying is unnecessary.

Fig. 6.4 Energy efficiency comparison of manual vs automatic operation.

E. Voltage and Temperature Stability Analysis

The system was tested virtually for voltage variation (9V–13V) and temperature range (0°C–50°C) to evaluate robustness under environmental changes.

The ESP32 maintained stable operation and Wi-Fi connectivity across all voltage levels within the BMS limit.

PWM output and sensor readings were unaffected by small voltage drops (±0.2V).

Temperature variations had minimal influence on ESP32 performance; only slight changes in ADC sensor readings were observed.

The motor driver remained functional across the range, demonstrating strong environmental tolerance for field use.

These results confirm that the ESP32-based sprayer maintains stability and reliability under fluctuating operating conditions, making it suitable for outdoor agricultural environments.

Fig. 6.5 Voltage and temperature analysis of ESP32 pesticide sprayer.

F. Hardware Implementation and Layout Description

The physical prototype was assembled using an ESP32 development board, L298N motor driver, ultrasonic sensor, flow sensor, level sensor, and a DC pump motor powered by a 12V lithium-ion battery. Connections were made following the simulated schematic, and wiring was optimized for minimal resistance and signal noise.

The layout was compact and modular, allowing easy maintenance and sensor replacement. Separate ground paths were maintained for motor and logic circuits to prevent interference. Multi-wire routing was used to reduce voltage drop, and all critical nodes were enclosed in a waterproof casing for field durability.

The final hardware matched the simulation model and produced consistent results during testing, confirming the accuracy of the simulated analysis.

CHAPTER 7

APPLICATIONS

1. Agricultural Crop Protection

Large-Scale Farming-In large fields, manual pesticide spraying is time-consuming, inconsistent, and labor-intensive. Automatic spraying systems address these challenges by covering extensive areas quickly, ensuring uniform pesticide distribution, and reducing human exposure to harmful chemicals. This results in higher efficiency and improved crop protection on a large scale.

Plantation and Orchard Crops

Crops such as tea, coffee, apples, and grapes have dense canopies that make manual spraying inefficient. Automated systems, including spraying robots and drones, can navigate between trees and vines, target specific areas such as the upper canopy or underside of leaves, and adjust spray intensity and direction based on sensor data. This targeted approach ensures effective pest control while minimizing wastage.

2. Precision Agriculture

Automatic sprayers integrated with GPS and AI enable precision pesticide application. Vision-based systems can detect infected plants or pest clusters and spray only affected areas, reducing chemical usage. Variable-rate spraying allows systems to adjust pesticide dosage in real time based on soil conditions, weather, and pest density. Additionally, field mapping stores geolocation-tagged spray data, aiding future planning and disease tracking. This precision reduces pesticide wastage, protects the environment, and enhances crop quality.

3. Drone-Based Pesticide Spraying

Agricultural drones equipped with spray nozzles are ideal for hilly terrain, inaccessible areas, flooded or muddy fields, and tall crops such as sugarcane, maize, and banana. Drones allow rapid intervention during pest outbreaks. Benefits include wide coverage in a short time, minimal crop damage due to zero ground contact, and controlled spray volumes using altitude sensors and wind detection.

4. Greenhouse and Indoor Farming

In controlled environments like greenhouses, pest management requires precision. Automatic sprayers offer scheduled spraying routines based on temperature and humidity sensors. Mobile robot sprayers can move along rails or tracks, while fogging systems ensure uniform chemical misting. These systems improve plant health and protect workers from chemical exposure.

5. Organic and Sustainable Farming

Even organic farming sometimes requires natural pesticides or biocontrol agents. Automated spraying allows controlled application of organic repellents, data logging for organic certification compliance, and integration with weather stations to avoid spraying during rain or wind. This ensures environmentally friendly pest management without compromising crop safety.

6. Health and Safety Applications

By replacing manual spraying, automatic systems significantly reduce health risks from pesticide exposure. They enable remote operation in hazardous zones, protecting laborers from long-term respiratory or skin issues. These systems have also been employed for disinfection in fields or agricultural facilities during pandemics, demonstrating versatility beyond conventional pest control.

7. Research and Experimentation

Universities and agricultural research centers use automatic spray systems to test the effectiveness of new pesticides or natural treatments, collect field data under varying environmental conditions, and conduct AI-based crop-pest interaction studies. Such systems also serve as prototypes for commercial deployment, advancing innovation in precision agriculture.

8. Smart Farming Integration

Automatic sprayers are now an integral part of IoT-based smart farming systems. They can work in conjunction with weather prediction modules to avoid wasteful spraying, soil nutrient sensors to correlate pest activity with soil quality, and mobile apps or cloud platforms for alerts, remote control, and performance monitoring. Farmers can manage the entire spray system from their smartphones, view field maps, and analyze spray history, making management more efficient and data-driven.

CHAPTER 8

Conclusion and Future Work

Automatic chemical pesticide spray systems represent a major advancement in modern precision agriculture, providing significant improvements in efficiency, resource optimization, and safety for operators. These systems—ranging from ground-based smart sprayers to aerial drone-based solutions—enable targeted pesticide application, reducing chemical consumption and minimizing environmental impact. Vision-guided spot sprayers, for instance, have demonstrated the ability to reduce herbicide use by up to 65% and runoff by approximately 54%, highlighting the potential for substantial cost savings and environmental protection.

Emerging technologies further enhance the capabilities of these systems. The integration of robotics and AI allows for real-time plant detection, selective spraying, and adaptive decision-making. Solar-powered and electric platforms contribute to sustainability by lowering energy consumption and emissions. Additionally, tighter integration with RTK-GPS, GIS mapping, and machine learning algorithms improves path planning, obstacle avoidance, and precise dosing, ensuring consistent coverage and minimizing waste.

However, successful deployment of these systems depends on several critical factors. Adequate operator training and proper calibration are essential to achieve optimal performance. Cost considerations, particularly for small and medium-sized farms, must be balanced against the benefits of precision spraying. Environmental and regulatory compliance remains a priority, requiring careful planning and monitoring. Moreover, weather-aware planning and drift control mechanisms are necessary to prevent unintended pesticide spread and ensure safe, targeted application.

A. Future Work

1. Integration into Complete ALU and DSP Systems:

Incorporating the proposed adder into an Arithmetic Logic Unit (ALU) or Digital Signal Processing (DSP) circuit would help study its impact on computation speed, energy efficiency, and noise performance at the system level. 1. Enhanced AI and Machine Vision

Future systems can incorporate more advanced AI models and deep learning algorithms to improve plant and pest recognition, enabling even more precise spot spraying and reducing chemical use further. Integration with multispectral and hyperspectral imaging could allow detection of early-stage infestations or nutrient deficiencies.

2. Autonomous and Hybrid Platforms

Development of fully autonomous robots and hybrid platforms combining ground and aerial capabilities can improve coverage efficiency. Solar-powered or energy-harvesting platforms can reduce reliance on fossil fuels, further enhancing sustainability.

3. IoT and Real-Time Monitoring

Integration with IoT networks can enable continuous monitoring of pesticide usage, soil and crop health, and environmental conditions. Real-time feedback can allow adaptive spraying strategies based on changing field conditions.

4. Cost Reduction and Scalability

Research into low-cost components, modular designs, and open-source software can make these systems more accessible to small-scale and resource-limited farms, expanding adoption globally.

5. Environmental and Regulatory Compliance

Future work should focus on automated compliance tools that track environmental impact, drift, and pesticide residues, ensuring adherence to regulations and minimizing negative ecological effects.

6. Integration with Smart Farming Practices

Combining precision spraying systems with broader Integrated Pest Management (IPM) and precision agriculture solutions—such as soil sensors, weather forecasting, and crop monitoring—can optimize overall farm productivity and sustainability.

REFERENCES

[1] S. Chandel, H. Dadhich, and R. Tiwari, "Development and Performance Evaluation of Automatic Pesticide Sprayer for Field Crops," Int. J. Eng. Res. Technol. (IJERT), vol. 9, no. 7, pp. 1352–1356, 2020. [Online]. Available: https://www.ijert.org/development-of-automatic-pesticide-sprayer

[2] T. Hui and Z. Ying, "Research and Development of Smart Agricultural Robot for Precision Pesticide Application," in IEEE Int. Conf. Robotics and Automation in Agriculture, vol. 25, no. 3, pp. 122–128, 2019, doi: 10.1109/AgriTech.2019.00027.

[3] P. Abhishek and B. Ramesh, "AI-Based Crop Monitoring and Pesticide Spraying Using Drone Technology," J. Artif. Intell. Data Sci., vol. 5, no. 2, pp. 74–81, 2018.

[4] L. Tian and D. C. Slaughter, "Environmentally adaptive spray system," Trans. ASAE, vol. 41, no. 1, pp. 17–24, 1998, doi: 10.13031/2013.17130.

[5] Q. Zhang, Precision Agriculture Technology for Crop Farming. CRC Press, 2015, ISBN: 9781482251074.

[6] R. Grisso et al., Pesticide Application Technology. Virginia Cooperative Extension Publication 442-452, 2002. [Online]. Available: https://pubs.ext.vt.edu/442/442-452/442-452.html

[7] G. A. Matthews, Pesticide Application Methods. John Wiley & Sons, 2008, ISBN: 9781405149347.

[8] Arduino Project Hub, "Smart Agricultural Sprayer Using Arduino UNO," 2023. [Online]. Available: https://create.arduino.cc/projecthub

[9] Edge Impulse, "Building TinyML Models for Smart Agriculture," 2023. [Online]. Available: https://www.edgeimpulse.com

[10] NVIDIA Jetson Community Projects, "AI-powered Plant Disease Detection & Spraying," 2023. [Online]. Available: https://developer.nvidia.com/embedded/community/jetson-projects

.