

Mark Scheme (Results)

January 2018

Pearson Edexcel International GCSE In Physics (4PH0) Paper 2P



Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.edexcel.com (alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus.

Pearson: helping people progress, everywhere
Pearson aspires to be the world's leading learning company. Our aim is to help
everyone progress in their lives through education. We believe in every kind of
learning, for all kinds of people, wherever they are in the world. We've been involved
in education for over 150 years, and by working across 70 countries, in 100
languages, we have built an international reputation for our commitment to high
standards and raising achievement through innovation in education. Find out more
about how we can help you and your students at: www.pearson.com/uk

January 2018
Publications Code 4PH0_2P_1801_MS
All the material in this publication is copyright
© Pearson Education Ltd 2018

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Question number	Answer	Notes	Marks
1 (a)	one mark for each correct tick;;; Energy source Tick wind	2 marks max. if 4 ticks 1 mark only if 5 ticks 0 marks if 6 ticks	3
	oil ✓		
	geothermal		
	bio-gas nuclear ✓		
(b)	 advantage: any one from high energy density / eq; short start up time / adaptable to demand; reliable technology; does not depend on weather conditions; (relatively) cheap; 	ignore ideas about transportation allow 'produces large amount of energy'	2
	 disadvantage: any one from produces CO₂ / greenhouse gases / air pollution / sulphur dioxide / nitrous oxide; causes global warming; causes acid rain; 	allow non-renewable ignore unqualified 'damages environment', 'pollution' etc.	

Total for question 1 = 5 marks

	Question number		Answer			Notes	Marks
2	(a) (i)	power = voltage	x current;		standard syr	ngements and use of nbols e.g. P = V x I v c/C/A for current	1
	(ii)	substitution; rearrangement; evaluation; e.g. 6.5 = 230 x I					3
		(I =) 6.5 / 230 (I =) 0.028 (A)			allow 0.03, (do not allow	0.0283 , 0.02826 (A)	
2	(b)	1 mark for each				1	3
		S1	S2	S3	Lamp		
		up	up		on		
		down	down	down	off		
		up	up	down	off		
		down	up	up	off		
		up	down	down	on		

Total for question 2 = 7 marks

Question number	Answer	Notes	Marks
3 (a)	left diagram: at least 3 correctly curved wavefronts centred on the gap; spacing of wavefronts is consistent with original wavefronts;	ignore where wavefront lines start and finish DOP judge spacing by eye	3
	right diagram: evenly spaced planar wavefronts (curved at the edges);	reject if any wavefront line is as long as original wavefront lines ignore spacing of wavefronts	
(b) (i)	(wave) speed = frequency x wavelength;	allow rearrangements and use of standard symbols e.g. $v = f \times \lambda$ condone s for speed	1
(ii)	substitution / rearrangement; evaluation of frequency; evaluation of wavelength to at least 2 significant figures;	allow alternative methods e.g. 6 / 4 = 4 / λ gains both method marks	3
	e.g. $6.0 = f \times 4.0$ f = 1.5 (Hz) $(\lambda_2 =) 2.7 \text{ (cm)}$	allow 2.67, 2.6 recurring condone 2.6, 2.66 etc. do not allow 3.0	

Question number	Answer	Notes	Marks
4 (a)	(total) momentum before (a collision) = (total) momentum after (a collision);	ignore unqualified 'momentum is conserved'	1
(b)	correct value of momentum before collision seen anywhere in the calculation; substitution into balanced equation; evaluation of velocity; e.g. (momentum before =) 1.6 (kgm/s) 1.6 = 0.16 x 8 + 0.16 x v (v =) 2 (m/s)	either as 0.16 x 10 or 1.6	3
(c)	calculation of KE before collision; calculation of KE of either ball after collision; evaluation of energy difference; e.g. $0.5 \times 0.16 \times 10^2$ $(0.5 \times 0.16 \times 8^2)$ OR $(0.5 \times 0.16 \times 2^2)$ $(8 - (5.12 + 0.32) =) 2.6$ (J)	ecf from (b) 8 (J) 5.12 OR 0.32 (J) allow 2.56 (J)	3

Total for question 4 = 7 marks

Question number	Answer	Notes	Marks
5 (a)	any 4 from: MP1. fewer particles outside the balloon; MP2. (hence) fewer impacts (per second)	condone idea that all particles have been removed	4
	on the outside of the balloon; MP3. (hence) pressure outside balloon is reduced; MP4. pressure inside balloon > pressure outside balloon;	ignore references to vacuum	
	MP5. (hence) air inside the balloon expands until the pressures balance;	reject 'air particles expanding'	
(b) (i)	pressure increases; (because) volume (of trapped air) has decreased / particles collide with liquid surface more (often);	allow walls for liquid surface	2
(ii)	water level increases / rises; greater {force / pressure} acts on the water (so can support greater weight of water above);	allow formula as justification p = hpg (because the increased pressure difference supports a greater height of water)	2
(iii)	water level decreases / falls; (because) pressure difference is now less/eq;		2

Total for question 5 = 10 marks

either correct moment seen; use of principle of moments; seen mathematically or in writing e.g. 'clockwise moment' answer of 0.25 (N) gets 2 mark e.g. W x 8 OR 0.1 x 12 W x 8 = 0.1 x 12 (W =) 0.15 (N) allow 0.2 (N) if supported by correct working reject if repulsion mentioned allow creating (additional) and clockwise moment and clockwise moment allow symbols I for current and whit; correct orientation; all 6 points correctly plotted; seen mathematically or in writing e.g. 'clockwise moment' seen mathematically or in writing e.g. 'clockwise moment' answer of 0.25 (N) gets 2 mark allow 0.2 (N) if supported by correct working allow current for coil and correct working reject if repulsion mentioned allow creating (additional) and clockwise moment allow symbols I for current and whith the current on x-axis allow symbols I for current and whith the current on x-axis reject plotting mark if allow symbols I for current and whith the current on x-axis reject plotting mark if answer of 0.25 (N) gets 2 mark allow 0.2 (N) if supported by correct working allow current for coil allow current for coil reject if repulsion mentioned allow creating (additional) and clockwise moment allow current for coil reject if repulsion mentioned allow current for coil reject if repulsion mentioned allow current for coil allow current for coil reject if repulsion mentioned allow current for coil allow c	
e.g. W x 8 OR 0.1 x 12 W x 8 = 0.1 x 12 (W =) 0.15 (N) coil becomes an electromagnet / coil produces a magnetic field; coil {attracts / exerts a force on} magnet; increasing anti-clockwise moment; (c) (i) sensible linear scales on both axes that occupy >50% of the grid; both axes labelled correctly with quantity and unit; correct orientation; all 6 points correctly plotted; answer of 0.25 (N) gets 2 marile allow 0.2 (N) if supported by correct working allow current for coil reject if repulsion mentioned allow creating (additional) and clockwise moment	3
W x 8 OR 0.1 x 12 W x 8 = 0.1 x 12 (W =) 0.15 (N) allow 0.2 (N) if supported by correct working	
a magnetic field; coil {attracts / exerts a force on} magnet; increasing anti-clockwise moment; (c) (i) sensible linear scales on both axes that occupy >50% of the grid; both axes labelled correctly with quantity and unit; correct orientation; all 6 points correctly plotted; reject if repulsion mentioned allow creating (additional) and clockwise moment reject if repulsion mentioned allow creating (additional) and clockwise moment allow symbols I for current an W for weight current on x-axis reject plotting mark if	
>50% of the grid; both axes labelled correctly with quantity and unit; correct orientation; all 6 points correctly plotted; >50% of the grid; allow symbols I for current an W for weight current on x-axis reject plotting mark if	3
non-linear scale used in region of plots	4
Current Total weight adde	
S 0.0 0.1	
0.1 0.5	1
Total 4 weight 0.5 2.1	
ndaid (N) 3 0.7 2.5	1
0.9 3.7	1
1.1 4.5	1
0 0.2 0.4 0.6 0.9 1.0 1.2 Considerat (A)	
(ii) straight line of best fit avoiding anomalous reading;	1
(iii) (repeat to) check accuracy / validity of reading; (because) reading appears to be anomalous; allow idea of checking to see same reading obtained again allow reading does not follow the trend / does not lie near the line of best fit	2

(iv)	pattern statement e.g. as current increases the force increases; suitable comment about linearity;	ignore references to weight allow (directly) proportional	2
(v)	relevant use of one set of data from graph or table; 8.1 (N);	exclude data from 0.7A reading allow ecf from line on graph allow answers that round to 8.1 (N)	2

Total for question 6 = 17 marks

	Questi numb		Answer	Notes	Marks
7	(a)	(i)	measuring cylinder;	allow graduated cylinder, burette, pipette, syringe	1
		(ii)	0.005 (cm ³)		1
	(b)	(i)	correctly calculated average; given to 3 significant figures; e.g. (average =) 300.8 (mm) (average to 3 s.f. =) 301 (mm)	DOP	2
		(ii)	use of radius in calculation; substitution and rearrangement; evaluation; e.g. radius = 150(.4) (mm) (length =) 1.0 / (π x 150.4 x 150.4)	allow ecf from (b)(i) throughout seen anywhere -1 for POT error answer of 3.5 x 10 ⁻⁶ (mm) gains 2 marks for using diameter instead of radius	3
			(length =) 1.4 x 10 ⁻⁵ (mm)	allow answers that round to 1.40-1.41	

Total for question 7 = 7 marks