



# Advanced Programming

## Error Handling & Exception Management in Java

**Instructor:** Ali Najimi

**Author:** Hossein Masihi

**Department of Computer Engineering**

**Sharif University of Technology**

**Fall 2025**





# Table of Contents

1. Traditional Error Management
2. Exception Handling in Java
3. `try` / `catch` / `finally`
4. Checked vs Unchecked Exceptions
5. Real-World Usage Examples
6. Visual Comparison Diagrams
7. Developer Humor (Break Slides)
8. Summary



# Before Exceptions — Traditional Error Management

```
int divide(int a, int b) {  
    if (b == 0) return -1; // error signal  
    return a / b;  
}
```

## Problems:

- Magic error values ( `-1` , `null` , etc.)
- Hard to detect real failure vs result
- No call stack → debugging is painful

Traditional error codes are weak and ambiguous.



# Exception Handling in Java

```
try {  
    // code that may fail  
} catch (Exception e) {  
    // recovery / fallback  
}
```

## Benefits:

- Clear failure path
- Stack trace preserved
- Encourages predictable failure patterns



## try / catch / finally

```
try {  
    FileReader f = new FileReader("data.txt");  
} catch (FileNotFoundException e) {  
    System.out.println("File not found");  
} finally {  
    System.out.println("Cleanup always runs");  
}
```

- **finally** always executes (except `System.exit()` / JVM crash).
- Use for **cleanup**: closing files, sockets, DB connections.



# Checked vs Unchecked Exceptions

Type	Inherits From	Must Handle?	Root Cause	Examples
Checked	Exception	Yes	External failures	IOException , SQLException
Unchecked	RuntimeException	No	Logic bugs	NullPointerException , ArithmeticException

Checked = environment uncertainty


Unchecked = programming mistake



# Visual Comparison — Checked

## Checked Exceptions

- Caused by environment (I/O, network)
- Developer must acknowledge the risk
- Encourages recovery strategy





# Visual Comparison — Unchecked

## Unchecked Exceptions

- Caused by incorrect logic in code
- No forced handling
- Should be solved by fixing logic






# Developer Humor Break

“It works on my machine.”

Translation:

I have absolutely no idea why it doesn't work anywhere else.






## Real-World Example — Checked

```
void loadConfig() throws IOException {  
    FileReader reader = new FileReader("config.json");  
    // process...  
}
```

- The file may not exist
- Storage may be corrupted
- Permissions may differ





## Real-World Example — Unchecked

```
void greet(User user) {  
    System.out.println(user.name); // may throw NullPointerException  
}
```

Correct approach:

```
void greet(User user) {  
    if (user == null) throw new IllegalArgumentException("User cannot be null");  
    System.out.println(user.name);  
}
```



## Developer Humor Break #2

Developer:

```
No need for error handling, my code cannot fail.
```

Production:

```
Exception: Are you sure about that?
```



# Big Picture Flow Diagram

Outside World (Unpredictable)



```
+-----+  
| CHECKED EXCEPTION |  
+-----+
```

Must handle or declare

Developer Logic (Bug)



```
+-----+  
| UNCHECKED EXCEPTION |  
+-----+
```

Fix the code logic



# Summary

Concept	Key Idea
Checked Exceptions	Handle real-world uncertainty
Unchecked Exceptions	Fix broken program logic
<code>finally</code>	Always used for cleanup
Good Practice	Fail clearly, fail meaningfully

Robust software is not only coded — it is **defensively designed**.



# Thank You!

**Sharif University of Technology — Advanced Programming — Fall 2025**