

# Day 6: Arrays & Array Methods

---

## صفیں اور طریقے

---

**Quote of the Day:** "Arrays are the backbone of data manipulation. Master them, and you master half of programming." - Kyle Simpson

"استعمال کرو۔ Arrays ایک سے زیادہ چیزوں کو سنبھالنا ہوتا ہے"






## Today's Learning Goals (آج کے اہداف)

---

By the end of today, you will:

- ☐ Create and manipulate arrays confidently
- ☐ Master array methods: push, pop, shift, unshift
- ☐ Use modern array methods: forEach, map, filter
- ☐ Understand zero-based indexing (0, 1, 2...)
- ☐ Build a Daraz Product Manager inventory system

## Time Breakdown (کل وقت: 150 منٹ)

-  7:00-7:05 PM (5min): Standup - Show your Utility Functions!
  -  7:05-8:05 PM (60min): Understanding arrays (3× Pomodoro)
  -  8:05-8:50 PM (45min): Practice with array methods
  -  8:50-9:25 PM (35min): Build Product Manager
  -  9:25-9:30 PM (5min): Quiz & reflection
-

## What We're Building Today

---

Today you'll create a **Daraz Product Manager** - an inventory system that stores products as array of objects, adds/removes items, filters out-of-stock products, calculates total value, and manages categories!

### Why This Matters for Your Career:

EVERY app uses arrays constantly:

- **Instagram:** Array of posts for your feed
- **Daraz:** Array of products in search results
- **WhatsApp:** Array of messages in each chat
- **YouTube:** Array of videos in your recommendations

Arrays are how we handle lists of data!

---

## سمجھنا (Understanding): What Are Arrays?

---

### The Real-World Analogy

#### Scenario: Aloo Paratha Layers (آلو پراٹھے کی تہیں)

Imagine you're making aloo paratha:

```
Layer 1 (top):    Ghee
Layer 2:          Dough
Layer 3:          Potato filling
Layer 4:          Dough
Layer 5 (bottom): Ghee
```

### This is an array!

- Each layer has a **position** (1st, 2nd, 3rd...)

- All layers are **stacked together**
- You can **add** more layers (push)
- You can **remove** layers (pop)
- Each layer can be **different** (ghee, dough, filling)

In JavaScript:

```
const paratha = ["Ghee", "Dough", "Potato", "Dough", "Ghee"];
```

## Daily Life Examples

### 1. Student Roll Numbers in Class:

```
Class List:
Position 0: Ali (Roll 101)
Position 1: Sara (Roll 102)
Position 2: Hassan (Roll 103)
Position 3: Fatima (Roll 104)
```

### 2. Cricket Batting Order:

```
Position 0: Babar Azam
Position 1: Fakhar Zaman
Position 2: Mohammad Rizwan
... (all the way to position 10)
```

### 3. Shopping Cart on Daraz:

```
Item 0: Laptop - Rs. 75,000
Item 1: Mouse - Rs. 1,200
Item 2: Keyboard - Rs. 3,500
```

## Why Does This Matter?

### Without arrays:

```
const student1 = "Ali";  
const student2 = "Sara";  
const student3 = "Hassan";  
const student4 = "Fatima";  
// ... for 100 students? 100 variables! 🤯
```

### With arrays:

```
const students = ["Ali", "Sara", "Hassan", "Fatima"];  
// Add 100 more? No problem!  
// One variable, unlimited data!
```

## The Mental Model

Think of an array like a **numbered row of dabbas** (ڈبوں کی قطار):

Index:	[0]	[1]	[2]	[3]
Value:	"Ali"	"Sara"	"Hassan"	"Fatima"
	↑	↑	↑	↑
	Dabba 0	Dabba 1	Dabba 2	Dabba 3

**Key point:** Arrays start counting at **ZERO** (not 1)!

---

## 📚 Building Block #1: Creating & Accessing Arrays

---

### What is an Array? (کیا ہے؟)

**Urdu Analogy:** Think of an array like a **tasbeeh** (تسبیح) - prayer beads on a string.

```
Bead 0: • (Bead at position 0)
Bead 1: • (Bead at position 1)
Bead 2: • (Bead at position 2)
... all on one string!
```

Each bead has a **position**, and they're all connected together!

## How to Create Arrays

```
// THINKING: Different ways to create arrays

// Method 1: Array literal (most common)
const cities = ["Lahore", "Karachi", "Islamabad"];

// Method 2: Empty array (add items later)
const scores = [];

// Method 3: Array with different types
const mixed = ["Ali", 20, true, "Lahore"];

// Method 4: Array constructor (less common)
const numbers = new Array(1, 2, 3);
```

## Zero-Based Indexing (سے شروع 0)

**CRITICAL:** Arrays start counting at **ZERO**, not one!

```
const cities = ["Lahore", "Karachi", "Islamabad", "Peshawar"];

// Index:      0          1          2          3
// Position: 1st      2nd      3rd      4th

console.log(cities[0]); // "Lahore" (first item!)
console.log(cities[1]); // "Karachi" (second item)
console.log(cities[2]); // "Islamabad" (third item)
console.log(cities[3]); // "Peshawar" (fourth item)
```

**Why zero-based?** It's a computer science convention. Just memorize: **first item = index 0!**

## Accessing Array Elements

```
// THINKING: Getting items from array

const fruits = ["Aam", "Kela", "Santra", "Angoor"];

// Get first item (index 0)
console.log(fruits[0]); // "Aam"

// Get last item (length - 1)
console.log(fruits[3]); // "Angoor"
console.log(fruits[fruits.length - 1]); // "Angoor" (works for any
length!)

// Get item in middle
console.log(fruits[1]); // "Kela"

// Try to get item that doesn't exist
console.log(fruits[10]); // undefined (no error, just undefined)
```

## Array Length Property

```
const students = ["Ali", "Sara", "Hassan"];

console.log(students.length); // 3 (total number of items)

// Last item is always at: length - 1
console.log(students[students.length - 1]); // "Hassan"
```

## Your First Example

```
// TODO: Create array of Pakistani cities
const cities = ["Lahore", _____, _____, _____];

// TODO: Access first city
console.log("First city:", cities[_____]);

// TODO: Access last city
console.log("Last city:", cities[cities._____ - 1]);

// TODO: How many cities?
console.log("Total cities:", cities._____);

// TODO: Access city at index 2
console.log("City at index 2:", cities[_____]);
```

## Common Mistakes

### ✗ Wrong:

```
const arr = ["A", "B", "C"];
console.log(arr[1]); // "A" ?
```

**Why wrong?** First item is index 0, not 1!

### ✓ Right:

```
const arr = ["A", "B", "C"];
console.log(arr[0]); // "A" ✓
console.log(arr[1]); // "B" ✓
```

### ✗ Wrong:

```
const arr = ["A", "B", "C"];
console.log(arr[arr.length]); // undefined (out of bounds!)
```

✅ Right:

```
const arr = ["A", "B", "C"];
console.log(arr[arr.length - 1]); // "C" (last item)
```

## Check Your Understanding

- ☐ What index is the first item?
- ☐ How do you get the last item?
- ☐ What does array.length return?
- ☐ What happens if you access index 100 in a 3-item array?

## Building Block #2: Modifying Arrays (push, pop, shift, unshift)

### What are Array Methods? (کیا ہیں؟)

**Urdu Analogy:** Think of a **queue at National Bank** (قطار):

```
push()    = Join queue at END (آخر میں آنا)
pop()     = Leave from END (آخر سے جانا)
unshift() = Cut the line at START (شروع میں آنا)
shift()   = Leave from START (شروع سے جانا)
```



## 1. push() - Add to End

```
// THINKING: Adding items to array

const fruits = ["Aam", "Kela"];
console.log(fruits); // ["Aam", "Kela"]

fruits.push("Santra");
console.log(fruits); // ["Aam", "Kela", "Santra"]

fruits.push("Angoor");
console.log(fruits); // ["Aam", "Kela", "Santra", "Angoor"]

// Can add multiple at once!
fruits.push("Anar", "Seb");
console.log(fruits); // ["Aam", "Kela", "Santra", "Angoor", "Anar", "Seb"]
```

## 2. pop() - Remove from End

```
// THINKING: Removing items from end

const cities = ["Lahore", "Karachi", "Islamabad"];
console.log(cities); // ["Lahore", "Karachi", "Islamabad"]

const removed = cities.pop();
console.log(removed); // "Islamabad" (returns removed item!)
console.log(cities); // ["Lahore", "Karachi"]

cities.pop();
console.log(cities); // ["Lahore"]
```

### 3. unshift() - Add to Start

```
// THINKING: Adding to front (cutting the line!)

const numbers = [2, 3, 4];
console.log(numbers); // [2, 3, 4]

numbers.unshift(1);
console.log(numbers); // [1, 2, 3, 4]

numbers.unshift(0);
console.log(numbers); // [0, 1, 2, 3, 4]
```

### 4. shift() - Remove from Start

```
// THINKING: Removing from front

const queue = ["Ali", "Sara", "Hassan"];
console.log(queue); // ["Ali", "Sara", "Hassan"]

const served = queue.shift();
console.log(served); // "Ali" (first person served!)
console.log(queue); // ["Sara", "Hassan"]
```

## Visual Summary

```
Original: ["A", "B", "C"]

push("D"):   ["A", "B", "C", "D"]    // Add to end
pop():       ["A", "B"]              // Remove from end
unshift("Z"): ["Z", "A", "B", "C"]    // Add to start
shift():     ["B", "C"]              // Remove from start
```

## Your First Example

```
// TODO: Practice array methods

const cart = ["Laptop"];

// TODO: Add "Mouse" to end
cart._____(_____);

// TODO: Add "Keyboard" to end
cart._____(_____);

console.log(cart); // ["Laptop", "Mouse", "Keyboard"]

// TODO: Remove last item
cart._____(_____);

console.log(cart); // ["Laptop", "Mouse"]

// TODO: Add "Headphones" to start
cart._____(_____);

console.log(cart); // ["Headphones", "Laptop", "Mouse"]
```

## Common Mistakes

### ✗ Wrong:

```
const arr = [1, 2, 3];
arr.push = 4; // Not how push works!
```

### ✓ Right:

```
const arr = [1, 2, 3];
arr.push(4); // Use parentheses to call method
```

### ✗ Wrong:

```
const arr = [1, 2, 3];  
const removed = arr.pop;  // Missing ()
```

### ✓ Right:

```
const arr = [1, 2, 3];  
const removed = arr.pop();  // Call the method!
```

## Check Your Understanding

- ☐ Which method adds to the end?
- ☐ Which method removes from the start?
- ☐ What does pop() return?
- ☐ Can you add multiple items with push()?

## Building Block #3: Looping Through Arrays

### Why Loop Arrays? (کیوں؟)

**Urdu Analogy:** Think of **checking each student's attendance** (حاضری):

```
For each student in class:  
  Call their name  
  Mark present/absent
```

Same with arrays - do something for EACH item!

## Method 1: for Loop (Traditional)

```
// THINKING: Loop with index

const cities = ["Lahore", "Karachi", "Islamabad"];

for (let i = 0; i < cities.length; i++) {
  console.log("City " + i + ":", cities[i]);
}

// Output:
// City 0: Lahore
// City 1: Karachi
// City 2: Islamabad
```

## Method 2: forEach() (Modern & Clean)

```
// THINKING: forEach automatically loops

const cities = ["Lahore", "Karachi", "Islamabad"];

cities.forEach(function(city) {
  console.log("City:", city);
});

// Even cleaner with arrow function:
cities.forEach(city => {
  console.log("City:", city);
});

// Output:
// City: Lahore
// City: Karachi
// City: Islamabad
```

## forEach with Index

```
// THINKING: Sometimes you need the index too

const students = ["Ali", "Sara", "Hassan"];

students.forEach((student, index) => {
  console.log(`Student ${index + 1}: ${student}`);
});

// Output:
// Student 1: Ali
// Student 2: Sara
// Student 3: Hassan
```

## Your First Example

```
const prices = [500, 1200, 350, 890];

// TODO: Loop and print each price
// HINT: Use forEach

prices.forEach(price => {
  console.log("Rs. " + _____);
});

// TODO: Calculate total using forEach
let total = 0;

prices.forEach(price => {
  total _____ price;
});

console.log("Total:", total);
```

## Check Your Understanding

- ☐ What's the difference between for and forEach?
- ☐ Can forEach access the index?

- ☐ Which is more modern?

---

## Building Block #4: Array Methods - map() and filter()

---

What is map()? (کیا ہے؟)

**Urdu Analogy:** Think of **tailor converting measurements** (درزی ناپ بدلتا ہے):

```
Input:  [32, 34, 36, 38] (inches)
Process: Convert each to cm (× 2.54)
Output: [81.28, 86.36, 91.44, 96.52] (cm)
```

**map() transforms each item and returns a NEW array!**

How map() Works

```
// THINKING: Transform all items

const prices = [100, 200, 300];

// Add 10% tax to each price
const withTax = prices.map(price => {
  return price * 1.1;
});

console.log(prices); // [100, 200, 300] (original unchanged!)
console.log(withTax); // [110, 220, 330] (new array!)
```

## Real Example: Format Currency

```
const amounts = [500, 1500, 2500];

const formatted = amounts.map(amount => {
  return "Rs. " + amount;
});

console.log(formatted);
// ["Rs. 500", "Rs. 1500", "Rs. 2500"]
```

## What is filter()? (کیا ہے؟)

**Urdu Analogy:** Think of **sorting rice** (چاول چھاننا):

```
Input: [good grain, stone, good grain, bad grain, good grain]
Filter: Keep only good grains
Output: [good grain, good grain, good grain]
```

**filter() selects items that pass a test!**

## How filter() Works

```
// THINKING: Keep only items that match condition

const numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10];

// Get only even numbers
const evenNumbers = numbers.filter(num => {
  return num % 2 === 0;
});

console.log(evenNumbers); // [2, 4, 6, 8, 10]
```



## Real Example: Filter by City

```
const cities = ["Lahore", "Karachi", "Larkana", "Islamabad", "Lyallpur"];

// Get cities starting with 'L'
const lCities = cities.filter(city => {
  return city.startsWith("L");
});

console.log(lCities);
// ["Lahore", "Larkana", "Lyallpur"]
```

## Combining map() and filter()

```
// THINKING: Chain methods together!

const prices = [50, 150, 300, 80, 250];

// Get expensive items (>100) and add tax
const expensiveWithTax = prices
  .filter(price => price > 100)
  .map(price => price * 1.1);

console.log(expensiveWithTax);
// [165, 330, 275] (only items >100, with 10% tax)
```

## Your First Example

```
const marks = [45, 78, 92, 33, 67, 88];

// TODO: Use filter to get passing marks ( $\geq 50$ )
const passing = marks.filter(mark  $\Rightarrow$  {
  return mark  $\geq$  50;
});

console.log("Passing:", passing);

// TODO: Use map to convert marks to percentages
const percentages = marks.map(mark  $\Rightarrow$  {
  return mark + "%";
});

console.log("Percentages:", percentages);

// TODO: Get students who scored above 80
const excellent = marks.filter(mark  $\Rightarrow$  mark  $\geq$  80);
console.log("Excellent:", excellent);
```

## Common Mistakes

### ✗ Wrong:

```
const doubled = numbers.map(num  $\Rightarrow$  {
  num * 2; // Missing return!
});
// Result: [undefined, undefined, undefined]
```

### ✓ Right:

```
const doubled = numbers.map(num  $\Rightarrow$  {
  return num * 2;
});
// OR (arrow function shorthand):
const doubled = numbers.map(num  $\Rightarrow$  num * 2);
```

## Check Your Understanding

- ☐ What does `map()` return?
  - ☐ What does `filter()` return?
  - ☐ Does `map()` change the original array?
  - ☐ Can you chain `map()` and `filter()`?
- 

## Practice Session: Array Mastery

---

### Practice Goal

By the end of this section, you'll manipulate arrays like a pro!

### Exercise 1: Pakistani Cities (ہم ساتھ کریں)

**Scenario:** Manage a list of Pakistani cities

**Starter Code:**

```
// TODO Step 1: Create array
const cities = ["Lahore", "Karachi", "Islamabad"];

// TODO Step 2: Add "Peshawar" to end
cities._____(_____);

// TODO Step 3: Add "Quetta" to end
cities._____(_____);

// TODO Step 4: Print all cities using forEach
cities.forEach(city => {
  console.log("• " + _____);
});

// TODO Step 5: Get cities starting with 'L'
const lCities = cities.filter(city => {
  return city._____(_____)
});

console.log("Cities with L:", lCities);
```

---

## Exercise 2: Shopping Cart Total (اب آپ)

**Problem:** Calculate total price of items in cart

### Requirements:

- ☐ Array of prices
- ☐ Calculate total using forEach
- ☐ Apply 15% discount to all items using map
- ☐ Filter items over Rs. 1000

### Starter Code:

```

const cartPrices = [500, 1500, 350, 2500, 750];

// TODO: Calculate total
let total = 0;
cartPrices.forEach(price => {
    total _____ price;
});
console.log("Total: Rs.", total);

// TODO: Apply 15% discount
const discounted = cartPrices.map(price => {
    return price _____ 0.85;
});
console.log("After discount:", discounted);

// TODO: Get expensive items (>1000)
const expensive = cartPrices.filter(price => {
    return price _____ 1000;
});
console.log("Expensive items:", expensive);

```

**Don't Look Below Until You Try!** 

---

### Hints (if stuck):

► Stuck on total?

```

cartPrices.forEach(price => {
    total += price; // Same as total = total + price
});

```

► Stuck on discount?

```

const discounted = cartPrices.map(price => {
    return price * 0.85; // 85% of original (15% off)
});

```

---

## Exercise 3: Student Grades

**Problem:** Process student grades

```
const students = [
  { name: "Ali", marks: 85 },
  { name: "Sara", marks: 92 },
  { name: "Hassan", marks: 78 },
  { name: "Fatima", marks: 45 }
];

// TODO: Get all student names
const names = students.map(student => {
  return student.____;
});
console.log("Names:", names);

// TODO: Get students who passed (marks ≥ 50)
const passed = students.filter(student => {
  return student.____ ≥ 50;
});
console.log("Passed:", passed);

// TODO: Get names of students who scored above 80
const toppers = students
  .filter(student => student.marks _____ 80)
  .map(student => student.____);

console.log("Toppers:", toppers);
```

---

## آج کا چیلنج (Today's Challenge)

### Project: Daraz Product Manager

ڈراز پروڈکٹ مینیجر

### The Problem:

You're managing inventory for a Daraz-style e-commerce platform! Build a product management system that handles adding products, removing out-of-stock items, calculating inventory value, finding expensive products, and filtering by category!

### What You're Building:

A console-based inventory system with array methods

### Success Criteria:

- ☐ Stores products as array of objects
  - ☐ Can add new products
  - ☐ Filters out-of-stock items
  - ☐ Calculates total inventory value
  - ☐ Finds most expensive product
  - ☐ Filters by category
  - ☐ Has search function
- 

## Phase 1: Planning (سوچیں پہلے)

Before coding, answer:

### 1. What structure for products?

```
{  
  name: "Laptop",  
  price: 75000,  
  stock: 5,  
  category: "Electronics"  
}
```

### 2. What operations do I need?

- Add product (push)
- Remove out-of-stock (filter)

- Calculate total value (forEach or reduce)
- Find max price (loop and compare)
- Filter by category (filter)
- Search by name (filter)

### 3. How will I test it?

- Start with sample products
- Test each function separately
- Check console output

#### Planning Checkpoint:

- ☐ I understand the product structure
  - ☐ I know which array methods to use
  - ☐ I have test cases in mind
- 

## Phase 2: Foundation (بنياد)

### Starter Code:



```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Daraz Product Manager</title>
</head>
<body>
  <h1>🛒 Daraz Product Manager</h1>
  <h2>ڈراز پروڈکٹ مینیجر</h2>
  <h3>Press F12 to see inventory management in action!</h3>

  <script>
    // =====
    // DARAZ PRODUCT MANAGER
    // By: [Your Name]
    // Date: [Today's Date]
    // =====

    console.log("🛒 ڈراز پروڈکٹ مینیجر");
    console.log("=====\n");

    // ===== INITIAL INVENTORY =====

    let products = [
      { name: "Laptop HP", price: 75000, stock: 5, category:
"Electronics" },
      { name: "Mouse Wireless", price: 1200, stock: 15, category:
"Electronics" },
      { name: "Office Chair", price: 8500, stock: 0, category:
"Furniture" },
      { name: "Desk Lamp", price: 2500, stock: 8, category:
"Furniture" },
      { name: "Notebook A4", price: 150, stock: 50, category:
"Stationery" },
      { name: "Pen Set", price: 300, stock: 0, category: "Stationery"
},
      { name: "Water Bottle", price: 450, stock: 20, category:
"Accessories" }
    ];

    console.log("📦 INITIAL INVENTORY");
    console.log("Total products:", products.length);
    console.log("");

    // ===== FUNCTION 1: Display All Products =====

    function displayProducts(productList) {

```

```

    console.log("📋 PRODUCT LIST:");
    console.log("_____");

    // TODO: Use forEach to display each product
    productList.forEach((product, index) => {
        const status = product.stock > 0 ? "✅ In Stock" : "❌ Out
of Stock";

        console.log(`${index + 1}. ${product.name}`);
        console.log(`    Price: Rs. ${product.price}`);
        console.log(`    Stock: ${product.stock} units`);
        console.log(`    Category: ${product.category}`);
        console.log(`    Status: ${status}`);
        console.log("----");
    });
    console.log("");
}

displayProducts(products);

// ===== FUNCTION 2: Add New Product =====

function addProduct(name, price, stock, category) {
    // TODO: Create product object
    const newProduct = {
        name: _____,
        price: _____,
        stock: _____,
        category: _____
    };

    // TODO: Add to products array
    products._____(newProduct);

    console.log(`✅ Added: ${name}`);
}

console.log("✚ ADDING NEW PRODUCTS");
addProduct("Keyboard Mechanical", 5500, 10, "Electronics");
addProduct("Monitor 24\"", 22000, 3, "Electronics");
console.log("");

// ===== FUNCTION 3: Remove Out-of-Stock Items =====

function removeOutOfStock() {
    console.log("🗑 REMOVING OUT-OF-STOCK ITEMS");

    // TODO: Count out-of-stock items
    const outOfStock = products.filter(product => {
        return product.stock _____ 0;
    });
}

```

```

    });

    console.log(`Found ${outOfStock.length} out-of-stock items:`);
    outOfStock.forEach(product => {
        console.log(`• ${product.name}`);
    });

    // TODO: Filter to keep only in-stock items
    products = products.filter(product => {
        return product.stock > 0;
    });

    console.log(`✅ Removed! Now ${products.length} products in
stock`);
    console.log("");
}

removeOutOfStock();

// ===== FUNCTION 4: Calculate Total Inventory Value
=====

function calculateTotalValue() {
    // TODO: Calculate total value (price × stock for each item)
    let totalValue = 0;

    products.forEach(product => {
        totalValue += product.price * product.stock;
    });

    console.log("💰 TOTAL INVENTORY VALUE");
    console.log(`Rs. ${totalValue.toLocaleString()}`);
    console.log("");

    return totalValue;
}

calculateTotalValue();

// ===== FUNCTION 5: Find Most Expensive Product =====

function findMostExpensive() {
    // TODO: Find product with highest price
    let maxPrice = 0;
    let expensive = null;

    products.forEach(product => {
        if (product.price > maxPrice) {
            maxPrice = product.price;

```

```

        expensive = product;
    }
});

console.log("💎 MOST EXPENSIVE PRODUCT");
console.log(`${expensive.name}: Rs. ${expensive.price}`);
console.log("");

return expensive;
}

findMostExpensive();

// ===== FUNCTION 6: Filter by Category =====

function filterByCategory(category) {
    // TODO: Get all products in this category
    const filtered = products.filter(product => {
        return product.category === category;
    });

    console.log(`📁 ${category.toUpperCase()} PRODUCTS`);
    console.log(`Found ${filtered.length} items`);

    filtered.forEach(product => {
        console.log(`• ${product.name} - Rs. ${product.price}`);
    });
    console.log("");

    return filtered;
}

filterByCategory("Electronics");
filterByCategory("Furniture");

// ===== FUNCTION 7: Search Products =====

function searchProducts(searchTerm) {
    // TODO: Find products containing search term
    const results = products.filter(product => {
        // Convert to lowercase for case-insensitive search
        return
product.name.toLowerCase().includes(searchTerm.toLowerCase());
    });

    console.log(`🔍 SEARCH: "${searchTerm}"`);

    if (results.length === 0) {
        console.log("No products found");
    }
}

```

```

    } else {
        console.log(`Found ${results.length} result(s):`);
        results.forEach(product => {
            console.log(`• ${product.name} - Rs.
${product.price}`);
        });
    }
    console.log("");

    return results;
}

searchProducts("Laptop");
searchProducts("Mouse");
searchProducts("Chair");

// ===== FUNCTION 8: Get Product Names Only =====

function getProductNames() {
    // TODO: Use map to get array of just names
    const names = products.map(product => {
        return product.____;
    });

    console.log("📋 ALL PRODUCT NAMES");
    console.log(names.join(", "));
    console.log("");

    return names;
}

getProductNames();

// ===== FUNCTION 9: Apply Discount =====

function applyDiscount(percent) {
    // TODO: Create new array with discounted prices
    const discounted = products.map(product => {
        return {
            ...product, // Copy all properties
            originalPrice: product.price,
            price: product.price ____ (1 - percent / 100)
        };
    });

    console.log(`💰 ${percent}% DISCOUNT APPLIED`);
    console.log("Sample:");
    discounted.slice(0, 3).forEach(product => {
        console.log(`${product.name}`);
    });
}

```

```

        console.log(` Was: Rs. ${product.originalPrice}`);
        console.log(` Now: Rs. ${product.price.toFixed(2)}`);
    });
    console.log("");

    return discounted;
}

applyDiscount(15); // 15% off!

// ===== SUMMARY =====

console.log("=====");
console.log("📊 INVENTORY SUMMARY");
console.log("=====");
console.log(`Total Products: ${products.length}`);
console.log(`Total Categories: ${[...new Set(products.map(p =>
p.category))].length}`);
console.log(`Total Value: Rs.
${calculateTotalValue().toLocaleString()}`);
console.log(`Most Expensive: ${findMostExpensive().name}`);
console.log("=====");

</script>
</body>
</html>

```

## Phase 3: Milestones (سنگ میل)

### Milestone 1: Basic Display Works

- ☐ Products array created
- ☐ displayProducts shows all items
- ☐ Each product shows correctly
- Test: Can you see all 7 products?

### Milestone 2: Add/Remove Works

- ☐ addProduct adds new items
- ☐ removeOutOfStock filters correctly

- ☐ Array length changes correctly
- Test: Add 2 products, should have 9 total

### Milestone 3: Calculations Work ☒

- ☐ Total value calculates correctly
- ☐ Most expensive product found
- ☐ Math is accurate
- Test: Manual check total value

### Milestone 4: Filtering Works ☒

- ☐ Category filter returns correct items
  - ☐ Search function finds products
  - ☐ Case-insensitive search works
  - Test: Search "laptop" and "LAPTOP" both work
- 

## Debugging Guide (اگر پھنس جائیں)

### Problem: forEach not working

- ☐ Check: Are you using parentheses? `.forEach()`
- ☐ Check: Is the parameter name consistent?
- ☐ Check: Did you use arrow function correctly?

### Problem: filter returns empty array

- ☐ Check: Is your condition correct?
- ☐ Check: Are you using `===` not `=`?
- ☐ Add `console.log` inside filter to see what's happening

### Problem: map returns undefined

- ☐ Check: Did you use `return` keyword?

- ☐ Check: Are you returning the right thing?
- ☐ Check: Arrow function shorthand: `item ⇒ item.prop`

### Common Logic Issues:

```
// ❌ WRONG: Forgot return
const names = products.map(product ⇒ {
  product.name; // Missing return!
});

// ✅ RIGHT:
const names = products.map(product ⇒ {
  return product.name;
});

// OR
const names = products.map(product ⇒ product.name);
```

## Extension Challenges (بونس چیلنج)

If you finish early:

### 🌟 Level 1: Advanced Filters

```
// Get products between price range
function getByPriceRange(min, max) {
  return products.filter(p ⇒ p.price ≥ min && p.price ≤ max);
}

// Sort by price (low to high)
function sortByPrice() {
  return [...products].sort((a, b) ⇒ a.price - b.price);
}
```

### 🌟🌟 Level 2: Statistics



```

// Calculate average price
function getAveragePrice() {
    const total = products.reduce((sum, p) => sum + p.price, 0);
    return total / products.length;
}

// Get low stock items (< 5)
function getLowStock() {
    return products.filter(p => p.stock < 5 && p.stock > 0);
}

```

### \*\*\* Level 3: Advanced Features

```

// Group products by category
function groupByCategory() {
    const grouped = {};
    products.forEach(product => {
        if (!grouped[product.category]) {
            grouped[product.category] = [];
        }
        grouped[product.category].push(product);
    });
    return grouped;
}

// Generate inventory report
function generateReport() {
    // Create detailed report with all statistics
}

```

## Daily Quiz (منٹ کا ٹیسٹ 5)

**Instructions:** Answer WITHOUT looking at notes!

### 1. What index is the first item in an array?

- A) 1

- B) 0
- C) -1
- D) Depends on array

► See Answer (Try first!)

**Answer: B** - 0. Arrays are zero-based, meaning the first item is at index 0. Remember: first item = index 0, second item = index 1, etc.

---

## 2. What does push() do?

- A) Removes first item
- B) Adds item to start
- C) Adds item to end
- D) Removes last item

► See Answer (Try first!)

**Answer: C** - Adds item to end. Think of joining a queue (قطار) at the end. `push()` adds to end, `pop()` removes from end.

---

## 3. What's the difference between map() and forEach()?

- A) They're the same
- B) map() returns new array, forEach() doesn't
- C) forEach() is faster
- D) map() only works with numbers

► See Answer (Try first!)

**Answer: B** - map() transforms each item and returns a NEW array. forEach() just loops through items and returns nothing. Use map() when you want to transform data!

---

#### 4. What will this return?

```
const arr = [1, 2, 3, 4, 5];  
const result = arr.filter(num => num > 3);
```

- A) [4, 5]
- B) [1, 2, 3]
- C) [3, 4, 5]
- D) [1, 2, 3, 4, 5]

► See Answer (Try first!)

**Answer: A** - [4, 5]. `filter()` keeps only items that pass the test. Only 4 and 5 are greater than 3, so only they remain.

---

#### 5. How do you get the last item of array `arr`?

- A) `arr[arr.length]`
- B) `arr[-1]`
- C) `arr[arr.length - 1]`
- D) `arr.last()`

► See Answer (Try first!)

**Answer: C** - `arr[arr.length - 1]`. If array has 5 items, length is 5, but last index is 4 (zero-based). So `length - 1` gives you the last index!

---

#### Scoring:

- **5/5:** 🎉 Array Master! You crushed it!
- **4/5:** 🤝 Excellent! Review the one you missed

- 3/5: 👍 Good! Practice array methods more



- /5: 🤔 Review all array concepts again

---

## 🎓 Today's Homework (گھر کا کام)

---

### Required (لازمی):

- ☐ Complete the Daraz Product Manager
- ☐ Test all functions with different data
- ☐ Explain to a family member: "What is an array?" using aloo paratha analogy

### Optional (اختیاری):

- ☐ Try the extension challenges
- ☐ Create a "Contact Book" using array of objects
- ☐ Build a "Todo List" with array methods
- ☐ Make a "Student Grade Manager" similar to Product Manager

### For Tomorrow:

- ☐ Think about: "How would I store related data together?"
- ☐ Arrays hold lists, but what about complex data?
- ☐ Tomorrow: Objects & JSON!

---

## 💭 Daily Reflection (روزانہ کی سوچ)

---

### What I Learned Today (آج میں نے کیا سیکھا)

---

---

مشکل کیا لگا (What I Found Difficult):

---

---

مزید کیا سیکھنا ہے (What I Want to Explore More):

---

---

My Confidence Level (1-10): \_\_\_\_\_

---

## Tomorrow's Preview

---

Tomorrow we'll learn about **Objects & JSON** where you'll build a **Restaurant Menu System!**

You'll learn how to:

- Store complex data in objects
- Access object properties
- Work with nested objects
- Convert between objects and JSON
- Build real-world data structures

**Get Ready By:**

- ☐ Making sure your Product Manager works
- ☐ Thinking: What if product needed more data? (images, reviews, ratings)
- ☐ Objects are the answer!

---

## Resources (اگر مزید پڑھنا ہو)

---

### Free Resources (3G-Friendly):

#### MDN - Arrays

- Link: [https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global\\_Objects/Array](https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array)
- Best for: Complete array methods reference

#### JavaScript Arrays in Urdu

- Search: "JavaScript array methods Urdu map filter"
- Best for: Visual learners

#### Practice Arrays

- Create arrays for: shopping lists, student names, cricket scores
- Practice: `forEach`, `map`, `filter` with real data

---

### CodeSensei's Tip of the Day:

*"Arrays are everywhere in real apps. Master `map()` and `filter()` - they're used constantly in professional code. When you see a list of anything on a website, that's an array being displayed. Instagram posts? Array. YouTube videos? Array. Daraz products? Array. Think in arrays!"*

*"سیکھ لو - پروفیشنل کوڈ میں ہر جگہ استعمال ہوتے ہیں۔ `filter()` اور `map()` ہر جگہ ہیں۔ Arrays"*

---

## Team Activity (Tomorrow's Standup)

---

**Tomorrow at 7:00 PM, be ready to share:**

1. Your Product Manager's total inventory value
  2. One array method you found most useful
  3. Explain the difference between push() and unshift() in Urdu
  4. One question about arrays
- 

کوڈ سیکھنا ایک سفر ہے، منزل نہیں۔ ہر دن ایک قدم آگے۔

*"Learning to code is a journey, not a destination. One step forward every day."*

**Day 6 Complete! See you tomorrow for Objects & JSON! 🚀**

اللہ حافظ! Tomorrow we structure our data better! 📁