



Chapter 9:

Image Segmentation

9.1 Introduction

- **Segmentation** is the operation of partitioning an image into component parts or into separate objects.
- In this chapter, we will investigate two very important topics: **thresholding** and **edge detection**
 - Single & double thresholding
 - How to determine the threshold value
 - Adaptive thresholding
 - Edge detection: 1st and 2nd derivatives
 - Canny edge detector
 - Hough Transform

Single Thresholding

- grayscale image -> binary image

A pixel becomes $\begin{cases} \text{white if its gray level is } > T, \\ \text{black if its gray level is } \leq T. \end{cases}$

```
>> r=imread('rice.tif');  
>> imshow(r),figure,imshow(r>110)
```





FIGURE 9.1 Thresholded image of rice grains.

Single Thresholding

```
>> b=imread('bacteria.tif');  
>> imshow(b),figure,imshow(b>100)
```



CRC Press

FIGURE 9.2 *Thresholded image of bacteria.*

Single Thresholding in Matlab: `im2bw()`

- MATLAB has the **`im2bw`** function, which thresholds an image, using the general syntax.
- It works on grayscale, colored, and indexed images of data type `uint8`, `uint16`, or `double`.

```
im2bw(image, level)
```



e.g.

```
>> im2bw(r, 0.43);  
>> im2bw(b, 0.39);
```

- choosing an appropriate value of T is important.

```
>> p=imread('paper1.tif');  
>> imshow(p), figure, imshow(p>241)
```

Nearly all gray values are very high.



Double Thresholding

- grayscale image with two thresholds -> binary image

a pixel becomes $\begin{cases} \text{white if its gray level is between } T_1 \text{ and } T_2, \\ \text{black if its gray level is otherwise.} \end{cases}$

```
>> [x,map]=imread('spine.tif');  
>> s=ind2gray(x,map);  
>> imshow(s),figure,imshow(s>115 & s<125)
```




FIGURE 9.4 The image *spine.tif* as the result after double thresholding.

Applications of Thresholding

1. Remove unnecessary detail: e.g. rice and bacteria images
2. bring out hidden detail : e.g. paper and spine images
3. remove a varying background from text or a drawing




FIGURE 9.5 Text on a varying background and thresholding.

Choosing an Appropriate Thresholding Value

```
>> n=imread('nodules1.tif');  
>> imshow(n);  
>> n1=im2bw(n,0.35);  
>> n2=im2bw(n,0.75);  
>> figure,imshow(n1),figure,imshow(n2)
```




FIGURE 9.6 *Attempts at thresholding.*

Histogram Analysis




FIGURE 9.7 *Histograms.*

Histogram Analysis

- Choosing a threshold value is easy only if we have a prior knowledge of individual histograms of objects and background.
 - However, in general, histogram of object and background is overlapped so that we cannot easily determine the appropriate threshold values.
- > needs more intelligent way to choose an optimal threshold.




FIGURE 9.8 *Splitting up a histogram for thresholding.*

Otsu's Method:

Choosing an Appropriate Thresholding Value

- Good classifier should be able to divide two classes so that each class has a small variance.
- method 1: Find threshold value **t** that makes sum of variances of two classes becomes minimum.

$$t = \arg \min_k [\omega_1(k) \text{var}_1(k) + \omega_2(k) \text{var}_2(k)]$$
$$\omega_1(k) = \sum_{i=0}^k p_i, \quad \omega_2(k) = \sum_{i=k+1}^{255} p_i$$

probability of pixel value i

*minimizes
within-class
variance*

- method 2(**faster**): Find threshold value **t** that makes difference of weighted average of two classes becomes maximum.

$$t = \arg \max_k [\omega_1(k) \omega_2(k) (\mu_1(k) - \mu_2(k))^2]$$

*maximizes
between-class
variance*

- Matlab command: `graythresh()`
- http://en.wikipedia.org/wiki/Otsu's_method

Example of Otsu's Method

```
>> tn=graythresh(n)

tn =

    0.5804

>> r=imread('rice.tif');
>> tr=graythresh(r)

tr =

    0.4902

>> b=imread('bacteria.tif');
>> tb=graythresh(b)

tb =

    0.3765

>> e=imread('eight.tif');
>> te=graythresh(e)

te =

    0.6490
```

```
>> imshow(im2bw(n,tn))
>> figure,imshow(im2bw(r,tr))
>> figure,imshow(im2bw(b,tb))
>> figure,imshow(im2bw(e,te))
```




FIGURE 9.9 Thresholding with values from *graythresh*.


Otsu's Method: Assumptions

- Histogram (and the image) are *bimodal*.
- No use of *spatial coherence*, nor any other notion of object structure.
- Assumes uniform illumination (implicitly), so the bimodal brightness behavior arises from object appearance differences only.

Adaptive Thresholding

- Sometimes a single global threshold values (even if it was extracted by Otsu's method) does not work.
 - Needs to determine the threshold values in each image block depending on the characteristic of each block.
- > adaptively thresholding

```
>> c=imread('circles.tif');  
>> x=ones(256,1)*[1:256];  
>> c2=double(c).*(x/2+50)+(1-double(c)).*x/2;  
>> c3=uint8(255*mat2gray(c2));
```



c3 from circles.tif




global thresholding

```
>> t=graythresh(c3)  
  
t =  
  
    0.4196  
  
>> ct=im2bw(c3,t);
```


Adaptive Thresholding

Problem
determination by
3D surface plots

surface plot of c3



global threshold
(black plane) onto c3




solution: apply blockwise thresholding adaptively

blkproc and
im2bw: pp233


```
>> p1=c3(:,1:64);  
>> p2=c3(:,65:128);  
>> p3=c3(:,129:192);  
>> p4=c3(:,193:256);
```

```
>> g1=im2bw(p1,graythresh(p1));  
>> g2=im2bw(p2,graythresh(p2));  
>> g3=im2bw(p3,graythresh(p3));  
>> g4=im2bw(p4,graythresh(p4));
```

```
>> imshow([g1 g2 g3 g4])
```



4 sub-blocks



Edge Detection in Matlab

- The general MATLAB command for finding edges is

```
edge(image, 'method', parameters . . .)
```

| | | | |
|----|----|----|----|
| 51 | 52 | 53 | 59 |
| 54 | 52 | 53 | 62 |
| 50 | 52 | 53 | 68 |
| 55 | 52 | 53 | 55 |


(a)

| | | | |
|----|----|-----|-----|
| 50 | 53 | 155 | 160 |
| 51 | 53 | 160 | 170 |
| 52 | 53 | 167 | 190 |
| 51 | 53 | 162 | 155 |

(b)

FIGURE 9.13 *Blocks of pixels.*

Derivatives and Edges




- derivative $f'(x) = df/dx$
- discrete version: $f(x+1) - f(x)$, $f(x) - f(x-1)$, $(f(x+1) - f(x-1))/2$
- Expansion into 2D image -> **gradient**

$$\begin{bmatrix} \frac{\partial f}{\partial x} & \frac{\partial f}{\partial y} \end{bmatrix} \xrightarrow{\text{magnitude}} \sqrt{\left(\frac{\partial f}{\partial x}\right)^2 + \left(\frac{\partial f}{\partial y}\right)^2}$$

Edge Detection Filters: Prewitt

$$P_x = \begin{bmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{bmatrix} \quad P_y = \begin{bmatrix} -1 & -1 & -1 \\ 0 & 0 & 0 \\ 1 & 1 & 1 \end{bmatrix}$$

```
>> ic=imread('ic.tif');
```




```
>> px=[-1 0 1;-1 0 1;-1 0 1];  
>> icx=filter2(px,ic);  
>> figure,imshow(icx/255)
```



Prewitt filter: Px


```
>> py=px';  
>> icy=filter2(py,ic);  
>> figure,imshow(icy/255)
```



Prewitt filter: Py

Edge Detection by Prewitt Filter


magnitude of
gradient images
(icx and icy)
-> gray scale



(a)

```
>> edge_p=sqrt(icx.^2+icy.^2);  
>> figure,imshow(edge_p/255)
```

Thresholding
magnitude of
gradient images
-> binary



(b)

```
>> edge_t=im2bw(edge_p/255,0.3);
```

`edge()` in matlab:
Prewitt magnitude +
thresholding + some
extra processing




FIGURE 9.19 The *prewitt* option of *edge*.


```
>> edge_p=edge(ic,'prewitt');
```

More Edge Detection Filters in Matlab


- Roberts cross-gradient filters: $\begin{bmatrix} 1 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$ and $\begin{bmatrix} 0 & 1 & 0 \\ -1 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$

- Sobel filters: $\begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$ and $\begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix}$


```
>> edge_r=edge(ic,'roberts');  
>> figure,imshow(edge_r)
```



```
>> edge_s=edge(ic,'sobel');  
>> figure,imshow(edge_s)
```




Second Derivatives for Edge Detection

- The Laplacian: $\nabla^2 f = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2}$  $\begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$

✓ Pros: isotropic(= rotation invariant) filter

✓ Cons: very sensitive to noise



The edge

First derivative

Second derivative

Absolute values



```
>> l=fspecial('laplacian',0);  
>> ic_l=filter2(l,ic);  
>> figure,imshow(mat2gray(ic_l))
```

Edge Detection by Zero Crossing

- The position where the result of the filter **changes sign**.
- E.g., the simple image given below and the result after filtering with a Laplacian mask
- What if we simply take all zero crossing points as edges ?






FIGURE 9.23 Locating zero crossings in an image. (a) A simple image. (b) After laplace filtering.

Edge Detection by Zero Crossing

- Two cases of zero crossing
 - ✓ They have a negative gray value and are orthogonally adjacent to a pixel whose gray value is positive.
 - ✓ They have a value of zero and are between negative- and positive-valued pixels



```
>> l=fspecial('laplace',0);  
>> icz=edge(ic,'zerocross',1);  
>> imshow(icz)
```



Too many edges are detected.
How can we improve the results?
-> [Marr-Hildreth Method](#)

Edge Detection by Zero Crossing

- **Marr-Hildreth** method

- ✓ Smooth the image with a Gaussian filter.
 - ✓ Convolve the result with a Laplacian filter.
 - ✓ Find the zero crossings.
- } Laplacian of Gaussian (LoG)

```
>> fspecial('log', 13, 2);  
>> edge(ic, 'log');
```

or

```
>> log=fspecial('log',13,2);  
>> edge(ic,'zerocross',log);
```



Canny Edge Detector

- Proposed by John Canny in 1986.
- The most popular edge filter ever !
- Stage 1: 1D DoG filters -> result: $x_e(x,y)$
 - ✓ Take our image x
 - ✓ Create a one-dimensional Gaussian filter g
 - ✓ Create a **1D filter** dg corresponding to the expression given in

$$\frac{d}{dx} e^{-\frac{x^2}{2\sigma^2}} = \left(-\frac{x}{\sigma^2} \right) e^{-\frac{x^2}{2\sigma^2}}$$



- derivative of Gaussian
- to smooth the noise and find possible candidate pixels for edges
- separable (1D filtering twice)

- ✓ Convolve g with dg to obtain gdg
- ✓ Apply gdg to x producing $x1$: horizontal operation
- ✓ Apply gdg' to x producing $x2$: vertical operation
- ✓ Form an magnitude of edge x_e with the equation: **gradient**

$$x_e = \sqrt{x1^2 + x2^2}$$

Canny Edge Detector




- Stage 2: Non-maxima suppression -> result: $g_N(x,y)$
 - Rejects pixels detected as edges in the Stage 1 by detecting the maximum derivative among adjacent pixels.
 - Thresholding alone is not a good way to detection edges in the result xe .
- ✓ Calculate **edge normal**(gradient vector) xg from the 1D gradient images $x1$ and $x2$.

$$xg = \tan^{-1} \left(\frac{x2}{x1} \right)$$

- ✓ Because it is generated using the gradient, xg typically contains wide ridges around local maxima. Thus, we need to thin those ridges.

Based on xg , quantize edge orientations into the predetermined steps. (e.g. **four orientations** in 3x3 region: **horizontal, vertical, +45°, -45°**)

- ✓ If a gradient $xe(x,y)$ is less than at least one of its two neighbors along an edge normal xg_i , let $g_N(x,y) = 0$ (suppression); otherwise, let $g_N(x,y) = xe(x,y)$.



Canny Edge Detector

- Stage 3: Hysteresis thresholding for binary edge image → result: $g_{NH}(x,y)$
 - uses two threshold values: T_L and T_H for lower and higher bounds respectively.
 - ✓ $g_{NH}(x,y) = g_N(x,y) \geq T_H$: strong edge pixels
 - ✓ $g_{NL}(x,y) = g_N(x,y) \geq T_L$
 - ✓ $g_{NL}(x,y) = g_N(x,y) - g_{NH}(x,y)$: weak edge pixels
 - ✓ Connectivity analysis in $g_{NH}(x,y)$
 1. Locate the next unvisited edge pixel, p , in $g_{NH}(x,y)$.
 2. Mark as valid edge pixels all the weak pixels in $g_{NL}(x,y)$ that are connected to p using 8 connectivity.
 3. If all nonzero pixels in $g_{NH}(x,y)$ have been processed, go to the next step. Otherwise, return to the first step.
 4. Set to 0 all pixels in $g_{NL}(x,y)$ that were not marked as valid edge pixels.
 - ✓ Append all the nonzero pixels from $g_{NL}(x,y)$ to $g_{NH}(x,y)$.

Canny Edge Detector in Matlab

```
>> [icc,t]=edge(ic,'canny');  
>> t  
  
t =  
  
    0.0500    0.1250  
  
>> imshow(icc)
```

- $BW = \text{EDGE}(I, 'canny', [low, high], SIGMA)$

↑ threshold limits for Stage 3
↑ standard deviation for Stage 1

- The higher we make the upper threshold, the fewer edges will be shown.






FIGURE 9.29 Canny edge detection.

default threshold and
standard deviation



`edge(ic, 'canny', [0, 0.05])`



`edge(ic, 'canny', [0.01, 0.5])`

FIGURE 9.30 Canny edge detection with different thresholds.

Hough Transform

- If the detected **edge points are sparse**, we might need to fit a line to those points. However it is a time-consuming and computationally inefficient process.
- Is there any way to find boundary lines to compensate the problem described above ? => Hough Transform
- Basic idea of Hough Transform
 - A coordinate (x,y) in an image can be transformed into a line $y = ax + b$ with all possible pairs of (a,b).
 - Every **pixel** at (x,y) coordinate **in the image** can be **mapped into a line in the transform array**.




FIGURE 9.31 A point in an image and its corresponding line in the transform.

Basic Idea of Hough Transform

5 pixels are transformed into 5 lines





FIGURE 9.32 An image and its corresponding lines in the transform.

- Higher value of cross point (a,b) in the transformed array indicates **more distinguished lines** (more pixels through the line) **in the image** !

Hough Transform for Generalization

- We cannot express a vertical line in the form $y = mx + c$, because m represents the gradient and a vertical line has infinite gradient.
- Any line can be described in terms of the two parameters r and θ .
 - ✓ r is the perpendicular distance from the line to the origin
 - ✓ θ is the angle of the line's perpendicular to the x axis



$$-90 < \theta \leq 90$$

$$x \cos \theta + y \sin \theta = r$$


We can calculate θ and r based on the image coordinate (x,y) .

See pp.253 for the derivation.

- Higher value of (r,θ) in the transformed array indicates stronger lines (more pixels through the line) in the image.

Hough Transform Example

- If we discretize θ to use only four values: -45° , 0° , 45° , 90°



| (x, y) | -45° | 0° | 45° | 90° |
|----------|-------------|-----------|------------|------------|
| (2,0) | 1.4 | 2 | 1.4 | 0 |
| (1,1) | 0 | 1 | 1.4 | 1 |
| (2,1) | 0.7 | 2 | 2.1 | 1 |
| (1,3) | -1.4 | 1 | 2.8 | 3 |
| (2,3) | -0.7 | 2 | 3.5 | 3 |
| (4,3) | 0.7 | 4 | 4.9 | 3 |
| (3,4) | -0.7 | 3 | 4.9 | 4 |

θ


r

$x \cos \theta + y \sin \theta = r$

- A single (x,y) coordinate generates four pairs of (r, θ) in this example.
- The **accumulator array** contains the **number of times each value of (r, θ)** appears in the above table.

| | -1.4 | -0.7 | 0 | 0.7 | 1 | 1.4 | 2 | 2.1 | 2.8 | 3 | 3.5 | 4 | 4.9 |
|-------------|------|------|---|-----|---|-----|---|-----|-----|---|-----|---|-----|
| -45° | 1 | 2 | 1 | 2 | | 1 | | | | | | | |
| 0° | | | | | 2 | | 3 | | | 1 | | 1 | |
| 45° | | | | | | 2 | | 1 | 1 | | 1 | | 2 |
| 90° | | | 1 | | 2 | | | | | 3 | | 1 | |

Hough Transform Example




Detected lines

Implementing Hough Transform in MATLAB


1. Decide on a discrete set of values of θ and r to use.
2. At each foreground pixel (x, y) in the image, calculate, the values $r = x\cos\theta + y\sin\theta$ for all θ .
3. Create an accumulator array whose sizes are the numbers of angles θ and values r in the chosen discretizations from Step 1, and
4. Step through all of our r values, updating the accumulator array as we go.

Hough Transform in MATLAB

- Discretizing r and θ
 - Let θ with the range of $0 \leq \theta < 2\pi$.
 - Restrict r to non-negative value.



(a)



(b)

FIGURE 9.37 A line parameterized with r and θ . (a) Using ordinary Cartesian axes. (b) Using matrix axes.

Example of Hough Transform in MATLAB

- Calculating the r values
 - ✓ If im is a **binary image**

```
>> [x,y]=find(im);
```

We can create a binary edge image by use of the `edge` function beforehand.

```
>> r=floor(x*cos(angles)+y*sin(angles));
```

- Forming the Accumulator Array

```
>> rmax=max(r(find(r>0)));  
>> acc=zeros(rmax+1,270);
```

- Updating
the Accumulator Array

```
function res=hough2(image)  
  
%  
% HOUGH2(IMAGE) creates the Hough transform corresponding to the image IMAGE  
%  
  
if ~isbw(image)  
    edges=edge(image,'canny');  
else  
    edges=image;  
end;  
[x,y]=find(edges);  
angles=[-90:180]*pi/180;  
r=floor(x*cos(angles)+y*sin(angles));  
rmax=max(r(find(r>0)));  
acc=zeros(rmax+1,270);  
for i=1:length(x),  
    for j=1:270,  
        if r(i,j)>=0  
            acc(r(i,j)+1,j)=acc(r(i,j)+1,j)+1;  
        end;  
    end;  
end;  
res=acc;
```

FIGURE 9.38 A simple MATLAB function for implementing the Hough transform.

Example of Hough Transform in MATLAB

```
>> c=imread('cameraman.tif');  
>> hc=hough2(c);
```

```
>> imshow(mat2gray(hc)*1.5)
```

```
>> max(hc(:))
```

```
ans =
```

```
91
```

```
>> [r,theta]=find(hc==91)
```

```
r =
```

```
138
```

```
theta =
```

```
181
```








FIGURE 9.40 A line from the Hough Transform.

How to Display the Detected Line in Matlab

```
function houghline(image,r,theta)
%
% Draws a line at perpendicular distance R from the upper left corner of the
% current figure, with perpendicular angle THETA to the left vertical axis.
% THETA is assumed to be in degrees.
%
[x,y]=size(image);
angle=pi*(181-theta)/180;
X=[1:x];
if sin(angle)==0
    line([r r],[0,y],'Color','black')
else
    line([0,y],[r/sin(angle),(r-y*cos(angle))/sin(angle)],'Color','black')
end;
```



(a)



(b)

See pp. 261 for more detailed information to use houghline().

Summary

- **Chap 9. Image Segmentation**
 - Single & double thresholding
 - How to determine the threshold value
 - Adaptive thresholding
 - Edge detection: 1st and 2nd derivatives
 - Canny edge detector
 - Hough Transform
- **Chap 10. Mathematical Morphology**
 - Erosion & dilation -> boundary detection
 - Opening & closing -> noise removal
 - Hit-or-miss transform -> shape detection
 - Binary applications: region filling, connected components, skeletons
 - Grayscale morphology -> edge detection, noise removal