

Import of chess tournaments into the chess-results.com database

The data can be uploaded on chess-results.com with an XML file.

Author Heinz Herzog, as at 18 February 2017, last change 20.11.2024

Requirements:

1) Each user needs a unique number (= CreatorID) so that tournaments can not be overwritten by other users. (Unfortunately necessary as there are also malicious people.)

2) Each tournament has a unique number (key)

The unique number is given by chess-results.com in **2 steps**:

Description

1) Requesting an SID (Security ID)

Call <https://chess-results.com/Uploadxml.aspx?key1=GETSID&source=1>

source	0..Program Swiss-Manager 1..Program Swiss-Chess 2..Program SwissSys 3...
--------	---

The following XML file is returned:

```
<?xml version="1.0" encoding="UTF-8"?>
<chessresults>
<result
  sidEncrypt=" C36E85386EDD4994144FDC156B6C37BA"
  sid="140972164"
  status="OK"/>
</chessresults>
```

Only for testing the

sid	Security-ID, necessary to authenticate the call
sidEncrypt	Sid-Encrypted. Only available for testing. In production not available.

2) Request a new database key.

This request may only be called once per tournament.

The database key must then be saved immediately in the application.

Call <https://chess-results.com/Uploadxml.aspx?key1=GETKEY>

The following XML file is expected (example):

```
<?xml version="1.0"?>
<chessresults>
  <getkey
    source="1"
    sid="C36E85386EDD4994144FDC156B6C37BA"
    creatorID="13121"
    federation="JPN"
    tournament="Test Unicode 横浜 Open"
  />
</chessresults>
```

Description of each field

Source	0..Program Swiss-Manager 1..Program Swiss-Chess 2..Program SwissSys 3..
sid	AES Encryption 128 bit of field sid from the call GETSID

creatorID	Unique ID for each user To prevent users from mistaken or deliberately uploading tournaments from other users.
federation	Country of the tournament (3-character FIDE code)
tournament	Tournament-name

If the call was successful, the following XML file is returned:

```
<?xml version="1.0" encoding="UTF-8"?>
<chessresults>
<result key="222557" status="OK"/>
</chessresults>
```

If the call was not successful, the following XML file is returned:

```
<?xml version="1.0" encoding="UTF-8"?>
<chessresults>
<result status="ERROR"/>
<messages>
<message type="error" Text="Error getting New chess-results.com key (node /chessresults/getkey
not found)"/>
</messages>
</chessresults>
```

After the unique tournament key has been requested, the tournament can be uploaded using the following XML file:

Tournament-Data

Field	Description
key	Unique tournament key (requested with GETKEY)
type	0 ... Single Swiss-System-tournament 1 ... Single Round robin tournament 2 ... Team Round robin tournament 3 ... Team Swiss-System-tournament
name	Tournament name (Maximum of 160 characters)
remark	remark (Maximum of 600 characters), If the remark stats with #, It is displayed on chess-results-com orange (Example http://chess-results.com/tnr215998.aspx?lan=1)
director	Tournament-director (Maximum of 80 characters)
organiser	Tournament- organiser (80 characters)
location	Tournament- location (80 characters)
arbiter	arbiters (1200 characters)
rounds	Total number of rounds
currentround	Current round (in Swiss system tournaments)
rankinground	Round of the ranking-list
sortstartrank	Type of sorting of the starting rank 1..Sorting according to the national rating, if none available then according to the FIDE-rating 2..Sorting according to the FIDE rating, if none available then according to the national- rating 3.Sorting first according to the FIDE rating, then by the national rating 4.Elomaximum of FIDE and national rating 5.Only according to national rating 6..Only according to FIDE rating Otherwise as 1
from	Tournament -Start-Date in the Form dd.mm.yyyy
to	Tournament -End-Date in the Form dd.mm.yyyy
ratedfide	N.. Tournament is not FIDE-rated J.. Tournament is FIDE-rated

	... If not known
ratednational	N.. Tournament is not national -rated J.. Tournament is national -rated ... If not known
tb1no	Number of the 1. Tie-Break (Details see File TieBreaks.xlsx)
tb2no	Number of the 2. Tie-Break
tb3no	Number of the 3. Tie-Break
tb4no	Number of the 4. Tie-Break
tb5no	Number of the 5. Tie-Break
replay	1 .. Default-Value 2 .. for double-rounded tournament n .. n- rounded tournament
timecontrol	timecontrol (100 characters)
homecolor	Only for team- tournaments. w .. Home team has white on board 1 s .. Home team has black on board 1
samecolor	Only for team- tournaments. J .. All players in the team have the same color N .. the colors are changed
playerperteam	Only for team- tournaments. Number of boards
ratingavg	rating-average of the tournament
endstatus	J .. the tournament is over (all results available) N .. the tournament is still running R .. it was reserved with GETKEY a key, but the tournament was not uploaded
tb1_detail	Details (Parameters) for Tie-Break 1 If the Tie-Break has parameter, then see Excel-File Tie-Breaks.xlsx Column P
tb2_detail	Details (Parameters) for Tie-Break 1
tb3_detail	Details (Parameters) for Tie-Break 2
tb4_detail	Details (Parameters) for Tie-Break 3
tb5_detail	Details (Parameters) for Tie-Break 4
chiefarbiter	chiefarbiter (maximal 120 Zeichen)
homepageorganiser	Homepage of the organiser (80 characters)
mail	Mail-address of the organiser (80 characters)
federation	Country of the tournament (3-character FIDE code)
creator	creatorID of the tournament

Player Data

Field	Description
No	Starting-rank-number (from 1 to n)
Id	ID-Number (numeric maximum 12 digits)
Lastname	32 characters
Firstname	30 characters
Atitle	academic title (14 characters)
Title	(FIDE)Title (4 characters)
Rtg	Rating for sorting Starting-rank
Rtgfide	FIDE-rating
Rtgnat	National-rating
Dob	Date of burth in the form dd.mm.yyyy (example 29.03.1977) If only the Year is available then yyyy (example 1977)
Sex	w..women c..computer m..man
Fed	Federtion oft he player (3-character FIDE code)
Board	Only for team- tournaments, otherwise 0. Board number in the team

Teamno	Only for team- tournaments, otherwise 0. Team-Starting rank-number
Clubname	Clubname/place/City (40 characters)
Fideid	FIDE-Id
Club	Club-Number (0..32000)
Typ	Usually for U08, U10, U12, S50 ... (4 characters) Can also be used for something else.
Group	Can be used for something. (4 characters)
Rank	ranking according field "rankinground" in the tournament-data
tb1	Tie-Break 1 according field "rankinground" in the tournament-data
tb2	Tie-Break 2 ...
tb3	Tie-Break 3 ...
tb4	Tie-Break 4 ...
tb5	Tie-Break 5 ...
pts	Points according field "rankinground" in the tournament-data
equal	If all Tie-Breaks are equal, then J, otherwise N Example, if rank 3 and rank 4 identical then J must set for rank 4. Then, the rank 4 is blank in the ranking list. If all Tie-Breaks are equal, the player are sorted according to the starting rank
kfaktor	(FIDE)-K-Factor
state	Only for round robin tournaments 0 .. player active 1 .. player removed, points do not count 2 .. player removed, points count

Intermediate ranking data (Only for Swiss system tournaments (team and individual))

Field	Description
round	round
rank	ranking from 1 to "rankinground"- 1. The data for the rank for round „rankinground“ is in the player data.
no	Starting rank number (from 1 to n)
tb1	Tie Break 1
tb2	Tie Break 2
tb3	Tie Break 3
tb4	Tie Break 4
tb5	Tie Break 5
equal	See player Data

Round-Data

Field	Description
round	round
date	Date in the form dd.mm.yyyy
time	Start time (15 characters) Example: 15:00

Playerpairing-Data

Field	Description
round	round
pairing	Pairings-number (1..number of pairings)
board	Only for team- tournaments, otherwise 1. Board-number (1..max-boards)
whiteno	Starting rank number white
blackno	Starting rank number black if white has a bye then -1 if white is not paired then -2
reswhite	Result white 1 .. win

	0,5 .. draw 0 .. lost
resblack	Result black
forfeit	K .. forfeit blank or empty otherwise

Security-Daten

Field	Description
Source	0..Programm Swiss-Manager 1..Programm Swiss-Chess 2..Programm SwissSys 3..
Sid	AES Encryption 128 bit of field sid from the GETSID request
creator_sid	AES Encryption 128 bit of field CreatorID from the tournament-Data
tnr_sid	AES Encryption 128 bit of field key from the tournament-Data

Important: The Sid, creator_sid, tnr_sid are not checked yet.

Only for team tournaments or individual Swiss system tournaments with team ranking:

Team-Data

Field	Description
no	Team-Starting rank-number (from 1 to Number of teams)
teamname	Team-Name (40 characters)
teamshort	Team-Name short (25 characters)
rank	Rank of the current round with results
points	Player point of the team
tb1	Tie Break 1
tb2	Tie Break 2
tb3	Tie Break 3
tb4	Tie Break 4
tb5	Tie Break 5
captain	Team-captain (70 characters)
federation	Country of the team (3-character FIDE code)
state	Only for round robin tournaments 0 .. team active 1 .. team removed, points do not count 2 .. team removed, points count
rtg_average	Average rating of the team
equal	If all Tie-Breaks are equal, then J, otherwise N See player-data

Team-Pairings-Daten

Field	Description
Round	round
pairing	Pairings-number (1..number of pairings)
no1	Starting rank number white
no2	Starting rank number black if white has a bye then -1 if white is not paired then -2
res1	Result (points) from white-team (no 1)
res2	Result (points) from black-team (no 2)

VB.NET Example program for the tournament-XML-Upload

```
Dim reader As New StreamReader("xml_file")
Dim xml As String = reader.ReadToEnd().Replace("<", "{").Replace(">", "}")
Dim URL As String = "http://chessresults.com/UploadXML.aspx?key1=UPLOAD"
Dim myWebClient As New WebClient
Dim data As New System.Collections.Specialized.NameValueCollection
data.Add("xml", xml)
Dim XML_Result as string = Encoding.UTF8.GetString(myWebClient.UploadValues(URL, "POST", data))
XML_Result ... analyse
```

VB.NET Example program for the AES- Encryption

Function Encrypt(ByVal DecryptedString As String) As String

Dim AES As AesManaged = New System.Security.Cryptography.AesManaged 'Instanzierung des AES-Objekts

AES.KeySize = 128

AES.BlockSize = 128

AES.Key = AES_Init() ' init: Key

AES.IV = AK2() ' init init-Vector

' create Memory-Stream and Crypto-Stream -> CreateEncryptor()

Dim ms As New IO.MemoryStream

Dim cs As New CryptoStream(ms, AES.CreateEncryptor(), CryptoStreamMode.Write)

' encrypt data

Dim Data() As Byte = System.Text.Encoding.UTF8.GetBytes(DecryptedString)

cs.Write(Data, 0, Data.Length)

cs.FlushFinalBlock()

cs.Close()

' output encrypted data as String:

Dim shb As SoapHexBinary = New SoapHexBinary(ms.ToArray) ' convert ByteArray to Hex-String

Encrypt = shb.ToString()

ms.Close()

AES.Clear()

End Function

Function Decrypt(ByVal EncryptedString As String) As String

Dim AES As New AesManaged

AES.KeySize = 128

AES.BlockSize = 128

AES.Key = AES_Init() ' init: Key

AES.IV = AK2() ' init init-Vector

' create Memory-Stream and Crypto-Stream -> CreateDecryptor()

Dim ms As New IO.MemoryStream

Dim cs As New CryptoStream(ms, AES.CreateDecryptor(), CryptoStreamMode.Write)

Try ' data decrypted :

Dim Data() As Byte = SoapHexBinary.Parse(EncryptedString).Value 'convert Hex-String to ByteArray

cs.Write(Data, 0, Data.Length)

cs.FlushFinalBlock()

cs.Close()

' output decrypted data as String:

Decrypt = System.Text.Encoding.UTF8.GetString(ms.ToArray)

ms.Close()

AES.Clear()

Catch ex As Exception

Decrypt = "?"

End Try

End Function