

NAME

`fclose` – close a stream

SYNOPSIS

```
#include <stdio.h>
```

```
int fclose(FILE *fp);
```

DESCRIPTION

The **fclose()** function flushes the stream pointed to by *fp* (writing any buffered output data using **fflush(3)**) and closes the underlying file descriptor.

RETURN VALUE

Upon successful completion 0 is returned. Otherwise, **EOF** is returned and *errno* is set to indicate the error. In either case any further access (including another call to **fclose()**) to the stream results in undefined behavior.

ERRORS**EBADF**

The file descriptor underlying *fp* is not valid.

The **fclose()** function may also fail and set *errno* for any of the errors specified for the routines **close(2)**, **write(2)** or **fflush(3)**.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
fclose()	Thread safety	MT-Safe

CONFORMING TO

C89, C99.

NOTES

Note that **fclose()** only flushes the user-space buffers provided by the C library. To ensure that the data is physically stored on disk the kernel buffers must be flushed too, for example, with **sync(2)** or **fsync(2)**.

SEE ALSO

close(2), **fcloseall(3)**, **fflush(3)**, **fopen(3)**, **setbuf(3)**

COLOPHON

This page is part of release 3.53 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.