

```
1: // $Id: jrpn.java,v 1.22 2013-10-11 19:19:01-07 - - $
2:
3: import java.util.Scanner;
4: import static java.lang.System.*;
5:
6: class jrpn {
7:     static int exit_status = 0;
8:     static final int EMPTY = -1;
9:     static final int SIZE = 16;
10:    static class stack_t {
11:        int top = EMPTY;
12:        double[] numbers = new double[SIZE];
13:    }
14:
15:    static void error (String format, Object... args) {
16:        out.flush();
17:        err.printf (format, args);
18:        err.flush();
19:        exit_status = 1;
20:    }
21:
22:    static void bad_operator (String oper) {
23:        error ("%s\\": invalid operator\\n", oper);
24:    }
25:
26:    static void push (stack_t stack, double number) {
27:        if (stack.top >= SIZE - 1) {
28:            out.printf ("%s: stack overflow\\n", number);
29:        }else {
30:            stack.numbers[++stack.top] = number;
31:        }
32:    }
33:
34:    static void do_binop (stack_t stack, char oper) {
35:        if (stack.top < 1) {
36:            out.printf ("%s': stack underflow", oper);
37:        }else {
38:            double right = stack.numbers[stack.top--];
39:            double left = stack.numbers[stack.top--];
40:            switch (oper) {
41:                case '+': push (stack, left + right); break;
42:                case '-': push (stack, left - right); break;
43:                case '*': push (stack, left * right); break;
44:                case '/': push (stack, left / right); break;
45:            }
46:        }
47:    }
48:
```

```
49:
50:     static void do_print (stack_t stack) {
51:         if (stack.top == EMPTY) {
52:             out.printf ("stack is empty\n");
53:         }else {
54:             for (int pos = 0; pos <= stack.top; ++pos) {
55:                 out.printf ("%s\n", stack.numbers[pos]);
56:             }
57:         }
58:     }
59:
60:     static void do_clear (stack_t stack) {
61:         stack.top = EMPTY;
62:     }
63:
64:     static void do_operator (stack_t stack, String oper) {
65:         switch (oper.charAt(0)) {
66:             case '+': do_binop (stack, '+'); break;
67:             case '-': do_binop (stack, '-'); break;
68:             case '*': do_binop (stack, '*'); break;
69:             case '/': do_binop (stack, '/'); break;
70:             case ';': do_print (stack);      break;
71:             case '@': do_clear (stack);      break;
72:             default : bad_operator (oper);   break;
73:         }
74:     }
75:
76:     static String argv_0() {
77:         String jarname = getProperty ("java.class.path");
78:         if (jarname.equals (".")) jarname = "jrpn";
79:         return jarname.substring (jarname.lastIndexOf ("/") + 1);
80:     }
81:
```

```
82:
83:     public static void main (String[] args) {
84:         if (args.length != 0) {
85:             err.printf ("Usage: %s\n", argv_0());
86:             exit (1);
87:         }
88:         Scanner stdin = new Scanner (in);
89:         stack_t stack = new stack_t();
90:         while (stdin.hasNext()) {
91:             String token = stdin.next();
92:             if (token.startsWith("#")) {
93:                 stdin.nextLine();
94:                 continue;
95:             }
96:             try {
97:                 double number = Double.parseDouble (token);
98:                 push (stack, number);
99:             } catch (NumberFormatException error) {
100:                 if (token.length() != 1) {
101:                     bad_operator (token);
102:                 } else {
103:                     do_operator (stack, token);
104:                 }
105:             }
106:         }
107:         exit (exit_status);
108:     }
109: }
```

```
1: ::::::::::::::::::::::::::::::
2: ../.score/test1.rpn
3: ::::::::::::::::::::::::::::::
4:      1  # $Id: test1.rpn,v 1.2 2015-01-26 13:26:15-08 - - $
5:      2  # tests for simple operators
6:      3  # Note that # starts a comment to end of line.
7:      4
8:      5  34 .3 + 23 8 * - ; @
9:      6  44 0 / ; @
10:     7  2 4 / ; @
11: ::::::::::::::::::::::::::::::
12: jtest1.output
13: ::::::::::::::::::::::::::::::
14:      1  -149.7
15:      2  Infinity
16:      3  0.5
17: ::::::::::::::::::::::::::::::
18: jtest1.status
19: ::::::::::::::::::::::::::::::
20:      1  STATUS = 0
```

```
1: ::::::::::::::::::::::::::::::
2: ../.score/test2.rpn
3: ::::::::::::::::::::::::::::::
4:      1  # $Id: test2.rpn,v 1.1 2013-09-25 13:09:38-07 - - $
5:      2  # test for generation of errors
6:      3  3 + ; # stack underflow error
7:      4  1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 #stack overflow
8:      5  error bad operator
9: ::::::::::::::::::::::::::::::
10: jtest2.output
11: ::::::::::::::::::::::::::::::
12:      1  '+' : stack underflow3.0
13:      2  1.0: stack overflow
14:      3  1.0: stack overflow
15:      4  1.0: stack overflow
16:      5  1.0: stack overflow
17:      6  1.0: stack overflow
18:      7  "error": invalid operator
19:      8  "bad": invalid operator
20:      9  "operator": invalid operator
21: ::::::::::::::::::::::::::::::
22: jtest2.status
23: ::::::::::::::::::::::::::::::
24:      1  STATUS = 1
```

```
1: ::::::::::::::::::::::::::::::
2: ../.score/test3.rpn
3: ::::::::::::::::::::::::::::::
4:     1  # $Id: test3.rpn,v 1.1 2013-09-25 13:09:38-07 - - $
5:     2  # tests for simple operators
6:     3  # Note that # starts a comment to end of line.
7:     4  34 .3 88 ;
8:     5  + + ; @ # should print one sum
9:     6  8 3 * 4 7 * + ; @ # should print one sum
10:    7  3 10 - ; @ # should print a negative number
11:    8  4 9 / ; @ #fraction
12:    9  7 0 / ; @ # infinity
13:   10  1e1000000 ; @ # infinity
14: ::::::::::::::::::::::::::::::
15: jtest3.output
16: ::::::::::::::::::::::::::::::
17:     1  34.0
18:     2  0.3
19:     3  88.0
20:     4  122.3
21:     5  52.0
22:     6  -7.0
23:     7  0.444444444444444444
24:     8  Infinity
25:     9  Infinity
26: ::::::::::::::::::::::::::::::
27: jtest3.status
28: ::::::::::::::::::::::::::::::
29:     1  STATUS = 0
```

```
1: // $Id: crpn.c,v 1.28 2014-04-08 15:23:19-07 - - $
2:
3: #include <assert.h>
4: #include <libgen.h>
5: #include <stdio.h>
6: #include <stdlib.h>
7:
8: int exit_status = EXIT_SUCCESS;
9: #define EMPTY (-1)
10: #define SIZE 16
11:
12: struct stack {
13:     int top;
14:     double numbers[SIZE];
15: };
16:
17: void bad_operator (const char *oper) {
18:     fflush (NULL);
19:     fprintf (stderr, "oper=\"%s\"\n", oper);
20:     fflush (NULL);
21:     exit_status = EXIT_FAILURE;
22: }
23:
24: void push (struct stack *the_stack, double number) {
25:     printf ("the_stack=%p, top=%d, number=%.15g\n",
26:            the_stack, the_stack->top, number);
27: }
28:
29: void do_binop (struct stack *the_stack, char oper) {
30:     printf ("the_stack=%p, top=%d, oper='%c'\n",
31:            the_stack, the_stack->top, oper);
32: }
33:
34: void do_print (struct stack *the_stack) {
35:     printf ("the_stack=%p, top=%d\n", the_stack, the_stack->top);
36: }
37:
38: void do_clear (struct stack *the_stack) {
39:     printf ("the_stack=%p, top=%d\n", the_stack, the_stack->top);
40: }
41:
42: void do_operator (struct stack *the_stack, const char *oper) {
43:     printf ("the_stack=%p, top=%d, oper=\"%s\"\n",
44:            the_stack, the_stack->top, oper);
45: }
46:
```

```
47:
48: int main (int argc, char **argv) {
49:     if (argc != 1) {
50:         fprintf (stderr, "Usage: %s\n", basename (argv[0]));
51:         fflush (NULL);
52:         exit (EXIT_FAILURE);
53:     }
54:     struct stack the_stack;
55:     the_stack.top = EMPTY;
56:     char buffer[1024];
57:     for (;;) {
58:         int scanrc = scanf ("%1023s", buffer);
59:         if (scanrc == EOF) break;
60:         assert (scanrc == 1);
61:         if (buffer[0] == '#') {
62:             scanrc = scanf ("%1023[^\n]", buffer);
63:             continue;
64:         }
65:         char *endptr;
66:         double number = strtod (buffer, &endptr);
67:         if (*endptr == '\0') {
68:             push (&the_stack, number);
69:         } else if (buffer[1] != '\0') {
70:             bad_operator (buffer);
71:         } else {
72:             do_operator (&the_stack, buffer);
73:         }
74:     }
75:     return exit_status;
76: }
77:
```



```
1: ::::::::::::::::::::::::::::::
2: ../.score/test1.rpn
3: ::::::::::::::::::::::::::::::
4:     1  # $Id: test1.rpn,v 1.2 2015-01-26 13:26:15-08 - - $
5:     2  # tests for simple operators
6:     3  # Note that # starts a comment to end of line.
7:     4
8:     5  34 .3 + 23 8 * - ; @
9:     6  44 0 / ; @
10:    7  2 4 / ; @
11: ::::::::::::::::::::::::::::::
12: ctest1.output
13: ::::::::::::::::::::::::::::::
14:     1  the_stack=0x7ffee0fb57f0, top=-1, number=34
15:     2  the_stack=0x7ffee0fb57f0, top=-1, number=0.3
16:     3  the_stack=0x7ffee0fb57f0, top=-1, oper="+"
17:     4  the_stack=0x7ffee0fb57f0, top=-1, number=23
18:     5  the_stack=0x7ffee0fb57f0, top=-1, number=8
19:     6  the_stack=0x7ffee0fb57f0, top=-1, oper="*"
20:     7  the_stack=0x7ffee0fb57f0, top=-1, oper="-"
21:     8  the_stack=0x7ffee0fb57f0, top=-1, oper=";"
22:     9  the_stack=0x7ffee0fb57f0, top=-1, oper="@"
23:    10  the_stack=0x7ffee0fb57f0, top=-1, number=44
24:    11  the_stack=0x7ffee0fb57f0, top=-1, number=0
25:    12  the_stack=0x7ffee0fb57f0, top=-1, oper="/"
26:    13  the_stack=0x7ffee0fb57f0, top=-1, oper=";"
27:    14  the_stack=0x7ffee0fb57f0, top=-1, oper="@"
28:    15  the_stack=0x7ffee0fb57f0, top=-1, number=2
29:    16  the_stack=0x7ffee0fb57f0, top=-1, number=4
30:    17  the_stack=0x7ffee0fb57f0, top=-1, oper="/"
31:    18  the_stack=0x7ffee0fb57f0, top=-1, oper=";"
32:    19  the_stack=0x7ffee0fb57f0, top=-1, oper="@"
33: ::::::::::::::::::::::::::::::
34: ctest1.status
35: ::::::::::::::::::::::::::::::
36:     1  STATUS = 0
```

```
1: #!/bin/sh
2: # $Id: mk,v 1.9 2016-01-11 21:51:08-08 - - $
3:
4: cid $0 jrpn.java crpn.c
5: mkc jrpn.java
6:
7: for test in ../.score/test*.rpn
8: do
9:     basename=${test##.*/}
10:    prefix=j${basename%.*}
11:    java -jar jrpn <$test >$prefix.output 2>&1
12:    echo STATUS = $? >$prefix.status
13:    catnv $test $prefix.output $prefix.status >$prefix.lis
14:    rm $prefix.output $prefix.status
15: done
16:
17: mkc crpn.c
18: ./crpn <../.score/test1.rpn >ctest1.output 2>&1
19: echo STATUS = $? >ctest1.status
20:
21: catnv ../.score/test1.rpn ctest1.output ctest1.status >ctest1.lis
22: rm ctest1.output ctest1.status
23:
24: mkpspdf -s12 Listing.ps jrpn.java* j*.lis crpn.c* c*.lis $0
```