

# Power Laws & Rich Get Richer

Social Computing

Department of Computer Science  
University of Massachusetts, Lowell

Hadi Amiri  
[hadi@cs.uml.edu](mailto:hadi@cs.uml.edu)



# Lecture Topics


- Popularity
- Power Laws
- Rich Get Richer model

# Popularity

- Popularity can be characterized by **extreme imbalances!**
  - People are known to their immediate social circle!
  - Few people achieve wider visibility!
  - Very few achieve global name recognition.
- Learning objectives:
  - How can we quantify these imbalances?
  - Why do they arise?
  - Can popularity be predicted?

# Power Law

- A function that decreases as  $k$  to some fixed power, e.g.  $1/k^2$ , is called a **power law**!
  - It allows to see very large values of  $k$  in data!
- Extreme imbalances are likely to arise!




$$P(k) = \frac{a}{k^c}$$

$$P(k) = \frac{1}{k^{40}}$$

# Power Law- Cnt.

- Histogram of the populations of all US cities with population of 10,000 or more.




# Power Law- Cnt.

- **Power law Test:** Given a dataset, test if it exhibits a power law distribution?
  1. Compute histogram of values wrt a popularity measure (e.g. #in-links, #downloads, population of cities, etc.)
  2. Test if the result approximately estimates a power law  $a/k^c$  for some  $a$  and  $c$ , and if so, estimate  $a$  and the exponent  $c$ .

# Power Law- Cnt.


- What should a power law plot look like?
  - $f(k)$ : the fraction of items that have value  $k$
  - If power law holds,  $f(k) = a/k^c$ ?
    - for some constant  $c$  and  $a$ .
  - $f(k) = a/k^c = ak^{-c}$
  - $\log f(k) = \log a - c \log k$ 
    - **straight line!** “ $\log f(k)$ ” as a function of “ $\log k$ ”
      - “ $c$ ”: slope, and
      - “ $\log a$ ”: y-intercept.
    - log-log plot!

$$y = b + cx$$










# Power Law- Cnt.

- If power-law holds, the “log -log” plot should be a **straight line**.









# Popularity


- Let's focus on the Web in which we can measure popularity accurately!
  - Popularity of a page

# Popularity- Cnt.

- Let's focus on the Web in which we can measure popularity accurately!
  - Popularity of a page ~ number of its **in-links**
    - Easy to count!

## Degree Centrality- Cnt.

- A node is central if it has ties to many other nodes
  - Look at the node degree



$$C(n_1) = \sum_{j=1}^n A_{1j} = \sum_{i=1}^n A_{i1} = 3$$

	n1	n2	n3	n4	n5	$\sum_{j=1}^n A_{ij}$
n1	0	1	1	1	0	3
n2	1	0	0	0	0	1
n3	1	0	0	0	0	1
n4	1	0	0	0	1	2
n5	0	0	0	1	0	1
$\sum_{i=1}^n A_{ij}$	3	1	1	2	1	


Adjacency Matrix (A)

# Popularity- Cnt.

- Question:
  - What fraction of pages on the Web have  $k$  in-links?

# Popularity- Cnt.

- Question:
  - What fraction of pages on the Web have  $k$  in-links?




Remote-only: older crawl

- $c \approx 2.1$
- The anomalous bump at 120 on the x-axis is due to a large *clique*\* formed by a single spammer.

\* Subset of nodes such that every two distinct nodes are adjacent (directly connected).

# Popularity- The Long Tail


- **Question:** Are most sales generated by a
  - **small set** of **popular items** (*hits*), or
  - **large set** of **less popular items** (*niches*)?



Check if this curve is changing shape over time, adding more area under the right at the expense of the left!

# Popularity- The Long Tail

- **Question:** Would personalization be useful?
  - E.g. through exposing people to items that (may not be popular but) match with their interests!






# Popularity- Cause

- What is causing Power laws / Popularity?

# Rich Get Richer (RGR)

**Rich-Get-Richer**: A simple model for the creation of links as a basis for power laws!

1. Pages  $(1, \dots, N)$  are created in order.
2. Each page creates one link to an **earlier** page.
3. When page  $j$  is created, it links to **page  $i < j$** :
  - a) With probability  $p$ ,  $j$  chooses  $i$  uniformly at random & creates **a link to  $i$** .
  - b) With probability  $(1 - p)$ ,  $j$  chooses  $i$  uniformly at random & copies  $i$ 's decision (creates **a link to the page that  $i$  points to**).




# RGR - Implication of Rule b

- b) With probability  $(1 - p)$ ,  $j$  chooses  $i$  uniformly at random & copies  $i$ 's decision (creates **a link to the page that  $i$  points to**).

# RGR - Implication of Rule b

- b) With probability  $(1-p)$ ,  $j$  chooses  $i$  uniformly at random & copies  $i$ 's decision (creates **a link to the page that  $i$  points to**)




The probability of linking to a page is proportional to the total number of pages that currently link to that page!

Copying mechanism  $\rightarrow$  RGR


# RGR - Power Law

- We observe power law, if we run this model for many pages
  - the fraction of pages with  $k$  in links will be distributed according to a power law  $1/k^c$ !
  - Value of the exponent  $c$  depends on the choice of  $p$ .
- Relation between  $c$  and  $p$ ?



# RGR - Power Law

- We observe power law, if we run this model for many pages
  - the fraction of pages with  $k$  in-links will be distributed according to a power law  $1/k^c$ !
  - Value of the exponent  $c$  depends on the choice of  $p$ .
- Relation between  $c$  and  $p$ ?
  - Smaller  $p$  / larger  $1-p$ 
    - Copying becomes more frequent
    - More likely to see extremely popular pages
    - $c$  gets larger



# RGR - Preferential Attachment

- Due to copying mechanism: the probability of linking to a page is proportional to the total number of pages that currently link to that page!
- Preferential Attachment:
  - **b)** With probability  $(1 - p)$ ,  $j$  chooses  $i$  with probability **proportional to  $i$ 's current number of in-links** and creates a link to  $i$ .
    - links are formed preferentially to pages with high popularity.

# RGR - Preferential Attachment

## Rich-Get-Richer:

1. Pages  $(1, \dots, N)$  are created in order.
2. Each page creates one link to an **earlier** page.
3. When page  $j$  is created, it links to **page  $i < j$** :
  - a) With probability  $p$ ,  $j$  chooses  $i$  uniformly at random and creates **a link to  $i$** .
  - b) With probability  $(1 - p)$ ,  $j$  chooses  $i$  with probability **proportional to  $i$ 's current number of in-links** and creates a link to  $i$ .



# RGR - Probabilistic Model

- Probabilistic model
  - $X_j(t)$ : number of in-links to node  $j$  at a time  $t$
- Two points about  $X_j(t)$ 
  1. Value of  $X_j(t)$  at time  $t=j$ 
    - $X_j(j) = 0$ 
      - node  $j$  starts with 0 in-link when it's first created at time  $j$ !
  2. Expected Change to  $X_j(.)$  over time

Compute the probability that node  $j$  gains an in-link in step  $t+1$ ?

# RGR - Probabilistic Model

- Expected Change to  $X_j(\cdot)$  over time
  - Probability that node  $j$  gains an in-link in step  $t+1$ ?
    - Happens if the newly created node  $t+1$  points to node  $j$ .
    - Two cases:
      1. With probability  $p$ , node  $t+1$  links to an earlier node chosen uniformly at random:
        - Thus, node  $t + 1$  links to node  $j$  with probability  $1/t$
      2. With probability  $1 - p$ , node  $t+1$  links to an earlier node with probability proportional to the node's current number of in-links.
        - At time  $t+1$ :
          - total number of links in the network?
            - $t$  (one out of each prior node)
          - How many of them point to node  $j$ ?
            - $X_j(t)$  (based on the definition)
          - Thus, node  $t + 1$  links to node  $j$  with probability  $X_j(t)/t$ .

$$\frac{p}{t} + \frac{(1 - p)X_j(t)}{t}.$$

# RGR - Probabilistic Model

- Deterministic approximation
  - Approximate  $X_j(t)$ —the # of in-links of node  $j$ —by a continuous function of time  $x_j(t)$ .
  - Model for rate of growth:

$$\frac{p}{t} + \frac{(1-p)X_j(t)}{t}.$$

$$\frac{dx_j}{dt} = \frac{p}{t} + \frac{(1-p)x_j}{t}. \quad \longrightarrow \quad x_j(t) = \frac{p}{q} \left[ \left( \frac{t}{j} \right)^q - 1 \right].$$

# RGR - Probabilistic Model

- Identifying power law in DA
  - For a given value of  $k$  and time  $t$ , what fraction of nodes have at least  $k$  in-links at  $t$ , OR
  - For a given value of  $k$  and time  $t$ , what fraction of all  $j$ s satisfy  $x_j(t) \geq k$ ?

$$x_j(t) = \frac{p}{q} \left[ \left( \frac{t}{j} \right)^q - 1 \right].$$

$$\left[ \frac{q}{p} \cdot k + 1 \right]^{-1/q}.$$

Power law:


The fraction of nodes with *at least*  $k$  in-links is proportional to  $k^{-1/q}$ .

# RGR - Probabilistic Model

- Explain power laws using the RGR model:

- phones receiving  $k$  calls per day
- books bought by  $k$  people
- papers with  $k$  citations
- cities with population  $k$

- Cities grow in proportion to their size, simply as a result of people having children!



- Once an item becomes popular, the rich-get-richer dynamics are likely to push it even higher!

# Reading

- Ch.18 Power Laws and Rich-Get-Richer Phenomena [NCM]