

## Subtype Wall-mounted heat pump water heater-80L-B1

Certificate Holder	GD Midea Air-Conditioning Equipment Co., Ltd.
Address	Lingang Road,
ZIP	
City	Guangdong
Country	CN
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	Wall-mounted heat pump water heater-80L-B1
Registration number	011-1W0769
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R290
Mass of Refrigerant	0.15 kg
Certification Date	09.02.2024
Testing basis	HP KEYMARK certification scheme rules V12

## Model EU-RSJ-08/80RDN7-B1

Model name	EU-RSJ-08/80RDN7-B1
Application	n/a
Units	Indoor
Climate zone (for heating)	Colder, Warmer, Warmer Climate, Colder Climate
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	No

## Heat Pump for Domestic Hot Water (DHW)

### EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

### EN 12102-2 | Average Climate

Sound power level indoor	54 dB(A)
--------------------------	----------

### EN 16147 | Average Climate

Declared load profile	M
Efficiency $\eta_{DHW}$	112 %
COP	2.61
Heating up time	4:40 h:min
Standby power input	14.0 W
Reference hot water temperature	52.8 °C
Mixed water at 40°C	85 l

### EN 12102-2 | Colder Climate

Sound power level indoor	54 dB(A)
--------------------------	----------

### EN 16147 | Colder Climate

Declared load profile	M
Efficiency $\eta_{DHW}$	95 %
COP	2.28
Heating up time	05:14 h:min
Standby power input	15.0 W
Reference hot water temperature	52.7 °C
Mixed water at 40°C	83 l

### EN 12102-2 | Warmer Climate

Sound power level indoor 54 dB(A)

EN 16147 | Warmer Climate

Declared load profile	M
Efficiency $\eta_{DHW}$	115 %
COP	2.75
Heating up time	4:02 h:min
Standby power input	14.0 W
Reference hot water temperature	52.8 °C
Mixed water at 40°C	84 l

## Model RSJ-08/80RDN7-B1

Model name	RSJ-08/80RDN7-B1
Application	n/a
Units	Indoor
Climate zone (for heating)	Colder, Warmer, Warmer Climate, Colder Climate
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	No

## Heat Pump for Domestic Hot Water (DHW)

### EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

### EN 12102-2 | Average Climate

Sound power level indoor	54 dB(A)
--------------------------	----------

### EN 16147 | Average Climate

Declared load profile	M
Efficiency $\eta_{DHW}$	112 %
COP	2.61
Heating up time	4:40 h:min
Standby power input	14.0 W
Reference hot water temperature	52.8 °C
Mixed water at 40°C	85 l

### EN 12102-2 | Colder Climate

Sound power level indoor	54 dB(A)
--------------------------	----------

### EN 16147 | Colder Climate

Declared load profile	M
Efficiency $\eta_{DHW}$	95 %
COP	2.28
Heating up time	05:14 h:min
Standby power input	15.0 W
Reference hot water temperature	52.7 °C
Mixed water at 40°C	83 l

### EN 12102-2 | Warmer Climate

Sound power level indoor 54 dB(A)

EN 16147 | Warmer Climate

Declared load profile	M
Efficiency $\eta_{DHW}$	115 %
COP	2.75
Heating up time	4:02 h:min
Standby power input	14.0 W
Reference hot water temperature	52.8 °C
Mixed water at 40°C	84 l