

Subtype Grant Aerona HPR29065

Certificate Holder	Grant Engineering (UK) Ltd
Address	Frankland Road Blagrove
ZIP	SN5 8YG
City	Swindon
Country	GB
Certification Body	BRE Global Limited
Subtype title	Grant Aerona HPR29065
Registration number	041-K006-06
Heat Pump Type	Outdoor Air/Water
Refrigerant	R290
Mass of Refrigerant	0.83 kg
Certification Date	14.01.2025
Testing basis	Heat Pump Keymark Scheme Rules Rev 15

**Model Grant Aerona HPR29065**

Model name	Grant Aerona HPR29065
Application	Heating + DHW + low temp
Units	Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	n/a

**Outdoor Air/Water****EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	129.3 %
COP	3.05
Heating up time	01:49 h:min
Standby power input	41 W
Reference hot water temperature	55.5 °C
Mixed water at 40°C	330 l

**EN 14511-4 | Heating**

Shutting off the heat transfer medium flow passed

Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

**EN 14511-2 | Heating**

	Low temperature	Medium temperature
Heat output	7.62 kW	7.23 kW
El input	1.54 kW	2.4 kW
COP	4.95	3

**EN 12102-1 | Average Climate**

	Low temperature	Medium temperature
Sound power level outdoor	51 dB(A)	52 dB(A)

**EN 14825 | Average Climate**

	Low temperature	Medium temperature
$\eta_s$	203 %	145 %
Prated	6.5 kW	6.5 kW
SCOP	5.16	3.7

Tbiv	-9 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.33 kW	5.98 kW
COP Tj = -7°C	3.25	2.33
Cdh Tj = -7 °C	0.9	0.9
Pdh Tj = +2°C	4.03 kW	3.99 kW
COP Tj = +2°C	5.22	3.77
Cdh Tj = +2 °C	0.9	0.9
Pdh Tj = +7°C	2.74 kW	2.75 kW
COP Tj = +7°C	6.85	4.74
Cdh Tj = +7 °C	0.9	0.9
Pdh Tj = 12°C	2.24 kW	2.41 kW
COP Tj = 12°C	8.07	6.17
Cdh Tj = +12 °C	0.9	0.9
Pdh Tj = Tbiv	6.18 kW	6.09 kW
COP Tj = Tbiv	2.91	2.09
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.99 kW	5.65 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.82	1.97
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.9	0.9
WTOL	60 °C	60 °C
Poff	7 W	7 W
PTO	25 W	25 W
PSB	7 W	7 W
PCK	20 W	20 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.48 kW	0.79 kW
Annual energy consumption Qhe	2603 kWh	3633 kWh