

Subtype CALIDO1 300

Certificate Holder	Advantix S.p.A.
Address	Via San Giuseppe Lavoratore, 24
ZIP	37040
City	Arcole Verona
Country	IT
Certification Body	ICIM S.p.A.
Subtype title	CALIDO1 300
Registration number	ICIM-PDC-000091
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R134a
Mass of Refrigerant	0.92 kg
Certification Date	21.12.2020
Testing basis	V8

Model CALIDO1 300	
Model name	CALIDO1 300
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW)	
EN 16147 Operating test	
Temperature operating range	2
Safety devices checking test	2
Condensate draining	2
EN 12102-2 Average Climate	
Sound power level indoor	58 dB(A)
EN 16147 Average Climate	
Declared load profile	XL
Efficiency η_{DHW}	118 %
COP	2.85
Heating up time	9:53 h:min
Standby power input	40.0 W
Reference hot water temperature	55.0 °C
Mixed water at 40°C	390 l

Model CALIDO1 300-S	
Model name	CALIDO1 300-S
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW)	
EN 16147 Operating test	
Temperature operating range	2
Safety devices checking test	2
Condensate draining	2
EN 12102-2 Average Climate	
Sound power level indoor	58 dB(A)
EN 16147 Average Climate	
Declared load profile	XL
Efficiency η_{DHW}	118 %
COP	2.85
Heating up time	9:53 h:min
Standby power input	40.0 W
Reference hot water temperature	55.0 °C
Mixed water at 40°C	390 l

Model CALIDO1 300-D	
Model name	CALIDO1 300-D
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW)	
EN 16147 Operating test	
Temperature operating range	2
Safety devices checking test	2
Condensate draining	2
EN 12102-2 Average Climate	
Sound power level indoor	58 dB(A)
EN 16147 Average Climate	
Declared load profile	XL
Efficiency η_{DHW}	118 %
COP	2.85
Heating up time	9:53 h:min
Standby power input	40.0 W
Reference hot water temperature	55.0 °C
Mixed water at 40°C	390 l