

## Subtype VIESSMANN Vitocal 262-A (300 L)

Certificate Holder	Viessmann Climate Solutions GmbH & Co. KG
Address	Viessmannstr. 1
ZIP	35107
City	Allendorf/Eder
Country	DE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	VIESSMANN Vitocal 262-A (300 L)
Registration number	011-1W0193
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R1234ze
Mass of Refrigerant	1.35 kg
Certification Date	30.06.2020



## Model VIESSMANN Vitocal 262-A (300 L) Typ T2E ze

Model name	VIESSMANN Vitocal 262-A (300 L) Typ T2E ze
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Indoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	Yes

## Heat Pump for Domestic Hot Water (DHW)

### EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

### EN 12102-2 | Average Climate

Sound power level indoor	53 dB(A)
--------------------------	----------

### EN 16147 | Average Climate

Declared load profile	XL
Efficiency $\eta_{DHW}$	165 %
COP	4.02
Heating up time	8:57 h:min
Standby power input	22.8 W
Reference hot water temperature	53.4 °C
Mixed water at 40°C	414 l



## Model VIESSMANN Vitocal 262-A (300 L) Typ T2H ze

Model name	VIESSMANN Vitocal 262-A (300 L) Typ T2H ze
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Indoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	Yes

## Heat Pump for Domestic Hot Water (DHW)

## EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

## EN 12102-2 | Average Climate

Sound power level indoor	53 dB(A)
--------------------------	----------

## EN 16147 | Average Climate

Declared load profile	XL
Efficiency $\eta_{DHW}$	165 %
COP	4.02
Heating up time	8:57 h:min
Standby power input	22.8 W
Reference hot water temperature	53.4 °C
Mixed water at 40°C	414 l



## Model VIESSMANN Vitocal 262-A (300L) Typ T2E ze

Model name	VIESSMANN Vitocal 262-A (300L) Typ T2E ze
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	Yes

## Heat Pump for Domestic Hot Water (DHW)

### EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

### EN 12102-2 | Average Climate

Sound power level indoor	50 dB(A)
--------------------------	----------

### EN 16147 | Average Climate

Declared load profile	XL
Efficiency $\eta_{DHW}$	141 %
COP	3.44
Heating up time	10:56 h:min
Standby power input	22.0 W
Reference hot water temperature	53.6 °C
Mixed water at 40°C	419 l



## Model VIESSMANN Vitocal 262-A (300L) Typ T2H ze

Model name	VIESSMANN Vitocal 262-A (300L) Typ T2H ze
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	Yes

## Heat Pump for Domestic Hot Water (DHW)

## EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

## EN 12102-2 | Average Climate

Sound power level indoor	50 dB(A)
--------------------------	----------

## EN 16147 | Average Climate

Declared load profile	XL
Efficiency $\eta_{DHW}$	141 %
COP	3.44
Heating up time	10:56 h:min
Standby power input	22.0 W
Reference hot water temperature	53.6 °C
Mixed water at 40°C	419 l