

Subtype VIESSMANN Vitocal 060-A Typ T0S-ze 060-A (250l)

Certificate Holder	Viessmann Climate Solutions GmbH & Co. KG
Address	Viessmannstr. 1
ZIP	35107
City	Allendorf/Eder
Country	DE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	VIESSMANN Vitocal 060-A Typ T0S-ze 060-A (250l)
Registration number	011-1W0192
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R1234ze
Mass of Refrigerant	1.25 kg
Certification Date	27.02.2020

Model VIESSMANN Vitocal 060-A Typ T0S-ze 060-A (250l)

Model name	VIESSMANN Vitocal 060-A Typ T0S-ze 060-A (250l)
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	Yes

Heat Pump for Domestic Hot Water (DHW)

EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

EN 12102-2 | Average Climate

Sound power level indoor	50 dB(A)
--------------------------	----------

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	132 %
COP	3.15
Heating up time	9:37 h:min
Standby power input	30.0 W
Reference hot water temperature	54.7 °C
Mixed water at 40°C	344 l

Model Carrier AquaSnap 250 DHW-HP-S

Model name	Carrier AquaSnap 250 DHW-HP-S
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	Yes

Heat Pump for Domestic Hot Water (DHW)

EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

EN 12102-2 | Average Climate

Sound power level indoor	53 dB(A)
--------------------------	----------

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	132 %
COP	3.15
Heating up time	9:37 h:min
Standby power input	30.0 W
Reference hot water temperature	54.7 °C
Mixed water at 40°C	344 l