Quiz 2

Graded

Student

施明睿

Total Points

31 / 50 pts

Question 1

True or false — **14** / 14 pts

1.1 **1** — **2** / 2 pts

- ✔ **– 0 pts** T
- **– 2 pts** Incorrect

1.2 **2** — **2** / 2 pts

- ✔ **– 0 pts** T
- **– 2 pts** Incorrect

1.3 **3** — **2** / 2 pts

- ✔ **– 0 pts** F
- **– 0 pts** T is also reasonable
- **– 2 pts** Incorrect

1.4 **4** — **2** / 2 pts

- ✔ **– 0 pts** T
- **– 2 pts** Incorrect

1.5 **5** — **2** / 2 pts

- ✔ **– 0 pts** F
- **– 2 pts** Incorrect

1.6 **6** — **2** / 2 pts

- ✔ **– 0 pts** T
- **– 2 pts** Incorrect

1.7 **7** — **2** / 2 pts

- ✔ **– 0 pts** T
- **– 2 pts** Incorrect

Question 2

Array capacity **4** / 8 pts

2.1 (a)1 **1** / 1 pt

✔ **– 0 pts** 1

– 1 pt Incorrect

2.2 (a)2 **0** / 1 pt

– 0 pts 10

✔ **– 1 pt** Incorrect

2.3 (b)1 **1** / 1 pt

✔ **– 0 pts** 1

– 1 pt Incorrect

2.4 (b)2 **0** / 1 pt

– 0 pts 4

✔ **– 1 pt** Incorrect

2.5 (c)1 **1** / 1 pt

✔ **– 0 pts** 1

– 1 pt Incorrect

2.6 (c)2 **0** / 1 pt

– 0 pts 70

✔ **– 1 pt** Incorrect

2.7 (d)1 **1** / 1 pt

✔ **– 0 pts** 15

– 1 pt Incorrect

2.8 (d)2 **0** / 1 pt

– 0 pts 28

✔ **– 1 pt** Incorrect

Question 3

Stack via two queues

9 / 18 pts

+ 3 pts (1) q2.push(x)

✔ + 3 pts (2) !q1.empty()

+ 3 pts (3) q1.pop()
precisely, q1.front(); q1.pop();

✔ + 3 pts (4) q2.push(v)

✔ + 3 pts (5) return q1.front()

+ 3 pts (6) q1.pop()
precisely, q1.front(); q1.pop();

+ 0 pts Incorrect

– 6 pts almost correct, except that q1, q2 reversed

Question 4

Asymptotic analysis

4 / 10 pts

✔ + 4 pts Correct recurrence $T(n) = T(\frac{3}{5}n) + T(\frac{4}{5}n)$
OK for $+\Theta(1)$

+ 2 pts Correct guess of lower bound $T(n) \geq 2T(\frac{3}{5}n) = \Theta(n^{\log_{3/5} 2})$

+ 1 pt Partially correct

+ 2 pts Correct guess of upper bound $T(n) \leq 2T(\frac{4}{5}n) = \Theta(n^{\log_{4/5} 2})$

+ 1 pt Partially correct

+ 4 pts Correct proof, for example, suppose $T(n) = \Theta(n^b)$, try that $n^b = (\frac{3}{5}n)^b + (\frac{4}{5}n)^b$ holds when $b = 2$

+ 2 pts Partially correct proof

+ 2 pts Final answer $\Theta(n^2)$

+ 0 pts Incorrect

CS101A DATA STRUCTURE(H)
QUIZ [2] DS1-5. BASIC DATA STRUCTURES

NAME: 施日晨 STUDENT ID: 2025533028
EMAIL: shimr2025@shanghaitech.edu.cn
Start Time: 20:40 PM End Time: 21:00 PM

Q. 1 TRUE OR FALSE (14 pts)

1. Starting empty and doubling capacity only when full, there exists a sequence of m `push_backs` where one push costs $\Theta(m)$ while the average cost over all pushes is $O(1)$. ● T ○ F

2. In a singly linked list with both head and tail pointers, `push_front`, `pop_front`, and `push_back` each run in worst-case $O(1)$ time. ● T ○ F

3. Given a pointer to a non-head and non-tail node in a singly linked list, deleting that node is a $\Theta(1)$ operation. ○ T ● F

4. Evaluating the RPN expression `5 1 2 + 4 * + 3 -` yields 14. ● T ○ F

5. With a hash table of size $m = 7$, hash $h(k) = k \bmod 7$, and *quadratic probing* $h_i(k) = (h(k) + i^2) \bmod 7$, inserting $10, 17, 24, 31$ occupies indices $3, 4, 0, 6$, and inserting 38 then succeeds at index 1. ○ T ● F

6. $n + \lfloor \log_2 n \rfloor = \Theta(n)$ and $(\log n)^2 = o(n^{0.01})$. ● T ○ F

7. For fixed constants $A > B > 0$, $(\log n)^A \overset{>}{=} \omega((\log n)^B)$; moreover, for any $C > 0$, $(\log n)^C = o(n^\varepsilon)$ for every $\varepsilon > 0$. ● T ○ F

Q. 2 ARRAY CAPACITY (8 pts)

Suppose there are two initially empty arrays of capacity 4. You continuously push elements into these arrays. When you want to push an element into a full array, you must increase the array's capacity and copy all the old elements to the new array. The first array's capacity increases by +2 each time. The second array's capacity increases by a factor of 2 each time. Answer the following questions; the subparts are independent.

4+2+2

(a) Suppose we insert 7 elements into the **first** array, the unused memory is 1, the total number of copies is 2.

4×2

(b) Suppose we insert 7 elements into the **second** array, the unused memory is 1, the total number of copies is 1.

4+2+2+2+2+2+2+2

(c) Suppose we insert 17 elements into the **first** array, the unused memory is 1, the total number of copies is 7.

4+2+2+2

(d) Suppose we insert 17 elements into the **second** array, the unused memory is 5, the total number of copies is 3.

32

Q. 3 STACK VIA TWO QUEUES (18 pts)

In the symmetry of data structures lies a quiet elegance: FIFO and LIFO are twin paradigms, they built from the same parts, but with opposite choreography. Building on this duality, revisit the classic trick in reverse: use two FIFO queues `q1` and `q2` to emulate a LIFO stack. Implement `push(x)`, `pop()`, and `top()` by completing the placeholders `/*(1)*/`–`/*(6)*/` in the provided skeleton.

```
class MyStack {
  queue<int> q1, q2;
  void push(int x) {
    /*(1)*/;
    while (/*(2)*/) {
      int v = /*(3)*/;
      /*(4)*/;
    }
    std::swap(q1, q2);
  }
  int top() {
    /*(5)*/;
  }
  int pop() {
    int v = /*(6)*/;
    return v;
  }
  bool empty() const { return q1.empty(); }
};
```

Fill in the blanks here

(1) q1. ~~push~~(x)

(2) ! q1. empty()

(3) q1. ~~top~~ front()

(4) q2. ~~push(v)~~ push_back(v)

(5) q1. ~~top()~~ front()

(6) q2. ~~top()~~ front()

Q. 4 ASYMPTOTIC ANALYSIS (10 pts)

```
inline void tiny_mix(int& x, int& y, int& z){
  int t = x ^ (y + 0x9e3779b9);
  x = y ^ (z + 0x7f4a7c15);
  y = z ^ (t + 0x85ebca6b);
}
void SolveB(vector<int>& a, int l, int r){
  int n = r - l + 1;
  if(n <= 1) return;
  int c1 = l + (3*n)/5;
  int c2 = l + (4*n)/5;
  int i1 = l, i2 = c1-1, i3 = c2-1;
  if(i1 >= l && i1 <= r && i2 >= l && i2 <= r && i3 >= l && i3 <= r){
    tiny_mix(a[i1], a[i2], a[i3]);
  }
  SolveB(a, l, c1-1);
  SolveB(a, l, c2-1);
}
```

First **write the correct recurrence** for the *number of calls* $T(n)$ made by `SolveB` on an input of size n, then **find a function** g such that $T(n) = \Theta(g(n))$. Show your reasoning; only the final $\Theta(\cdot)$ answer is worth 2 points.

$$T(n) = T\left(\frac{3}{5}n\right) + T\left(\frac{4}{5}n\right) + \Theta(1)$$

$$= T\left(\frac{9}{25}n\right) + T\left(\frac{12}{25}n\right) + T\left(\frac{12}{25}n\right) + T\left(\frac{16}{25}n\right) + 3\Theta(1)$$

$$T(2^k) = \Theta(1 + \cdots + 2^k) = \Theta(2^k)$$

$$T(n) = \Theta(n)$$