Quiz 3

Graded

Student

施明睿

Total Points

28 / 50 pts

Question 1

True or false — **6** / 15 pts

1.1 **a** — **3** / 3 pts

- ✔ **– 0 pts** F
- **– 3 pts** Incorrect

1.2 **b** — **3** / 3 pts

- ✔ **– 0 pts** T
- **– 3 pts** Incorrect

1.3 **c** — **0** / 3 pts

- **– 0 pts** F
- ✔ **– 3 pts** Incorrect

1.4 **d** — **0** / 3 pts

- **– 0 pts** T
- ✔ **– 3 pts** Incorrect

1.5 **e** — **0** / 3 pts

- **– 0 pts** T
- ✔ **– 3 pts** Incorrect

Question 2

Fill in the blanks **9** / 15 pts

2.1 **a** **0** / 3 pts

– **0 pts** 1/2

✔ – **3 pts** incorrect

2.2 **b1** **1.5** / 1.5 pts

✔ – **0 pts** $\Theta(n^2)$

– **1.5 pts** incorrect

2.3 **b2** **1.5** / 1.5 pts

✔ – **0 pts** $\Theta(n)$

– **1.5 pts** incorrect

2.4 **c** **0** / 3 pts

– **0 pts** $\Theta(\log n)$

✔ – **3 pts** incorrect

2.5 **d** **3** / 3 pts

✔ – **0 pts** bubble sort

– **3 pts** incorrect

2.6 **e** **3** / 3 pts

✔ – **0 pts** insertion sort

– **3 pts** incorrect

Question 3

Alternating bubble sort **13** / 20 pts

3.1 **a** **3** / 3 pts

✔ **– 0 pts** B

– 3 pts incorrect

3.2 **b** **3** / 3 pts

✔ **– 0 pts** $\Theta(n^2)$

– 3 pts incorrect

3.3 **c1** **2** / 2 pts

✔ **– 0 pts** lower

– 2 pts incorrect

3.4 **c2** **2** / 2 pts

✔ **– 0 pts** upper/new_upper

– 2 pts incorrect

3.5 **c3** **2** / 2 pts

✔ **– 0 pts** 0/lower

– 2 pts incorrect

3.6 **d** **0** / 3 pts

– 0 pts T

✔ **– 3 pts** Incorrect

3.7 **e** **1** / 5 pts

– 0 pts {3,4,2,6,5,1,0,7}
{0,3,4,2,6,5,1,7}
{0,3,2,4,5,1,6,7}
{0,1,3,2,4,5,6,7}
{0,1,2,3,4,5,6,7}

– 1 pt Partially incorrect

– 2 pts Partially incorrect

– 3 pts Partially incorrect (or write correctly after each while loop)

✔ **– 4 pts** Partially incorrect

– 5 pts Incorrect

– 1 pt ignore break after the 5th for loop

CS 101A Fall 2025 - Quiz 3
November, 11, 2025 - 20 Minutes

Name: 施明睿 Student ID: 2025533028

---

1. (15 points) True or False

Determine whether the following statements are true or false.

(a) (3') Merge sort is not an in place sorting since it requires $\Theta(\log n)$ space. ○ True ● False

(b) (3') When an array contains distinct elements and is arranged in descending order, the time complexity of quick sort (always choose the last element as pivot) is $\Theta(n^2)$. ● True ○ False

(c) (3') There exists an comparison-base sort algorithm that needs $O(1)$ extra space and takes $o(n \log n)$ time. ● True ○ False

(d) (3') For an array $\{a_n\}$ with distinct elements, for fixed i, j, if $\forall a_k \neq a_i,\ a_k \neq a_j,\ (a_k - a_i)(a_k - a_j) > 0$, then a_i and a_j will be compared in any case when using randomized quick-sort to make $\{a_n\}$ sorted. $a_k \geq a_i$ $a_k \geq a_j$ ○ True ● False

(e) (3') When performing flagged bubble sort on a array of n elements, the minimum number of comparisons is $n - 1$. ○ True ● False

2. (15 points) Fill in the blanks

(a) (3') If we use randomized quick-sort (i.e., randomly choosing pivots) to sort the array $[3, 4, 6, 2, 1, 5, 8, 0]$, the probability that 2 and 5 are compared is $\frac{1}{3}$.

(b) (3') The worst case runtime of insertion sort is Θ (n^2), and the best case runtime is Θ (n). (The array has n entries.)

(c) (3') In average case, the space complexity of quick sort on n elements is Θ($n \log n$) .

(d) (3') The following is the process of sorting an array $\{7, 8, 5, 2, 4, 6, 3\}$ by a sorting algorithm $\{7, 8, 5, 2, 4, 6, 3\} \to \{7, 5, 2, 4, 6, 3, 8\} \to \{5, 2, 4, 6, 3, 7, 8\} \to \{2, 4, 5, 3, 6, 7, 8\} \to \{2, 4, 3, 5, 6, 7, 8\} \to \{2, 3, 4, 5, 6, 7, 8\} \to \{2, 3, 4, 5, 6, 7, 8\}$
Which sorting algorithm is it? bubble sort

(e) (3') The array {8,9,10,4,5,6,20,1,2} is the result of insertion sort after two passes of the outer loop. (fill in the blank with "bubble" or "insertion")

3. (20 points) Alternating bubble sort

```
template <typename Type>
void bubble(Type* const array, int n) {
    int lower = 0;
    int upper = n - 1;
    while (true) {
        int new_upper = lower;
        for (int i = lower; i < upper; ++i) {
            if (array[i] > array[i + 1]) {
                Type tmp = array[i];
                array[i] = array[i + 1];
                array[i + 1] = tmp;
                new_upper = i;}
        }
```

```
        upper = new_upper;
        if (lower == upper) { break; }
        int new_lower = upper;
        for (int i = upper; i > lower; --i) {
                if (array[i - 1] > array[i]) {
                        Type tmp = array[i];
                        array[i] = array[i - 1];
                        array[i - 1] = tmp;
                        new_lower = i;}
        }
        lower = new_lower;
        if (lower == upper) { break; }
}
```

Suppose we apply this algorithm to an array with n entries.

(a) (3') Compared with the standard one-way bubble sort, the main optimization of the given code is: B

A. Using binary search to locate swap positions

B. Using a bidirectional pass to push both the maximum and minimum toward the boundaries, shrinking the unsorted range

C. Using a faster swap trick to reduce assignments

(b) (3') In the worst case (array in reverse order), the time complexity of this algorithm is Θ (n^2).

(c) (6') After the first for loop (from lower to upper) in the first iteration of the while loop completes, the statement "upper = new_upper" updates the right boundary of the unsorted range to the last swap position i, skipping the already sorted suffix. Thus, the unsorted range of the array shrinks to [lower , upper] (fill in the name of the variable). If no swap occurs in this pass, then *new_upper* will be equal to lower.

(d) (3') For this code to sort a custom **Type** correctly, Type must define the operator >. Additionally, swapping via a temporary requires that the type supports copying or moving. ○ True ● False

(e) (5') Sort the array {3, 7, 4, 2, 6, 5, 1, 0} using the algorithm above. Write down the array after each **for** loop.

0 {3, 7, 4, 2, 6, 5, 1, 0}

1 {0, 3, 4, 2, 6, 5, 1, 7}

2 {0, 1, 3, 4, 2, 5, 6, 7}

3 {0, 1, 2, 3, 4, 5, 6, 7}

4 {0, 1, 2, 3, 4, 5, 6, 7}