

VueJS - Examples

Dr. B. Prabavathy
Associate Professor



Ex 5: Display a student's result based on whether the student is present and, if present, whether the student has passed.

Nested if Example

```
<script setup>
import { ref } from 'vue'
const isPresent = ref(true)
const hasPassed = ref(true)
</script>
<template>
  <div>
    <h2>Student Result</h2>
    <p v-if="isPresent">
      Student is present.
      <span v-if="hasPassed">
        Student has passed the exam.
      </span>
      <span v-else>
        Student has failed the exam.
      </span>
    </p>
    <p v-else>
      Student is absent.
    </p>
  </div>
</template>
```

Student Details

Student Result

Student is present. Student has passed the exam.

Student Details

Student Result

Student is absent.

Student Details

Student Result

Student is present. Student has failed the exam.



Ex 6: Two-Way Binding using v-model - Example

- `v-model="studentName"` creates two-way binding.
- **When the user types, studentName is automatically updated.**
- **When studentName changes, the input field is also updated.**

```
<script setup>
import { ref } from 'vue'
const studentName = ref("")
</script>
<template>
  <div>
    <h2>Student Registration</h2>
    <label>Enter your name:</label>
    <input v-model="studentName" placeholder="Enter name">
    <p>Student Name: {{ studentName }}</p>
  </div>
</template>
```

Student Details

Student Registration

Enter your name:

Student Name: prabavathy

Student Details

Student Registration

Enter your name:

Student Name: prabav



Ex: 7 Image Slider using Directives

```
<script setup>
import { ref } from 'vue'
const currentImage = ref(0)
const images = [ 'baby1.jpg', 'baby2.jpg', 'baby3.jpg']
function nextImage() {
  currentImage.value = (currentImage.value + 1) % images.length
}
function previousImage() {
  currentImage.value = (currentImage.value - 1 + images.length) % images.length
}
</script>
<template>
  <div>
    <h2>Image Slider</h2>
    
    <button @click="previousImage"> Previous </button>
    <button @click="nextImage"> Next </button>
    <p v-if="currentImage == 0"> First Image </p>
    <p v-else-if="currentImage == images.length - 1"> Last Image </p>
    <p v-else> Middle Image </p>
  </div>
</template>
```

Student Details

Image Slider



Previous Next

First Image

Student Details

Image Slider



Previous Next

Last Image

v 1.2

Output Snapshots

Student Details

Image Slider



Previous Next

Middle Image



Ex. 8: Simple Todo List

```
<script setup>
import { ref } from 'vue'
const newTodo = ref("")
const todos = ref([])
function addTodo() {
  if (newTodo.value !== "") {
    todos.value.push(newTodo.value)
    newTodo.value = ""
  }
}
</script>
<template>
  <div>
    <h2>Todo List</h2>
    <input v-model="newTodo" placeholder="Enter a task" >
    <button @click="addTodo"> Add </button>
    <ul>
      <li v-for="todo in todos" :key="todo"> {{ todo }} </li>
    </ul>
  </div>
</template>
```

Student Details

Todo List

Enter a task

- Paul Project Discussion
- FYP Review
- Balaji Paper

Ex. 9: Five Playcards with random color

```
<script setup>
import { ref } from 'vue'
const cards = ref([
  { id: 1, color: 'red' },
  { id: 2, color: 'blue' },
  { id: 3, color: 'green' },
  { id: 4, color: 'orange' },
  { id: 5, color: 'purple' }
])
</script>
<template>
  <div>
    <h2>Play Cards</h2>
    <div class="cards">
      <div v-for="card in cards" :key="card.id" class="card"
        :style="{ backgroundColor: card.color }">
        >
          Card {{ card.id }}
        </div>
      </div>
    </div>
  </div>
</template>
```

```
<style scoped>
.cards {
  display: flex;
  gap: 10px;
}
.card {
  width: 100px;
  height: 140px;
  color: white;
  display: flex;
  align-items: center;
  justify-content: center;
  border-radius: 10px;
}</style>
```

Student Details

Play Cards



Ex. 10: fetching user data from a public API and displaying it in Vue

```
<script setup>
import { ref, onMounted } from 'vue'
const users = ref([])

async function getUsers() {
  const response = await fetch(
    'https://jsonplaceholder.typicode.com/users'
  )
  users.value = await response.json()
}

onMounted(() => {
  getUsers()
})
```

In Vue, :key is used with v-for so that Vue can uniquely identify each item in the list.

```
</script>
<template>
  <div>
    <h2>Users</h2>
    <ul>
      <li v-for="user in users" :key="user.id"> {{ user.name }} - {{ user.email }}
    </li>
    </ul>
  </div>
</template>
```

Student Details

Users

- Leanne Graham - Sincere@april.biz
- Ervin Howell - Shanna@melissa.tv
- Clementine Bauch - Nathan@yesenia.net
- Patricia Lebsack - Julianne.OConner@kory.org
- Chelsey Dietrich - Lucio_Hettinger@annie.ca
- Mrs. Dennis Schulist - Karley_Dach@jasper.info
- Kurtis Weissnat - Telly.Hoeger@billy.biz
- Nicholas Runolfsdottir V - Sherwood@rosamond.me
- Glenna Reichert - Chaim_McDermott@dana.io
- Clementina DuBuque - Rey.Padberg@karina.biz

