



**Threagile**

Agile Threat Modeling

---

# Threat Model Report

## ChemoDemo IT OT Infrastructure

10 July 2025

ChemoDemo Security Team

# Table of Contents

## Results Overview

Management Summary	5
Impact Analysis of 235 Initial Risks in 18 Categories	6
Risk Mitigation	8
Impact Analysis of 235 Remaining Risks in 18 Categories	9
Application Overview	11
Data-Flow Diagram	13
Security Requirements	14
Abuse Cases	15
Tag Listing	16
STRIDE Classification of Identified Risks	17
Assignment by Function	20
RAA Analysis	23
Data Mapping	26
Out-of-Scope Assets: 0 Assets	27
Potential Model Failures: 171 / 171 Risks	28
Questions: 0 / 0 Questions	29

## Risks by Vulnerability Category

Identified Risks by Vulnerability Category	30
Cross-Site Scripting (XSS): 8 / 8 Risks	31
Missing Authentication: 12 / 12 Risks	33
Path-Traversal: 8 / 8 Risks	36
Unguarded Access From Internet: 5 / 5 Risks	39
Code Backdooring: 1 / 1 Risk	41
Missing Hardening: 2 / 2 Risks	44
Missing Network Segmentation: 4 / 4 Risks	46
Missing Vault (Secret Storage): 1 / 1 Risk	48
Unencrypted Technical Assets: 9 / 9 Risks	50
Accidental Secret Leak: 1 / 1 Risk	53
DoS-risky Access Across Trust-Boundary: 11 / 11 Risks	55
Incomplete Model: 45 / 45 Risks	58
Missing Identity Propagation: 2 / 2 Risks	65
Unchecked Deployment: 1 / 1 Risk	67
Unnecessary Communication Link: 50 / 50 Risks	69
Unnecessary Technical Asset: 17 / 17 Risks	76
Wrong Communication Link Content: 50 / 50 Risks	79
Wrong Trust Boundary Content: 8 / 8 Risks	87

**Risks by Technical Asset**

Identified Risks by Technical Asset	90
DC1: 15 / 15 Risks	91
DC2: 8 / 8 Risks	98
FW4: 22 / 22 Risks	101
NTP: 2 / 2 Risks	109
OS1: 11 / 11 Risks	111
R2: 26 / 26 Risks	115
S0: 5 / 5 Risks	125
S1: 12 / 12 Risks	128
S2: 5 / 5 Risks	133
S3: 11 / 11 Risks	136
S4: 25 / 25 Risks	141
S5: 8 / 8 Risks	149
S6: 7 / 7 Risks	152
TI1: 5 / 5 Risks	155
TI2: 4 / 4 Risks	158
WC1: 4 / 4 Risks	161
WC2: 4 / 4 Risks	164
WC3: 4 / 4 Risks	167
C1: 4 / 4 Risks	170
C2: 4 / 4 Risks	172
ES1: 5 / 5 Risks	174
FW1: 4 / 4 Risks	177
FW2: 5 / 5 Risks	180
FW3: 15 / 15 Risks	183
R1: 4 / 4 Risks	190
R3: 8 / 8 Risks	193
R4: 8 / 8 Risks	197

**Data Breach Probabilities by Data Asset**

Identified Data Breach Probabilities by Data Asset	201
erp-data: 22 / 22 Risks	202
production-data: 41 / 41 Risks	203

**Trust Boundaries**

DMZ	205
OT-TB1	205
OT-TB2	205
Office	205

Operations	206
<hr/>	
<b>About Threagile</b>	
Risk Rules Checked by Threagile	208
Disclaimer	221

## Management Summary



Threagile toolkit was used to model the architecture of "ChemoDemo IT OT Infrastructure" and derive risks by analyzing the components and data flows. The risks identified during this analysis are shown in the following chapters. Identified risks during threat modeling do not necessarily mean that the vulnerability associated with this risk actually exists: it is more to be seen as a list of potential risks and threats, which should be individually reviewed and reduced by removing false positives. For the remaining risks it should be checked in the design and implementation of "ChemoDemo IT OT Infrastructure" whether the mitigation advices have been applied or not.

Each risk finding references a chapter of the OWASP ASVS (Application Security Verification Standard) audit checklist. The OWASP ASVS checklist should be considered as an inspiration by architects and developers to further harden the application in a Defense-in-Depth approach. Additionally, for each risk finding a link towards a matching OWASP Cheat Sheet or similar with technical details about how to implement a mitigation is given.

In total **235 initial risks** in **18 categories** have been identified during the threat modeling process:

**0 critical risk**  
**0 high risk**  
**29 elevated risk**  
**19 medium risk**  
**187 low risk**

**235 unchecked**  
**0 in discussion**  
**0 accepted**  
**0 in progress**  
**0 mitigated**  
**0 false positive**



# Impact Analysis of 235 Initial Risks in 18 Categories

The most prevalent impacts of the **235 initial risks** (distributed over **18 risk categories**) are (taking the severity ratings into account and using the highest for each category):

Risk finding paragraphs are clickable and link to the corresponding chapter.

**Elevated: Cross-Site Scripting (XSS):** 8 Initial Risks - Exploitation likelihood is *Likely with Medium impact*.

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

**Elevated: Missing Authentication:** 12 Initial Risks - Exploitation likelihood is *Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to access or modify sensitive data in an unauthenticated way.

**Elevated: Path-Traversal:** 8 Initial Risks - Exploitation likelihood is *Very Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to read sensitive files (configuration data, key/credential files, deployment files, business data files, etc.) from the filesystem of affected components.

**Elevated: Unguarded Access From Internet:** 5 Initial Risks - Exploitation likelihood is *Very Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to directly attack sensitive systems without any hardening components in-between due to them being directly exposed on the internet.

**Medium: Code Backdooring:** 1 Initial Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk remains unmitigated, attackers might be able to execute code on and completely takeover production environments.

**Medium: Missing Hardening:** 2 Initial Risks - Exploitation likelihood is *Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

**Medium: Missing Network Segmentation:** 4 Initial Risks - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers successfully attacking other components of the system might have an easy path towards more valuable targets, as they are not separated by network segmentation.

**Medium: Missing Vault (Secret Storage):** 1 Initial Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

**Medium: Unencrypted Technical Assets:** 9 Initial Risks - Exploitation likelihood is *Unlikely with High impact*.

If this risk is unmitigated, attackers might be able to access unencrypted data when successfully compromising sensitive components.

Low: **Accidental Secret Leak:** 1 Initial Risk - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk is unmitigated, attackers which have access to affected sourcecode repositories or artifact registries might find secrets accidentally checked-in.

Low: **DoS-risky Access Across Trust-Boundary:** 11 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk remains unmitigated, attackers might be able to disturb the availability of important parts of the system.

Low: **Incomplete Model:** 45 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk is unmitigated, other risks might not be noticed as the model is incomplete.

Low: **Missing Identity Propagation:** 2 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk is unmitigated, attackers might be able to access or modify foreign data after a successful compromise of a component within the system due to missing resource-based authorization checks.

Low: **Unchecked Deployment:** 1 Initial Risk - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk remains unmitigated, vulnerabilities in custom-developed software or their dependencies might not be identified during continuous deployment cycles.

Low: **Unnecessary Communication Link:** 50 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk is unmitigated, attackers might be able to target unnecessary communication links.


Low: **Unnecessary Technical Asset:** 17 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this risk is unmitigated, attackers might be able to target unnecessary technical assets.

Low: **Wrong Communication Link Content:** 50 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this potential model error is not fixed, some risks might not be visible.

Low: **Wrong Trust Boundary Content:** 8 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.  
If this potential model error is not fixed, some risks might not be visible.

# Risk Mitigation



The following chart gives a high-level overview of the risk tracking status (including mitigated risks):



After removal of risks with status *mitigated* and *false positive* the following 235 remain unmitigated:

- 0 unmitigated critical risk
- 0 unmitigated high risk
- 29 unmitigated elevated risk
- 19 unmitigated medium risk
- 187 unmitigated low risk

- 0 business side related
- 191 architecture related
- 16 development related
- 28 operations related





# Impact Analysis of 235 Remaining Risks in 18 Categories

The most prevalent impacts of the **235 remaining risks** (distributed over **18 risk categories**) are (taking the severity ratings into account and using the highest for each category):

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated: **Cross-Site Scripting (XSS)**: 8 Remaining Risks - Exploitation likelihood is *Likely with Medium impact*.

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Elevated: **Missing Authentication**: 12 Remaining Risks - Exploitation likelihood is *Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to access or modify sensitive data in an unauthenticated way.

Elevated: **Path-Traversal**: 8 Remaining Risks - Exploitation likelihood is *Very Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to read sensitive files (configuration data, key/credential files, deployment files, business data files, etc.) from the filesystem of affected components.

Elevated: **Unguarded Access From Internet**: 5 Remaining Risks - Exploitation likelihood is *Very Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to directly attack sensitive systems without any hardening components in-between due to them being directly exposed on the internet.

Medium: **Code Backdooring**: 1 Remaining Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk remains unmitigated, attackers might be able to execute code on and completely takeover production environments.

Medium: **Missing Hardening**: 2 Remaining Risks - Exploitation likelihood is *Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Medium: **Missing Network Segmentation**: 4 Remaining Risks - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers successfully attacking other components of the system might have an easy path towards more valuable targets, as they are not separated by network segmentation.

Medium: **Missing Vault (Secret Storage)**: 1 Remaining Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

**Medium: Unencrypted Technical Assets:** 9 Remaining Risks - Exploitation likelihood is *Unlikely* with *High* impact.

If this risk is unmitigated, attackers might be able to access unencrypted data when successfully compromising sensitive components.

**Low: Accidental Secret Leak:** 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers which have access to affected sourcecode repositories or artifact registries might find secrets accidentally checked-in.

**Low: DoS-risky Access Across Trust-Boundary:** 11 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk remains unmitigated, attackers might be able to disturb the availability of important parts of the system.

**Low: Incomplete Model:** 45 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, other risks might not be noticed as the model is incomplete.

**Low: Missing Identity Propagation:** 2 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to access or modify foreign data after a successful compromise of a component within the system due to missing resource-based authorization checks.

**Low: Unchecked Deployment:** 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk remains unmitigated, vulnerabilities in custom-developed software or their dependencies might not be identified during continuous deployment cycles.

**Low: Unnecessary Communication Link:** 50 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to target unnecessary communication links.

**Low: Unnecessary Technical Asset:** 17 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to target unnecessary technical assets.

**Low: Wrong Communication Link Content:** 50 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this potential model error is not fixed, some risks might not be visible.

**Low: Wrong Trust Boundary Content:** 8 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this potential model error is not fixed, some risks might not be visible.

# Application Overview

## Business Criticality

The overall business criticality of "ChemoDemo IT OT Infrastructure" was rated as:

( archive | operational | important | **CRITICAL** | mission-critical )


## Business Overview

Die ChemoDemo AG ist ein mittelständisches Unternehmen der chemischen Industrie mit einem hohen Automatisierungsgrad in der Produktion. Die Herstellung erfolgt in mehreren Prozessschritten, gesteuert über eine OT-Infrastruktur mit direkter Anbindung an zentrale IT-Systeme. Der unterbrechungsfreie Betrieb der Produktionsanlagen ist geschäftskritisch, da Lieferverpflichtungen, Qualitätssicherung und regulatorische Vorgaben stark von der Verfügbarkeit und Integrität der Systeme abhängen. Neben der Produktion unterstützt die IT auch kaufmännische Prozesse wie ERP, Reporting und Wartungsplanung.

## Technical Overview


Die technische Infrastruktur der ChemoDemo AG ist segmentiert in IT- und OT-Bereiche, die über mehrere Firewalls und ein Zonenkonzept verbunden sind. Im OT-Bereich steuern speicherprogrammierbare Steuerungen (PLCs) die Produktionsanlagen, unterstützt durch Engineering- und Operator-Stationen. Zentrale Schnittstellen wie der MIS-Server und ein Jump Server ermöglichen kontrollierten Zugriff zwischen IT- und OT-Komponenten. Die IT-Infrastruktur besteht aus Clients, Servern (z..B. ERP, Historian, Domaincontroller) sowie Wartungssystemen. Alle Zugriffe erfolgen über klar definierte Kommunikationspfade mit Authentifizierung, Netzwerksegmentierung und Monitoring.

## IT/OT Infrastruktur der ChemoDemo AG:



# Data-Flow Diagram

The following diagram was generated by Threatgile based on the model input and gives a high-level overview of the data-flow between technical assets. The RAA value is the calculated *Relative Attacker Attractiveness* in percent. For a full high-resolution version of this diagram please refer to the PNG image file alongside this report.



# Security Requirements

This chapter lists the custom security requirements which have been defined for the modeled target.

*This list is not complete and regulatory or law relevant security requirements have to be taken into account as well. Also custom individual security requirements might exist for the project.*

# Abuse Cases

This chapter lists the custom abuse cases which have been defined for the modeled target.

*This list is not complete and regulatory or law relevant abuse cases have to be taken into account as well. Also custom individual abuse cases might exist for the project.*

# Tag Listing

This chapter lists what tags are used by which elements.

## **dmz**

S0, DMZ

## **it**

C1, C2, DC1, R1, S2, S5, S6, WC1, WC2, WC3, erp-data, Office, Operations

## **ot**

DC2, ES1, FW4, OS1, R2, R3, R4, S3, TI1, TI2, OT-TB1, OT-TB2

## **production**

production-data

## **secure-zone**

FW1, FW2, FW3, FW4, NTP, S4, DMZ, Office



# STRIDE Classification of Identified Risks

This chapter clusters and classifies the risks by STRIDE categories: In total **235 potential risks** have been identified during the threat modeling process of which **0 in the Spoofing** category, **12 in the Tampering** category, **0 in the Repudiation** category, **114 in the Information Disclosure** category, **11 in the Denial of Service** category, and **98 in the Elevation of Privilege** category.

Risk finding paragraphs are clickable and link to the corresponding chapter.

## Spoofing

n/a

## Tampering

**Elevated: Cross-Site Scripting (XSS): 8 / 8 Risks** - Exploitation likelihood is *Likely with Medium impact*.

For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

**Medium: Code Backdooring: 1 / 1 Risk** - Exploitation likelihood is *Unlikely with Medium impact*.

For each build-pipeline component Code Backdooring risks might arise where attackers compromise the build-pipeline in order to let backdoored artifacts be shipped into production. Aside from direct code backdooring this includes backdooring of dependencies and even of more lower-level build infrastructure, like backdooring compilers (similar to what the XcodeGhost malware did) or dependencies.

**Medium: Missing Hardening: 2 / 2 Risks** - Exploitation likelihood is *Likely with Low impact*.

Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.

**Low: Unchecked Deployment: 1 / 1 Risk** - Exploitation likelihood is *Unlikely with Low impact*.

For each build-pipeline component Unchecked Deployment risks might arise when the build-pipeline does not include established DevSecOps best-practices. DevSecOps best-practices scan as part of CI/CD pipelines for vulnerabilities in source- or byte-code, dependencies, container layers, and dynamically against running test systems. There are several open-source and commercial tools existing in the categories DAST, SAST, and IAST.

## Repudiation

n/a

## Information Disclosure

**Elevated: Path-Traversal: 8 / 8 Risks** - Exploitation likelihood is *Very Likely* with *Medium* impact. When a filesystem is accessed Path-Traversal or Local-File-Inclusion (LFI) risks might arise. The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed or stored.

**Medium: Missing Vault (Secret Storage): 1 / 1 Risk** - Exploitation likelihood is *Unlikely* with *Medium* impact.

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

**Medium: Unencrypted Technical Assets: 9 / 9 Risks** - Exploitation likelihood is *Unlikely* with *High* impact.

Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.

**Low: Accidental Secret Leak: 1 / 1 Risk** - Exploitation likelihood is *Unlikely* with *Low* impact.

Sourcecode repositories (including their histories) as well as artifact registries can accidentally contain secrets like checked-in or packaged-in passwords, API tokens, certificates, crypto keys, etc.

**Low: Incomplete Model: 45 / 45 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When the threat model contains unknown technologies or transfers data over unknown protocols, this is an indicator for an incomplete model.

**Low: Wrong Communication Link Content: 50 / 50 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a communication link is defined as readonly, but does not receive any data asset, or when it is defined as not readonly, but does not send any data asset, it is likely to be a model failure.

## Denial of Service

**Low: DoS-risky Access Across Trust-Boundary: 11 / 11 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

Assets accessed across trust boundaries with critical or mission-critical availability rating are more prone to Denial-of-Service (DoS) risks.

## Elevation of Privilege

**Elevated: Missing Authentication: 12 / 12 Risks** - Exploitation likelihood is *Likely* with *Medium* impact.

Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

**Elevated: Unguarded Access From Internet: 5 / 5 Risks** - Exploitation likelihood is *Very Likely* with *Medium* impact.

Internet-exposed assets must be guarded by a protecting service, application, or reverse-proxy.

**Medium: Missing Network Segmentation: 4 / 4 Risks** - Exploitation likelihood is *Unlikely* with *Medium* impact.

Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webserver or content management systems etc.) should be better protected by a network segmentation trust-boundary.

**Low: Missing Identity Propagation: 2 / 2 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

Technical assets (especially multi-tenant systems), which usually process data for endusers should authorize every request based on the identity of the enduser when the data flow is authenticated (i.e. non-public). For DevOps usages at least a technical-user authorization is required.

**Low: Unnecessary Communication Link: 50 / 50 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical communication link does not send or receive any data assets, this is an indicator for an unnecessary communication link (or for an incomplete model).

**Low: Unnecessary Technical Asset: 17 / 17 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical asset does not process or store any data assets, this is an indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

**Low: Wrong Trust Boundary Content: 8 / 8 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a trust boundary of type network-policy-namespace-isolation contains non-container assets it is likely to be a model failure.

# Assignment by Function

This chapter clusters and assigns the risks by functions which are most likely able to check and mitigate them: In total **235 potential risks** have been identified during the threat modeling process of which **0 should be checked by Business Side**, **191 should be checked by Architecture**, **16 should be checked by Development**, and **28 should be checked by Operations**.

Risk finding paragraphs are clickable and link to the corresponding chapter.

## Business Side

n/a

## Architecture

Elevated: **Missing Authentication**: 12 / 12 Risks - Exploitation likelihood is *Likely* with *Medium* impact.

Apply an authentication method to the technical asset. To protect highly sensitive data consider the use of two-factor authentication for human users.

Elevated: **Unguarded Access From Internet**: 5 / 5 Risks - Exploitation likelihood is *Very Likely* with *Medium* impact.

Encapsulate the asset behind a guarding service, application, or reverse-proxy. For admin maintenance a bastion-host should be used as a jump-server. For file transfer a store-and-forward-host should be used as an indirect file exchange platform.

Medium: **Missing Vault (Secret Storage)**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Consider using a Vault (Secret Storage) to securely store and access config secrets (like credentials, private keys, client certificates, etc.).

Low: **Incomplete Model**: 45 / 45 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Try to find out what technology or protocol is used instead of specifying that it is unknown.

Low: **Missing Identity Propagation**: 2 / 2 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

When processing requests for endusers if possible authorize in the backend against the propagated identity of the enduser. This can be achieved in passing JWTs or similar tokens and checking them in the backend services. For DevOps usages apply at least a technical-user authorization.

Low: **Unchecked Deployment**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

Apply DevSecOps best-practices and use scanning tools to identify vulnerabilities in source- or byte-code, dependencies, container layers, and optionally also via dynamic scans against running test systems.

Low: **Unnecessary Communication Link**: 50 / 50 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Try to avoid using technical communication links that do not send or receive anything.

Low: **Unnecessary Technical Asset**: 17 / 17 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Try to avoid using technical assets that do not process or store anything.

Low: **Wrong Communication Link Content**: 50 / 50 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Try to model the correct readonly flag and/or data sent/received of communication links. Also try to use communication link types matching the target technology/machine types.

Low: **Wrong Trust Boundary Content**: 8 / 8 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Try to model the correct types of trust boundaries and data assets.

## Development

Elevated: **Cross-Site Scripting (XSS)**: 8 / 8 Risks - Exploitation likelihood is *Likely* with *Medium* impact.

Try to encode all values sent back to the browser and also handle DOM-manipulations in a safe way to avoid DOM-based XSS. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Elevated: **Path-Traversal**: 8 / 8 Risks - Exploitation likelihood is *Very Likely* with *Medium* impact.

Before accessing the file cross-check that it resides in the expected folder and is of the expected type and filename/suffix. Try to use a mapping if possible instead of directly accessing by a filename which is (partly or fully) provided by the caller. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

## Operations

Medium: **Code Backdooring**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Reduce the attack surface of backdooring the build pipeline by not directly exposing the build pipeline components on the public internet and also not exposing it in front of unmanaged (out-of-scope) developer clients. Also consider the use of code signing to prevent code modifications.

Medium: **Missing Hardening**: 2 / 2 Risks - Exploitation likelihood is *Likely* with *Low* impact.

Try to apply all hardening best practices (like CIS benchmarks, OWASP recommendations, vendor recommendations, DevSec Hardening Framework, DBSAT for Oracle databases, and others).

Medium: **Missing Network Segmentation:** 4 / 4 Risks - Exploitation likelihood is *Unlikely* with *Medium* impact.

Apply a network segmentation trust-boundary around the highly sensitive assets and/or datastores.

Medium: **Unencrypted Technical Assets:** 9 / 9 Risks - Exploitation likelihood is *Unlikely* with *High* impact.

Apply encryption to the technical asset.

Low: **Accidental Secret Leak:** 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

Establish measures preventing accidental check-in or package-in of secrets into sourcecode repositories and artifact registries. This starts by using good .gitignore and .dockerignore files, but does not stop there. See for example tools like "*git-secrets*" or "*Talisman*" to have check-in preventive measures for secrets. Consider also to regularly scan your repositories for secrets accidentally checked-in using scanning tools like "*gitleaks*" or "*gitrob*".

Low: **DoS-risky Access Across Trust-Boundary:** 11 / 11 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Apply anti-DoS techniques like throttling and/or per-client load blocking with quotas. Also for maintenance access routes consider applying a VPN instead of public reachable interfaces. Generally applying redundancy on the targeted technical asset reduces the risk of DoS.

# RAA Analysis

For each technical asset the "**Relative Attacker Attractiveness**" (RAA) value was calculated in percent. The higher the RAA, the more interesting it is for an attacker to compromise the asset. The calculation algorithm takes the sensitivity ratings and quantities of stored and processed data into account as well as the communication links of the technical asset. Neighbouring assets to high-value RAA targets might receive an increase in their RAA value when they have a communication link towards that target ("Pivoting-Factor").

The following lists all technical assets sorted by their RAA value from highest (most attacker attractive) to lowest. This list can be used to prioritize on efforts relevant for the most attacker-attractive technical assets:

Technical asset paragraphs are clickable and link to the corresponding chapter.

**S6:** RAA 100%

Historian Database

**OS1:** RAA 73%

Operator Station

**TI1:** RAA 52%

Controller with I/O

**TI2:** RAA 52%

Controller with I/O

**DC2:** RAA 40%

Domain Controller OT

**S3:** RAA 38%

Manufacturing Information System

**DC1:** RAA 34%

Domain Controller

**WC2:** RAA 33%

Historian Web Client

**WC3:** RAA 33%

Data Monitor Web Client

**WC1:** RAA 27%

Operator Web Client

**S5:** RAA 16%

WSUS Server

**S4:** RAA 14%  
Jump Server

**FW4:** RAA 10%  
OT Firewall

**R2:** RAA 8%  
OT Network Router

**FW3:** RAA 6%  
IT Firewall

**R4:** RAA 6%  
Anlagenbus Router

**S2:** RAA 6%  
Virus Scan Server

**NTP:** RAA 5%  
NTP-Server

**S0:** RAA 5%  
RAS Server

**FW1:** RAA 4%  
Internet Firewall

**FW2:** RAA 4%  
External Firewall

**ES1:** RAA 3%  
Engineering Station

**R1:** RAA 2%  
ISDN Router

**R3:** RAA 1%  
Anlagenbus Router

**S1:** RAA 1%  
Beispielkomponente für OT-TB1


**C1:** RAA 0%  
Remote PC Wartung Support



**C2:** RAA 0%  
PC Support

## Data Mapping

The following diagram was generated by Threagile based on the model input and gives a high-level distribution of data assets across technical assets. The color matches the identified data breach probability and risk level (see the "Data Breach Probabilities" chapter for more details). A solid line stands for *data is stored by the asset* and a dashed one means *data is processed by the asset*. For a full high-resolution version of this diagram please refer to the PNG image file alongside this report.



## Out-of-Scope Assets: 0 Assets

This chapter lists all technical assets that have been defined as out-of-scope. Each one should be checked in the model whether it should better be included in the overall risk analysis:

Technical asset paragraphs are clickable and link to the corresponding chapter.

No technical assets have been defined as out-of-scope.

## Potential Model Failures: 171 / 171 Risks

This chapter lists potential model failures where not all relevant assets have been modeled or the model might itself contain inconsistencies. Each potential model failure should be checked in the model against the architecture design:

Risk finding paragraphs are clickable and link to the corresponding chapter.

**Medium: Missing Vault (Secret Storage): 1 / 1 Risk** - Exploitation likelihood is *Unlikely* with *Medium* impact.

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

**Low: Incomplete Model: 45 / 45 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When the threat model contains unknown technologies or transfers data over unknown protocols, this is an indicator for an incomplete model.

**Low: Unnecessary Communication Link: 50 / 50 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical communication link does not send or receive any data assets, this is an indicator for an unnecessary communication link (or for an incomplete model).

**Low: Unnecessary Technical Asset: 17 / 17 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical asset does not process or store any data assets, this is an indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

**Low: Wrong Communication Link Content: 50 / 50 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a communication link is defined as readonly, but does not receive any data asset, or when it is defined as not readonly, but does not send any data asset, it is likely to be a model failure.

**Low: Wrong Trust Boundary Content: 8 / 8 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a trust boundary of type network-policy-namespace-isolation contains non-container assets it is likely to be a model failure.

## Questions: 0 / 0 Questions

This chapter lists custom questions that arose during the threat modeling process.

No custom questions arose during the threat modeling process.

## Identified Risks by Vulnerability Category

In total **235 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 29 as elevated, 19 as medium, and 187 as low.**

These risks are distributed across **18 vulnerability categories**. The following sub-chapters of this section describe each identified risk category.

## Cross-Site Scripting (XSS): 8 / 8 Risks

**Description** (Tampering): [CWE 79](#)

For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

### Impact

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

### Detection Logic

In-scope web applications.

### Risk Rating

The risk rating depends on the sensitivity of the data processed or stored in the web application.

### False Positives

When the technical asset is not accessed via a browser-like component (i.e not by a human user initiating the request that gets passed through all components until it reaches the web application) this can be considered a false positive.

### Mitigation (Development): XSS Prevention

Try to encode all values sent back to the browser and also handle DOM-manipulations in a safe way to avoid DOM-based XSS. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V5 - Validation, Sanitization and Encoding Verification Requirements](#)

Cheat Sheet: [Cross Site Scripting Prevention Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Cross-Site Scripting (XSS)** was found **8 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **NTP**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@NTP](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **S0**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@S0](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **S1**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@S1](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **S3**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@S3](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **S4**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@S4](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **WC1**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@WC1](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **WC2**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@WC2](#)

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **WC3**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@WC3](#)

**Unchecked**



## Missing Authentication: 12 / 12 Risks

**Description** (Elevation of Privilege): [CWE 306](#)

Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

### Impact

If this risk is unmitigated, attackers might be able to access or modify sensitive data in an unauthenticated way.

### Detection Logic

In-scope technical assets (except load-balancer, reverse-proxy, service-registry, waf, ids, and ips and in-process calls) should authenticate incoming requests when the asset processes or stores sensitive data. This is especially the case for all multi-tenant assets (there even non-sensitive ones).

### Risk Rating

The risk rating (medium or high) depends on the sensitivity of the data sent across the communication link. Monitoring callers are exempted from this risk.

### False Positives

Technical assets which do not process requests regarding functionality or data linked to end-users (customers) can be considered as false positives after individual review.

### Mitigation (Architecture): Authentication of Incoming Requests

Apply an authentication method to the technical asset. To protect highly sensitive data consider the use of two-factor authentication for human users.

ASVS Chapter: [V2 - Authentication Verification Requirements](#)

Cheat Sheet: [Authentication Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Missing Authentication** was found **12 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Elevated Risk Severity*

**Missing Authentication** covering communication link **DC1-to-FW4** from **DC1** to **FW4**:  
Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@DC1>dc1-to-fw4@DC1@FW4`

**Unchecked**

**Missing Authentication** covering communication link **DC2-to-DC1** from **DC2** to **DC1**:  
Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@DC2>dc2-to-dc1@DC2@DC1`

**Unchecked**

**Missing Authentication** covering communication link **R2-to-DC2-NTP** from **R2** to **DC2**:  
Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@R2>r2-to-dc2-ntp@R2@DC2`

**Unchecked**

**Missing Authentication** covering communication link **R2-to-OS1-Admin** from **R2** to **OS1**:  
Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@R2>r2-to-os1-admin@R2@OS1`

**Unchecked**

**Missing Authentication** covering communication link **R2-to-OS1** from **R2** to **OS1**: Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@R2>r2-to-os1@R2@OS1`

**Unchecked**

**Missing Authentication** covering communication link **R4-to-TI1** from **R4** to **TI1**: Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@R4>r4-to-ti1@R4@TI1`

**Unchecked**

**Missing Authentication** covering communication link **R4-to-TI2** from **R4** to **TI2**: Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@R4>r4-to-ti2@R4@TI2`

**Unchecked**

**Missing Authentication** covering communication link **S2-to-DC1** from **S2** to **DC1**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@S2>s2-to-dc1@S2@DC1

**Unchecked**

**Missing Authentication** covering communication link **S3-to-DC1** from **S3** to **DC1**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@S3>s3-to-dc1@S3@DC1

**Unchecked**

**Missing Authentication** covering communication link **S3-to-FW4** from **S3** to **FW4**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@S3>s3-to-fw4@S3@FW4

**Unchecked**

**Missing Authentication** covering communication link **S4-to-DC1-NTP** from **S4** to **DC1**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@S4>s4-to-dc1-ntp@S4@DC1

**Unchecked**

**Missing Authentication** covering communication link **S5-to-DC1** from **S5** to **DC1**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@S5>s5-to-dc1@S5@DC1

**Unchecked**

## Path-Traversal: 8 / 8 Risks

**Description** (Information Disclosure): [CWE 22](#)

When a filesystem is accessed Path-Traversal or Local-File-Inclusion (LFI) risks might arise. The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed or stored.

### Impact

If this risk is unmitigated, attackers might be able to read sensitive files (configuration data, key/credential files, deployment files, business data files, etc.) from the filesystem of affected components.

### Detection Logic

Filesystems accessed by in-scope callers.

### Risk Rating

The risk rating depends on the sensitivity of the data stored inside the technical asset.

### False Positives

File accesses by filenames not consisting of parts controllable by the caller can be considered as false positives after individual review.

### Mitigation (Development): Path-Traversal Prevention

Before accessing the file cross-check that it resides in the expected folder and is of the expected type and filename/suffix. Try to use a mapping if possible instead of directly accessing by a filename which is (partly or fully) provided by the caller. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V12 - File and Resources Verification Requirements](#)

Cheat Sheet: [Input Validation Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Path-Traversal** was found **8 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Elevated Risk Severity

**Path-Traversal** risk at **DC2** against filesystem **DC1** via **DC2-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@DC2@DC1@DC2>dc2-to-dc1`

**Unchecked**

**Path-Traversal** risk at **R2** against filesystem **DC2** via **R2-to-DC2-NTP**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@R2@DC2@R2>r2-to-dc2-ntp`

**Unchecked**

**Path-Traversal** risk at **S2** against filesystem **DC1** via **S2-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S2@DC1@S2>s2-to-dc1`

**Unchecked**

**Path-Traversal** risk at **S3** against filesystem **DC1** via **S3-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S3@DC1@S3>s3-to-dc1`

**Unchecked**

**Path-Traversal** risk at **S4** against filesystem **DC1** via **S4-to-DC1-NTP**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S4@DC1@S4>s4-to-dc1-ntp`

**Unchecked**

**Path-Traversal** risk at **S4** against filesystem **DC1** via **S4-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S4@DC1@S4>s4-to-dc1`

**Unchecked**

**Path-Traversal** risk at **S5** against filesystem **DC1** via **S5-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S5@DC1@S5>s5-to-dc1`

**Unchecked**

**Path-Traversal** risk at **S6** against filesystem **DC1** via **S6-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

path-traversal@S6@DC1@S6>s6-to-dc1

**Unchecked**

## Unguarded Access From Internet: 5 / 5 Risks

**Description** (Elevation of Privilege): [CWE 501](#)

Internet-exposed assets must be guarded by a protecting service, application, or reverse-proxy.

### Impact

If this risk is unmitigated, attackers might be able to directly attack sensitive systems without any hardening components in-between due to them being directly exposed on the internet.

### Detection Logic

In-scope technical assets (excluding load-balancer) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) when accessed directly from the internet. All web-server, web-application, reverse-proxy, waf, and gateway assets are exempted from this risk when they do not consist of custom developed code and the data-flow only consists of HTTP or FTP protocols. Access from monitoring systems as well as VPN-protected connections are exempted.

### Risk Rating

The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

### False Positives

When other means of filtering client requests are applied equivalent of reverse-proxy, waf, or gateway components.

### Mitigation (Architecture): Encapsulation of Technical Asset

Encapsulate the asset behind a guarding service, application, or reverse-proxy. For admin maintenance a bastion-host should be used as a jump-server. For file transfer a store-and-forward-host should be used as an indirect file exchange platform.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Unguarded Access From Internet** was found **5 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Elevated Risk Severity

**Unguarded Access from Internet of S6 by S4 via S4-to-S6:** Exploitation likelihood is *Very Likely* with *Medium* impact.

[unguarded-access-from-internet@S6@S4@S4>s4-to-s6](#)

**Unchecked**

### Medium Risk Severity

**Unguarded Access from Internet of DC1 by S4 via S4-to-DC1-NTP:** Exploitation likelihood is *Very Likely* with *Low* impact.

[unguarded-access-from-internet@DC1@S4@S4>s4-to-dc1-ntp](#)

**Unchecked**

**Unguarded Access from Internet of DC1 by S4 via S4-to-DC1:** Exploitation likelihood is *Very Likely* with *Low* impact.

[unguarded-access-from-internet@DC1@S4@S4>s4-to-dc1](#)

**Unchecked**

**Unguarded Access from Internet of FW4 by S4 via S4-to-FW4:** Exploitation likelihood is *Very Likely* with *Low* impact.

[unguarded-access-from-internet@FW4@S4@S4>s4-to-fw4](#)

**Unchecked**

**Unguarded Access from Internet of S3 by S4 via S4-to-S3:** Exploitation likelihood is *Very Likely* with *Low* impact.

[unguarded-access-from-internet@S3@S4@S4>s4-to-s3](#)

**Unchecked**



## Code Backdooring: 1 / 1 Risk

**Description** (Tampering): [CWE 912](#)

For each build-pipeline component Code Backdooring risks might arise where attackers compromise the build-pipeline in order to let backdoored artifacts be shipped into production. Aside from direct code backdooring this includes backdooring of dependencies and even of more lower-level build infrastructure, like backdooring compilers (similar to what the XcodeGhost malware did) or dependencies.

### Impact

If this risk remains unmitigated, attackers might be able to execute code on and completely takeover production environments.

### Detection Logic

In-scope development relevant technical assets which are either accessed by out-of-scope unmanaged developer clients and/or are directly accessed by any kind of internet-located (non-VPN) component or are themselves directly located on the internet.

### Risk Rating

The risk rating depends on the confidentiality and integrity rating of the code being handled and deployed as well as the placement/calling of this technical asset on/from the internet.

### False Positives

When the build-pipeline and sourcecode-repo is not exposed to the internet and considered fully trusted (which implies that all accessing clients are also considered fully trusted in terms of their patch management and applied hardening, which must be equivalent to a managed developer client environment) this can be considered a false positive after individual review.

### Mitigation (Operations): Build Pipeline Hardening

Reduce the attack surface of backdooring the build pipeline by not directly exposing the build pipeline components on the public internet and also not exposing it in front of unmanaged (out-of-scope) developer clients. Also consider the use of code signing to prevent code modifications.

ASVS Chapter: [V10 - Malicious Code Verification Requirements](#)

Cheat Sheet: [Vulnerable Dependency Management Cheat Sheet](#)

## Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Code Backdooring** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Medium Risk Severity*

**Code Backdooring** risk at **S5**: Exploitation likelihood is *Unlikely* with *Medium* impact.

code-backdooring@S5

**Unchecked**

## Missing Hardening: 2 / 2 Risks

**Description** (Tampering): [CWE 16](#)

Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.

### Impact

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

### Detection Logic

In-scope technical assets with RAA values of 55 % or higher. Generally for high-value targets like datastores, application servers, identity providers and ERP systems this limit is reduced to 40 %

### Risk Rating

The risk rating depends on the sensitivity of the data processed or stored in the technical asset.

### False Positives

Usually no false positives.

### Mitigation (Operations): System Hardening

Try to apply all hardening best practices (like CIS benchmarks, OWASP recommendations, vendor recommendations, DevSec Hardening Framework, DBSAT for Oracle databases, and others).

ASVS Chapter: [V14 - Configuration Verification Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Missing Hardening** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Medium Risk Severity*

**Missing Hardening** risk at **OS1**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@OS1](#)

**Unchecked**

**Missing Hardening** risk at **S6**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@S6](#)

**Unchecked**

## Missing Network Segmentation: 4 / 4 Risks

**Description** (Elevation of Privilege): [CWE 1008](#)

Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webserver or content management systems etc.) should be better protected by a network segmentation trust-boundary.

### Impact

If this risk is unmitigated, attackers successfully attacking other components of the system might have an easy path towards more valuable targets, as they are not separated by network segmentation.

### Detection Logic

In-scope technical assets with high sensitivity and RAA values as well as datastores when surrounded by assets (without a network trust-boundary in-between) which are of type client-system, web-server, web-application, cms, web-service-rest, web-service-soap, build-pipeline, sourcecode-repository, monitoring, or similar and there is no direct connection between these (hence no requirement to be so close to each other).

### Risk Rating

Default is low risk. The risk is increased to medium when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

### False Positives

When all assets within the network segmentation trust-boundary are hardened and protected to the same extend as if all were containing/processing highly sensitive data.

### Mitigation (Operations): Network Segmentation

Apply a network segmentation trust-boundary around the highly sensitive assets and/or datastores.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Missing Network Segmentation** was found **4 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Medium Risk Severity

**Missing Network Segmentation** to further encapsulate and protect **TI1** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-network-segmentation@TI1](#)

**Unchecked**

**Missing Network Segmentation** to further encapsulate and protect **TI2** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-network-segmentation@TI2](#)

**Unchecked**

### Low Risk Severity

**Missing Network Segmentation** to further encapsulate and protect **OS1** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@OS1](#)

**Unchecked**

**Missing Network Segmentation** to further encapsulate and protect **S6** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@S6](#)

**Unchecked**

## Missing Vault (Secret Storage): 1 / 1 Risk

**Description** (Information Disclosure): [CWE 522](#)

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

### Impact

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

### Detection Logic

Models without a Vault (Secret Storage).

### Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

### False Positives

Models where no technical assets have any kind of sensitive config data to protect can be considered as false positives after individual review.

### Mitigation (Architecture): Vault (Secret Storage)

Consider using a Vault (Secret Storage) to securely store and access config secrets (like credentials, private keys, client certificates, etc.).

ASVS Chapter: [V6 - Stored Cryptography Verification Requirements](#)

Cheat Sheet: [Cryptographic Storage Cheat Sheet](#)

### Check

Is a Vault (Secret Storage) in place?



## Risk Findings

The risk **Missing Vault (Secret Storage)** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Medium Risk Severity*

**Missing Vault (Secret Storage)** in the threat model (referencing asset **T11** as an example):  
Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-vault@T11](#)

**Unchecked**

## Unencrypted Technical Assets: 9 / 9 Risks

**Description** (Information Disclosure): [CWE 311](#)

Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.

### Impact

If this risk is unmitigated, attackers might be able to access unencrypted data when successfully compromising sensitive components.

### Detection Logic

In-scope unencrypted technical assets (excluding reverse-proxy, load-balancer, waf, ids, ips and embedded components like library) storing data assets rated at least as confidential or critical. For technical assets storing data assets rated as strictly-confidential or mission-critical the encryption must be of type data-with-enduser-individual-key.

### Risk Rating

Depending on the confidentiality rating of the stored data-assets either medium or high risk.

### False Positives

When all sensitive data stored within the asset is already fully encrypted on document or data level.

**Mitigation** (Operations): Encryption of Technical Asset

Apply encryption to the technical asset.

ASVS Chapter: [V6 - Stored Cryptography Verification Requirements](#)

Cheat Sheet: [Cryptographic Storage Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Unencrypted Technical Assets** was found **9 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Medium Risk Severity

**Unencrypted Technical Asset** named **TI1**: Exploitation likelihood is *Unlikely* with *High* impact.

[unencrypted-asset@TI1](#)

**Unchecked**

**Unencrypted Technical Asset** named **TI2**: Exploitation likelihood is *Unlikely* with *High* impact.

[unencrypted-asset@TI2](#)

**Unchecked**

**Unencrypted Technical Asset** named **DC1**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@DC1](#)

**Unchecked**

**Unencrypted Technical Asset** named **DC2**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@DC2](#)

**Unchecked**

**Unencrypted Technical Asset** named **FW4**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@FW4](#)

**Unchecked**

**Unencrypted Technical Asset** named **OS1**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@OS1](#)

**Unchecked**

**Unencrypted Technical Asset** named **WC1**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@WC1](#)

**Unchecked**

**Unencrypted Technical Asset** named **WC2**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@WC2](#)

**Unchecked**

**Unencrypted Technical Asset** named **WC3**: Exploitation likelihood is *Unlikely* with *Medium* impact.

unencrypted-asset@WC3

**Unchecked**

## Accidental Secret Leak: 1 / 1 Risk

**Description** (Information Disclosure): [CWE 200](#)

Sourcecode repositories (including their histories) as well as artifact registries can accidentally contain secrets like checked-in or packaged-in passwords, API tokens, certificates, crypto keys, etc.

### Impact

If this risk is unmitigated, attackers which have access to affected sourcecode repositories or artifact registries might find secrets accidentally checked-in.

### Detection Logic

In-scope sourcecode repositories and artifact registries.

### Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

### False Positives

Usually no false positives.

### Mitigation (Operations): Build Pipeline Hardening

Establish measures preventing accidental check-in or package-in of secrets into sourcecode repositories and artifact registries. This starts by using good .gitignore and .dockerignore files, but does not stop there. See for example tools like "*git-secrets*" or "*Talisman*" to have check-in preventive measures for secrets. Consider also to regularly scan your repositories for secrets accidentally checked-in using scanning tools like "*gitleaks*" or "*gitrob*".

ASVS Chapter: [V14 - Configuration Verification Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Accidental Secret Leak** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Low Risk Severity*

**Accidental Secret Leak** risk at **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

[accidental-secret-leak@S5](#)

**Unchecked**

## DoS-risky Access Across Trust-Boundary: 11 / 11 Risks

**Description** (Denial of Service): [CWE 400](#)

Assets accessed across trust boundaries with critical or mission-critical availability rating are more prone to Denial-of-Service (DoS) risks.

### Impact

If this risk remains unmitigated, attackers might be able to disturb the availability of important parts of the system.

### Detection Logic

In-scope technical assets (excluding load-balancer) with availability rating of critical or higher which have incoming data-flows across a network trust-boundary (excluding devops usage).

### Risk Rating

Matching technical assets with availability rating of critical or higher are at low risk. When the availability rating is mission-critical and neither a VPN nor IP filter for the incoming data-flow nor redundancy for the asset is applied, the risk-rating is considered medium.

### False Positives

When the accessed target operations are not time- or resource-consuming.

### Mitigation (Operations): Anti-DoS Measures

Apply anti-DoS techniques like throttling and/or per-client load blocking with quotas. Also for maintenance access routes consider applying a VPN instead of public reachable interfaces. Generally applying redundancy on the targeted technical asset reduces the risk of DoS.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Denial of Service Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **DoS-risky Access Across Trust-Boundary** was found **11 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Denial-of-Service** risky access of **DC1** by **DC2** via **DC2-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@DC1@DC2@DC2>dc2-to-dc1`

**Unchecked**

**Denial-of-Service** risky access of **DC2** by **R2** via **R2-to-DC2-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@DC2@R2@R2>r2-to-dc2-ntp`

**Unchecked**

**Denial-of-Service** risky access of **FW2** by **S0** via **S0-to-FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@FW2@S0@S0>s0-to-fw2`

**Unchecked**

**Denial-of-Service** risky access of **FW3** by **WC1** via **WC1-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@FW3@WC1@WC1>wc1-to-fw3`

**Unchecked**

**Denial-of-Service** risky access of **FW3** by **WC2** via **WC2-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@FW3@WC2@WC2>wc2-to-fw3`

**Unchecked**

**Denial-of-Service** risky access of **FW3** by **WC3** via **WC3-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@FW3@WC3@WC3>wc3-to-fw3`

**Unchecked**

**Denial-of-Service** risky access of **FW4** by **DC1** via **DC1-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

`dos-risky-access-across-trust-boundary@FW4@DC1@DC1>dc1-to-fw4`

**Unchecked**



**Denial-of-Service** risky access of **FW4** by **S3** via **S3-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@FW4@S3@S3>s3-to-fw4

**Unchecked**

**Denial-of-Service** risky access of **FW4** by **S4** via **S4-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@FW4@S4@S4>s4-to-fw4

**Unchecked**

**Denial-of-Service** risky access of **OS1** by **R2** via **R2-to-OS1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@OS1@R2@R2>r2-to-os1-admin

**Unchecked**

**Denial-of-Service** risky access of **OS1** by **R2** via **R2-to-OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@OS1@R2@R2>r2-to-os1

**Unchecked**

## Incomplete Model: 45 / 45 Risks

**Description** (Information Disclosure): [CWE 1008](#)

When the threat model contains unknown technologies or transfers data over unknown protocols, this is an indicator for an incomplete model.

### Impact

If this risk is unmitigated, other risks might not be noticed as the model is incomplete.

### Detection Logic

All technical assets and communication links with technology type or protocol type specified as unknown.

### Risk Rating

low

### False Positives

Usually no false positives as this looks like an incomplete model.

### Mitigation (Architecture): Threat Modeling Completeness

Try to find out what technology or protocol is used instead of specifying that it is unknown.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Threat Modeling Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Incomplete Model** was found **45 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Unknown Protocol** specified for communication link **C1-to-FW1** at technical asset **C1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@C1>c1-to-fw1@C1](#)

**Unchecked**

**Unknown Protocol** specified for communication link **C2-to-R1** at technical asset **C2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@C2>c2-to-r1@C2](#)

**Unchecked**

**Unknown Protocol** specified for communication link **DC1-to-FW4** at technical asset **DC1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@DC1>dc1-to-fw4@DC1](#)

**Unchecked**

**Unknown Protocol** specified for communication link **DC1-to-NTP** at technical asset **DC1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@DC1>dc1-to-ntp@DC1](#)

**Unchecked**

**Unknown Protocol** specified for communication link **DC2-to-DC1** at technical asset **DC2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@DC2>dc2-to-dc1@DC2](#)

**Unchecked**

**Unknown Protocol** specified for communication link **ES1-to-R2** at technical asset **ES1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@ES1>es1-to-r2@ES1](#)

**Unchecked**

**Unknown Protocol** specified for communication link **FW1-to-S0** at technical asset **FW1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@FW1>fw1-to-s0@FW1](#)

**Unchecked**

**Unknown Protocol** specified for communication link **FW2-to-FW3** at technical asset **FW2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW2>fw2-to-fw3@FW2

**Unchecked**

**Unknown Protocol** specified for communication link **FW3-to-WC1** at technical asset **FW3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW3>fw3-to-wc1@FW3

**Unchecked**

**Unknown Protocol** specified for communication link **FW3-to-WC2** at technical asset **FW3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW3>fw3-to-wc2@FW3

**Unchecked**

**Unknown Protocol** specified for communication link **FW3-to-WC3** at technical asset **FW3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW3>fw3-to-wc3@FW3

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-FW3** at technical asset **FW4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-fw3@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-R2-Admin** at technical asset **FW4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-r2-admin@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-R2** at technical asset **FW4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-r2@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-S4** at technical asset **FW4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-s4@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **OS1-to-R2** at technical asset **OS1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@OS1>os1-to-r2@OS1

**Unchecked**

**Unknown Protocol** specified for communication link **R1-to-FW4** at technical asset **R1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R1>r1-to-fw4@R1

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-DC2-NTP** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-dc2-ntp@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-ES1-Admin** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-es1-admin@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-ES1** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-es1@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-OS1-Admin** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-os1-admin@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-OS1** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-os1@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-S1-(MIS)** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-s1-mis@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-S1-Admin** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-s1-admin@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-S1** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-s1@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R3-to-R4-(MIS)** at technical asset **R3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R3>r3-to-r4-mis@R3

**Unchecked**

**Unknown Protocol** specified for communication link **R3-to-R4** at technical asset **R3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R3>r3-to-r4@R3

**Unchecked**

**Unknown Protocol** specified for communication link **R4-to-TI1** at technical asset **R4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R4>r4-to-ti1@R4

**Unchecked**

**Unknown Protocol** specified for communication link **R4-to-TI2** at technical asset **R4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R4>r4-to-ti2@R4

**Unchecked**

**Unknown Protocol** specified for communication link **S0-to-FW2** at technical asset **S0**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S0>s0-to-fw2@S0

**Unchecked**

**Unknown Protocol** specified for communication link **S1-to-R2-NTP** at technical asset **S1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S1>s1-to-r2-ntp@S1

**Unchecked**

**Unknown Protocol** specified for communication link **S1-to-R3-(MIS)** at technical asset **S1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S1>s1-to-r3-mis@S1

**Unchecked**

**Unknown Protocol** specified for communication link **S1-to-R3** at technical asset **S1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S1>s1-to-r3@S1

**Unchecked**

**Unknown Protocol** specified for communication link **S2-to-DC1** at technical asset **S2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S2>s2-to-dc1@S2

**Unchecked**

**Unknown Protocol** specified for communication link **S3-to-DC1** at technical asset **S3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S3>s3-to-dc1@S3

**Unchecked**

**Unknown Protocol** specified for communication link **S3-to-FW4** at technical asset **S3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S3>s3-to-fw4@S3

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-DC1-NTP** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-dc1-ntp@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-DC1** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-dc1@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-FW4** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-fw4@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S2** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s2@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S3** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s3@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S5** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s5@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S6** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s6@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S5-to-DC1** at technical asset **S5**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S5>s5-to-dc1@S5

**Unchecked**

**Unknown Protocol** specified for communication link **S6-to-DC1** at technical asset **S6**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S6>s6-to-dc1@S6

**Unchecked**



## Missing Identity Propagation: 2 / 2 Risks

**Description** (Elevation of Privilege): [CWE 284](#)

Technical assets (especially multi-tenant systems), which usually process data for endusers should authorize every request based on the identity of the enduser when the data flow is authenticated (i.e. non-public). For DevOps usages at least a technical-user authorization is required.

### Impact

If this risk is unmitigated, attackers might be able to access or modify foreign data after a successful compromise of a component within the system due to missing resource-based authorization checks.

### Detection Logic

In-scope service-like technical assets which usually process data based on enduser requests, if authenticated (i.e. non-public), should authorize incoming requests based on the propagated enduser identity when their rating is sensitive. This is especially the case for all multi-tenant assets (there even less-sensitive rated ones). DevOps usages are exempted from this risk.

### Risk Rating

The risk rating (medium or high) depends on the confidentiality, integrity, and availability rating of the technical asset.

### False Positives

Technical assets which do not process requests regarding functionality or data linked to end-users (customers) can be considered as false positives after individual review.

**Mitigation** (Architecture): Identity Propagation and Resource-based Authorization

When processing requests for endusers if possible authorize in the backend against the propagated identity of the enduser. This can be achieved in passing JWTs or similar tokens and checking them in the backend services. For DevOps usages apply at least a technical-user authorization.

ASVS Chapter: [V4 - Access Control Verification Requirements](#)

Cheat Sheet: [Access Control Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Missing Identity Propagation** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Missing Enduser Identity Propagation** over communication link **FW4-to-S3** from **FW4** to **S3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-identity-propagation@FW4>fw4-to-s3@FW4@S3](#)

**Unchecked**

**Missing Enduser Identity Propagation** over communication link **S4-to-S3** from **S4** to **S3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-identity-propagation@S4>s4-to-s3@S4@S3](#)

**Unchecked**

## Unchecked Deployment: 1 / 1 Risk

**Description** (Tampering): [CWE 1127](#)

For each build-pipeline component Unchecked Deployment risks might arise when the build-pipeline does not include established DevSecOps best-practices. DevSecOps best-practices scan as part of CI/CD pipelines for vulnerabilities in source- or byte-code, dependencies, container layers, and dynamically against running test systems. There are several open-source and commercial tools existing in the categories DAST, SAST, and IAST.

### Impact

If this risk remains unmitigated, vulnerabilities in custom-developed software or their dependencies might not be identified during continuous deployment cycles.

### Detection Logic

All development-relevant technical assets.

### Risk Rating

The risk rating depends on the highest rating of the technical assets and data assets processed by deployment-receiving targets.

### False Positives

When the build-pipeline does not build any software components it can be considered a false positive after individual review.

### Mitigation (Architecture): Build Pipeline Hardening

Apply DevSecOps best-practices and use scanning tools to identify vulnerabilities in source- or byte-code, dependencies, container layers, and optionally also via dynamic scans against running test systems.

ASVS Chapter: [V14 - Configuration Verification Requirements](#)

Cheat Sheet: [Vulnerable Dependency Management Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Unchecked Deployment** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### *Low Risk Severity*

**Unchecked Deployment** risk at **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unchecked-deployment@S5](#)

**Unchecked**

## Unnecessary Communication Link: 50 / 50 Risks

**Description** (Elevation of Privilege): [CWE 1008](#)

When a technical communication link does not send or receive any data assets, this is an indicator for an unnecessary communication link (or for an incomplete model).

### Impact

If this risk is unmitigated, attackers might be able to target unnecessary communication links.

### Detection Logic

In-scope technical assets' technical communication links not sending or receiving any data assets.

### Risk Rating

low

### False Positives

Usually no false positives as this looks like an incomplete model.

### Mitigation (Architecture): Attack Surface Reduction

Try to avoid using technical communication links that do not send or receive anything.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Unnecessary Communication Link** was found **50 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Unnecessary Communication Link** titled **C1-to-FW1** at technical asset **C1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@C1>c1-to-fw1@C1](#)

**Unchecked**

**Unnecessary Communication Link** titled **C2-to-R1** at technical asset **C2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@C2>c2-to-r1@C2](#)

**Unchecked**

**Unnecessary Communication Link** titled **DC1-to-FW4** at technical asset **DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@DC1>dc1-to-fw4@DC1](#)

**Unchecked**

**Unnecessary Communication Link** titled **DC1-to-NTP** at technical asset **DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@DC1>dc1-to-ntp@DC1](#)

**Unchecked**

**Unnecessary Communication Link** titled **DC2-to-DC1** at technical asset **DC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@DC2>dc2-to-dc1@DC2](#)

**Unchecked**

**Unnecessary Communication Link** titled **ES1-to-R2** at technical asset **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@ES1>es1-to-r2@ES1](#)

**Unchecked**

**Unnecessary Communication Link** titled **FW1-to-S0** at technical asset **FW1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@FW1>fw1-to-s0@FW1](#)

**Unchecked**

**Unnecessary Communication Link** titled **FW2-to-FW3** at technical asset **FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW2>fw2-to-fw3@FW2

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-FW4** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-fw4@FW3

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-WC1** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-wc1@FW3

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-WC2** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-wc2@FW3

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-WC3** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-wc3@FW3

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-FW3** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-fw3@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-R2-Admin** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-r2-admin@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-R2** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-r2@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-S3** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-s3@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-S4** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-s4@FW4

**Unchecked**

**Unnecessary Communication Link** titled **OS1-to-R2** at technical asset **OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@OS1>os1-to-r2@OS1

**Unchecked**

**Unnecessary Communication Link** titled **R1-to-FW4** at technical asset **R1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R1>r1-to-fw4@R1

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-DC2-NTP** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-dc2-ntp@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-ES1-Admin** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-es1-admin@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-ES1** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-es1@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-OS1-Admin** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-os1-admin@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-OS1** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-os1@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-S1-(MIS)** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-s1-mis@R2

**Unchecked**



**Unnecessary Communication Link** titled **R2-to-S1-Admin** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-s1-admin@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-S1** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-s1@R2

**Unchecked**

**Unnecessary Communication Link** titled **R3-to-R4-(MIS)** at technical asset **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R3>r3-to-r4-mis@R3

**Unchecked**

**Unnecessary Communication Link** titled **R3-to-R4** at technical asset **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R3>r3-to-r4@R3

**Unchecked**

**Unnecessary Communication Link** titled **R4-to-TI1** at technical asset **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R4>r4-to-ti1@R4

**Unchecked**

**Unnecessary Communication Link** titled **R4-to-TI2** at technical asset **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R4>r4-to-ti2@R4

**Unchecked**

**Unnecessary Communication Link** titled **S0-to-FW2** at technical asset **S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S0>s0-to-fw2@S0

**Unchecked**

**Unnecessary Communication Link** titled **S1-to-R2-NTP** at technical asset **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S1>s1-to-r2-ntp@S1

**Unchecked**

**Unnecessary Communication Link** titled **S1-to-R3-(MIS)** at technical asset **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S1>s1-to-r3-mis@S1

**Unchecked**

**Unnecessary Communication Link** titled **S1-to-R3** at technical asset **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S1>s1-to-r3@S1

**Unchecked**

**Unnecessary Communication Link** titled **S2-to-DC1** at technical asset **S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S2>s2-to-dc1@S2

**Unchecked**

**Unnecessary Communication Link** titled **S3-to-DC1** at technical asset **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S3>s3-to-dc1@S3

**Unchecked**

**Unnecessary Communication Link** titled **S3-to-FW4** at technical asset **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S3>s3-to-fw4@S3

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-DC1-NTP** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-dc1-ntp@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-DC1** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-dc1@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-FW4** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-fw4@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S2** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s2@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S3** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s3@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S5** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s5@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S6** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s6@S4

**Unchecked**

**Unnecessary Communication Link** titled **S5-to-DC1** at technical asset **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S5>s5-to-dc1@S5

**Unchecked**

**Unnecessary Communication Link** titled **S6-to-DC1** at technical asset **S6**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S6>s6-to-dc1@S6

**Unchecked**

**Unnecessary Communication Link** titled **WC1-to-FW3** at technical asset **WC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@WC1>wc1-to-fw3@WC1

**Unchecked**

**Unnecessary Communication Link** titled **WC2-to-FW3** at technical asset **WC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@WC2>wc2-to-fw3@WC2

**Unchecked**

**Unnecessary Communication Link** titled **WC3-to-FW3** at technical asset **WC3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@WC3>wc3-to-fw3@WC3

**Unchecked**

## Unnecessary Technical Asset: 17 / 17 Risks

**Description** (Elevation of Privilege): [CWE 1008](#)

When a technical asset does not process or store any data assets, this is an indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

### Impact

If this risk is unmitigated, attackers might be able to target unnecessary technical assets.

### Detection Logic

Technical assets not processing or storing any data assets.

### Risk Rating

low

### False Positives

Usually no false positives as this looks like an incomplete model.

### Mitigation (Architecture): Attack Surface Reduction

Try to avoid using technical assets that do not process or store anything.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Unnecessary Technical Asset** was found **17 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Unnecessary Technical Asset** named **C1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@C1](#)

**Unchecked**

**Unnecessary Technical Asset** named **C2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@C2](#)

**Unchecked**

**Unnecessary Technical Asset** named **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@ES1](#)

**Unchecked**

**Unnecessary Technical Asset** named **FW1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@FW1](#)

**Unchecked**

**Unnecessary Technical Asset** named **FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@FW2](#)

**Unchecked**

**Unnecessary Technical Asset** named **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@FW3](#)

**Unchecked**

**Unnecessary Technical Asset** named **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@FW4](#)

**Unchecked**

**Unnecessary Technical Asset** named **NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@NTP](#)

**Unchecked**

**Unnecessary Technical Asset** named **R1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@R1

**Unchecked**

**Unnecessary Technical Asset** named **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@R2

**Unchecked**

**Unnecessary Technical Asset** named **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@R3

**Unchecked**

**Unnecessary Technical Asset** named **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@R4

**Unchecked**

**Unnecessary Technical Asset** named **S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S0

**Unchecked**

**Unnecessary Technical Asset** named **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S1

**Unchecked**

**Unnecessary Technical Asset** named **S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S2

**Unchecked**

**Unnecessary Technical Asset** named **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S4

**Unchecked**

**Unnecessary Technical Asset** named **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S5

**Unchecked**

## Wrong Communication Link Content: 50 / 50 Risks

**Description** (Information Disclosure): [CWE 1008](#)

When a communication link is defined as readonly, but does not receive any data asset, or when it is defined as not readonly, but does not send any data asset, it is likely to be a model failure.

### Impact

If this potential model error is not fixed, some risks might not be visible.

### Detection Logic

Communication links with inconsistent data assets being sent/received not matching their readonly flag or otherwise inconsistent protocols not matching the target technology type.

### Risk Rating

low

### False Positives

Usually no false positives as this looks like an incomplete model.

### Mitigation (Architecture): Model Consistency

Try to model the correct readonly flag and/or data sent/received of communication links. Also try to use communication link types matching the target technology/machine types.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Threat Modeling Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Wrong Communication Link Content** was found **50 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **C1** regarding communication link **C1-to-FW1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@C1@C1>c1-to-fw1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **C2** regarding communication link **C2-to-R1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@C2@C2>c2-to-r1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **DC1** regarding communication link **DC1-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@DC1@DC1>dc1-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **DC1** regarding communication link **DC1-to-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@DC1@DC1>dc1-to-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **DC2** regarding communication link **DC2-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@DC2@DC2>dc2-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **ES1** regarding communication link **ES1-to-R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@ES1@ES1>es1-to-r2

**Unchecked**



**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW1** regarding communication link **FW1-to-S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW1@FW1>fw1-to-s0

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW2** regarding communication link **FW2-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW2@FW2>fw2-to-fw3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-WC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-wc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-WC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-wc2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-WC3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-wc3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-fw3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-R2-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-r2-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-r2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-s3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-s4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **OS1** regarding communication link **OS1-to-R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@OS1@OS1>os1-to-r2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R1** regarding communication link **R1-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R1@R1>r1-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-DC2-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-dc2-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-ES1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-es1-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-es1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-OS1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-os1-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-os1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-S1-(MIS)**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-s1-mis

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-S1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-s1-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-s1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R3** regarding communication link **R3-to-R4-(MIS)**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R3@R3>r3-to-r4-mis

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R3** regarding communication link **R3-to-R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R3@R3>r3-to-r4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R4** regarding communication link **R4-to-TI1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R4@R4>r4-to-ti1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R4** regarding communication link **R4-to-TI2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R4@R4>r4-to-ti2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S0** regarding communication link **S0-to-FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S0@S0>s0-to-fw2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S1** regarding communication link **S1-to-R2-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S1@S1>s1-to-r2-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S1** regarding communication link **S1-to-R3-(MIS)**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S1@S1>s1-to-r3-mis

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S1** regarding communication link **S1-to-R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S1@S1>s1-to-r3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S2** regarding communication link **S2-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S2@S2>s2-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S3** regarding communication link **S3-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S3@S3>s3-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S3** regarding communication link **S3-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S3@S3>s3-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-DC1-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-dc1-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s5

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S6**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s6

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S5** regarding communication link **S5-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S5@S5>s5-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S6** regarding communication link **S6-to-DC1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S6@S6>s6-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **WC1** regarding communication link **WC1-to-FW3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@WC1@WC1>wc1-to-fw3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **WC2** regarding communication link **WC2-to-FW3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@WC2@WC2>wc2-to-fw3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **WC3** regarding communication link **WC3-to-FW3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@WC3@WC3>wc3-to-fw3

**Unchecked**

## Wrong Trust Boundary Content: 8 / 8 Risks

**Description** (Elevation of Privilege): [CWE 1008](#)

When a trust boundary of type network-policy-namespace-isolation contains non-container assets it is likely to be a model failure.

### Impact

If this potential model error is not fixed, some risks might not be visible.

### Detection Logic

Trust boundaries which should only contain containers, but have different assets inside.

### Risk Rating

low

### False Positives

Usually no false positives as this looks like an incomplete model.

### Mitigation (Architecture): Model Consistency

Try to model the correct types of trust boundaries and data assets.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Threat Modeling Cheat Sheet](#)

### Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

## Risk Findings

The risk **Wrong Trust Boundary Content** was found **8 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

### Low Risk Severity

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **DC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@DC2

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@ES1

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@OS1

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@R3

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@R4

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@S1

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **TI1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@TI1

**Unchecked**



**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **T12**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@T12

**Unchecked**

## Identified Risks by Technical Asset

In total **235 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 29 as elevated, 19 as medium, and 187 as low.**

These risks are distributed across **27 in-scope technical assets**. The following sub-chapters of this section describe each identified risk grouped by technical asset. The RAA value of a technical asset is the calculated "Relative Attacker Attractiveness" value in percent.

## DC1: 15 / 15 Risks

### Description

Domain Controller

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Missing Authentication** covering communication link **DC2-to-DC1** from **DC2** to **DC1**:  
Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@DC2>dc2-to-dc1@DC2@DC1`

**Unchecked**

**Missing Authentication** covering communication link **S2-to-DC1** from **S2** to **DC1**: Exploitation  
likelihood is *Likely* with *Medium* impact.

`missing-authentication@S2>s2-to-dc1@S2@DC1`

**Unchecked**

**Missing Authentication** covering communication link **S3-to-DC1** from **S3** to **DC1**: Exploitation  
likelihood is *Likely* with *Medium* impact.

`missing-authentication@S3>s3-to-dc1@S3@DC1`

**Unchecked**

**Missing Authentication** covering communication link **S4-to-DC1-NTP** from **S4** to **DC1**:  
Exploitation likelihood is *Likely* with *Medium* impact.

`missing-authentication@S4>s4-to-dc1-ntp@S4@DC1`

**Unchecked**

**Missing Authentication** covering communication link **S5-to-DC1** from **S5** to **DC1**: Exploitation  
likelihood is *Likely* with *Medium* impact.

`missing-authentication@S5>s5-to-dc1@S5@DC1`

**Unchecked**

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **DC1**: Exploitation likelihood is *Unlikely* with *Medium*  
impact.

`unencrypted-asset@DC1`

**Unchecked**

**Unguarded Access from Internet of DC1 by S4 via S4-to-DC1-NTP:** Exploitation likelihood is *Very Likely* with *Low* impact.

unguarded-access-from-internet@DC1@S4@S4>s4-to-dc1-ntp

**Unchecked**

**Unguarded Access from Internet of DC1 by S4 via S4-to-DC1:** Exploitation likelihood is *Very Likely* with *Low* impact.

unguarded-access-from-internet@DC1@S4@S4>s4-to-dc1

**Unchecked**

## Low Risk Severity

**Denial-of-Service** risky access of **DC1** by **DC2** via **DC2-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@DC1@DC2@DC2>dc2-to-dc1

**Unchecked**

**Unknown Protocol** specified for communication link **DC1-to-FW4** at technical asset **DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@DC1>dc1-to-fw4@DC1

**Unchecked**

**Unknown Protocol** specified for communication link **DC1-to-NTP** at technical asset **DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@DC1>dc1-to-ntp@DC1

**Unchecked**

**Unnecessary Communication Link** titled **DC1-to-FW4** at technical asset **DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@DC1>dc1-to-fw4@DC1

**Unchecked**

**Unnecessary Communication Link** titled **DC1-to-NTP** at technical asset **DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@DC1>dc1-to-ntp@DC1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **DC1** regarding communication link **DC1-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@DC1@DC1>dc1-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **DC1** regarding communication link **DC1-to-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@DC1@DC1>dc1-to-ntp

**Unchecked**

## Asset Information

ID:	DC1
Type:	process
Usage:	devops
RAA:	34 %
Size:	service
Technology:	local-file-system
Tags:	it
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	erp-data
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	critical	(rated 4 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

### DC1-to-NTP (outgoing)

Domain Controller 1 synchronisiert sich mit NTP-Server (NTP)

Target:	NTP
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none

Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### DC1-to-FW4 (outgoing)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Target: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

### Incoming Communication Links: 7

Source technical asset names are clickable and link to the corresponding chapter.

#### S6-to-DC1 (incoming)

Server 6 synchronisiert sich über Domain Controller 1 (NTP)

Source: S6  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none

VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### S5-to-DC1 (incoming)

Server 5 synchronisiert sich über Domain Controller 1 (NTP)

Source: S5  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### S4-to-DC1-NTP (incoming)

Server 4 synchronisiert sich über Domain Controller 1 (NTP)

Source: S4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### S4-to-DC1 (incoming)

Zugriff Server 4 auf Domain Controller DC1 (Jump Server zu Komponenten im Operations Netzwerk)

Source:	S4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

#### S3-to-DC1 (incoming)

Server 3 synchronisiert sich über Domain Controller 1 (NTP)

Source:	S3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

#### S2-to-DC1 (incoming)

Server 2 synchronisiert sich über Domain Controller 1 (NTP)

Source:	S2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business



Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

**DC2-to-DC1 (incoming)**

Domain Controller 2 synchronisiert sich mit Domain Controller 1 (NTP)

Source: DC2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## DC2: 8 / 8 Risks

### Description

Domain Controller OT

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **DC2** against filesystem **DC1** via **DC2-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

[path-traversal@DC2@DC1@DC2>dc2-to-dc1](#)

**Unchecked**

**Missing Authentication** covering communication link **R2-to-DC2-NTP** from **R2** to **DC2**: Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@R2>r2-to-dc2-ntp@R2@DC2](#)

**Unchecked**

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **DC2**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@DC2](#)

**Unchecked**

#### *Low Risk Severity*

**Denial-of-Service** risky access of **DC2** by **R2** via **R2-to-DC2-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@DC2@R2@R2>r2-to-dc2-ntp](#)

**Unchecked**

**Unknown Protocol** specified for communication link **DC2-to-DC1** at technical asset **DC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@DC2>dc2-to-dc1@DC2](#)

**Unchecked**

**Unnecessary Communication Link** titled **DC2-to-DC1** at technical asset **DC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@DC2>dc2-to-dc1@DC2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **DC2** regarding communication link **DC2-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@DC2@DC2>dc2-to-dc1

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **DC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@DC2

**Unchecked**

## Asset Information

ID:	DC2
Type:	process
Usage:	devops
RAA:	40 %
Size:	service
Technology:	local-file-system
Tags:	ot
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	production-data
Formats Accepted:	JSON

## Asset Rating

Owner:	OT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	critical	(rated 4 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)

CIA-Justification:

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### DC2-to-DC1 (outgoing)

Domain Controller 2 synchronisiert sich mit Domain Controller 1 (NTP)

Target:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### R2-to-DC2-NTP (incoming)

Server 1 synchronisiert sich über Domain Controller 2 (NTP)

Source:	R2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## FW4: 22 / 22 Risks

### Description

OT Firewall

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Missing Authentication** covering communication link **DC1-to-FW4** from **DC1** to **FW4**:  
Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@DC1>dc1-to-fw4@DC1@FW4](#)

**Unchecked**

**Missing Authentication** covering communication link **S3-to-FW4** from **S3** to **FW4**:  
Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@S3>s3-to-fw4@S3@FW4](#)

**Unchecked**

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **FW4**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@FW4](#)

**Unchecked**

**Unguarded Access from Internet of FW4 by S4 via S4-to-FW4**: Exploitation likelihood is *Very Likely* with *Low* impact.

[unguarded-access-from-internet@FW4@S4@S4>s4-to-fw4](#)

**Unchecked**

#### *Low Risk Severity*

**Denial-of-Service** risky access of **FW4** by **DC1** via **DC1-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@FW4@DC1@DC1>dc1-to-fw4](#)

**Unchecked**

**Denial-of-Service** risky access of **FW4** by **S3** via **S3-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@FW4@S3@S3>s3-to-fw4

**Unchecked**

**Denial-of-Service** risky access of **FW4** by **S4** via **S4-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

dos-risky-access-across-trust-boundary@FW4@S4@S4>s4-to-fw4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-FW3** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-fw3@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-R2-Admin** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-r2-admin@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-R2** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-r2@FW4

**Unchecked**

**Unknown Protocol** specified for communication link **FW4-to-S4** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@FW4>fw4-to-s4@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-FW3** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-fw3@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-R2-Admin** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-r2-admin@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-R2** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-r2@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-S3** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-s3@FW4

**Unchecked**

**Unnecessary Communication Link** titled **FW4-to-S4** at technical asset **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW4>fw4-to-s4@FW4

**Unchecked**

**Unnecessary Technical Asset** named **FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@FW4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-fw3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-R2-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-r2-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-r2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-s3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW4** regarding communication link **FW4-to-S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW4@FW4>fw4-to-s4

**Unchecked**

## Asset Information

ID: FW4

Type:	process
Usage:	devops
RAA:	10 %
Size:	system
Technology:	gateway
Tags:	ot, secure-zone
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	OT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	critical	(rated 4 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 5

Target technical asset names are clickable and link to the corresponding chapter.

### FW4-to-S4 (outgoing)

Zugriff Firewall 4 auf Server 4 (MIS Verbindung - Remote Access)

Target:	S4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business



Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### FW4-to-S3 (outgoing)

Zugriff Firewall 4 auf MIS Server 3 (MIS Verbindung - Remote Access)

Target: S3  
Protocol: ssh  
Encrypted: true  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### FW4-to-R2-Admin (outgoing)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Target: R2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### FW4-to-R2 (outgoing)

Zugriff Firewall 4 auf Router 2 (Remote Access)

Target:	R2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

#### FW4-to-FW3 (outgoing)

Zugriff Firewall 4 auf Firewall 3

Target:	FW3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	devops
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### Incoming Communication Links: 5

Source technical asset names are clickable and link to the corresponding chapter.

#### S4-to-FW4 (incoming)

Zugriff Server 4 auf Firewall 4 (Remote Access)

Source:	S4
Protocol:	unknown-protocol
Encrypted:	false

Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

### S3-to-FW4 (incoming)

Zugriff Server 3 auf Firewall 4 (MIS Verbindung)

Source:	S3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

### R1-to-FW4 (incoming)

Zugriff Router 1 auf Firewall 4

Source:	R1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	devops
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none

Data Sent: none

#### FW3-to-FW4 (incoming)

Zugriff Firewall 3 auf Firewall 4 (MIS Verbindung - Remote Access)

Source: FW3  
Protocol: ssh  
Encrypted: true  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### DC1-to-FW4 (incoming)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Source: DC1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## NTP: 2 / 2 Risks

### Description

NTP-Server

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **NTP**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@NTP](#)

Unchecked

#### *Low Risk Severity*

**Unnecessary Technical Asset** named **NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@NTP](#)

Unchecked

### Asset Information

ID:	NTP
Type:	process
Usage:	business
RAA:	5 %
Size:	service
Technology:	application-server
Tags:	secure-zone
Internet:	true
Machine:	virtual
Encryption:	transparent
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

## Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

### DC1-to-NTP (incoming)

Domain Controller 1 synchronisiert sich mit NTP-Server (NTP)

Source:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## OS1: 11 / 11 Risks

### Description

Operator Station

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Missing Authentication** covering communication link **R2-to-OS1-Admin** from **R2** to **OS1**: Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@R2>r2-to-os1-admin@R2@OS1](#)

**Unchecked**

**Missing Authentication** covering communication link **R2-to-OS1** from **R2** to **OS1**: Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@R2>r2-to-os1@R2@OS1](#)

**Unchecked**

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **OS1**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@OS1](#)

**Unchecked**

**Missing Hardening** risk at **OS1**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@OS1](#)

**Unchecked**

#### *Low Risk Severity*

**Denial-of-Service** risky access of **OS1** by **R2** via **R2-to-OS1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@OS1@R2@R2>r2-to-os1-admin](#)

**Unchecked**

**Denial-of-Service** risky access of **OS1** by **R2** via **R2-to-OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@OS1@R2@R2>r2-to-os1](#)

**Unchecked**

**Missing Network Segmentation** to further encapsulate and protect **OS1** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

missing-network-segmentation@OS1

**Unchecked**

**Unknown Protocol** specified for communication link **OS1-to-R2** at technical asset **OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@OS1>os1-to-r2@OS1

**Unchecked**

**Unnecessary Communication Link** titled **OS1-to-R2** at technical asset **OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@OS1>os1-to-r2@OS1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **OS1** regarding communication link **OS1-to-R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@OS1@OS1>os1-to-r2

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@OS1

**Unchecked**

## Asset Information

ID:	OS1
Type:	process
Usage:	business
RAA:	73 %
Size:	service
Technology:	desktop
Tags:	ot
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	production-data



Data Stored: production-data  
Formats Accepted: JSON

## Asset Rating

Owner: OT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: critical (rated 4 in scale of 5)  
Availability: critical (rated 4 in scale of 5)  
CIA-Justification:

## Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

### OS1-to-R2 (outgoing)

Zugriff Operator Station 1 auf Router 2 (MIS Verbindung)

Target: R2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

## Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

### R2-to-OS1-Admin (incoming)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Source: R2  
Protocol: unknown-protocol

Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

### R2-to-OS1 (incoming)

Zugriff Router 2 auf Operator Station 1 (MIS Verbindung)

Source:	R2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## R2: 26 / 26 Risks

### Description

OT Network Router

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **R2** against filesystem **DC2** via **R2-to-DC2-NTP**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@R2@DC2@R2>r2-to-dc2-ntp`

**Unchecked**

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **R2-to-DC2-NTP** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@R2>r2-to-dc2-ntp@R2`

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-ES1-Admin** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@R2>r2-to-es1-admin@R2`

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-ES1** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@R2>r2-to-es1@R2`

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-OS1-Admin** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@R2>r2-to-os1-admin@R2`

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-OS1** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@R2>r2-to-os1@R2`

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-S1-(MIS)** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-s1-mis@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-S1-Admin** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-s1-admin@R2

**Unchecked**

**Unknown Protocol** specified for communication link **R2-to-S1** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@R2>r2-to-s1@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-DC2-NTP** at technical asset **R2**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-dc2-ntp@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-ES1-Admin** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-es1-admin@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-ES1** at technical asset **R2**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-es1@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-OS1-Admin** at technical asset **R2**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-os1-admin@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-OS1** at technical asset **R2**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-os1@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-S1-(MIS)** at technical asset **R2**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-s1-mis@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-S1-Admin** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-s1-admin@R2

**Unchecked**

**Unnecessary Communication Link** titled **R2-to-S1** at technical asset **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@R2>r2-to-s1@R2

**Unchecked**

**Unnecessary Technical Asset** named **R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@R2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-DC2-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-dc2-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-ES1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-es1-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-es1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-OS1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-os1-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-OS1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-os1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-S1-(MIS)**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-s1-mis

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-S1-Admin**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-s1-admin

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R2** regarding communication link **R2-to-S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@R2@R2>r2-to-s1

**Unchecked**

## Asset Information

ID:	R2
Type:	process
Usage:	devops
RAA:	8 %
Size:	system
Technology:	gateway
Tags:	ot
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	OT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 8

Target technical asset names are clickable and link to the corresponding chapter.

### R2-to-S1-Admin (outgoing)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Target:	S1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### R2-to-S1-(MIS) (outgoing)

Zugriff Router 2 auf Server 1 (MIS Verbindung)

Target:	S1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### R2-to-S1 (outgoing)

Zugriff Router 2 auf Server 1 (Remote Access)

Target:	S1
Protocol:	unknown-protocol

Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

#### R2-to-OS1-Admin (outgoing)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Target:	OS1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

#### R2-to-OS1 (outgoing)

Zugriff Router 2 auf Operator Station 1 (MIS Verbindung)

Target:	OS1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false



Data Sent: none  
Data Received: none

#### R2-to-ES1-Admin (outgoing)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Target: ES1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### R2-to-ES1 (outgoing)

Zugriff Router 2 auf Engineering Station 1 (Remote Access)

Target: ES1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### R2-to-DC2-NTP (outgoing)

Server 1 synchronisiert sich über Domain Controller 2 (NTP)

Target: DC2  
Protocol: unknown-protocol

Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### Incoming Communication Links: 5

Source technical asset names are clickable and link to the corresponding chapter.

#### S1-to-R2-NTP (incoming)

Server 1 synchronisiert sich über Domain Controller 2 (NTP)

Source:	S1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

#### OS1-to-R2 (incoming)

Zugriff Operator Station 1 auf Router 2 (MIS Verbindung)

Source:	OS1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false

Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### FW4-to-R2-Admin (incoming)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Source: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### FW4-to-R2 (incoming)

Zugriff Firewall 4 auf Router 2 (Remote Access)

Source: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### ES1-to-R2 (incoming)

## Zugriff Engineering Station 1 auf Router 2 (Remote Access)

Source:	ES1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## S0: 5 / 5 Risks

### Description

RAS Server

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **S0**: Exploitation likelihood is *Likely* with *Medium* impact.

cross-site-scripting@S0

**Unchecked**

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **S0-to-FW2** at technical asset **S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S0>s0-to-fw2@S0

**Unchecked**

**Unnecessary Communication Link** titled **S0-to-FW2** at technical asset **S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S0>s0-to-fw2@S0

**Unchecked**

**Unnecessary Technical Asset** named **S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S0

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S0** regarding communication link **S0-to-FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S0@S0>s0-to-fw2

**Unchecked**

### Asset Information

ID:	S0
Type:	process
Usage:	business
RAA:	5 %
Size:	service

Technology:	application-server
Tags:	dmz
Internet:	true
Machine:	virtual
Encryption:	transparent
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

### Asset Rating

Owner:	IT	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### S0-to-FW2 (outgoing)

Zugriff DMZ RAS Server 0 auf Firewall 2

Target:	FW2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none

Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### FW1-to-S0 (incoming)

Zugriff Firewall 1 auf DMZ RAS Server 0

Source:	FW1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## S1: 12 / 12 Risks

### Description

Beispielkomponente für OT-TB1

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **S1**: Exploitation likelihood is *Likely* with *Medium* impact.

cross-site-scripting@S1

**Unchecked**

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **S1-to-R2-NTP** at technical asset **S1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S1>s1-to-r2-ntp@S1

**Unchecked**

**Unknown Protocol** specified for communication link **S1-to-R3-(MIS)** at technical asset **S1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S1>s1-to-r3-mis@S1

**Unchecked**

**Unknown Protocol** specified for communication link **S1-to-R3** at technical asset **S1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S1>s1-to-r3@S1

**Unchecked**

**Unnecessary Communication Link** titled **S1-to-R2-NTP** at technical asset **S1**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S1>s1-to-r2-ntp@S1

**Unchecked**

**Unnecessary Communication Link** titled **S1-to-R3-(MIS)** at technical asset **S1**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S1>s1-to-r3-mis@S1

**Unchecked**



**Unnecessary Communication Link** titled **S1-to-R3** at technical asset **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S1>s1-to-r3@S1

**Unchecked**

**Unnecessary Technical Asset** named **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S1** regarding communication link **S1-to-R2-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S1@S1>s1-to-r2-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S1** regarding communication link **S1-to-R3-(MIS)**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S1@S1>s1-to-r3-mis

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S1** regarding communication link **S1-to-R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S1@S1>s1-to-r3

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **S1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@S1

**Unchecked**

## Asset Information

ID:	S1
Type:	process
Usage:	business
RAA:	1 %
Size:	component
Technology:	application-server
Tags:	none
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false

Redundant: true  
Custom-Developed: false  
Client by Human: false  
Data Processed: none  
Data Stored: none  
Formats Accepted: none of the special data formats accepted

### Asset Rating

Owner: OT-Team  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: important (rated 3 in scale of 5)  
Availability: operational (rated 2 in scale of 5)  
CIA-Justification:

### Outgoing Communication Links: 3

Target technical asset names are clickable and link to the corresponding chapter.

#### S1-to-R3-(MIS) (outgoing)

Zugriff Server 1 auf Router 3 (MIS Verbindung)

Target: R3  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### S1-to-R3 (outgoing)

Zugriff Server 1 auf Router 3 (Remote Access)

Target: R3

Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

### S1-to-R2-NTP (outgoing)

Server 1 synchronisiert sich über Domain Controller 2 (NTP)

Target: R2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

## Incoming Communication Links: 3

Source technical asset names are clickable and link to the corresponding chapter.

### R2-to-S1-(MIS) (incoming)

Zugriff Router 2 auf Server 1 (MIS Verbindung)

Source: R2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user

Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### R2-to-S1-Admin (incoming)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Source: R2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### R2-to-S1 (incoming)

Zugriff Router 2 auf Server 1 (Remote Access)

Source: R2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## S2: 5 / 5 Risks

### Description

Virus Scan Server

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **S2** against filesystem **DC1** via **S2-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

[path-traversal@S2@DC1@S2>s2-to-dc1](#)

**Unchecked**

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **S2-to-DC1** at technical asset **S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@S2>s2-to-dc1@S2](#)

**Unchecked**

**Unnecessary Communication Link** titled **S2-to-DC1** at technical asset **S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@S2>s2-to-dc1@S2](#)

**Unchecked**

**Unnecessary Technical Asset** named **S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@S2](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S2** regarding communication link **S2-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@S2@S2>s2-to-dc1](#)

**Unchecked**

### Asset Information

ID:	S2
Type:	process
Usage:	devops
RAA:	6 %

Size:	service
Technology:	tool
Tags:	it
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

### S2-to-DC1 (outgoing)

Server 2 synchronisiert sich über Domain Controller 1 (NTP)

Target:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false

Data Sent: none  
Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### S4-to-S2 (incoming)

Zugriff Server 4 auf Server 2 (Jump Server zu Komponenten im Operations Netzwerk)

Source: S4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## S3: 11 / 11 Risks

### Description

Manufacturing Information System

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **S3** against filesystem **DC1** via **S3-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S3@DC1@S3>s3-to-dc1`

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **S3**: Exploitation likelihood is *Likely* with *Medium* impact.

`cross-site-scripting@S3`

**Unchecked**

#### *Medium Risk Severity*

**Unguarded Access from Internet** of **S3** by **S4** via **S4-to-S3**: Exploitation likelihood is *Very Likely* with *Low* impact.

`unguarded-access-from-internet@S3@S4@S4>s4-to-s3`

**Unchecked**

#### *Low Risk Severity*

**Missing Enduser Identity Propagation** over communication link **FW4-to-S3** from **FW4** to **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

`missing-identity-propagation@FW4>fw4-to-s3@FW4@S3`

**Unchecked**

**Missing Enduser Identity Propagation** over communication link **S4-to-S3** from **S4** to **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

`missing-identity-propagation@S4>s4-to-s3@S4@S3`

**Unchecked**

**Unknown Protocol** specified for communication link **S3-to-DC1** at technical asset **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@S3>s3-to-dc1@S3`

**Unchecked**



**Unknown Protocol** specified for communication link **S3-to-FW4** at technical asset **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S3>s3-to-fw4@S3

**Unchecked**

**Unnecessary Communication Link** titled **S3-to-DC1** at technical asset **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S3>s3-to-dc1@S3

**Unchecked**

**Unnecessary Communication Link** titled **S3-to-FW4** at technical asset **S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S3>s3-to-fw4@S3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S3** regarding communication link **S3-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S3@S3>s3-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S3** regarding communication link **S3-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S3@S3>s3-to-fw4

**Unchecked**

## Asset Information

ID:	S3
Type:	process
Usage:	business
RAA:	38 %
Size:	service
Technology:	report-engine
Tags:	ot
Internet:	false
Machine:	virtual
Encryption:	data-with-symmetric-shared-key
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	production-data

Data Stored: none  
Formats Accepted: JSON

## Asset Rating

Owner: OT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: critical (rated 4 in scale of 5)  
Availability: important (rated 3 in scale of 5)  
CIA-Justification:

## Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

### S3-to-FW4 (outgoing)

Zugriff Server 3 auf Firewall 4 (MIS Verbindung)

Target: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

### S3-to-DC1 (outgoing)

Server 3 synchronisiert sich über Domain Controller 1 (NTP)

Target: DC1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false

Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

#### S4-to-S3 (incoming)

Zugriff Server 4 auf Server 3 (Jump Server zu Komponenten im Operations Netzwerk)

Source:	S4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

#### FW4-to-S3 (incoming)

Zugriff Firewall 4 auf MIS Server 3 (MIS Verbindung - Remote Access)

Source:	FW4
Protocol:	ssh
Encrypted:	true
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false

Data Received: none

Data Sent: none

## S4: 25 / 25 Risks

### Description

Jump Server

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **S4** against filesystem **DC1** via **S4-to-DC1-NTP**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S4@DC1@S4>s4-to-dc1-ntp`

**Unchecked**

**Path-Traversal** risk at **S4** against filesystem **DC1** via **S4-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S4@DC1@S4>s4-to-dc1`

**Unchecked**

**Cross-Site Scripting (XSS)** risk at **S4**: Exploitation likelihood is *Likely* with *Medium* impact.

`cross-site-scripting@S4`

**Unchecked**

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **S4-to-DC1-NTP** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@S4>s4-to-dc1-ntp@S4`

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-DC1** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@S4>s4-to-dc1@S4`

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-FW4** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@S4>s4-to-fw4@S4`

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S2** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s2@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S3** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s3@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S5** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s5@S4

**Unchecked**

**Unknown Protocol** specified for communication link **S4-to-S6** at technical asset **S4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

incomplete-model@S4>s4-to-s6@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-DC1-NTP** at technical asset **S4**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-dc1-ntp@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-DC1** at technical asset **S4**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-dc1@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-FW4** at technical asset **S4**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-fw4@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S2** at technical asset **S4**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s2@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S3** at technical asset **S4**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s3@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S5** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s5@S4

**Unchecked**

**Unnecessary Communication Link** titled **S4-to-S6** at technical asset **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S4>s4-to-s6@S4

**Unchecked**

**Unnecessary Technical Asset** named **S4**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-DC1-NTP**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-dc1-ntp

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-dc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s5

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S4** regarding communication link **S4-to-S6**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S4@S4>s4-to-s6

**Unchecked**

## Asset Information

ID:	S4
Type:	process
Usage:	business
RAA:	14 %
Size:	service
Technology:	application-server
Tags:	secure-zone
Internet:	true
Machine:	virtual
Encryption:	transparent
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 7

Target technical asset names are clickable and link to the corresponding chapter.

### S4-to-S6 (outgoing)

Zugriff Server 4 auf Server 2 (Jump Server zu Komponenten im Operations Netzwerk)



Target:	S6
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

#### S4-to-S5 (outgoing)

Zugriff Server 4 auf Server 5 (Jump Server zu Komponenten im Operations Netzwerk)

Target:	S5
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

#### S4-to-S3 (outgoing)

Zugriff Server 4 auf Server 3 (Jump Server zu Komponenten im Operations Netzwerk)

Target:	S3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business

Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

**S4-to-S2 (outgoing)**

Zugriff Server 4 auf Server 2 (Jump Server zu Komponenten im Operations Netzwerk)

Target: S2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

**S4-to-FW4 (outgoing)**

Zugriff Server 4 auf Firewall 4 (Remote Access)

Target: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

**S4-to-DC1-NTP (outgoing)**

Server 4 synchronisiert sich über Domain Controller 1 (NTP)

Target:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

**S4-to-DC1 (outgoing)**

Zugriff Server 4 auf Domain Controller DC1 (Jump Server zu Komponenten im Operations Netzwerk)

Target:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

**Incoming Communication Links: 1**

Source technical asset names are clickable and link to the corresponding chapter.

**FW4-to-S4 (incoming)**

Zugriff Firewall 4 auf Server 4 (MIS Verbindung - Remote Access)

Source:	FW4
Protocol:	unknown-protocol

Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## S5: 8 / 8 Risks

### Description

WSUS Server

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **S5** against filesystem **DC1** via **S5-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S5@DC1@S5>s5-to-dc1`

**Unchecked**

#### *Medium Risk Severity*

**Code Backdooring** risk at **S5**: Exploitation likelihood is *Unlikely* with *Medium* impact.

`code-backdooring@S5`

**Unchecked**

#### *Low Risk Severity*

**Accidental Secret Leak** risk at **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

`accidental-secret-leak@S5`

**Unchecked**

**Unchecked Deployment** risk at **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

`unchecked-deployment@S5`

**Unchecked**

**Unknown Protocol** specified for communication link **S5-to-DC1** at technical asset **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@S5>s5-to-dc1@S5`

**Unchecked**

**Unnecessary Communication Link** titled **S5-to-DC1** at technical asset **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

`unnecessary-communication-link@S5>s5-to-dc1@S5`

**Unchecked**

**Unnecessary Technical Asset** named **S5**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@S5

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S5** regarding communication link **S5-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S5@S5>s5-to-dc1

**Unchecked**

## Asset Information

ID:	S5
Type:	process
Usage:	devops
RAA:	16 %
Size:	service
Technology:	artifact-registry
Tags:	it
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

**Outgoing Communication Links: 1**

Target technical asset names are clickable and link to the corresponding chapter.

**S5-to-DC1 (outgoing)**

Server 5 synchronisiert sich über Domain Controller 1 (NTP)

Target:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

**Incoming Communication Links: 1**

Source technical asset names are clickable and link to the corresponding chapter.

**S4-to-S5 (incoming)**

Zugriff Server 4 auf Server 5 (Jump Server zu Komponenten im Operations Netzwerk)

Source:	S4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## S6: 7 / 7 Risks

### Description

Historian Database

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Path-Traversal** risk at **S6** against filesystem **DC1** via **S6-to-DC1**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`path-traversal@S6@DC1@S6>s6-to-dc1`

**Unchecked**

**Unguarded Access from Internet of S6 by S4** via **S4-to-S6**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`unguarded-access-from-internet@S6@S4@S4>s4-to-s6`

**Unchecked**

#### *Medium Risk Severity*

**Missing Hardening** risk at **S6**: Exploitation likelihood is *Likely* with *Low* impact.

`missing-hardening@S6`

**Unchecked**

#### *Low Risk Severity*

**Missing Network Segmentation** to further encapsulate and protect **S6** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

`missing-network-segmentation@S6`

**Unchecked**

**Unknown Protocol** specified for communication link **S6-to-DC1** at technical asset **S6**: Exploitation likelihood is *Unlikely* with *Low* impact.

`incomplete-model@S6>s6-to-dc1@S6`

**Unchecked**



**Unnecessary Communication Link** titled **S6-to-DC1** at technical asset **S6**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@S6>s6-to-dc1@S6

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **S6** regarding communication link **S6-to-DC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@S6@S6>s6-to-dc1

**Unchecked**

## Asset Information

ID:	S6
Type:	datastore
Usage:	business
RAA:	100 %
Size:	system
Technology:	database
Tags:	it
Internet:	false
Machine:	virtual
Encryption:	data-with-symmetric-shared-key
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	production-data
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	confidential	(rated 4 in scale of 5)
Integrity:	critical	(rated 4 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)
CIA-Justification:		

**Outgoing Communication Links: 1**

Target technical asset names are clickable and link to the corresponding chapter.

**S6-to-DC1 (outgoing)**

Server 6 synchronisiert sich über Domain Controller 1 (NTP)

Target:	DC1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

**Incoming Communication Links: 1**

Source technical asset names are clickable and link to the corresponding chapter.

**S4-to-S6 (incoming)**

Zugriff Server 4 auf Server 2 (Jump Server zu Komponenten im Operations Netzwerk)

Source:	S4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## TI1: 5 / 5 Risks

### Description

Controller with I/O

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### Elevated Risk Severity

**Missing Authentication** covering communication link **R4-to-TI1** from **R4** to **TI1**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@R4>r4-to-ti1@R4@TI1

**Unchecked**

#### Medium Risk Severity

**Unencrypted Technical Asset** named **TI1**: Exploitation likelihood is *Unlikely* with *High* impact.

unencrypted-asset@TI1

**Unchecked**

**Missing Network Segmentation** to further encapsulate and protect **TI1** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Medium* impact.

missing-network-segmentation@TI1

**Unchecked**

**Missing Vault (Secret Storage)** in the threat model (referencing asset **TI1** as an example): Exploitation likelihood is *Unlikely* with *Medium* impact.

missing-vault@TI1

**Unchecked**

#### Low Risk Severity

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **TI1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@TI1

**Unchecked**

### Asset Information

ID: TI1

Type: external-entity  
 Usage: business  
 RAA: 52 %  
 Size: component  
 Technology: iot-device  
 Tags: ot  
 Internet: false  
 Machine: physical  
 Encryption: none  
 Multi-Tenant: false  
 Redundant: true  
 Custom-Developed: false  
 Client by Human: false  
 Data Processed: none  
 Data Stored: production-data  
 Formats Accepted: JSON

## Asset Rating

Owner: OT  
 Confidentiality: strictly-confidential (rated 5 in scale of 5)  
 Integrity: critical (rated 4 in scale of 5)  
 Availability: critical (rated 4 in scale of 5)  
 CIA-Justification:

## Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

### R4-to-TI1 (incoming)

Zugriff Router 4 auf Controller TI1 (Remote Access)

Source: R4  
 Protocol: unknown-protocol  
 Encrypted: false  
 Authentication: none  
 Authorization: technical-user  
 Read-Only: false  
 Usage: business

Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## TI2: 4 / 4 Risks

### Description

Controller with I/O

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### Elevated Risk Severity

**Missing Authentication** covering communication link **R4-to-TI2** from **R4** to **TI2**: Exploitation likelihood is *Likely* with *Medium* impact.

missing-authentication@R4>r4-to-ti2@R4@TI2

**Unchecked**

#### Medium Risk Severity

**Unencrypted Technical Asset** named **TI2**: Exploitation likelihood is *Unlikely* with *High* impact.

unencrypted-asset@TI2

**Unchecked**

**Missing Network Segmentation** to further encapsulate and protect **TI2** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Medium* impact.

missing-network-segmentation@TI2

**Unchecked**

#### Low Risk Severity

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **TI2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@TI2

**Unchecked**

### Asset Information

ID:	TI2
Type:	external-entity
Usage:	business
RAA:	52 %
Size:	component

Technology: iot-device  
 Tags: ot  
 Internet: false  
 Machine: physical  
 Encryption: none  
 Multi-Tenant: false  
 Redundant: true  
 Custom-Developed: false  
 Client by Human: false  
 Data Processed: none  
 Data Stored: production-data  
 Formats Accepted: JSON

### Asset Rating

Owner: OT  
 Confidentiality: strictly-confidential (rated 5 in scale of 5)  
 Integrity: critical (rated 4 in scale of 5)  
 Availability: critical (rated 4 in scale of 5)  
 CIA-Justification:

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### R4-to-TI2 (incoming)

Zugriff Router 4 auf Controller TI2 (Remote Access)

Source: R4  
 Protocol: unknown-protocol  
 Encrypted: false  
 Authentication: none  
 Authorization: technical-user  
 Read-Only: false  
 Usage: business  
 Tags: none  
 VPN: false  
 IP-Filtered: false  
 Data Received: none

Data Sent: none



## WC1: 4 / 4 Risks

### Description

Operator Web Client

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **WC1**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@WC1](#)

Unchecked

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **WC1**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@WC1](#)

Unchecked

#### *Low Risk Severity*

**Unnecessary Communication Link** titled **WC1-to-FW3** at technical asset **WC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@WC1>wc1-to-fw3@WC1](#)

Unchecked

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **WC1** regarding communication link **WC1-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@WC1@WC1>wc1-to-fw3](#)

Unchecked

### Asset Information

ID:	WC1
Type:	external-entity
Usage:	business
RAA:	27 %
Size:	component

Technology:	web-application
Tags:	it
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	true
Data Processed:	erp-data
Data Stored:	none
Formats Accepted:	JSON

### Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	operational	(rated 2 in scale of 5)
CIA-Justification:		

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### WC1-to-FW3 (outgoing)

Zugriff WC1 auf Firewall 3 (MIS Verbindung - Remote Access)

Target:	FW3
Protocol:	ssh
Encrypted:	true
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none

Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### FW3-to-WC1 (incoming)

Zugriff Firewall 3 auf WC1

Source:	FW3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## WC2: 4 / 4 Risks

### Description

Historian Web Client

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **WC2**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@WC2](#)

Unchecked

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **WC2**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@WC2](#)

Unchecked

#### *Low Risk Severity*

**Unnecessary Communication Link** titled **WC2-to-FW3** at technical asset **WC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@WC2>wc2-to-fw3@WC2](#)

Unchecked

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **WC2** regarding communication link **WC2-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@WC2@WC2>wc2-to-fw3](#)

Unchecked

### Asset Information

ID:	WC2
Type:	external-entity
Usage:	business
RAA:	33 %
Size:	component

Technology: web-application  
Tags: it  
Internet: false  
Machine: physical  
Encryption: none  
Multi-Tenant: false  
Redundant: false  
Custom-Developed: false  
Client by Human: true  
Data Processed: production-data  
Data Stored: none  
Formats Accepted: JSON

### Asset Rating

Owner: IT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: operational (rated 2 in scale of 5)  
Availability: operational (rated 2 in scale of 5)  
CIA-Justification:

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### WC2-to-FW3 (outgoing)

Zugriff WC2 auf Firewall 3 (MIS Verbindung - Remote Access)

Target: FW3  
Protocol: ssh  
Encrypted: true  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none

Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### FW3-to-WC2 (incoming)

Zugriff Firewall 3 auf WC2

Source:	FW3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## WC3: 4 / 4 Risks

### Description

Data Monitor Web Client

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Elevated Risk Severity*

**Cross-Site Scripting (XSS)** risk at **WC3**: Exploitation likelihood is *Likely* with *Medium* impact.

cross-site-scripting@WC3

**Unchecked**

#### *Medium Risk Severity*

**Unencrypted Technical Asset** named **WC3**: Exploitation likelihood is *Unlikely* with *Medium* impact.

unencrypted-asset@WC3

**Unchecked**

#### *Low Risk Severity*

**Unnecessary Communication Link** titled **WC3-to-FW3** at technical asset **WC3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@WC3>wc3-to-fw3@WC3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **WC3** regarding communication link **WC3-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@WC3@WC3>wc3-to-fw3

**Unchecked**

### Asset Information

ID:	WC3
Type:	external-entity
Usage:	business
RAA:	33 %
Size:	component

Technology: web-application  
Tags: it  
Internet: false  
Machine: physical  
Encryption: none  
Multi-Tenant: false  
Redundant: false  
Custom-Developed: false  
Client by Human: true  
Data Processed: production-data  
Data Stored: none  
Formats Accepted: JSON

### Asset Rating

Owner: IT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: operational (rated 2 in scale of 5)  
Availability: operational (rated 2 in scale of 5)  
CIA-Justification:

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### WC3-to-FW3 (outgoing)

Zugriff WC3 auf Firewall 3 (MIS Verbindung - Remote Access)

Target: FW3  
Protocol: ssh  
Encrypted: true  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none



Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### FW3-to-WC3 (incoming)

Zugriff Firewall 3 auf WC3

Source:	FW3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## C1: 4 / 4 Risks

### Description

Remote PC Wartung Support

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **C1-to-FW1** at technical asset **C1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@C1>c1-to-fw1@C1](#)

**Unchecked**

**Unnecessary Communication Link** titled **C1-to-FW1** at technical asset **C1**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@C1>c1-to-fw1@C1](#)

**Unchecked**

**Unnecessary Technical Asset** named **C1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@C1](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the  
communication link's readonly flag) at **C1** regarding communication link **C1-to-FW1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@C1@C1>c1-to-fw1](#)

**Unchecked**

### Asset Information

ID:	C1
Type:	external-entity
Usage:	devops
RAA:	0 %
Size:	component
Technology:	client-system
Tags:	it
Internet:	true
Machine:	physical
Encryption:	none

Multi-Tenant: false  
Redundant: false  
Custom-Developed: false  
Client by Human: true  
Data Processed: none  
Data Stored: none  
Formats Accepted: JSON

## Asset Rating

Owner: IT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: operational (rated 2 in scale of 5)  
Availability: operational (rated 2 in scale of 5)  
CIA-Justification:

## Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

### C1-to-FW1 (outgoing)

Zugriff C1 auf Firewall 1

Target: FW1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

## C2: 4 / 4 Risks

### Description

PC Support

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **C2-to-R1** at technical asset **C2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@C2>c2-to-r1@C2](#)

**Unchecked**

**Unnecessary Communication Link** titled **C2-to-R1** at technical asset **C2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@C2>c2-to-r1@C2](#)

**Unchecked**

**Unnecessary Technical Asset** named **C2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@C2](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **C2** regarding communication link **C2-to-R1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@C2@C2>c2-to-r1](#)

**Unchecked**

### Asset Information

ID:	C2
Type:	external-entity
Usage:	devops
RAA:	0 %
Size:	component
Technology:	client-system
Tags:	it
Internet:	true
Machine:	physical
Encryption:	none

Multi-Tenant: false  
Redundant: false  
Custom-Developed: false  
Client by Human: true  
Data Processed: none  
Data Stored: none  
Formats Accepted: JSON

### Asset Rating

Owner: IT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: operational (rated 2 in scale of 5)  
Availability: operational (rated 2 in scale of 5)  
CIA-Justification:

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### C2-to-R1 (outgoing)

Zugriff Client 2 auf Router 1

Target: R1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: none  
Read-Only: false  
Usage: devops  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

## ES1: 5 / 5 Risks

### Description

Engineering Station

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **ES1-to-R2** at technical asset **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@ES1>es1-to-r2@ES1](#)

**Unchecked**

**Unnecessary Communication Link** titled **ES1-to-R2** at technical asset **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@ES1>es1-to-r2@ES1](#)

**Unchecked**

**Unnecessary Technical Asset** named **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@ES1](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **ES1** regarding communication link **ES1-to-R2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@ES1@ES1>es1-to-r2](#)

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **ES1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-trust-boundary-content@ES1](#)

**Unchecked**

### Asset Information

ID:	ES1
Type:	process
Usage:	business
RAA:	3 %
Size:	service

Technology:	desktop
Tags:	ot
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

### Asset Rating

Owner:	OT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### ES1-to-R2 (outgoing)

#### Zugriff Engineering Station 1 auf Router 2 (Remote Access)

Target:	R2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none

Data Received: none

## Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

### R2-to-ES1-Admin (incoming)

Domain Controller 1 administriert die Windowssysteme OS1, ES1 und S1

Source:	R2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

### R2-to-ES1 (incoming)

Zugriff Router 2 auf Engineering Station 1 (Remote Access)

Source:	R2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none



## FW1: 4 / 4 Risks

### Description

Internet Firewall

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **FW1-to-S0** at technical asset **FW1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@FW1>fw1-to-s0@FW1](#)

**Unchecked**

**Unnecessary Communication Link** titled **FW1-to-S0** at technical asset **FW1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@FW1>fw1-to-s0@FW1](#)

**Unchecked**

**Unnecessary Technical Asset** named **FW1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@FW1](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW1** regarding communication link **FW1-to-S0**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@FW1@FW1>fw1-to-s0](#)

**Unchecked**

### Asset Information

ID:	FW1
Type:	process
Usage:	devops
RAA:	4 %
Size:	system
Technology:	gateway
Tags:	secure-zone
Internet:	true
Machine:	physical

Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

### Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)
CIA-Justification:		

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### FW1-to-S0 (outgoing)

Zugriff Firewall 1 auf DMZ RAS Server 0

Target:	S0
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

## Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

### C1-to-FW1 (incoming)

Zugriff C1 auf Firewall 1

Source:	C1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## FW2: 5 / 5 Risks

### Description

External Firewall

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Denial-of-Service** risky access of **FW2** by **S0** via **S0-to-FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@FW2@S0@S0>s0-to-fw2](#)

**Unchecked**

**Unknown Protocol** specified for communication link **FW2-to-FW3** at technical asset **FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@FW2>fw2-to-fw3@FW2](#)

**Unchecked**

**Unnecessary Communication Link** titled **FW2-to-FW3** at technical asset **FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@FW2>fw2-to-fw3@FW2](#)

**Unchecked**

**Unnecessary Technical Asset** named **FW2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@FW2](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW2** regarding communication link **FW2-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@FW2@FW2>fw2-to-fw3](#)

**Unchecked**

### Asset Information

ID:	FW2
Type:	process
Usage:	devops
RAA:	4 %
Size:	system

Technology:	gateway
Tags:	secure-zone
Internet:	true
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

### Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)
CIA-Justification:		

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### FW2-to-FW3 (outgoing)

Zugriff Firewall 2 auf Firewall 3

Target:	FW3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none

Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

#### S0-to-FW2 (incoming)

Zugriff DMZ RAS Server 0 auf Firewall 2

Source:	S0
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## FW3: 15 / 15 Risks

### Description

IT Firewall

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Denial-of-Service** risky access of **FW3** by **WC1** via **WC1-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@FW3@WC1@WC1>wc1-to-fw3](#)

**Unchecked**

**Denial-of-Service** risky access of **FW3** by **WC2** via **WC2-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@FW3@WC2@WC2>wc2-to-fw3](#)

**Unchecked**

**Denial-of-Service** risky access of **FW3** by **WC3** via **WC3-to-FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[dos-risky-access-across-trust-boundary@FW3@WC3@WC3>wc3-to-fw3](#)

**Unchecked**

**Unknown Protocol** specified for communication link **FW3-to-WC1** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@FW3>fw3-to-wc1@FW3](#)

**Unchecked**

**Unknown Protocol** specified for communication link **FW3-to-WC2** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@FW3>fw3-to-wc2@FW3](#)

**Unchecked**

**Unknown Protocol** specified for communication link **FW3-to-WC3** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@FW3>fw3-to-wc3@FW3](#)

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-FW4** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@FW3>fw3-to-fw4@FW3](#)

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-WC1** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-wc1@FW3

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-WC2** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-wc2@FW3

**Unchecked**

**Unnecessary Communication Link** titled **FW3-to-WC3** at technical asset **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-communication-link@FW3>fw3-to-wc3@FW3

**Unchecked**

**Unnecessary Technical Asset** named **FW3**: Exploitation likelihood is *Unlikely* with *Low* impact.

unnecessary-technical-asset@FW3

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-FW4**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-fw4

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-WC1**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-wc1

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-WC2**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-wc2

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **FW3** regarding communication link **FW3-to-WC3**: Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-communication-link-content@FW3@FW3>fw3-to-wc3

**Unchecked**

## Asset Information

ID: FW3  
Type: process



Usage:	devops
RAA:	6 %
Size:	system
Technology:	gateway
Tags:	secure-zone
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	IT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	critical	(rated 4 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 4

Target technical asset names are clickable and link to the corresponding chapter.

FW3-to-WC3 (outgoing)  
Zugriff Firewall 3 auf WC3

Target:	WC3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none

VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### FW3-to-WC2 (outgoing)

Zugriff Firewall 3 auf WC2

Target: WC2  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### FW3-to-WC1 (outgoing)

Zugriff Firewall 3 auf WC1

Target: WC1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

#### FW3-to-FW4 (outgoing)

Zugriff Firewall 3 auf Firewall 4 (MIS Verbindung - Remote Access)

Target:	FW4
Protocol:	ssh
Encrypted:	true
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### Incoming Communication Links: 5

Source technical asset names are clickable and link to the corresponding chapter.

#### WC3-to-FW3 (incoming)

Zugriff WC3 auf Firewall 3 (MIS Verbindung - Remote Access)

Source:	WC3
Protocol:	ssh
Encrypted:	true
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

#### WC2-to-FW3 (incoming)

Zugriff WC2 auf Firewall 3 (MIS Verbindung - Remote Access)

Source:	WC2
Protocol:	ssh
Encrypted:	true
Authentication:	credentials

Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### WC1-to-FW3 (incoming)

Zugriff WC1 auf Firewall 3 (MIS Verbindung - Remote Access)

Source: WC1  
Protocol: ssh  
Encrypted: true  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

#### FW4-to-FW3 (incoming)

Zugriff Firewall 4 auf Firewall 3

Source: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: devops  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## FW2-to-FW3 (incoming)

### Zugriff Firewall 2 auf Firewall 3

Source:	FW2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none

## R1: 4 / 4 Risks

### Description

ISDN Router

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **R1-to-FW4** at technical asset **R1**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@R1>r1-to-fw4@R1](#)

**Unchecked**

**Unnecessary Communication Link** titled **R1-to-FW4** at technical asset **R1**: Exploitation  
likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@R1>r1-to-fw4@R1](#)

**Unchecked**

**Unnecessary Technical Asset** named **R1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@R1](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the  
communication link's readonly flag) at **R1** regarding communication link **R1-to-FW4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@R1@R1>r1-to-fw4](#)

**Unchecked**

### Asset Information

ID:	R1
Type:	process
Usage:	devops
RAA:	2 %
Size:	system
Technology:	gateway
Tags:	it
Internet:	false
Machine:	physical
Encryption:	none

Multi-Tenant: false  
Redundant: false  
Custom-Developed: false  
Client by Human: false  
Data Processed: none  
Data Stored: none  
Formats Accepted: JSON

### Asset Rating

Owner: IT  
Confidentiality: internal (rated 2 in scale of 5)  
Integrity: operational (rated 2 in scale of 5)  
Availability: important (rated 3 in scale of 5)  
CIA-Justification:

### Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

#### R1-to-FW4 (outgoing)

Zugriff Router 1 auf Firewall 4

Target: FW4  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: credentials  
Authorization: technical-user  
Read-Only: false  
Usage: devops  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Sent: none  
Data Received: none

### Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

## C2-to-R1 (incoming)

### Zugriff Client 2 auf Router 1

Source:	C2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	devops
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	none
Data Sent:	none



## R3: 8 / 8 Risks

### Description

Anlagenbus Router

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **R3-to-R4-(MIS)** at technical asset **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@R3>r3-to-r4-mis@R3](#)

**Unchecked**

**Unknown Protocol** specified for communication link **R3-to-R4** at technical asset **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@R3>r3-to-r4@R3](#)

**Unchecked**

**Unnecessary Communication Link** titled **R3-to-R4-(MIS)** at technical asset **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@R3>r3-to-r4-mis@R3](#)

**Unchecked**

**Unnecessary Communication Link** titled **R3-to-R4** at technical asset **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@R3>r3-to-r4@R3](#)

**Unchecked**

**Unnecessary Technical Asset** named **R3**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@R3](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R3** regarding communication link **R3-to-R4-(MIS)**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@R3@R3>r3-to-r4-mis](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R3** regarding communication link **R3-to-R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@R3@R3>r3-to-r4](#)

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **R3**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@R3

**Unchecked**

## Asset Information

ID:	R3
Type:	process
Usage:	devops
RAA:	1 %
Size:	system
Technology:	gateway
Tags:	ot
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	OT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

R3-to-R4-(MIS) (outgoing)  
Zugriff Router 3 auf Router 4 (MIS Verbindung)

Target:	R4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### R3-to-R4 (outgoing)

Zugriff Router 3 auf Router 4 (Remote Access)

Target:	R4
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

## Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

### S1-to-R3-(MIS) (incoming)

Zugriff Server 1 auf Router 3 (MIS Verbindung)

Source:	S1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials

Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

### S1-to-R3 (incoming)

Zugriff Server 1 auf Router 3 (Remote Access)

Source: S1  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

## R4: 8 / 8 Risks

### Description

Anlagenbus Router

### Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

#### *Low Risk Severity*

**Unknown Protocol** specified for communication link **R4-to-TI1** at technical asset **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@R4>r4-to-ti1@R4](#)

**Unchecked**

**Unknown Protocol** specified for communication link **R4-to-TI2** at technical asset **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[incomplete-model@R4>r4-to-ti2@R4](#)

**Unchecked**

**Unnecessary Communication Link** titled **R4-to-TI1** at technical asset **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@R4>r4-to-ti1@R4](#)

**Unchecked**

**Unnecessary Communication Link** titled **R4-to-TI2** at technical asset **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-communication-link@R4>r4-to-ti2@R4](#)

**Unchecked**

**Unnecessary Technical Asset** named **R4**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@R4](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R4** regarding communication link **R4-to-TI1**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@R4@R4>r4-to-ti1](#)

**Unchecked**

**Wrong Communication Link Content** (data assets sent/received not matching the communication link's readonly flag) at **R4** regarding communication link **R4-to-TI2**: Exploitation likelihood is *Unlikely* with *Low* impact.

[wrong-communication-link-content@R4@R4>r4-to-ti2](#)

**Unchecked**

**Wrong Trust Boundary Content** (non-container asset inside container trust boundary) at **R4**:  
Exploitation likelihood is *Unlikely* with *Low* impact.

wrong-trust-boundary-content@R4

**Unchecked**

## Asset Information

ID:	R4
Type:	process
Usage:	devops
RAA:	6 %
Size:	system
Technology:	gateway
Tags:	ot
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	true
Custom-Developed:	false
Client by Human:	false
Data Processed:	none
Data Stored:	none
Formats Accepted:	JSON

## Asset Rating

Owner:	OT	
Confidentiality:	internal	(rated 2 in scale of 5)
Integrity:	operational	(rated 2 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:		

## Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

R4-to-TI2 (outgoing)

Zugriff Router 4 auf Controller TI2 (Remote Access)

Target:	TI2
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

#### R4-to-TI1 (outgoing)

Zugriff Router 4 auf Controller TI1 (Remote Access)

Target:	TI1
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	none
Data Received:	none

### Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

#### R3-to-R4-(MIS) (incoming)

Zugriff Router 3 auf Router 4 (MIS Verbindung)

Source:	R3
Protocol:	unknown-protocol
Encrypted:	false
Authentication:	credentials

Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none

### R3-to-R4 (incoming)

Zugriff Router 3 auf Router 4 (Remote Access)

Source: R3  
Protocol: unknown-protocol  
Encrypted: false  
Authentication: none  
Authorization: technical-user  
Read-Only: false  
Usage: business  
Tags: none  
VPN: false  
IP-Filtered: false  
Data Received: none  
Data Sent: none



## Identified Data Breach Probabilities by Data Asset

In total **235 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 29 as elevated, 19 as medium, and 187 as low.**

These risks are distributed across **2 data assets**. The following sub-chapters of this section describe the derived data breach probabilities grouped by data asset.

Technical asset names and risk IDs are clickable and link to the corresponding chapter.

## erp-data: 22 / 22 Risks

Financial and business data in ERP

ID:	erp-data
Usage:	business
Quantity:	many
Tags:	it
Origin:	Office
Owner:	Business
Confidentiality:	confidential (rated 4 in scale of 5)
Integrity:	important (rated 3 in scale of 5)
Availability:	important (rated 3 in scale of 5)
CIA-Justification:	Supports enterprise operations
Processed by:	WC1
Stored by:	DC1
Sent via:	none
Received via:	none
Data Breach:	<b>probable</b>

Data Breach Risks: This data asset has data breach potential because of 22 remaining risks:

Probable: path-traversal@DC2@DC1@DC2>dc2-to-dc1

Probable: path-traversal@S2@DC1@S2>s2-to-dc1

Probable: path-traversal@S3@DC1@S3>s3-to-dc1

Probable: path-traversal@S4@DC1@S4>s4-to-dc1-ntp

Probable: path-traversal@S4@DC1@S4>s4-to-dc1

Probable: path-traversal@S5@DC1@S5>s5-to-dc1

Probable: path-traversal@S6@DC1@S6>s6-to-dc1

Possible: cross-site-scripting@WC1

Possible: missing-authentication@DC2>dc2-to-dc1@DC2@DC1

Possible: missing-authentication@S2>s2-to-dc1@S2@DC1

Possible: missing-authentication@S3>s3-to-dc1@S3@DC1

Possible: missing-authentication@S4>s4-to-dc1-ntp@S4@DC1

Possible: missing-authentication@S5>s5-to-dc1@S5@DC1

Possible: unguarded-access-from-internet@DC1@S4@S4>s4-to-dc1-ntp

Possible: unguarded-access-from-internet@DC1@S4@S4>s4-to-dc1

Improbable: unencrypted-asset@DC1

Improbable: unencrypted-asset@WC1

Improbable: incomplete-model@DC1>dc1-to-fw4@DC1

Improbable: incomplete-model@DC1>dc1-to-ntp@DC1

Improbable: unnecessary-communication-link@DC1>dc1-to-fw4@DC1

Improbable: unnecessary-communication-link@DC1>dc1-to-ntp@DC1

Improbable: unnecessary-communication-link@WC1>wc1-to-fw3@WC1

## production-data: 41 / 41 Risks

### Data from PLCs and control systems

ID:	production-data
Usage:	business
Quantity:	many
Tags:	production
Origin:	OT
Owner:	Plant Operations
Confidentiality:	confidential (rated 4 in scale of 5)
Integrity:	critical (rated 4 in scale of 5)
Availability:	critical (rated 4 in scale of 5)
CIA-Justification:	Essential for process control
Processed by:	OS1, S3, WC2, WC3
Stored by:	DC2, OS1, S6, TI1, TI2
Sent via:	none
Received via:	none
Data Breach:	<b>probable</b>

Data Breach Risks: This data asset has data breach potential because of 41 remaining risks:

Probable: path-traversal@R2@DC2@R2>r2-to-dc2-ntp

Possible: cross-site-scripting@S3

Possible: cross-site-scripting@WC2

Possible: cross-site-scripting@WC3

Possible: missing-authentication@R2>r2-to-dc2-ntp@R2@DC2

Possible: missing-authentication@R2>r2-to-os1-admin@R2@OS1

Possible: missing-authentication@R2>r2-to-os1@R2@OS1

Possible: missing-authentication@R4>r4-to-ti1@R4@TI1

Possible: missing-authentication@R4>r4-to-ti2@R4@TI2

Possible: unguarded-access-from-internet@S3@S4@S4>s4-to-s3

Possible: unguarded-access-from-internet@S6@S4@S4>s4-to-s6

Improbable: missing-identity-propagation@FW4>fw4-to-s3@FW4@S3

Improbable: missing-identity-propagation@S4>s4-to-s3@S4@S3

Improbable: missing-hardening@OS1

Improbable: missing-hardening@S6

Improbable: missing-network-segmentation@OS1

Improbable: missing-network-segmentation@S6

Improbable: missing-network-segmentation@TI1

Improbable: missing-network-segmentation@TI2

Improbable: unencrypted-asset@DC2

Improbable: unencrypted-asset@OS1

Improbable: unencrypted-asset@TI1

Improbable: unencrypted-asset@TI2

Improbable: unencrypted-asset@WC2

Improbable: unencrypted-asset@WC3  
Improbable: incomplete-model@DC2>dc2-to-dc1@DC2  
Improbable: incomplete-model@OS1>os1-to-r2@OS1  
Improbable: incomplete-model@S3>s3-to-dc1@S3  
Improbable: incomplete-model@S3>s3-to-fw4@S3  
Improbable: incomplete-model@S6>s6-to-dc1@S6  
Improbable: unnecessary-communication-link@DC2>dc2-to-dc1@DC2  
Improbable: unnecessary-communication-link@OS1>os1-to-r2@OS1  
Improbable: unnecessary-communication-link@S3>s3-to-dc1@S3  
Improbable: unnecessary-communication-link@S3>s3-to-fw4@S3  
Improbable: unnecessary-communication-link@S6>s6-to-dc1@S6  
Improbable: unnecessary-communication-link@WC2>wc2-to-fw3@WC2  
Improbable: unnecessary-communication-link@WC3>wc3-to-fw3@WC3  
Improbable: wrong-trust-boundary-content@DC2  
Improbable: wrong-trust-boundary-content@OS1  
Improbable: wrong-trust-boundary-content@TI1  
Improbable: wrong-trust-boundary-content@TI2

# Trust Boundaries

In total **5 trust boundaries** have been modeled during the threat modeling process.

## DMZ

### Demilitarized Zone

ID: DMZ  
Type: [network-on-prem](#)  
Tags: dmz, secure-zone  
Assets inside: S0  
Boundaries nested: none

## OT-TB1

### Terminal Bus Zone

ID: OT-TB1  
Type: [network-policy-namespace-isolation](#)  
Tags: ot  
Assets inside: DC2, ES1, OS1, S1  
Boundaries nested: none

## OT-TB2

### Anlagenbus Zone

ID: OT-TB2  
Type: [network-policy-namespace-isolation](#)  
Tags: ot  
Assets inside: R3, R4, TI1, TI2  
Boundaries nested: none

## Office

### Office Network

ID: Office  
Type: [network-on-prem](#)

Tags: it, secure-zone  
Assets inside: NTP, WC1, WC2, WC3  
Boundaries nested: none

## Operations

### Operations Management Zone

ID: Operations  
Type: network-on-prem  
Tags: it  
Assets inside: DC1, S2, S3, S4, S5, S6  
Boundaries nested: none

## Shared Runtimes

In total **0 shared runtime** has been modeled during the threat modeling process.

# Risk Rules Checked by Threagile

**Threagile Version:** 1.0.0

**Threagile Build Timestamp:** 20240730113903

**Threagile Execution Timestamp:** 20250709220552

**Model Filename:** /app/work/threagile\_full.yaml

**Model Hash (SHA256):** 8305f7961fe5d91f111fb8f4c954ffb0b572009f1c673124bebabe4679ed7392

Threagile (see <https://threagile.io> for more details) is an open-source toolkit for agile threat modeling, created by Christian Schneider (<https://christian-schneider.net>): It allows to model an architecture with its assets in an agile fashion as a YAML file directly inside the IDE. Upon execution of the Threagile toolkit all standard risk rules (as well as individual custom rules if present) are checked against the architecture model. At the time the Threagile toolkit was executed on the model input file the following risk rules were checked:

## Accidental Secret Leak

accidental-secret-leak

**STRIDE:** Information Disclosure

**Description:** Sourcecode repositories (including their histories) as well as artifact registries can accidentally contain secrets like checked-in or packaged-in passwords, API tokens, certificates, crypto keys, etc.

**Detection:** In-scope sourcecode repositories and artifact registries.

**Rating:** The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

## Code Backdooring

code-backdooring

**STRIDE:** Tampering

**Description:** For each build-pipeline component Code Backdooring risks might arise where attackers compromise the build-pipeline in order to let backdoored artifacts be shipped into production. Aside from direct code backdooring this includes backdooring of dependencies and even of more lower-level build infrastructure, like backdooring compilers (similar to what the XcodeGhost malware did) or dependencies.

**Detection:** In-scope development relevant technical assets which are either accessed by out-of-scope unmanaged developer clients and/or are directly accessed by any kind of internet-located (non-VPN) component or are themselves directly located on the internet.

**Rating:** The risk rating depends on the confidentiality and integrity rating of the code being handled and deployed as well as the placement/calling of this technical asset on/from the internet.

## Container Base Image Backdooring

container-baseimage-backdooring



**STRIDE:** Tampering

**Description:** When a technical asset is built using container technologies, Base Image Backdooring risks might arise where base images and other layers used contain vulnerable components or backdoors.

**Detection:** In-scope technical assets running as containers.

**Rating:** The risk rating depends on the sensitivity of the technical asset itself and of the data assets.

### **Container Platform Escape**

container-platform-escape

**STRIDE:** Elevation of Privilege

**Description:** Container platforms are especially interesting targets for attackers as they host big parts of a containerized runtime infrastructure. When not configured and operated with security best practices in mind, attackers might exploit a vulnerability inside an container and escape towards the platform as highly privileged users. These scenarios might give attackers capabilities to attack every other container as owning the container platform (via container escape attacks) equals to owning every container.

**Detection:** In-scope container platforms.

**Rating:** The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

### **Cross-Site Request Forgery (CSRF)**

cross-site-request-forgery

**STRIDE:** Spoofing

**Description:** When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

**Detection:** In-scope web applications accessed via typical web access protocols.

**Rating:** The risk rating depends on the integrity rating of the data sent across the communication link.

### **Cross-Site Scripting (XSS)**

cross-site-scripting

**STRIDE:** Tampering

**Description:** For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

**Detection:** In-scope web applications.

**Rating:** The risk rating depends on the sensitivity of the data processed or stored in the web application.

### **DoS-risky Access Across Trust-Boundary**

**dos-risky-access-across-trust-boundary**

**STRIDE:** Denial of Service

**Description:** Assets accessed across trust boundaries with critical or mission-critical availability rating are more prone to Denial-of-Service (DoS) risks.

**Detection:** In-scope technical assets (excluding load-balancer) with availability rating of critical or higher which have incoming data-flows across a network trust-boundary (excluding devops usage).

**Rating:** Matching technical assets with availability rating of critical or higher are at low risk. When the availability rating is mission-critical and neither a VPN nor IP filter for the incoming data-flow nor redundancy for the asset is applied, the risk-rating is considered medium.

**Incomplete Model****incomplete-model**

**STRIDE:** Information Disclosure

**Description:** When the threat model contains unknown technologies or transfers data over unknown protocols, this is an indicator for an incomplete model.

**Detection:** All technical assets and communication links with technology type or protocol type specified as unknown.

**Rating:** low

**LDAP-Injection****ldap-injection**

**STRIDE:** Tampering

**Description:** When an LDAP server is accessed LDAP-Injection risks might arise. The risk rating depends on the sensitivity of the LDAP server itself and of the data assets processed or stored.

**Detection:** In-scope clients accessing LDAP servers via typical LDAP access protocols.

**Rating:** The risk rating depends on the sensitivity of the LDAP server itself and of the data assets processed or stored.

**Missing Authentication****missing-authentication**

**STRIDE:** Elevation of Privilege

**Description:** Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

**Detection:** In-scope technical assets (except load-balancer, reverse-proxy, service-registry, waf, ids, and ips and in-process calls) should authenticate incoming requests when the asset processes or stores sensitive data. This is especially the case for all multi-tenant assets (there even non-sensitive ones).

**Rating:** The risk rating (medium or high) depends on the sensitivity of the data sent across

the communication link. Monitoring callers are exempted from this risk.

### Missing Two-Factor Authentication (2FA)

missing-authentication-second-factor

STRIDE: Elevation of Privilege

Description: Technical assets (especially multi-tenant systems) should authenticate incoming requests with two-factor (2FA) authentication when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by humans.

Detection: In-scope technical assets (except load-balancer, reverse-proxy, waf, ids, and ips) should authenticate incoming requests via two-factor authentication (2FA) when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by a client used by a human user.

Rating: medium

### Missing Build Infrastructure

missing-build-infrastructure

STRIDE: Tampering

Description: The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Detection: Models with in-scope custom-developed parts missing in-scope development (code creation) and build infrastructure components (devops-client, sourcecode-repo, build-pipeline, etc.).

Rating: The risk rating depends on the highest sensitivity of the in-scope assets running custom-developed parts.

### Missing Cloud Hardening

missing-cloud-hardening

STRIDE: Tampering

Description: Cloud components should be hardened according to the cloud vendor best practices. This affects their configuration, auditing, and further areas.

Detection: In-scope cloud components (either residing in cloud trust boundaries or more specifically tagged with cloud provider types).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

### Missing File Validation

missing-file-validation

STRIDE: Spoofing

- Description:** When a technical asset accepts files, these input files should be strictly validated about filename and type.
- Detection:** In-scope technical assets with custom-developed code accepting file data formats.
- Rating:** The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

## Missing Hardening

missing-hardening

- STRIDE:** Tampering
- Description:** Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.
- Detection:** In-scope technical assets with RAA values of 55 % or higher. Generally for high-value targets like datastores, application servers, identity providers and ERP systems this limit is reduced to 40 %
- Rating:** The risk rating depends on the sensitivity of the data processed or stored in the technical asset.

## Missing Identity Propagation

missing-identity-propagation

- STRIDE:** Elevation of Privilege
- Description:** Technical assets (especially multi-tenant systems), which usually process data for endusers should authorize every request based on the identity of the enduser when the data flow is authenticated (i.e. non-public). For DevOps usages at least a technical-user authorization is required.
- Detection:** In-scope service-like technical assets which usually process data based on enduser requests, if authenticated (i.e. non-public), should authorize incoming requests based on the propagated enduser identity when their rating is sensitive. This is especially the case for all multi-tenant assets (there even less-sensitive rated ones). DevOps usages are exempted from this risk.
- Rating:** The risk rating (medium or high) depends on the confidentiality, integrity, and availability rating of the technical asset.

## Missing Identity Provider Isolation

missing-identity-provider-isolation

- STRIDE:** Elevation of Privilege
- Description:** Highly sensitive identity provider assets and their identity datastores should be isolated from other assets by their own network segmentation trust-boundary (execution-environment boundaries do not count as network isolation).
- Detection:** In-scope identity provider assets and their identity datastores when surrounded by other (not identity-related) assets (without a network trust-boundary in-between).

This risk is especially prevalent when other non-identity related assets are within the same execution environment (i.e. same database or same application server).

Rating: Default is high impact. The impact is increased to very-high when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

### Missing Identity Store

missing-identity-store

STRIDE: Spoofing

Description: The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Detection: Models with authenticated data-flows authorized via enduser-identity missing an in-scope identity store.

Rating: The risk rating depends on the sensitivity of the enduser-identity authorized technical assets and their data assets processed and stored.

### Missing Network Segmentation

missing-network-segmentation

STRIDE: Elevation of Privilege

Description: Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webserver or content management systems etc.) should be better protected by a network segmentation trust-boundary.

Detection: In-scope technical assets with high sensitivity and RAA values as well as datastores when surrounded by assets (without a network trust-boundary in-between) which are of type client-system, web-server, web-application, cms, web-service-rest, web-service-soap, build-pipeline, sourcecode-repository, monitoring, or similar and there is no direct connection between these (hence no requirement to be so close to each other).

Rating: Default is low risk. The risk is increased to medium when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

### Missing Vault (Secret Storage)

missing-vault

STRIDE: Information Disclosure

Description: In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Detection: Models without a Vault (Secret Storage).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

## Missing Vault Isolation

missing-vault-isolation

STRIDE: Elevation of Privilege

Description: Highly sensitive vault assets and their datastores should be isolated from other assets by their own network segmentation trust-boundary (execution-environment boundaries do not count as network isolation).

Detection: In-scope vault assets when surrounded by other (not vault-related) assets (without a network trust-boundary in-between). This risk is especially prevalent when other non-vault related assets are within the same execution environment (i.e. same database or same application server).

Rating: Default is medium impact. The impact is increased to high when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

## Missing Web Application Firewall (WAF)

missing-waf

STRIDE: Tampering

Description: To have a first line of filtering defense, security architectures with web-services or web-applications should include a WAF in front of them. Even though a WAF is not a replacement for security (all components must be secure even without a WAF) it adds another layer of defense to the overall system by delaying some attacks and having easier attack alerting through it.

Detection: In-scope web-services and/or web-applications accessed across a network trust boundary not having a Web Application Firewall (WAF) in front of them.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

## Mixed Targets on Shared Runtime

mixed-targets-on-shared-runtime

STRIDE: Elevation of Privilege

Description: Different attacker targets (like frontend and backend/datastore components) should not be running on the same shared (underlying) runtime.

Detection: Shared runtime running technical assets of different trust-boundaries is at risk. Also mixing backend/datastore with frontend components on the same shared runtime is considered a risk.

Rating: The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset running on the shared runtime.

## Path-Traversal

path-traversal

STRIDE: Information Disclosure

Description: When a filesystem is accessed Path-Traversal or Local-File-Inclusion (LFI) risks might arise. The risk rating depends on the sensitivity of the technical asset itself

and of the data assets processed or stored.

Detection: Filesystems accessed by in-scope callers.

Rating: The risk rating depends on the sensitivity of the data stored inside the technical asset.

## Push instead of Pull Deployment

push-instead-of-pull-deployment

STRIDE: Tampering

Description: When comparing push-based vs. pull-based deployments from a security perspective, pull-based deployments improve the overall security of the deployment targets. Every exposed interface of a production system to accept a deployment increases the attack surface of the production system, thus a pull-based approach exposes less attack surface relevant interfaces.

Detection: Models with build pipeline components accessing in-scope targets of deployment (in a non-readonly way) which are not build-related components themselves.

Rating: The risk rating depends on the highest sensitivity of the deployment targets running custom-developed parts.

## Search-Query Injection

search-query-injection

STRIDE: Tampering

Description: When a search engine server is accessed Search-Query Injection risks might arise.

Detection: In-scope clients accessing search engine servers via typical search access protocols.

Rating: The risk rating depends on the sensitivity of the search engine server itself and of the data assets processed or stored.

## Server-Side Request Forgery (SSRF)

server-side-request-forgery

STRIDE: Information Disclosure

Description: When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Detection: In-scope non-client systems accessing (using outgoing communication links) targets with either HTTP or HTTPS protocol.

Rating: The risk rating (low or medium) depends on the sensitivity of the data assets receivable via web protocols from targets within the same network trust-boundary as well on the sensitivity of the data assets receivable via web protocols from the target asset itself. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF.

## Service Registry Poisoning



**service-registry-poisoning****STRIDE:** Spoofing**Description:** When a service registry used for discovery of trusted service endpoints Service Registry Poisoning risks might arise.**Detection:** In-scope service registries.**Rating:** The risk rating depends on the sensitivity of the technical assets accessing the service registry as well as the data assets processed or stored.**SQL/NoSQL-Injection****sql-nosql-injection****STRIDE:** Tampering**Description:** When a database is accessed via database access protocols SQL/NoSQL-Injection risks might arise. The risk rating depends on the sensitivity technical asset itself and of the data assets processed or stored.**Detection:** Database accessed via typical database access protocols by in-scope clients.**Rating:** The risk rating depends on the sensitivity of the data stored inside the database.**Unchecked Deployment****unchecked-deployment****STRIDE:** Tampering**Description:** For each build-pipeline component Unchecked Deployment risks might arise when the build-pipeline does not include established DevSecOps best-practices. DevSecOps best-practices scan as part of CI/CD pipelines for vulnerabilities in source- or byte-code, dependencies, container layers, and dynamically against running test systems. There are several open-source and commercial tools existing in the categories DAST, SAST, and IAST.**Detection:** All development-relevant technical assets.**Rating:** The risk rating depends on the highest rating of the technical assets and data assets processed by deployment-receiving targets.**Unencrypted Technical Assets****unencrypted-asset****STRIDE:** Information Disclosure**Description:** Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.**Detection:** In-scope unencrypted technical assets (excluding reverse-proxy, load-balancer, waf, ids, ips and embedded components like library) storing data assets rated at least as confidential or critical. For technical assets storing data assets rated as strictly-confidential or mission-critical the encryption must be of type data-with-enduser-individual-key.



Rating: Depending on the confidentiality rating of the stored data-assets either medium or high risk.

### Unencrypted Communication

unencrypted-communication

STRIDE: Information Disclosure

Description: Due to the confidentiality and/or integrity rating of the data assets transferred over the communication link this connection must be encrypted.

Detection: Unencrypted technical communication links of in-scope technical assets (excluding monitoring traffic as well as local-file-access and in-process-library-call) transferring sensitive data.

Rating: Depending on the confidentiality rating of the transferred data-assets either medium or high risk.

### Unguarded Access From Internet

unguarded-access-from-internet

STRIDE: Elevation of Privilege

Description: Internet-exposed assets must be guarded by a protecting service, application, or reverse-proxy.

Detection: In-scope technical assets (excluding load-balancer) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) when accessed directly from the internet. All web-server, web-application, reverse-proxy, waf, and gateway assets are exempted from this risk when they do not consist of custom developed code and the data-flow only consists of HTTP or FTP protocols. Access from monitoring systems as well as VPN-protected connections are exempted.

Rating: The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

### Unguarded Direct Datastore Access

unguarded-direct-datastore-access

STRIDE: Elevation of Privilege

Description: Datastores accessed across trust boundaries must be guarded by some protecting service or application.

Detection: In-scope technical assets of type datastore (except identity-store-ldap when accessed from identity-provider and file-server when accessed via file transfer protocols) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) which have incoming data-flows from assets outside across a network trust-boundary. DevOps config and deployment access is excluded from this risk.

**Rating:** The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

### Unnecessary Communication Link

unnecessary-communication-link

**STRIDE:** Elevation of Privilege

**Description:** When a technical communication link does not send or receive any data assets, this is an indicator for an unnecessary communication link (or for an incomplete model).

**Detection:** In-scope technical assets' technical communication links not sending or receiving any data assets.

**Rating:** low

### Unnecessary Data Asset

unnecessary-data-asset

**STRIDE:** Elevation of Privilege

**Description:** When a data asset is not processed or stored by any data assets and also not transferred by any communication links, this is an indicator for an unnecessary data asset (or for an incomplete model).

**Detection:** Modelled data assets not processed or stored by any data assets and also not transferred by any communication links.

**Rating:** low

### Unnecessary Data Transfer

unnecessary-data-transfer

**STRIDE:** Elevation of Privilege

**Description:** When a technical asset sends or receives data assets, which it neither processes or stores this is an indicator for unnecessarily transferred data (or for an incomplete model). When the unnecessarily transferred data assets are sensitive, this poses an unnecessary risk of an increased attack surface.

**Detection:** In-scope technical assets sending or receiving sensitive data assets which are neither processed nor stored by the technical asset are flagged with this risk. The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset. Monitoring data is exempted from this risk.

**Rating:** The risk assessment is depending on the confidentiality and integrity rating of the transferred data asset either low or medium.

### Unnecessary Technical Asset

unnecessary-technical-asset

**STRIDE:** Elevation of Privilege

**Description:** When a technical asset does not process or store any data assets, this is an

indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

Detection: Technical assets not processing or storing any data assets.

Rating: low

## Untrusted Deserialization

untrusted-deserialization

STRIDE: Tampering

Description: When a technical asset accepts data in a specific serialized form (like Java or .NET serialization), Untrusted Deserialization risks might arise.

Detection: In-scope technical assets accepting serialization data formats (including EJB and RMI protocols).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

## Wrong Communication Link Content

wrong-communication-link-content

STRIDE: Information Disclosure

Description: When a communication link is defined as readonly, but does not receive any data asset, or when it is defined as not readonly, but does not send any data asset, it is likely to be a model failure.

Detection: Communication links with inconsistent data assets being sent/received not matching their readonly flag or otherwise inconsistent protocols not matching the target technology type.

Rating: low

## Wrong Trust Boundary Content

wrong-trust-boundary-content

STRIDE: Elevation of Privilege

Description: When a trust boundary of type network-policy-namespace-isolation contains non-container assets it is likely to be a model failure.

Detection: Trust boundaries which should only contain containers, but have different assets inside.

Rating: low

## XML External Entity (XXE)

xml-external-entity

STRIDE: Information Disclosure

Description: When a technical asset accepts data in XML format, XML External Entity (XXE) risks might arise.

Detection: In-scope technical assets accepting XML data formats.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data

assets processed and stored. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF (and XXE vulnerabilities are often also SSRF vulnerabilities).

# Disclaimer

ChemoDemo Security Team conducted this threat analysis using the open-source Threagile toolkit on the applications and systems that were modeled as of this report's date. Information security threats are continually changing, with new vulnerabilities discovered on a daily basis, and no application can ever be 100% secure no matter how much threat modeling is conducted. It is recommended to execute threat modeling and also penetration testing on a regular basis (for example yearly) to ensure a high ongoing level of security and constantly check for new attack vectors.

This report cannot and does not protect against personal or business loss as the result of use of the applications or systems described. ChemoDemo Security Team and the Threagile toolkit offers no warranties, representations or legal certifications concerning the applications or systems it tests. All software includes defects: nothing in this document is intended to represent or warrant that threat modeling was complete and without error, nor does this document represent or warrant that the architecture analyzed is suitable to task, free of other defects than reported, fully compliant with any industry standards, or fully compatible with any operating system, hardware, or other application. Threat modeling tries to analyze the modeled architecture without having access to a real working system and thus cannot and does not test the implementation for defects and vulnerabilities. These kinds of checks would only be possible with a separate code review and penetration test against a working system and not via a threat model.

By using the resulting information you agree that ChemoDemo Security Team and the Threagile toolkit shall be held harmless in any event.

This report is confidential and intended for internal, confidential use by the client. The recipient is obligated to ensure the highly confidential contents are kept secret. The recipient assumes responsibility for further distribution of this document.

In this particular project, a timebox approach was used to define the analysis effort. This means that the author allotted a prearranged amount of time to identify and document threats. Because of this, there is no guarantee that all possible threats and risks are discovered. Furthermore, the analysis applies to a snapshot of the current state of the modeled architecture (based on the architecture information provided by the customer) at the examination time.

## Report Distribution

Distribution of this report (in full or in part like diagrams or risk findings) requires that this disclaimer as well as the chapter about the Threagile toolkit and method used is kept intact as part of the distributed report or referenced from the distributed parts.