

Program No.16

Aim

To build a simple peer-to-peer network with two PCs in Cisco Packet Tracer, connect them using a copper crossover cable and assign static IP addresses within the same subnet

Step 1: Add the Devices

1. Open Cisco Packet Tracer.
2. Click on End Devices in the bottom-left corner menu.
3. Drag two PC icons onto the workspace. They will appear as PC0 and PC1

Step 2: Connect the PCs

1. Click on the Connections icon (lightning bolt symbol) in the bottom-left menu.
2. Select the Copper Cross-Over cable (dashed red line). (Note: Modern physical devices auto-sense, but in simulation labs connecting identical devices like two PCs directly requires a crossover cable).
3. Click on PC0, select FastEthernet0, then click on PC1 and select FastEthernet0. The link lights will turn green once connected properly.

Step 3: Configure IP Addresses

1. Click on PC0, go to the Desktop tab, and click IP Configuration.
 - IPv4 Address: 192.168.1.10
 - Subnet Mask: 255.255.255.0
2. Close the window, click on PC1, go to Desktop -> IP Configuration:
 - IPv4 Address: 192.168.1.11
 - Subnet Mask: 255.255.255.0

Step 4: Test Connectivity

1. Click on PC0, go to Desktop, and open Command Prompt.
2. Type the ping command for the second computer and press Enter:

```
ping 192.168.1.11
```

If you see "Reply from 192.168.1.11...", your network is successfully configured and communicating

Transmit a PDU from PC0 to PC1

Check ip address and subnet using ipconfig