CS & IT ENGINEERING

COMPUTER NETWORKS

IPv4 Header & Fragmentation

Lecture No-2

By- Ankit Doyla Sir

IPv4 Header

IPv4 Header

VER ✓	HL ✓	Services ✓	Total Length ✓
Identification No. ✓		Flags ✓	Fragment offset ✓
Time to Live (8bit)		Protocol (8bit)	Header checksum (16bit)
Source IP Address (32bit)			
Destination IP Address (32bit)			
Option			

TTL : = 8bit $\xrightarrow{\text{Range}}$ 0 to $2^8 - 1$ → 0 to 255

1. TTL is used to avoid infinite looping
2. TTL field is used to control the maximum no. of hops visited by datagram.
3. When a source host sends a datagram ,it stores a number in this field. Each router that process the datagram decrements this number by one. If TTL field reaches zero before the datagram arrives at its destination ,then the datagram is discarded and an ICMP message is sent back to sender.



NID	SM	IF
—	—	a
—	—	b
—	—	c
0.0.0.0	0.0.0.0	d

→ Default entry

IPAdd
AND
0.0.0.0
0.0.0.0


TTL=64 63 0
TTL=64 63 2
R1
R2
R3
TTL=5 4 2 1
InFinite Looping


TTL=5
TTL=4
TTL=3
TTL=2
TTL=4
TTL=3
TTL=2
TTL=1
TTL=3
TTL=2
TTL=1
TTL=0
TTL=2
TTL=1
TTL=0
TTL=1
TTL=0
TTL=0
Accepted
S
R1
R2
R3
D
ICMP message = TTL exceeded


AL
TL
NL
DL
PL
NL
DLL
PL
NL
DLL
PL
AL
TL
NL
DLL
PL
S
R1
R2
D
LAN-1
LAN-2

Protocol : (8 bit)

1. This 8 bit field tell us which protocol is encapsulated in the IP packet.
2. At the time of traffic , some packets must be discarded. In this case it will be advantageous to know which protocol data it contains.
3. The order in which router eliminate the datagram from buffer is-

ICMP> IGMP>UDP>TCP



Note: Inside the IP datagram it can be TCP Packet, UDP Packet, ICMP or IGMP Packet



OSPF → (89)

① ICMP (01)

② IGMP (02)

③ UDP (17)

④ TCP (06)

THANK YOU
GW
SOLDIERS !