Website Vulnerability Scanner Report

✔ https://avniet.ac.in/

The Light Website Scanner didn't check for critical issues like SQLi, XSS, Command Injection, XXE, etc.
Upgrade to run Deep scans with 40+ tests and detect more vulnerabilities.

Summary

Overall risk level:
High

Risk ratings:

Critical:	0
High:	1
Medium:	0
Low:	6
Info:	1

Scan information:

Start time:	Mar 11, 2026 / 22:04:22 UTC+0530
Finish time:	Mar 11, 2026 / 22:05:09 UTC+0530
Scan duration:	47 sec
Tests performed:	38
Scan status:	Finished

Findings

Vulnerabilities found for php 8.4.8
port 443/tcp

CVE	CVSS	EPSS Score	EPSS Percentile	Summary
CVE-2025-14180	8.2	0.00034	0.09726	In PHP versions 8.1.* before 8.1.34, 8.2.* before 8.2.30, 8.3.* before 8.3.29, 8.4.* before 8.4.16, 8.5.* before 8.5.1 when using the PDO PostgreSQL driver with PDO::ATTR_EMULATE_PREPARES enabled, an invalid character sequence (such as \x99) in a prepared statement parameter may cause the quoting function PQescapeStringConn to return NULL, leading to a null pointer dereference in pdo_parse_params() function. This may lead to crashes (segmentation fault) and affect the availability of the target server.
CVE-2025-14178	6.5	0.00022	0.05631	In PHP versions:8.1.* before 8.1.34, 8.2.* before 8.2.30, 8.3.* before 8.3.29, 8.4.* before 8.4.16, 8.5.* before 8.5.1, a heap buffer overflow occurs in array_merge() when the total element count of packed arrays exceeds 32-bit limits or HT_MAX_SIZE, due to an integer overflow in the precomputation of element counts using zend_hash_num_elements(). This may lead to memory corruption or crashes and affect the integrity and availability of the target server.
CVE-2025-14177	6.3	0.00059	0.18234	In PHP versions:8.1.* before 8.1.34, 8.2.* before 8.2.30, 8.3.* before 8.3.29, 8.4.* before 8.4.16, 8.5.* before 8.5.1, the getimagesize() function may leak uninitialized heap memory into the APPn segments (e.g., APP1) when reading images in multi-chunk mode (such as via php://filter). This occurs due to a bug in php_read_stream_all_chunks() that overwrites the buffer without advancing the pointer, leaving tail bytes uninitialized. This may lead to information disclosure of sensitive heap data and affect the confidentiality of the target server.
CVE-2025-6491	5.9	0.00153	0.35741	In PHP versions:8.1.* before 8.1.33, 8.2.* before 8.2.29, 8.3.* before 8.3.23, 8.4.* before 8.4.10 when parsing XML data in SOAP extensions, overly large (>2Gb) XML namespace prefix may lead to null pointer dereference. This may lead to crashes and affect the availability of the target server.
CVE-2025-1735	5.9	0.00089	0.25205	In PHP versions:8.1.* before 8.1.33, 8.2.* before 8.2.29, 8.3.* before 8.3.23, 8.4.* pgsql and pdo_pgsql escaping functions do not check if the underlying quoting functions returned errors. This could cause crashes if Postgres server rejects the string as invalid.

Details

Risk description:
The risk is that an attacker could search for an appropriate exploit (or create one himself) for any of these vulnerabilities and use it to attack the system.

Since the vulnerabilities were discovered using only version-based testing, the risk level for this finding will not exceed 'high' severity. Critical risks will be assigned to vulnerabilities identified through accurate active testing methods.

Recommendation:

In order to eliminate the risk of these vulnerabilities, we recommend you check the installed software version and upgrade to the latest version.

Classification:

EPSS score : 0.00153
EPSS percentile : 0.35741
CISA KEV: False
CVE : CVE-2025-14180, CVE-2025-14178, CVE-2025-14177, CVE-2025-6491, CVE-2025-1735
CVSS V3 : 8.2
CWE : CWE-1035

Missing security header: Referrer-Policy

port 443/tcp

CONFIRMED

URL	Evidence
https://avniet.ac.in/	Response headers do not include the Referrer-Policy HTTP security header as well as the <meta> tag with name 'referrer' is not present in the response. Request / Response

Details

Risk description:

The risk is that if a user visits a web page (e.g. "http://example.com/pricing/") and clicks on a link from that page going to e.g. "https://www.google.com", the browser will send to Google the full originating URL in the `Referer` header, assuming the Referrer-Policy header is not set. The originating URL could be considered sensitive information and it could be used for user tracking.

Recommendation:

The Referrer-Policy header should be configured on the server side to avoid user tracking and inadvertent information leakage. The value `no-referrer` of this header instructs the browser to omit the Referer header entirely.

References:

https://developer.mozilla.org/en-US/docs/Web/Security/Referer_header:_privacy_and_security_concerns

Classification:

CWE : CWE-693
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Missing security header: Strict-Transport-Security

port 443/tcp

CONFIRMED

URL	Evidence
https://avniet.ac.in/	Response headers do not include the HTTP Strict-Transport-Security header Request / Response

Details

Risk description:

The risk is that lack of this header permits an attacker to force a victim user to initiate a clear-text HTTP connection to the server, thus opening the possibility to eavesdrop on the network traffic and extract sensitive information (e.g. session cookies).

Recommendation:

The Strict-Transport-Security HTTP header should be sent with each HTTPS response. The syntax is as follows:

```
Strict-Transport-Security: max-age=<seconds>[; includeSubDomains]
```

The parameter `max-age` gives the time frame for requirement of HTTPS in seconds and should be chosen quite high, e.g. several months. A value below 7776000 is considered as too low by this scanner check.
The flag `includeSubDomains` defines that the policy applies also for sub domains of the sender of the response.

Classification:

CWE : CWE-693
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Missing security header: Content-Security-Policy

port 443/tcp

CONFIRMED

URL	Evidence
https://avniet.ac.in/	Response does not include the HTTP Content-Security-Policy security header or meta tag Request / Response

Details

Risk description:

The risk is that if the target application is vulnerable to XSS, lack of this header makes it easily exploitable by attackers.

Recommendation:

Configure the Content-Security-Header to be sent with each HTTP response in order to apply the specific policies needed by the application.

References:

https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html
https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Content-Security-Policy

Classification:

CWE : CWE-1021
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Missing security header: X-Content-Type-Options

port 443/tcp

CONFIRMED

URL	Evidence
https://avniet.ac.in/	Response headers do not include the X-Content-Type-Options HTTP security header Request / Response

Details

Risk description:

The risk is that lack of this header could make possible attacks such as Cross-Site Scripting or phishing in Internet Explorer browsers.

Recommendation:

We recommend setting the X-Content-Type-Options header such as `X-Content-Type-Options: nosniff` .

References:

https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options

Classification:

CWE : CWE-693
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Robots.txt file found

port 443/tcp

CONFIRMED

URL
https://avniet.ac.in/robots.txt

Details

Risk description:

There is no particular security risk in having a robots.txt file. However, it's important to note that adding endpoints in it should not be considered a security measure, as this file can be directly accessed and read by anyone.

Recommendation:

We recommend you to manually review the entries from robots.txt and remove the ones which lead to sensitive locations in the website (ex. administration panels, configuration files, etc).

References:
https://www.theregister.co.uk/2015/05/19/robotstxt/

Classification:
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Server software and technology found

port 443/tcp

UNCONFIRMED

Software / Version	Category
Clipboard.js	JavaScript libraries
Elementor 3.35.6	Page builders, WordPress plugins
Essential Addons for Elementor	WordPress plugins
jQuery Migrate 3.4.1	JavaScript libraries
core-js 3.46.0	JavaScript libraries
Google Font API	Font scripts
HTTP/3	Miscellaneous
jQuery 3.7.1	JavaScript libraries
jQuery UI 1.13.3	JavaScript libraries
LiteSpeed	Web servers
Morphext 2.8.6	JavaScript graphics, JavaScript libraries
MySQL	Databases
PHP 8.4.8	Programming languages
Swiper	JavaScript libraries
TablePress	WordPress plugins
Priority Hints	Performance
WordPress 6.9.3	CMS, Blogs
Astra 4.12.3	WordPress themes
ElementsKit	WordPress plugins
Lodash 1.13.7	JavaScript libraries
RSS	Miscellaneous
YouTube	Video players

Details

Risk description:
The risk is that an attacker could use this information to mount specific attacks against the identified software type and version.

Recommendation:
We recommend you to eliminate the information which permits the identification of software platform, technology, server and operating system: HTTP server headers, HTML meta information, etc.

References:
https://owasp.org/www-project-web-security-testing-guide/stable/4-Web_Application_Security_Testing/01-Information_Gathering/02-Fingerprint_Web_Server.html

Classification:

CWE : CWE-200
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Security.txt file is missing

port 443/tcp

CONFIRMED

URL
Missing: https://avniet.ac.in/.well-known/security.txt

Details

Risk description:

There is no particular risk in not having a security.txt file for your server. However, this file is important because it offers a designated channel for reporting vulnerabilities and security issues.

Recommendation:

We recommend you to implement the security.txt file according to the standard, in order to allow researchers or users report any security issues they find, improving the defensive mechanisms of your server.

References:

https://securitytxt.org/

Classification:

CWE : CWE-1188
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration

Scan coverage information

List of tests performed (38)

Port 443

- ✔ Scanned for version-based vulnerabilities of server-side software
- ✔ Scanned for missing HTTP header - Content Security Policy
- ✔ Scanned for missing HTTP header - Referrer
- ✔ Scanned for missing HTTP header - Strict-Transport-Security
- ✔ Scanned for missing HTTP header - X-Content-Type-Options
- ✔ Scanned for robots.txt file
- ✔ Scanned for website technologies
- ✔ Scanned for absence of the security.txt file
- ✔ Scanned for client access policies
- ✔ Scanned for use of untrusted certificates
- ✔ Scanned for enabled HTTP debug methods
- ✔ Scanned for enabled HTTP OPTIONS method
- ✔ Scanned for secure communication
- ✔ Scanned for directory listing
- ✔ Scanned for passwords submitted unencrypted
- ✔ Scanned for error messages
- ✔ Scanned for debug messages
- ✔ Scanned for code comments
- ✔ Scanned for passwords submitted in URLs
- ✔ Scanned for domain too loose set for cookies
- ✔ Scanned for mixed content between HTTP and HTTPS
- ✔ Scanned for cross domain file inclusion
- ✔ Scanned for internal error code
- ✔ Scanned for HttpOnly flag of cookie
- ✔ Scanned for Secure flag of cookie
- ✔ Scanned for login interfaces
- ✔ Scanned for secure password submission
- ✔ Scanned for sensitive data
- ✔ Scanned for unsafe HTTP header Content Security Policy

- ✔ Scanned for OpenAPI files
- ✔ Scanned for file upload
- ✔ Scanned for SQL statement in request parameter
- ✔ Scanned for password returned in later response
- ✔ Scanned for Path Disclosure
- ✔ Scanned for Session Token in URL
- ✔ Scanned for API endpoints
- ✔ Scanned for emails
- ✔ Scanned for missing HTTP header - Rate Limit

Scan parameters

target:	https://avniet.ac.in/
scan_type:	Light
authentication:	False

Scan stats

Unique Injection Points Detected:	400
URLs spidered:	6
Total number of HTTP requests:	15
Average time until a response was received:	756ms