

# Lab 6: Perform RPC, SMB, and FTP Enumeration

---

## Lab Scenario

As an ethical hacker or penetration tester, you should use different enumeration techniques to obtain as much information as possible about the systems in the target network. This lab will demonstrate various techniques for extracting detailed information that can be used to exploit underlying vulnerabilities in target systems, and to launch further attacks.

## Lab Objectives

- Perform SMB enumeration using NetScanTools Pro
- Perform RPC, SMB, and FTP enumeration using Nmap

## Overview of Other Enumeration Techniques

Besides the methods of enumeration covered so far (NetBIOS, SNMP, LDAP, NFS, and DNS), various other techniques such as RPC, SMB, and FTP enumeration can be used to extract detailed network information about the target.

- **RPC Enumeration:** Enumerating RPC endpoints enables vulnerable services on these service ports to be identified
- **SMB Enumeration:** Enumerating SMB services enables banner grabbing, which obtains information such as OS details and versions of services running
- **FTP Enumeration:** Enumerating FTP services yields information about port 21 and any running FTP services; this information can be used to launch various attacks such as FTP bounce, FTP brute force, and packet sniffing

## Task 1: Perform SMB Enumeration using NetScanTools Pro

NetScanTools Pro is an integrated collection of Internet information-gathering and network-troubleshooting utilities for network professionals. The utility makes it easy to find IPv4/IPv6 addresses, hostnames, domain names, email addresses, and URLs related to the target system.

Here, we will use the NetScanTools Pro tool to perform SMB enumeration.

1. ☐ Click [Windows 10](#) to switch to the **Windows 10** machine.
2. ☐ Double-click the **NetScanTools Pro Demo** icon from **Desktop** to launch the tool.

If the **Reminder** window opens, click **Start the DEMO**, and in the **DEMO Version** window, click **Start NetScanTools Pro Demo....**

3.  The **NetScanTools Pro** main window appears, as shown in the screenshot.



Welcome



Welcome



Check for New Version



Blog/Twitter/FB

[Click here to Buy Now!](#)

Welcome to NetScanTools® Pro Demo. This software is a demo, all the tools are 100% function except you cannot save results to a text file, the History Database does not save your interface IP.  
This demo cannot be converted to a full version.

Please select from the Automated or Manual tools or tools grouped by function on the left panel.

The tool icons are color coded:

Red icon tools contact the target, green icon tools listen to network traffic,  
blue icon tools work with your local system and gray icon tools contact third party systems.

Press the F1 key to view the extensive local help including Getting Started Information.

NetScanTools Pro Version 11.86.3

WinPcap/Npcap Compatible Active Network Interfaces:

Ethernet 2 - IPv4: 10.10.10.10 - IPv6 Link Local - fe80::5081:d041:f459:f50d%6 - Microsoft Hyper-V Network Adapter #2

Registration Status: Not registered. Please register.

Maintenance Plan: Expiration Date Not Found.

Automated Tools

Manual Tools (all)

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

4. ☐ In the left pane, under the **Manual Tools (all)** section, scroll down and click the **SMB Scanner** option, as shown in the screenshot.

If a dialog box appears explaining the tool, click **OK**.



Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)

Welcome to NetScanTools® Pro Demo. This software is a demo, all the tools are 100% function except you cannot save results to a text file, the History Database does not save your interface IP.

This demo cannot be converted to a full version.

Please select from the Automated or Manual tools or tools grouped by function on the left panel.

The tool icons are color coded:

Red icon tools contact the target, green icon tools listen to network traffic, blue icon tools work with your local system and gray icon tools contact third party systems.

Press the F1 key to view the extensive local help including Getting Started Information.

NetScanTools Pro Version 11.86.3

WinPcap/Npcap Compatible Active Network Interfaces:


Ethernet 2 - IPv4: 10.10.10.10 - IPv6 Link Local - fe80::8938:b9fe:1e1e:5d84%6 - Microsoft Hyper-V Network Adapter #2

Registration Status: Not registered. Please register.

Maintenance Plan: Expiration Date Not Found.

5. ☐ In the right pane, click the **Start SMB Scanner (external App)** button.

If the **Demo Version Message** pop-up appears, click **OK**. In the **Reminder** window, click **Start the DEMO**.



Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)

The SMB Scanner scans a list of IPv4 addresses or hostnames and determines which versions of SMB (Server Message Block) are running on the target.

Start SMB Scanner (external App)


IPv4

IPv6

[Jump To Automated](#)

[Reports](#)

☐ Add to Favorites

6.  The **SMB Scanner** window appears; click the **Edit Target List** button.





Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)[Jump To Automated](#)

The SMB Scanner scans a list of IPv4 addresses or hostnames and determines which

NetScanTools® SMB Scanner v1.2.3 - DEMO

Get SMB Versions

Stop

Edit Target List

Shares

☒ Do Share Check☒ Edit Share Login Credentials☒ Delete Login Credentials on Exit☒ Delete Share Results on Exit

Connection Timeout Settings (milliseconds)

Connect

5000

Receive

5000



Set Defaults

	IP Address	Latency	MAC Address	NetBIOS Name	DNS Name	SMB 1	SMB 2.0.2	SMB 2.1	SMB 3
	<all>		<all>		<all>		<all>	<all>	<all>

7. ☐ The **Edit Target List** window appears. In the **Hostname or IPv4 Address** field, enter the target IP address (**10.10.10.19**, in this example). Click the **Add to List** button to add the target IP address to **Target List**.
8. ☐ Similarly, add another target IP address (**10.10.10.16**, in this example) to **Target List** and click **OK**.

In this task, we are targeting the **Windows Server 2019** (10.10.10.19) and **Windows Server 2016** (10.10.10.16) machines.



Welcome

Automated Tools

Manual Tools (all)

Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

Click here to Buy Now!

The SMB Scanner scans a list of IPv4 addresses or hostnames and determines which

Jump To Automated

NetScanTools® SMB Scanner v1.2.3 - DEMO

Get SMB Versions Stop Shares Connection Timeout Settings (milliseconds)

**Edit Target List**

Create/Maintain a list of Target Systems using this Editor.

Hostname or IPv4 Address  
10.10.10.16 **Add to List**

**1** Import from File **2** Export to File

Import hostnames or IP addresses from a text file. One per line.

Export the List to a text file.

**3** OK Cancel

Target List

Target Name
10.10.10.19
10.10.10.16

Up Down Delete Edit Selection Clear List

IPv4 Address Range Generator

Starting IPv4 Address  
10 , 10 , 10 , 1 P

Ending IPv4 Address  
10 , 10 , 10 , 254 P

Generate IP Range

9.  Now, click **Edit Share Login Credentials** to add credentials to access the target systems.



Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)

The SMB Scanner scans a list of IPv4 addresses or hostnames and determines which

[Jump To Automated](#)

NetScanTools® SMB Scanner v1.2.3 - DEMO



Get SMB Versions



Stop



Edit Target List

Shares

☒ Do Share Check☒ Edit Share Login Credentials☒ Delete Login Credentials on Exit☒ Delete Share Results on Exit

Connection Timeout Settings (milliseconds)

Connect

5000

Receive

5000



Set Defaults

	IP Address	Latency	MAC Address	NetBIOS Name	DNS Name	SMB 1	SMB 2.0.2	SMB 2.1	SMB 3
	<all>	<all>	<all>	<all>	<all>	<all>	<all>	<all>	<all>
1	10.10.10.19								
2	10.10.10.16								

10. ☐ The **Login Credentials List for Share Checking** window appears. Enter **Administrator** and **Pa\$\$w0rd** in the **Username** and **Password** fields, respectively. Click **Add to List** to add the credentials to the list and click **OK**.

In this task, we are using the login credentials for the **Windows Server 2019** and **Windows Server 2016** machines to understand the tool. In reality, attackers may add a list of login credentials by which they can log in to the target machines and obtain the required SMB share information.



Welcome

Automated Tools

Manual Tools (all)

Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

Click here to Buy Now!

Jump To Automated

The SMB Scanner scans a list of IP addresses or hostnames and determines which

NetScanTools® SMB Scanner v1.2.3 - DEMO

Get SMB Versions Stop Shares Connection Timeout Settings (milliseconds)

Login Credentials List for Share Checking

Username

Administrator

Password

Pa\$\$w0rd

Add to List

OK

Cancel

Edit Entry

Up

Down

Delete

Edit Selection

Clear List

Username

Password

	IP Address	Latency	MAC Address
<all>	<all>	<all>	<all>
1	10.10.10.19		
2	10.10.10.16		

1	SMB 3.0.2
<all>	<all>

11. ☐ In the **SMB Scanner** window, click the **Get SMB Versions** button.
12. ☐ Once the scan is complete, the result appears, displaying information such as the NetBIOS Name, DNS Name, SMB versions, and Shares for each target IP address.





Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)

The SMB Scanner scans a list of IPv4 addresses or hostnames and determines which

[Jump To Automated](#)

## NetScanTools® SMB Scanner v1.2.3 - DEMO

Get SMB Versions

Stop

Complete - 100%

Edit Target List

Shares

☒ Do Share Check☒ Edit Share Login Credentials☒ Delete Login Credentials on Exit☒ Delete Share Results on Exit

Connection Timeout Settings (milliseconds)

Connect

5000


Receive

5000



Set Defaults

	IP Address	Latency	MAC Address	NetBIOS Name	DNS Name	SMB 1	SMB 2.0.2	SMB 2.1	SMB 3.0
	<all>	<all>	<all>	<all>	<all>	<all>	<all>	<all>	<all>
1	10.10.10.19	1 ms	02:15:5D:11:12:C5	SERVER2019	www.goodshopping....	No	Yes	Yes	Yes
2	10.10.10.16	1 ms	02:15:5D:11:12:C6	SERVER2016	SERVER2016	Yes	Yes	Yes	Yes

13.  Right-click on any of the machines (in this example, we will use **10.10.10.19**) and click **View Shares** from the available options.



Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)

The SMB Scanner scans a list of IPv4 addresses or hostnames and determines which

[Jump To Automated](#)

NetScanTools® SMB Scanner v1.2.3 - DEMO



Get SMB Versions



Stop

Complete - 100%



Edit Target List

Shares

☒ Do Share Check☒ Edit Share Login Credentials☒ Delete Login Credentials on Exit☒ Delete Share Results on Exit

Connection Timeout Settings (milliseconds)

Connect

5000

Receive

5000



Set Defaults

	IP Address	Latency	MAC Address	NetBIOS Name	DNS Name	SMB 1	SMB 2.0.2	SMB 2.1	SMB 3
	<all>	<all>	<all>	<all>	<all>	<all>	<all>	<all>	<all>
1	10.10.10.19	1 ms	02:15:5D:11:12:C5	SERVER2019	www.goodshopping....	No	Yes	Yes	Yes
2	10.10.10.16			SERVER2016	SERVER2016	Yes	Yes	Yes	Yes

Copy

Copy as HTML

Clear


Print Grid

View Shares

Export as Text

Export as HTML

Select All

14.  The **Shares for 10.10.10.19** window appears, displaying detailed information about shared files such as Share Name, Type, Remark, Path, Permissions, and Credentials Used.



Welcome

Automated Tools

Manual Tools (all)



Routing Table - IPv6



\*nix RPC Info



Service Lookup



Simple Services



SMB Scanner



SMTP Server Tests



SNMP - Core



SNMP - Advanced



SSL Certificate Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

[Click here to Buy Now!](#)

The SMB Scanner scans a list of IP/dns addresses or hostnames and determines which

[Jump To Automated](#)

NetScanTools® SMB Scanner v1.2.3 - DEMO

[Get SMB Versions](#) [Stop](#) [Shares](#) [Connection Timeout Settings \(milliseconds\)](#)

Shares for 10.10.10.19

Share Name	Type	Remark	Path	Permissions	Credentials Used
Users	Disk Drive Share		C:\Users	N/A	Administrator/Password
ADMIN\$	Disk Drive Share, Special Share	Remote Admin	C:\Windows	N/A	Administrator/Password
C\$	Disk Drive Share, Special Share	Default share	C:\	N/A	Administrator/Password
IPC\$	Disk Drive Share, Special Share	Remote IPC		N/A	Administrator/Password

[Export to Text File](#)

15. ☐ You can view the details of the shared files for the target IP address **10.10.10.16** in the same way.
  16. ☐ This concludes the demonstration of performing SMB enumeration on the target systems using NetScanTools Pro.
  17. ☐ Close all open windows and document all the acquired information.
- 

## Task 2: Perform RPC, SMB, and FTP Enumeration using Nmap

Nmap is a utility used for network discovery, network administration, and security auditing. It is also used to perform tasks such as network inventory, service upgrade schedule management, and host or service uptime monitoring.

Here, we will use Nmap to carry out RPC, SMB, and FTP enumeration.

Before starting this lab, we must configure the FTP service in the target machine (**Windows Server 2019**). To do so, follow **Steps 1-10**.

1. ☐ Click [Windows Server 2019](#) to switch to the **Windows Server 2019** machine.
2. ☐ Click on the **File Explorer** icon at the bottom of **Desktop**. In the **File Explorer** window, right-click on **Local Disk (C:)** and click **New --> Folder**.

← → ↕ ↑ > This PC > Local Disk (C:) >

★ Quick access

- Desktop
- Downloads
- Documents
- Pictures
- DVD Drive (D:) SSS\_
- System32

This PC

- 3D Objects
- Desktop
- Documents
- Downloads
- Music
- Pictures
- Videos
- Local Disk (C:)
- DVD Drive (D:) SSS\_
- CEH-Tools (\\WIND
- Network

Name	Date modified	Type	Size
\$Recycle.Bin	9/15/2018 12:19 AM	File folder	
Documents and Settings	4/14/2020 9:25 PM	File folder	
inetpub	4/14/2020 11:16 PM	File folder	
PerfLogs	9/15/2018 12:19 AM	File folder	
Program Files	5/1/2020 5:37 AM	File folder	
Program Files (x86)	4/30/2020 11:25 PM	File folder	
ProgramData		File folder	
Recovery		File folder	
SQLServer2017Media		File folder	
System Volume Information		File folder	
Users		File folder	
Windows		File folder	
pagefile.sys		System file	720,896 KB

- View >
- Sort by >
- Group by >
- Refresh


- Paste
- Paste shortcut

- Give access to >

- New >

- Properties

- Folder
- Shortcut
- Bitmap image
- Contact
- WinRAR archive
- Rich Text Document
- Text Document
- WinRAR ZIP archive

3.  A **New Folder** appears. Rename it to **FTP-Site Data**, as shown in the screenshot.



← → ↕ ↑ This PC > Local Disk (C:) >


★ Quick access

- Desktop
- Downloads
- Documents
- Pictures
- DVD Drive (D:) SSS\_
- System32

This PC

- 3D Objects
- Desktop
- Documents
- Downloads
- Music
- Pictures
- Videos
- Local Disk (C:)
- DVD Drive (D:) SSS\_
- CEH-Tools (\\WIND
- Network

Name	Date modified	Type	Size
\$Recycle.Bin	9/15/2018 12:19 AM	File folder	
Documents and Settings	4/14/2020 9:25 PM	File folder	
inetpub	4/14/2020 11:16 PM	File folder	
PerfLogs	9/15/2018 12:19 AM	File folder	
Program Files	5/1/2020 5:37 AM	File folder	
Program Files (x86)	4/30/2020 11:25 PM	File folder	
ProgramData	4/15/2020 1:55 AM	File folder	
Recovery	4/14/2020 9:25 PM	File folder	
SQLServer2017Media	4/15/2020 12:35 AM	File folder	
System Volume Information	4/14/2020 9:34 PM	File folder	
Users	4/14/2020 11:16 PM	File folder	
Windows	4/15/2020 1:43 AM	File folder	
pagefile.sys	6/9/2020 1:40 AM	System file	720,896 KB
FTP-Site Data	6/9/2020 2:41 AM	File folder	

4.  Close the window and click on the **Type here to search** icon at the bottom of the **Desktop**. Type **iis**. In the search results, click on **Internet Information Services Manager (IIS) Manager**, as shown in the screenshot.



Recycle Bin



OWASP ZAP  
2.8.0



desktop.ini



Filters



### Best match



Internet Information Services (IIS) Manager  
Desktop app

### Apps



Internet Information Services (IIS) 6.0 Manager

5. ☐ In the **Internet Information Services (IIS) Manager** window, click to expand **SERVER2019 (SERVER2019\Administrator)** in the left pane. Right-click **Sites**, and then click **Add FTP Site....**

### Connections



- Start Page
- SERVER2019 (SERVER2019\Administrative)
  - Application Pools
  - Sites

- Add Website...
- Refresh
- Add FTP Site...
- Switch to Content View



## SERVER2019 Home

Filter:



Go



Show All

Group by:

Area



### ASP.NET



.NET  
Compilation



.NET Error  
Pages



.NET  
Globalization



.NET Trust  
Levels



Application  
Settings



Connection  
Strings



Machine Key



Pages and  
Controls



Providers



Session State



FTP  
Authentic...



FTP  
Authorizat...



FTP  
Directory  
Browsing



FTP  
Firewall  
Support



FTP  
IP  
Address a...



FTP  
Logging



FTP  
Logon  
Attempt R...



FTP  
Messages



FTP  
Request  
Filtering



FTP  
SSL  
Settings



FTP  
User  
Isolation

### IIS



Authentic...



Compression



Default  
Document



Directory  
Browsing



Error Pages



Failed  
Request Tra...



Handler  
Mappings



HTTP  
Redirect



HTTP  
Respon...



ISAPI and  
CGI Restri...



ISAPI Filters



Modules



Output  
Caching



Request  
Filtering



Server  
Certificates



Worker  
Processes

### Management



Configurat...  
Editor



Feature  
Delegation




Shared  
Configurat...

6. ☐ In the **Add FTP Site** window, type **CEH.com** in the **FTP site name** field. In the **Physical path** field, click on the icon. In the **Browse For Folder** window, click **Local Disk (C:)** and **FTP-Site Data**, and then click **OK**.

File View Help

## Connections



- Start Page
- SERVER2019 (SERVER2019\Administrators)
- Application Pools
- Sites



## SERVER2019 Home

Filter:

Go

Show All

Group by: Area

## ASP.NET

.NET  
Authorizat....NET  
Compilation

## FTP

FTP  
Authentic...FTP  
Authorizat...

## IIS



Authentic...



Compression



Modules

Output  
Caching

## Management

Configurat...  
EditorFeature  
Delegation

Add FTP Site



## Site Information

FTP site name:

CEH.com

Content Directory

Physical path:

## Browse For Folder

Select the physical path for the new FTP site.

- Local Disk (C:)
  - \$Recycle.Bin
  - Documents and Settings
  - FTP-Site Data
  - inetpub
  - PerfLogs
  - Program Files
  - Program Files (x86)

Make New Folder

OK

Cancel

Previous

Next

Finish

Cancel

7. ☐ In the **Add FTP Site** window, check the entered details and click **Next**.



Connections



- Start Page
- SERVER2019 (SERVER2019\Ad...
- Application Pools
- Sites



SERVER2019 Home

Filter:

Go



Show All

Group by:

Area



ASP.NET



.NET  
Authorizat...



.NET  
Compilation

FTP



FTP  
Authentic...



FTP  
Authorizat...

IIS



Authentic...



Compression



Modules



Output  
Caching

Management



Configurat...  
Editor



Feature  
Delegation

Add FTP Site



Site Information

FTP site name:

CEH.com

Content Directory

Physical path:

C:\FTP-Site Data




Previous

Next

Finish

Cancel

8.  The **Binding and SSL Settings** wizard appears. Under the **Binding** section, in the **IP Address** field, click the drop-down icon and select **10.10.10.19**. Under the **SSL** section, select the **No SSL** radio button and click **Next**.

## Connections



- Start Page
- SERVER2019 (SERVER2019\Administrative)
  - Application Pools
  - Sites



## SERVER2019 Home

Filter:



Go



Show All

Group by:

Area



## ASP.NET

.NET  
Authorizat....NET  
Compilation

## FTP

FTP  
Authentic...FTP  
Authorizat...

## IIS



Authentic...



Compression

## Modules



Modules

Output  
Caching

## Management

Configurat...  
EditorFeature  
Delegation

## Add FTP Site



## Binding and SSL Settings

## Binding

IP Address:

10.10.10.19

Port:

21

☐ Enable Virtual Host Names:

Virtual Host (example: ftp.contoso.com):

☒ Start FTP site automatically

## SSL

☒ No SSL☐ Allow SSL☐ Require SSL

SSL Certificate:

Not Selected

Select...

View...

Previous

Next

Finish

Cancel

9. ☐ The **Authentication and Authorization Information** wizard appears. In the **Allow access to** section, select **All users** from the drop-down list. In the **Permissions** section, select both the **Read** and **Write** options and click **Finish**.

Connections



- Start Page
- SERVER2019 (SERVER2019\Ad...
- Application Pools
- Sites



SERVER2019 Home

Filter:

Go



Show All

Group by:

Area



ASP.NET



.NET  
Authorizat...



.NET  
Compilation

FTP



FTP  
Authentic...



FTP  
Authorizat...

IIS



Authentic...



Compression



Modules



Output  
Caching

Management



Configurat...  
Editor



Feature  
Delegation

Add FTP Site



Authentication and Authorization Information

Authentication

☐ Anonymous

☐ Basic

Authorization

Allow access to:

All users

Permissions

☒ Read


☒ Write

Previous


Next

Finish

Cancel

10.  The **Internet Information Services (IIS) Manager** window appears with a newly added FTP site (**CEH.com**) in the left pane. Click the **Site** node in the left pane and note that the **Status** is **Started (ftp)**, as shown in the screenshot.

## Connections



- Start Page
- SERVER2019 (SERVER2019\Ad...
- Application Pools
- Sites
  - CEH.com
  - Default Web Site
  - GoodShopping
  - MovieScope

## Sites

Filter:  Go  Group by: No Grouping

Name	ID	Status	Binding	Path
CEH.com	4	Started (ftp)	10.10.10.19:21: (ftp)	C:\FTP-Site Data
Default Web Site	1	Started (ht...	*:80 (http),808:* (net.tcp),localhos...	%SystemDrive%\inetpub\wwwroot
GoodShopping	2	Started (ht...	www.goodshopping.com on 10.1...	C:\inetpub\wwwroot\GoodShopping
MovieScope	3	Started (ht...	www.moviescope.com on 10.10.1...	C:\inetpub\wwwroot\moviescope

11. ☐ Close all windows.
12. ☐ Click [Parrot Security](#) to switch to the **Parrot Security** machine.
13. ☐ Click the **MATE Terminal** icon at the top of the **Desktop** window to open a **Terminal** window.





Parrot



CEHv11 Module 16  
Hacking Wireless  
Networks



attacker's Home



Security\_Script.-  
html



README.license



Trash



CEHv11 Module 13  
Hacking Web  
Servers



CEHv11 Module 14  
Hacking Web  
Applications



14. ☐ A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
15. ☐ In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

The password that you type will not be visible.

16. ☐ Now, type **cd** and press **Enter** to jump to the root directory.

File Edit View Search Terminal Help

```
[attacker@parrot]-[~] Module 16  
$sudo su  
[sudo] password for attacker:  
[root@parrot]-[/home/attacker]  
#cd  
[root@parrot]-[~]  
#
```

README.license

Trash

CEHv11 Module 13  
Hacking Web  
Servers

CEHv11 Module 14  
Hacking Web  
Applications

17. ☐ In the **Parrot Terminal** window, type **nmap -p 21 [Target IP Address]** (in this case, **10.10.10.19**) and press **Enter**.
18. ☐ The scan result appears, indicating that port 21 is open and the FTP service is running on it, as shown in the screenshot.

File Edit View Search Terminal Help

`[attacker@parrot]-[~] Module 16``$sudo su``[sudo] password for attacker:``[root@parrot]-[/home/attacker]``#cd``[root@parrot]-[~]``#nmap -p 21 10.10.10.19``Starting Nmap 7.80 ( https://nmap.org ) at 2020-08-21 02:46 EDT``Nmap scan report for www.goodshopping.com (10.10.10.19)``Host is up (0.00031s latency).``README license`

PORT	STATE	SERVICE
------	-------	---------

21/tcp	open	ftp
--------	------	-----

`MAC Address: 02:15:5D:08:11:74 (Unknown)``Trash``Nmap done: 1 IP address (1 host up) scanned in 0.19 seconds``[root@parrot]-[~]``#``CEHv11 Module 13``Hacking Web  
Servers``CEHv11 Module 14``Hacking Web  
Applications`

19. ☐ In the terminal window, type **nmap -T4 -A [Target IP Address]** (in this example, the target IP address is **10.10.10.19**) and press **Enter**.

In this command, **-T4** specifies the timing template (the number can be 0-5) and **-A** specifies aggressive scan. The aggressive scan option supports OS detection (-O), version scanning (-sV), script scanning (-sC), and traceroute (--traceroute).



File Edit View Search Terminal Help

```
[root@parrot]-[~]
#nmap -T4 -A 10.10.10.19
```

Starting Nmap 7.80 ( <https://nmap.org> ) at 2020-08-21 02:47 EDT

Nmap scan report for www.goodshopping.com (10.10.10.19)

Host is up (0.00096s latency).

Not shown: 988 filtered ports

PORT	STATE	SERVICE	VERSION
21/tcp	open	ftp	Microsoft ftpd

| ftp-syst:

|\_ SYST: Windows\_NT

80/tcp	open	http	Microsoft IIS httpd 10.0
--------	------	------	--------------------------

| http-methods:

|\_ Potentially risky methods: TRACE

|\_ http-server-header: Microsoft-IIS/10.0

|\_ http-title: GoodShopping

111/tcp	open	rpcbind	2-4 (RPC #100000)
---------	------	---------	-------------------

| rpcinfo:

program	version	port/proto	service
100000	2,3,4	111/tcp	rpcbind
100000	2,3,4	111/tcp6	rpcbind
100000	2,3,4	111/udp	rpcbind
100000	2,3,4	111/udp6	rpcbind
100003	2,3	2049/udp	nfs
100003	2,3	2049/udp6	nfs
100003	2,3,4	2049/tcp	nfs
100003	2,3,4	2049/tcp6	nfs
100005	1,2,3	2049/tcp	mountd
100005	1,2,3	2049/tcp6	mountd
100005	1,2,3	2049/udp	mountd
100005	1,2,3	2049/udp6	mountd

20. ☐ The scan result appears, displaying that port 80 is open, and giving detailed information about the services running on it, along with their versions.



File Edit View Search Terminal Help

```
|_ http-server-header: Microsoft-IIS/10.0
|_ http-title: GoodShopping
111/tcp open  rpcbind 2-4 (RPC #100000)
| rpcinfo:
|   program version    port/proto  service
|   100000  2,3,4      111/tcp    rpcbind
|   100000  2,3,4      111/tcp6   rpcbind
|   100000  2,3,4      111/udp    rpcbind
|   100000  2,3,4      111/udp6   rpcbind
|   100003  2,3        2049/udp   nfs
|   100003  2,3        2049/udp6  nfs
|   100003  2,3,4      2049/tcp   nfs
|   100003  2,3,4      2049/tcp6  nfs
|   100005  1,2,3      2049/tcp   mountd
|   100005  1,2,3      2049/tcp6  mountd
|   100005  1,2,3      2049/udp   mountd
|   100005  1,2,3      2049/udp6  mountd
|   100021  1,2,3,4    2049/tcp   nlockmgr
|   100021  1,2,3,4    2049/tcp6  nlockmgr
|   100021  1,2,3,4    2049/udp   nlockmgr
|   100021  1,2,3,4    2049/udp6  nlockmgr
|   100024  1          2049/tcp   status
|   100024  1          2049/tcp6  status
|   100024  1          2049/udp   status
|   100024  1          2049/udp6  status
135/tcp open  msrpc      Microsoft Windows RPC
139/tcp open  netbios-ssn Microsoft Windows netbios-ssn
445/tcp open  microsoft-ds?
1801/tcp open  msmq?
2049/tcp open  mountd     1-3 (RPC #100005)
```

File Edit View Search Terminal Help

```
2103/tcp open  msrpc Microsoft Windows RPC
2105/tcp open  msrpc Microsoft Windows RPC
2107/tcp open  msrpc Microsoft Windows RPC
3389/tcp open  ms-wbt-server Microsoft Terminal Services
```

```
| rdp-ntlm-info:
```

```
|   Target_Name: SERVER2019
|   NetBIOS_Domain_Name: SERVER2019
|   NetBIOS_Computer_Name: SERVER2019
|   DNS_Domain_Name: Server2019
|   DNS_Computer_Name: Server2019
|   Product_Version: 10.0.17763
|   System_Time: 2020-08-21T06:48:32+00:00
```

```
| ssl-cert: Subject: commonName=Server2019
```

```
| Not valid before: 2020-04-14T04:31:46
```

```
| Not valid after: 2020-10-14T04:31:46
```

```
| ssl-date: 2020-08-21T06:49:12+00:00; +1s from scanner time.
```

```
MAC Address: 02:15:5D:08:11:74 (Unknown)
```

```
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
```

```
OS fingerprint not ideal because: Missing a closed TCP port so results incomplete
```

```
No OS matches for host
```

```
Network Distance: 1 hop
```

```
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows
```

```
Host script results:
```

```
|_ nbstat: NetBIOS name: SERVER2019, NetBIOS user: <unknown>, NetBIOS MAC: 02:15:5d:08:11:74 (unknown)
```

```
|_ smb2-security-mode:
```

```
|   2.02: Message signing
```

```
|_ Message signing enabled but not required
```

```
|_ smb2-time:
```

```
|   date: 2020-08-21T06:48:32
```

21. ☐ Click the **MATE Terminal** icon at the top of the **Desktop** window to open a new **Terminal** window.
22. ☐ A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
23. ☐ In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

The password that you type will not be visible.

24. ☐ Now, type **cd** and press **Enter** to jump to the root directory.

```

[attacker@parrot]-[~] Microsoft Windows RPC
[attacker@parrot]-[~] $sudo su marpc Microsoft Windows RPC
[sudo] password for attacker: Microsoft Windows RPC
[root@parrot]-[/home/attacker] Microsoft Windows RPC
[root@parrot]-[/home/attacker] #cd /tmp

```

```
└─[root@parrot]-[~]RVER2019
```

```
# BIOS Domain Name: SERVER0012
```

25. ☐ In the terminal window, type **nmap -p [Target Port] -A [Target IP Address]** (in this example, the target port is **445** and the target IP address is **10.10.10.19**) and press **Enter**.

In this command, **-p** specifies the port to be scanned, and **-A** specifies aggressive scan. The aggressive scan option supports OS detection (**-O**), version scanning (**-sV**), script scanning (**-sC**), and traceroute (**--traceroute**).

26. ☐ The scan result appears, displaying that port 445 is open, and giving detailed information under the **Host script results** section about the running SMB, as shown in the screenshot.



File Edit View Search Terminal Help

```
[root@parrot]~# nmap -p 445 -A 10.10.10.19
Starting Nmap 7.80 ( https://nmap.org ) at 2020-08-21 03:03 EDT
Nmap scan report for www.goodshopping.com (10.10.10.19)
Host is up (0.00037s latency).
Target Name: SERVER2019
PORT      STATE SERVICE      VERSION
445/tcp   open  microsoft-ds?
MAC Address: 02:15:5D:08:11:74 (Unknown)
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
OS fingerprint not ideal because: Missing a closed TCP port so results incomplete
No OS matches for host
Network Distance: 1 hop
Host script results:
|_ nbstat: NetBIOS name: SERVER2019, NetBIOS user: <unknown>, NetBIOS MAC: 02:15:5d:08:11:74 (unknown)
|_ smb2-security-mode: 08:11:74 (Unknown)
|_ 2.02: Message signing enabled but not required
|_ smb2-time:
|_ date: 2020-08-21T07:03:35
|_ start_date: N/A
TRACEROUTE
HOP RTT ADDRESS
1 0.37 ms www.goodshopping.com (10.10.10.19)
OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 50.89 seconds
[root@parrot]~#
```

27. ☐ In the terminal window, type **nmap -p [Target Port] -A [Target IP Address]** (in this example, the target port is **21** and target IP address is **10.10.10.19**) and press **Enter**.

In this command, **-p** specifies the port to be scanned and **-A** specifies aggressive scan. The aggressive scan option supports OS detection (**-O**), version scanning (**-sV**), script scanning (**-sC**), and traceroute (**--traceroute**).

28. ☐ The scan result appears, displaying that port 21 is open, and giving traceroute information, as shown in the screenshot.

```
Applications Places System Parrot Terminal
File Edit View Search Terminal Help
HOP RTT op ADDRESS Microsoft Windows RPC
1 0.37 ms www.goodshopping.com (10.10.10.19) RPC
2107/tcp open http Microsoft Windows RPC
OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 50.89 seconds
[root@parrot]-[~]# nmap -p 21 -A 10.10.10.19
Starting Nmap 7.80 ( https://nmap.org ) at 2020-08-21 03:07 EDT
Nmap scan report for www.goodshopping.com (10.10.10.19)
Host is up (0.00049s latency).
|_ Product Version: 10.0.17763
PORT      STATE SERVICE VERSION
21/tcp    open  ftp      Microsoft ftpd 6.0.2600.5512
|_ ftp-syst: before: 2020-08-14T04:31:46
|_ N_SYST: Windows_NT 6.0.2600-10-14T04:31:46
MAC Address: 02:15:5D:08:11:74 (Unknown)
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
OS fingerprint not ideal because: Missing a closed TCP port so results incomplete
No OS matches for host because: Missing a closed TCP port so results incomplete
Network Distance: 1 hop
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows
TRACEROUTE
HOP RTT op ADDRESS
1 0.49 ms www.goodshopping.com (10.10.10.19)
|_ smb2-security-mode:
OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 4.84 seconds
[root@parrot]-[~]#
```



29. ☐ This concludes the demonstration of performing RPC, SMB, and FTP enumeration using Nmap.
30. ☐ Close all open windows and document all the acquired information.