

What is CI and CD?

Continuous Integration

Continuous Integration (CI) is a development practice where developers frequently integrate their code changes into a shared repository, preferably several times a day. Each integration is automatically verified by

1. Building the project and
2. Running automated tests.

This process allows teams to detect problems early, improve software quality, and reduce the time it takes to validate and release new software updates.

Continuous Deployment

As the name suggests, deploying your code `continuously` to various environments (dev/stage/prod)

Continuous Deployment in Github

We'll be deploying a next.js app to EC2 servers via Docker




You don't really need Docker here, since it's deploying on a simple EC2 server.

If you deploy to

1. GCP App runner
2. ECS
3. Kubernetes

then it makes more sense to deploy a `dockerised`

Architecture diagram



Last step keeps changing based on where you're pushing your image

Monorepo we're dealing with today

<https://github.com/100xdevs-cohort-2/week-18-2-ci-cd>

This monorepo has 3 apps inside -

1. bank-webhook
2. merchant-app
3. user-app

We'll be deploying all three to the same ec2 instance

How to create a CI/CD pipeline?

For Github, you can add all your pipelines to `.github/workflows`

For eg - <https://github.com/code100x/cms/blob/main/.github/workflows/lint.yml>

```

1  name: Linting and formatting on PR
2  on:
3    pull_request:
4      branches:
5        - '**'
6
7  jobs:
8    Continuous-Integration:
9      name: Performs linting, formatting on the application
10     runs-on: ubuntu-latest
11     steps:
12       - name: Checkout the Repository
13         uses: actions/checkout@v3
14       - name: Install Dependencies
15         run: npm install --legacy-peer-deps
16       - name: Run linting check
17         run: npm run lint:check
18       - name: Check formatting
19         run: npm run format:fix

```

Anytime a PR comes on any branch, run the following jobs

Name of the job

Name of the job
Machine to run the job on

Clone the repo on the machine

Install dependencies

Runs lint checks, if it fails, the workflow fails

CD pipelines look like this finally -

Require approval from specific reviewers before merging
[Rulesets](#) ensure specific people approve pull requests before they're merged. Add rule ×

✓ All checks have passed
1 successful check Hide all checks

✓ Linting and formatting on PR / Performs linting, formatting on the application (pull_request) S... Details


✓ This branch has no conflicts with the base branch
Merging can be performed automatically.

Merge pull request ▼ You can also [open this in GitHub Desktop](#) or view [command line instructions](#).

Hint - Use <https://onlineyamltools.com/convert-yaml-to-json> to see the pipeline in json

Step 1 - Create the CI pipeline

Make sure that whenever someone tries to create a PR, we build the project and make sure that it builds as expected



Lets add a build pipeline for our repo

Anytime a user creates a PR, we need to run `npm run build` and only if it succeeds should the workflow succeed

- Fork the main repo - <https://github.com/100xdevs-cohort-2/week-18-2-ci-cd>
- Add `.github/workflows/build.yml` in the root folder
- Create the workflow

```
name: Build on PR

on:
  pull_request:
    branches:
      - master


jobs:
  build:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v3
      - name: Use Node.js
        uses: actions/setup-node@v3
        with:
          node-version: '20'

      - name: Install Dependencies
        run: npm install

      - name: Run Build
        run: npm run build
```

[Copy](#)

- Push this to master branch
- Create a new branch with some minimal changes and create a PR from it
- You should see the workflow run



Let's add a deploy step

- Create dockerfiles for the `apps` you have
- Create `docker/Dockerfile.user`

```
FROM node:20.12.0-alpine3.19

WORKDIR /usr/src/app

COPY package.json package-lock.json turbo.json tsconfig.json ./

COPY apps ./apps
COPY packages ./packages

# Install dependencies
RUN npm install

# Can you add a script to the global package.json that does this?
RUN cd packages/db && npx prisma generate && cd ../../

# Can you filter the build down to just one app?
RUN npm run build

CMD ["npm", "run", "start-user-app"]
```

Copy

- Add `start-user-app` script to the root `package.json`

```
"start-user-app": "cd ./apps/user-app && npm run start"
```

Copy



You don't really need to build every app for every dockerfile. Can you change the build command so that only a single app is built for each dockerfile?

```
[5/8] COPY packages-1/packages-1
=> [6/8] RUN npm install
=> [7/8] RUN npm run build
=> => # docs:build: - Environments: .env
=> => # docs:build:
=> => # web:build: ▲ Next.js 14.1.4
=> => # web:build:
=> => # web:build: Creating an optimized production build ...
=> => # docs:build: Creating an optimized production build ...
```

- Create the CD pipeline that
 - Clones the repo
 - Builds the docker image
 - Pushes the docker image

```
name: Build and Deploy to Docker Hub

on:
  push:
```

```
branches:
  - master


jobs:
  build-and-push:
    runs-on: ubuntu-latest
    steps:
      - name: Check Out Repo
        uses: actions/checkout@v2




      - name: Log in to Docker Hub
        uses: docker/login-action@v1
        with:
          username: ${ secrets.DOCKER_USERNAME }
          password: ${ secrets.DOCKER_PASSWORD }



      - name: Build and Push Docker image
        uses: docker/build-push-action@v2
        with:
          context: .
          file: ./Dockerfile
          push: true
          tags: 100xdevs/web-app:latest # Replace with your Docker Hub username and repository name



      - name: Verify Pushed Image
        run: docker pull 100xdevs/web-app:latest # Replace with your Docker Hub username and repository name
```


- Make sure to add the `dockerhub` secrets to `github secrets` of the repo (DOCKER_USERNAME, DOCKER_PASSWORD)
- You should see a workflow running

 Protect this branch from force pushing or deletion, or require status checks before merging. [View documentation.](#)


 master  3 Branches  0 Tags

 **hkirat** Added deploy step 

 `.github/workflows`  1 queued check Added deploy step



Check dockerhub to ensure the image has indeed reached there



Let's pull the docker image

Ref - <https://github.com/appleboy/ssh-action>

- Create an ec2 server
 - Download its keypair file
 - Allow http/https traffic
 - Ubuntu base image
- Download docker on the machine
 - <https://docs.docker.com/engine/install/ubuntu/>
 - `sudo docker run hello-world`
- Update workflow to pull the latest image on the ec2 machine

```
name: Build and Deploy to Docker Hub

on:
  push:
    branches:
      - master # Adjusted to trigger on pushes to master
```

Copy

```

jobs:
  build-and-push:
    runs-on: ubuntu-latest
    steps:
      - name: Check Out Repo
        uses: actions/checkout@v2

      - name: Prepare Dockerfile
        run: cp ./docker/Dockerfile.user ./Dockerfile

      - name: Log in to Docker Hub
        uses: docker/login-action@v1
        with:
          username: ${ secrets.DOCKER_USERNAME }
          password: ${ secrets.DOCKER_PASSWORD }

      - name: Build and Push Docker image
        uses: docker/build-push-action@v2
        with:
          context: .
          file: ./Dockerfile
          push: true
          tags: 100xdevs/web-app:latest

      - name: Verify Pushed Image
        run: docker pull 100xdevs/web-app:latest

      - name: Deploy to EC2
        uses: appleboy/ssh-action@master
        with:
          host: ${ secrets.SSH_HOST }
          username: ${ secrets.SSH_USERNAME }
          key: ${ secrets.SSH_KEY }
          script: |
            sudo docker pull 100xdevs/web-app:latest
            sudo docker stop web-app || true
            sudo docker rm web-app || true
            sudo docker run -d --name web-app -p 3005:3000 100xdevs/web-app:latest

```

- Point userapp.your_domain.com to the IP of the server
- Add nginx reverse proxy to forward requests from userapp.your_domain.com to port on which the app is running

```

server {
    server_name userapp.100xdevs.com;

    location / {
        proxy_pass http://localhost:3005;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection 'upgrade';
        proxy_set_header Host $host;
        proxy_cache_bypass $http_upgrade;
    }
}

```

Copy

```
        # Basic Authentication
        auth_basic "Restricted Content";
        auth_basic_user_file /etc/nginx/.htpasswd;
    }

    listen 443 ssl; # managed by Certbot
    ssl_certificate /etc/letsencrypt/live/userapp.100xdevs.com/fullchain.pem; # managed by Certbot
    ssl_certificate_key /etc/letsencrypt/live/userapp.100xdevs.com/privkey.pem; # managed by Certbot
    include /etc/letsencrypt/options-ssl-nginx.conf; # managed by Certbot
    ssl_dhparam /etc/letsencrypt/ssl-dhparams.pem; # managed by Certbot
}
```

- Install certbot and Refresh certificate

```
sudo certbot --nginx
```

Copy

Take home assignments

1. Get a DB on [neon.tech](#) / [RDS](#) / [Aeiven](#) and add a DB migration step to the DB
2. Pass in the DB credentials while starting the docker image
3. Start the docker image so that it restarts if it goes down (similar to pm2)