

EXPERIMENT-1

AIM : Write SQL queries to CREATE TABLES for various databases using DDL commands (i.e. CREATE, ALTER, DROP, TRUNCATE).

CREATE TABLE:

Creates a table with specified constraints

SYNTAX:

CREATE TABLE tablename (column1 data_

type [constraint] [, column2 data_ type

[constraint]) [,

PRIMARY KEY (column1 [, column2])) [,

FOREIGN KEY (column1 [, column2]) REFERENCES tablename) [,CONSTRAINT constraint]);

```
SQL> CREATE TABLE employees (  
2     employee_id INT PRIMARY KEY,  
3     first_name VARCHAR(50),  
4     last_name VARCHAR(50),  
5     job_title VARCHAR(100),  
6     hire_date DATE,  
7     salary DECIMAL(10, 2)  
8 );
```

Table created.

```
SQL> DESC employees;
```

Name	Null?	Type
EMPLOYEE_ID	NOT NULL	NUMBER(38)
FIRST_NAME		VARCHAR2(50)
LAST_NAME		VARCHAR2(50)
JOB_TITLE		VARCHAR2(100)
HIRE_DATE		DATE
SALARY		NUMBER(10,2)

ALTER TABLE :

Used to add or modify table details like column names and data types, column constraints.

```
SQL> ALTER TABLE employees
  2  ADD email VARCHAR(100);
```

Table altered.

```
SQL> DESC employees;
```

Name	Null?	Type
EMPLOYEE_ID	NOT NULL	NUMBER(38)
FIRST_NAME		VARCHAR2(50)
LAST_NAME		VARCHAR2(50)
JOB_TITLE		VARCHAR2(100)
HIRE_DATE		DATE
SALARY		NUMBER(10,2)
EMAIL		VARCHAR2(100)

```
SQL> ALTER TABLE employees
  2  DROP COLUMN hire_date;
```

Table altered.

```
SQL> DESC employees;
```

Name	Null?	Type
EMPLOYEE_ID	NOT NULL	NUMBER(38)
FIRST_NAME		VARCHAR2(50)
LAST_NAME		VARCHAR2(50)
JOB_TITLE		VARCHAR2(100)
SALARY		NUMBER(10,2)
EMAIL		VARCHAR2(100)

DROP TABLE:

Deletes the specified table.

SYNTAX:

DROP TABLE table_name;

```
SQL> CREATE TABLE example_table (  
2     id INT PRIMARY KEY,  
3     name VARCHAR(50),  
4     date_of_birth DATE  
5 );
```

Table created.

```
SQL> DROP TABLE example_table;
```

Table dropped.

```
SQL> DESC example_table;
```

ERROR:

ORA-04043: object example_table does not exist

RENAME TABLE:

To rename table_name, column_name SYNTAXES:

RENAME new_table_name TO old_table_name;

```
SQL> RENAME employees to employee;
```

```
Table renamed.
```

```
SQL> desc employee;
```

Name	Null?	Type
EMPLOYEE_ID	NOT NULL	NUMBER(38)
FIRST_NAME		VARCHAR2(50)
LAST_NAME		VARCHAR2(50)
JOB_TITLE		VARCHAR2(100)
SALARY		NUMBER(10,2)
EMAIL		VARCHAR2(100)

TRUNCATE TABLE:

To remove all rows in a specified table.

SYNTAX:

TRUNCATE TABLE table_name;

```
SQL> TRUNCATE TABLE employee;
```

```
Table truncated.
```

EXPERIMENT-2

AIM : TO Write SQL queries to MANIPULATE TABLES for various databases using DML commands(i.e. INSERT, SELECT, UPDATE, DELETE,).

Creating table :

```
SQL> CREATE TABLE student1 (  
2   id INT PRIMARY KEY,  
3   name VARCHAR(50),  
4   age INT,  
5   email VARCHAR(100),  
6   registration_date NUMBER  
7 );
```

Table created.

INSERT COMMAND:

It is used to add values to a table.

SYNTAX:

INSERT INTO tablename

VALUES (value1,value2,...,valuen);

INSERT INTO tablename (column1, column2,...,column)

VALUES (value1, value2,...,valuen);

```
SQL> INSERT INTO student1 VALUES(2,'parvathi',19,'parvathi@gmail.com',2023-2-2);

1 row created.

SQL> INSERT INTO student1 VALUES(3,'naveen',17,'naveen@gmail.com',2023-3-3);

1 row created.

SQL> INSERT INTO student1 VALUES(4,'kavya',17,'kavya@gmail.com',2023-4-4);

1 row created.
```

SELECT COMMAND:

The SELECT command used to list the contents of a table.

SYNTAX:

Select * from table_name;

Select col_name from table_name;

```
SQL> select * FROM student1;
```

ID	NAME	AGE
1	bindu	18
	bindu@gmail.com	
	2021	
2	parvathi	19
	parvathi@gmail.com	
	2019	

ID	NAME	AGE

EMAIL		

REGISTRATION_DATE		

3	naveen	17
	naveen@gmail.com	
	2017	
4	kavya	17
	kavya@gmail.com	

UPDATE COMMAND:

The update command used to modify the contents of specified table.

SYNTAX:

UPDATE tablename

SET column_name = value[,

Column_name = value]

[WHERE condition_list];

```
SQL> UPDATE student1 SET name='shiva' WHERE age=19;

1 row updated.

SQL> SELECT * FROM student1;

      ID NAME                AGE
-----
EMAIL
-----
REGISTRATION_DATE
-----
      1 bindu                18
bindu@gmail.com
      2021

      2 shiva                19
parvathi@gmail.com
      2019
```

DELETE COMMAND:

To delete all rows or specified rows in a table.

SYNTAX:

DELETE FROM tablename [WHERE condition_list];

```
SQL> DELETE from student1 WHERE age=18;
```

```
1 row deleted.
```

```
SQL> select * from student1;
```

ID	NAME	AGE
2	shiva parvathi@gmail.com 2019	19
3	naveen naveen@gmail.com 2017	17

Experiment-3

Aim: To implement a view level design using CREATE VIEW, ALTER VIEW and DELETE VIEW ddl commands.

Creating a table:

```
SQL> CREATE TABLE student2 (  
2     id INT PRIMARY KEY,  
3     name VARCHAR(50),  
4     age INT,  
5     email VARCHAR(100),  
6     registration_date NUMBER,  
7     grade VARCHAR(10)  
8 );  
  
Table created.
```

By using insert command we can insert values in a tables

```
SQL> INSERT INTO student2 VALUES(1,'bindu',12,'bindu@gmail.com',2023-01-01,'A');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(2,'preethi',13,'preethi@gmail.com',2023-02-02,'B');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(3,'pooji',13,'pooji@gmail.com',2023-02-03,'C');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(4,'suppi',14,'suppi@gmail.com',2023-02-04,'D');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(5,'usha',15,'usha@gmail.com',2023-02-05,'E');  
  
1 row created.
```

Creating view counsellor:

```
SQL> CREATE VIEW counsellor AS SELECT name,age,grade FROM student2;  
  
View created.
```

Inserting values into counsellor:

```
SQL> INSERT INTO student2 VALUES(1,'bindu',12,'bindu@gmail.com',2023-01-01,'A');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(2,'preethi',13,'preethi@gmail.com',2023-02-02,'B');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(3,'pooji',13,'pooji@gmail.com',2023-02-03,'C');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(4,'suppi',14,'suppi@gmail.com',2023-02-04,'D');  
  
1 row created.  
  
SQL> INSERT INTO student2 VALUES(5,'usha',15,'usha@gmail.com',2023-02-05,'E');  
  
1 row created.
```

Selecting specific row :

```
SQL> SELECT * FROM counsellor;
```

NAME	AGE	GRADE
bindu	12	A
preethi	13	B
pooji	13	C
suppi	14	D
usha	15	E

Update :

```
SQL> UPDATE counsellor SET name = 'samyu' WHERE age=12;
```

```
1 row updated.
```

```
SQL> SELECT * FROM counsellor;
```

NAME	AGE	GRADE
samyu	12	A
preethi	13	B
pooji	13	C
suppi	14	D
usha	15	E

truncate or drop view:

```
SQL> DROP VIEW counsellor;  
View dropped.
```

EXPERIMENT-4

AIM : To create/perform relational set operations(i.e UNION, UNION ALL, INTERSECT, MINUS, CROSS JOIN, NATURAL JOIN.)

Creating tables :

```
SQL> CREATE TABLE students3 (  
2     student_id INT PRIMARY KEY,  
3     name VARCHAR(50),  
4     age INT,  
5     email VARCHAR(100),  
6     registration_date NUMBER  
7 );
```

Table created.

```
SQL> CREATE TABLE courses1 (  
2     course_id INT PRIMARY KEY,  
3     course_name VARCHAR(50),  
4     instructor VARCHAR(50),  
5     start_date NUMBER,  
6     end_date NUMBER  
7 );
```

Table created.

Inserting values into personal data table :

```
SQL> INSERT INTO students3 VALUES(1,'jaggu',10,'jaggu@gmail.com',2023-10-10);  
1 row created.  
  
SQL> INSERT INTO students3 VALUES(2,'govardhan',10,'govardhan@gmail.com',2023-10-11);  
1 row created.  
  
SQL> INSERT INTO students3 VALUES(3,'kutty',11,'kutty@gmail.com',2023-10-12);  
1 row created.  
  
SQL> INSERT INTO students3 VALUES(4,'sonu',12,'sonu@gmail.com',2023-10-13);  
1 row created.
```

Inserting values into information table :

```
SQL> INSERT INTO courses1 VALUES(11,'cse','shiva',2023-10-13,2023-10-30);  
1 row created.  
  
SQL> INSERT INTO courses1 VALUES(12,'csd','shamu',2023-10-14,2023-11-30);  
1 row created.  
  
SQL> INSERT INTO courses1 VALUES(13,'csm','sharun',2023-10-15,2023-11-28);  
1 row created.  
  
SQL> INSERT INTO courses1 VALUES(14,'eee','shonn',2023-10-16,2023-11-27);  
1 row created.  
  
SQL> INSERT INTO courses1 VALUES(15,'ece','shony',2023-10-18,2023-11-23);  
1 row created.
```

Union operation :

```
SQL> SELECT name from students3  
2 UNION  
3 SELECT course_name from courses1;
```

NAME

csd
cse
csm
ece
eee
govardhan
jaggu
kutty
sonu

9 rows selected.

Union all operation :

```
SQL> SELECT name from students3  
2  UNION ALL  
3  SELECT course_name from courses1;
```

NAME

jaggu
govardhan
kutty
sonu
cse
csd
csm
eee
ece

9 rows selected.

Intersect operation :

```
SQL> SELECT name from students3  
2  INTERSECT  
3  SELECT course_name from courses1;
```

no rows selected

Minus operation :

```
SQL> SELECT name from students3  
2  MINUS  
3  SELECT course_name from courses1;
```

NAME

govardhan
jaggu
kutty
sonu

EXPERIMENT-5

Aim: write SQL queries for the aggregate functions(sum,count,min,max,avg)

Creating a table:

```
SQL> CREATE TABLE students4 (  
2     student_id INT PRIMARY KEY,  
3     first_name VARCHAR(50),  
4     last_name VARCHAR(50),  
5     phone_number VARCHAR(15),  
6     address VARCHAR(255)  
7 );
```

Table created.

Inserting values into table :

```
SQL> INSERT INTO students4 VALUES(1,'Y','bindu',123456,'atp');
```

1 row created.

```
SQL> INSERT INTO students4 VALUES(2,'k','jyothi',123478,'ktc');
```

1 row created.

```
SQL> INSERT INTO students4 VALUES(3,'A','usha',123409,'tdp');
```

1 row created.

```
SQL> INSERT INTO students4 VALUES(4,'u','suppi',123402,'amp');
```

1 row created.

Selecting table :

STUDENT_ID	FIRST_NAME	LAST_NAME	PHONE_NUMBER	ADDRESS
1	Y	bindu atp	123456	
2	k	jyothi ktc	123478	

Sum();

```
SQL> SELECT SUM(student_id) FROM students4;

SUM(STUDENT_ID)
-----
                15
```

Avg();

```
SQL> SELECT AVG(student_id) FROM students4;

AVG(STUDENT_ID)
-----
                3
```

Min();

```
SQL> SELECT MIN(student_id) FROM students4;

MIN(STUDENT_ID)
-----
                1
```

Max();

```
SQL> SELECT MAX(student_id) FROM students4;

MAX(STUDENT_ID)
-----
                5
```

Count();

```
SQL> SELECT COUNT(student_id) FROM students4;

COUNT(STUDENT_ID)
-----
                  5
```

EXPERIMENT-6

AIM: Write SQL queries to perform JOIN OPERATIONS (i.e. CONDITIONAL JOIN, EQUI JOIN, LEFT OUTER JOIN, RIGHT OUTER JOIN, FULL OUTER JOIN)

CREATING TABLE student :

```
SQL> CREATE TABLE student10(  
2  name varchar(10),  
3  roll_no number,  
4  dept varchar(10),  
5  primary key(name)  
6  );
```

Table created.

Inserting tables into student table :

```
SQL> INSERT INTO student10 VALUES('SHIVA',531,'CSE');
```

1 row created.

```
SQL> INSERT INTO student10 VALUES('MOUNIKA',532,'CSE');
```

1 row created.

```
SQL> SELECT * FROM student10;
```

NAME	ROLL_NO	DEPT
SHIVA	531	CSE
MOUNIKA	532	CSE
JAGAN	530	CSE
ARJUN	505	CSE

Creating table Library :

```
SQL> CREATE TABLE library(  
  2  roll_no number,  
  3  book varchar(10)  
  4  );
```

Table created.

Inserting values into library table :

```
SQL-CSE530>INSERT INTO library VALUES (530,'DBMS');
```

1 row created.

```
SQL-CSE530>INSERT INTO library VALUES (531,'JAVA');
```

1 row created.

```
SQL-CSE530>INSERT INTO library VALUES (537,'MATHS');
```

1 row created.

```
SQL-CSE530>INSERT INTO library VALUES (528,'SE');
```

1 row created.

```
SQL-CSE530>SELECT * FROM library;
```

ROLL_NO	BOOK
530	DBMS
531	JAVA
537	MATHS
528	SE

CONDITIONAL JOIN :

```
SQL> SELECT * FROM student10 JOIN library on student10.roll_no = library.roll_no;
```

NAME	ROLL_NO	DEPT	ROLL_NO	BOOK
SHIVA	531	CSE	531	DBMS
MOUNIKA	532	CSE	532	JAVA
JAGAN	530	CSE	530	MATHS
ARJUN	505	CSE	505	SE

EQUI JOIN :

```
SQL> SELECT * FROM student10 JOIN library USING (roll_no);
```

ROLL_NO	NAME	DEPT	BOOK
531	SHIVA	CSE	DBMS
532	MOUNIKA	CSE	JAVA
530	JAGAN	CSE	MATHS
505	ARJUN	CSE	SE

NATURAL LEFT OUTER JOIN :

```
SQL> SELECT * FROM student10 NATURAL LEFT OUTER JOIN library ;
```

ROLL_NO	NAME	DEPT	BOOK
531	SHIVA	CSE	DBMS
532	MOUNIKA	CSE	JAVA
530	JAGAN	CSE	MATHS
505	ARJUN	CSE	SE

NATURAL RIGHT OUTER JOIN :

```
SQL> SELECT * FROM student10 NATURAL RIGHT OUTER JOIN library ;
```

ROLL_NO	NAME	DEPT	BOOK
531	SHIVA	CSE	DBMS
532	MOUNIKA	CSE	JAVA
530	JAGAN	CSE	MATHS
505	ARJUN	CSE	SE

NATURAL FULL OUTER JOIN :

```
SQL> SELECT * FROM student10 NATURAL FULL OUTER JOIN library ;
```

ROLL_NO	NAME	DEPT	BOOK
531	SHIVA	CSE	DBMS
532	MOUNIKA	CSE	JAVA
530	JAGAN	CSE	MATHS
505	ARJUN	CSE	SE

EXPERIMENT-7

AIM: TO WRITE SQL QUERIES TO PERFORM SPECIAL OPERATIONS(i.e LIKE,BETWEEN,ISNULL,ISNOTNULL)

Creating a table

```
SQL> CREATE TABLE students6 (  
2   student_id INT PRIMARY KEY,  
3   first_name VARCHAR(50),  
4   last_name VARCHAR(50),  
5   date_of_birth NUMBER,  
6   gender CHAR(1),  
7   email VARCHAR(100)  
8 );
```

Table created.

Inserting values :

```
SQL> INSERT INTO students6 VALUES(1,'A','bindu',2023-02-01,'f','bindu@gmail.com');  
1 row created.  
  
SQL> INSERT INTO students6 VALUES(2,'B','kutty',2023-02-02,'f','kutty@gmail.com');  
1 row created.  
  
SQL> INSERT INTO students6 VALUES(3,'c','sonu',2023-03-02,'f','sonu@gmail.com');  
1 row created.  
  
SQL> INSERT INTO students6 VALUES(4,'d','sunny',2023-03-03,'m','sunny@gmail.com');  
1 row created.  
  
SQL> INSERT INTO students6 VALUES(5,'e','sandeep',2023-03-07,'m','sandeep@gmail.com');  
1 row created.  
  
SQL> INSERT INTO students6 VALUES(6,'f','netra',2023-03-08,'f','netra@gmail.com');  
1 row created.  
  
SQL> INSERT INTO students6 VALUES(7,'g','abhi',2023-06-08,'m','abhi@gmail.com');  
1 row created.
```


Is Null operation :

```
SQL> SELECT * from students6;
```

```
STUDENT_ID FIRST_NAME
```

```
LAST_NAME
```

```
DATE_OF_BIRTH G
```

```
EMAIL
```

```
-----
1 A
bindu
bindu@gmail.com
2020 f
```

```
2 B
kutty
kutty@gmail.com
2019 f
```

```
STUDENT_ID FIRST_NAME
```

```
LAST_NAME
```

```
DATE_OF_BIRTH G
```

```
EMAIL
```

```
-----
3 c
sonu
sonu@gmail.com
2018 f
```

```
4 d
sunny
2017 m
```

```
SQL> SELECT * FROM students6 WHERE gender IS NULL;

no rows selected
```

Is not null operation :

```
SQL> SELECT * FROM students6 WHERE gender IS NOT NULL;
```

```
STUDENT_ID FIRST_NAME
```

```
LAST_NAME
```

```
DATE_OF_BIRTH G
```

```
EMAIL
```

```
-----
1 A
bindu
bindu@gmail.com
2020 f
```

```
2 B
kutty
kutty@gmail.com
2019 f
```

Between operation :

```
SQL> SELECT * FROM students6 WHERE student_id BETWEEN 1 and 5;
```

```
STUDENT_ID FIRST_NAME
```

```
-----
```

```
LAST_NAME DATE_OF_BIRTH G
```

```
-----
```

```
EMAIL
```

```
-----
```

```
1 A
```

```
bindu 2020 f
```

```
bindu@gmail.com
```

```
2 B
```

```
kutty 2019 f
```

```
kutty@gmail.com
```

```
STUDENT_ID FIRST_NAME
```

```
-----
```

```
LAST_NAME DATE_OF_BIRTH G
```

```
-----
```

```
EMAIL
```

```
3 c
```

```
sonu 2018 f
```

```
sonu@gmail.com
```

```
4 d
```

```
sunny 2017 m
```

Like operation:

```
SQL-CSE530>SELECT *FROM students_in WHERE branch LIKE 'CSE%';
```

```
NAME R_NO BRANC BLOCK FEE
```

```
-----
```

```
Jagadeesh 530 CSE B 2500000
```

```
Anees 553 CSE B 2200000
```

```
Balaji 510 CSE A 2200000
```

```
Baba 509 CSE A 2900000
```

```
Tauheed 547 CSE A 3500000
```

```
SQL> SELECT * FROM students6 WHERE last_name LIKE 'sunny%';
```

```
STUDENT_ID FIRST_NAME
```

```
-----
```

```
LAST_NAME DATE_OF_BIRTH G
```

```
-----
```

```
EMAIL
```

```
4 d
```

```
sunny 2017 m
```

```
sunny@gmail.com
```

Exists operation :

```
SQL> SELECT * FROM students6 WHERE EXISTS (SELECT last_name FROM students6);
```

```
STUDENT_ID FIRST_NAME
```

```
LAST_NAME
```

```
DATE_OF_BIRTH G
```

```
EMAIL
```

```
1 A
```

```
bindu
```

```
2020 f
```

```
bindu@gmail.com
```

```
2 B
```

```
kutty
```

```
2019 f
```

```
kutty@gmail.com
```

EXPERIMENT-8

AIM : Write SQL queries to perform ORACLE BUILT-IN FUNCTIONS (i.e. DATE, TIME).

Built-in Functions

1. Character Functions I. Case-conversion functions
- II. Character manipulation functions
2. Number Functions
3. DATE functions
4. CREATING TABLE :

```
SQL> CREATE TABLE names(  
2 first_name VARCHAR(20) NOT NULL,  
3 last_name VARCHAR(20) NOT NULL  
4 );
```

Table created.

INSERTING VALUES :

```
SQL> INSERT ALL  
2 INTO names VALUES('bindu','chitran')  
3 INTO names VALUES('preethi','reddy')  
4 INTO names VALUES('pooji','gattamaneni')  
5 INTO names VALUES('kavya','battini')  
6 SELECT * FROM dual;
```

4 rows created.

Character Functions

I. Case-conversion functions :

LOWER ();

```
SQL> SELECT LOWER(first_name) FROM names;

LOWER(FIRST_NAME)
-----
bindu
preethi
pooji
kavya
```

UPPER();

```
SQL> SELECT UPPER(first_name) FROM names;

UPPER(FIRST_NAME)
-----
BINDU
PREETHI
POOJI
KAVYA
```

INITCAP();

```
SQL> SELECT INITCAP(first_name) FROM names;

INITCAP(FIRST_NAME)
-----
Bindu
Preethi
Pooji
Kavya
```

Character manipulation functions:

CONCAT();

```
SQL> SELECT CONCAT(first_name,last_name) FROM names;

CONCAT(FIRST_NAME, LAST_NAME)
-----
binduchitran
preethireddy
poojigattamaneni
kavyabattini
```

SUBSTR():

```
SQL> SELECT SUBSTR(first_name,1,4) FROM names;

SUBSTR(FIRST_NAME,1,4)
-----
bind
pre
pooj
kavy
```

LENGTH() :

```
SQL> SELECT LENGTH(first_name) FROM names;

LENGTH(FIRST_NAME)
-----
5
7
5
5
```

INSTR() :

```
SQL> SELECT INSTR(first_name,'KA') FROM names;

INSTR(FIRST_NAME, 'KA')
-----
0
0
0
0
```

TRIM() :

```
SQL> SELECT TRIM('A' FROM first_name) FROM names;

TRIM('A' FROM FIRST_NAME)
-----
bindu
preethi
pooji
kavya
```

2. Number Functions :ROUND() :

```
SQL> SELECT ROUND(11.111,2) FROM dual;

ROUND(11.111,2)
-----
11.11
```

MOD() :

```
SQL> SELECT MOD(11,2) FROM dual;

MOD(11,2)
-----
1
```

2. DATE functions :SYSDATE()

```
SQL> SELECT SYSDATE FROM dual;

SYSDATE
-----
19-DEC-23
```

MONTHS-BETWEEN() :

```
SQL> SELECT MONTHS_BETWEEN(SYSDATE, '19-DEC-23') FROM dual;

MONTHS_BETWEEN(SYSDATE, '19-DEC-23')
-----
0
```

ADD_MONTHS() :

```
SQL> SELECT ADD_MONTHS(SYSDATE, 12) FROM dual;

ADD_MONTH
-----
19-DEC-24
```

NEXT DAY() :

```
SQL> SELECT NEXT_DAY(SYSDATE, 'MONDAY') FROM dual;

NEXT_DAY(
-----
25-DEC-23
```

LAST DAY() :

```
SQL> SELECT LAST_DAY(SYSDATE) FROM dual;

LAST_DAY(
-----
31-DEC-23
```



```
SQL> SELECT CURRENT_TIMESTAMP(3) FROM dual;
```

```
CURRENT_TIMESTAMP(3)
```

```
-----
```

```
19-DEC-23 10.41.44.884 PM +05:30
```

224G1A05A0

EXPERIMENT-9

AIM: Write SQL queries to perform KEY CONSTRAINTS (i.e. PRIMARY KEY, FOREIGN KEY, UNIQUE NOT NULL, CHECK, DEFAULT).

Types of SQL Constraints.

1. NOT NULL - Ensures that a column cannot have a NULL value
2. UNIQUE - Ensures that all values in a column are different
3. PRIMARY KEY - A combination of a NOT NULL and UNIQUE. Uniquely identifies each row in a table
4. FOREIGN KEY - Uniquely identifies a row/record in another table
5. CHECK - Ensures that all values in a column satisfies a specific condition
6. DEFAULT - Sets a default value for a column when no value is specified

1.NOT NULL Constraint Example:

```
SQL> CREATE TABLE order2(  
2 id NUMBER PRIMARY KEY,  
3 product_name VARCHAR2(50) NOT NULL,  
4 quantity NUMBER  
5 );
```

Table created.

```
SQL> INSERT INTO order2 VALUES(1, 'AGRABATHI', 29);
```

1 row created.

```
SQL> INSERT INTO order2 VALUES(4, '', 29);  
INSERT INTO order2 VALUES(4, '', 29)  
*
```

ERROR at line 1:

ORA-01400: cannot insert NULL into ("C##513"."ORDER2"."PRODUCT_NAME")

2.UNIQUE CONSTRAINT Example:

```
SQL> CREATE TABLE employee1(  
2 id NUMBER PRIMARY KEY,  
3 name VARCHAR(50) NOT NULL,  
4 e_mail VARCHAR2(50) UNIQUE  
5 );
```

Table created.

```
SQL> INSERT INTO employee1 VALUES(529,'HimaBindu','himabindu567@gmail.com');
```

1 row created.

3.PRIMARY KEY CONSTRAINT Example:

```
SQL> CREATE TABLE stud1(  
2 ID NUMBER PRIMARY KEY,  
3 first_name VARCHAR(20) NOT NULL,  
4 last_name VARCHAR(20) NOT NULL  
5 );
```

Table created.

```
SQL> INSERT INTO stud VALUES(529,'HARRY','POTTER');
```

1 row created.

4.FORIEGN KEY CONSTRAINTS Example:

```
SQL> CREATE TABLE orders3(  
2 id NUMBER PRIMARY KEY,  
3 order_num NUMBER NOT NULL,  
4 stud_id NUMBER REFERENCES stud(id)  
5 );
```

Table created.

```
SQL> INSERT INTO orders3 VALUES(11,2,111);  
INSERT INTO orders3 VALUES(11,2,111)
```

*

ERROR at line 1:

ORA-02291: integrity constraint (C##513.SYS_C008386) violated - parent key n
ot
found

5.CHECK CONSTRAINTS Example:

```
SQL> CREATE TABLE parts2(  
  2 part_id NUMBER PRIMARY KEY,  
  3 part_name VARCHAR2(50) NOT NULL,  
  4 buy_price NUMBER(9,2) CHECK(buy_price>0)  
  5 );
```

Table created.

```
SQL> INSERT INTO parts2 VALUES(1,'AGRABATHI',876);
```

1 row created.

```
SQL> INSERT INTO parts2 VALUES(1,'AGRABATHI',-876);  
INSERT INTO parts2 VALUES(1,'AGRABATHI',-876)
```

*

ERROR at line 1:

ORA-02290: check constraint (C##513.SYS_C008388) violated

6.DEFAULT CONSTRAINTS Example:

```
SQL> CREATE TABLE customers2(  
2  name VARCHAR2(50) NOT NULL,  
3  id NUMBER PRIMARY KEY,  
4  country VARCHAR2(20) DEFAULT 'IND'  
5  );
```

Table created.

```
SQL> INSERT INTO customers2 VALUES('ARYA',1,'USA');
```

1 row created.

```
SQL> INSERT INTO customers2(name,id) VALUES('ALLU',2);
```

1 row created.

```
SQL> SELECT * FROM customers2;
```

NAME	ID
ARYA	1
USA	
ALLU	2
IND	

Experiment -10

AIM: Write a PL/ SQL program for calculating the factorial of a given number.

```
Microsoft Windows [Version 10.0.19045.2728]
(c) Microsoft Corporation. All rights reserved.

C:\Users\HP>sqlplus

SQL*Plus: Release 21.0.0.0.0 - Production on Thu Nov 30 19:28:41 2023
Version 21.3.0.0.0

Copyright (c) 1982, 2021, Oracle. All rights reserved.

Enter user-name: system
Enter password:
Last Successful login time: Wed Nov 29 2023 21:03:10 -05:00

Connected to:
Oracle Database 21c Express Edition Release 21.0.0.0.0 - Production
Version 21.3.0.0.0

SQL>
```

1.

```
SQL> SET SERVEROUT ON
SQL>
```

2.

```
SQL> SET SERVEROUT ON
SQL> edit ex10
```

3.

```
DECLARE
fac NUMBER :=1;
n NUMBER := 10;
BEGIN
WHILE n > 0 LOOP
fac:=n*fac;
n:=n-1;
END LOOP;
DBMS_OUTPUT.PUT_LINE(FAC);
END;
/|
```

4.

```
SQL> @ex10  
3628800  
  
PL/SQL procedure successfully completed.  
  
SQL>
```

Experiment -11

AIM Write a PL/SQL program for finding the given number is prime number or not.

```
Microsoft Windows [Version 10.0.19045.2728]
(c) Microsoft Corporation. All rights reserved.

C:\Users\HP>sqlplus

SQL*Plus: Release 21.0.0.0.0 - Production on Thu Nov 30 19:36:06 2023
Version 21.3.0.0.0

Copyright (c) 1982, 2021, Oracle. All rights reserved.

Enter user-name: system
Enter password:
Last Successful login time: Thu Nov 30 2023 19:33:16 -05:00

Connected to:
Oracle Database 21c Express Edition Release 21.0.0.0.0 - Production
Version 21.3.0.0.0
```

1.

```
SQL> SET SERVEROUT ON
SQL> edit experiment11
```


2.

 experiment11 - Notepad

File Edit Format View Help

```
DECLARE
n NUMBER;
i NUMBER;
temp NUMBER;
BEGIN
n := 13;
i := 2;
temp := 1;
FOR i IN 2..n/2
LOOP
IF MOD(n, i) = 0
THEN
temp := 0;
EXIT;
END IF;
END LOOP;
IF temp = 1
THEN
DBMS_OUTPUT.PUT_LINE(n||' is a prime number');
ELSE
DBMS_OUTPUT.PUT_LINE(n||' is not a prime number');
END IF;
END;
```

```
SQL> @experiment11
13 is a prime number

PL/SQL procedure successfully completed.
```

Experiment -12

AIM: Write a PL/SQL program for displaying the Fibonacci series up to an integer.

1.

```
C:\Users\HP>sqlplus

SQL*Plus: Release 21.0.0.0.0 - Production on Thu Nov 30 19:36:06 2023
Version 21.3.0.0.0

Copyright (c) 1982, 2021, Oracle. All rights reserved.

Enter user-name: system
Enter password:
Last Successful login time: Thu Nov 30 2023 19:33:16 -05:00

Connected to:
Oracle Database 21c Express Edition Release 21.0.0.0.0 - Production
Version 21.3.0.0.0
```

```
SQL> SET SERVEROUT ON
SQL> edit experiment12
```



experiment12 - Notepad

File Edit Format View Help

```
DECLARE
FIRST NUMBER := 0;
SECOND NUMBER := 1;
TEMP NUMBER;
N NUMBER := 5;
I NUMBER;
BEGIN
DBMS_OUTPUT.PUT_LINE('SERIES:');
DBMS_OUTPUT.PUT_LINE(FIRST);
DBMS_OUTPUT.PUT_LINE(SECOND);
FOR I IN 2..N
LOOP
TEMP:=FIRST+SECOND;
FIRST := SECOND;
SECOND := TEMP;
DBMS_OUTPUT.PUT_LINE(TEMP);
END LOOP;
END;
/
```

2.

```
SQL> @experiment12
SERIES:
0
1
1
2
3
5

PL/SQL procedure successfully completed.

SQL>
```

Experiment -13

AIM: Write PL/SQL program to implement Stored Procedure on table.

1.

```
SQL> CREATE TABLE SAILOR(  
2  ID NUMBER(10) PRIMARY KEY,  
3  NAME VARCHAR2(100)  
4  );
```

Table created.

2.

```
SQL> CREATE OR REPLACE PROCEDURE INSERTUSER  
2  (ID IN NUMBER,  
3  NAME IN VARCHAR2)  
4  IS  
5  BEGIN  
6  INSERT INTO SAILOR VALUES(ID,NAME);  
7  DBMS_OUTPUT.PUT_LINE('RECORD INSERTED SUCCESSFULLY');  
8  END;  
9  /
```

Procedure created.

3.

```
1  DECLARE  
2  CNT NUMBER;  
3  BEGIN  
4  INSERTUSER(101,'NARASIMHA');  
5  SELECT COUNT(*) INTO CNT FROM SAILOR;  
6  DBMS_OUTPUT.PUT_LINE(CNT||' RECORD IS INSERTED SUCCESSFULLY');  
7* END;  
SQL> /  
RECORD INSERTED SUCCESSFULLY  
1 RECORD IS INSERTED SUCCESSFULLY  
PL/SQL procedure successfully completed.
```

Experiment – 14

AIM: Write PL/SQL program to implement Stored Function on table.

1.

```
SQL> CREATE OR REPLACE FUNCTION ADDER(N1 IN NUMBER, N2 IN NUMBER)
  2  RETURN NUMBER
  3  IS
  4  N3 NUMBER(8);
  5  BEGIN
  6  N3 :=N1+N2;
  7  RETURN N3;
  8  END;
  9  /

Function created.
```

2.

```
SQL> DECLARE
  2  N3 NUMBER(2);
  3  BEGIN
  4  N3 := ADDER(11,12);
  5  DBMS_OUTPUT.PUT_LINE('ADDITION IS: '||N3);
  6  END;
  7  /
```

```
ADDITION IS: 23
```

```
PL/SQL procedure successfully completed.
```

3.

```
SQL> CREATE FUNCTION fact(x number)
  2  RETURN number
  3  IS
  4  f number;
  5  BEGIN
  6  IF x=0 THEN
  7  f := 1;
  8  ELSE
  9  f := x * fact(x-1);
 10  END IF;
 11  RETURN f;
 12  END;
 13  /
```

```
Function created.
```

4.

```
SQL> DECLARE
  2  num NUMBER;
  3  factorial NUMBER;
  4  BEGIN
  5  num := 6;
  6  factorial := fact(num);
  7  dbms_output.put_line(' Factorial ' || num || ' is ' || factorial);
  8  END;
  9  /
Factorial 6 is 720

PL/SQL procedure successfully completed.
```

5.

```
SQL> DROP FUNCTION fact;

Function dropped.
```

Experiment – 15

AIM: Write PL/SQL program to implement Trigger on table.

1.

```
SQL> CREATE TABLE DEPARTMENT(  
2  DEPT_NAME VARCHAR2(20),  
3  BUILDING VARCHAR2(15),  
4  BUDGET NUMERIC(12,2) CHECK (BUDGET > 0),  
5  PRIMARY KEY(DEPT_NAME)  
6  );
```

Table created.

2.

```
SQL> CREATE TABLE INSTRUCTOR(  
2  ID VARCHAR2(5),  
3  NAME VARCHAR2(20) NOT NULL,  
4  DEPT_NAME VARCHAR2(20),  
5  SALARY NUMERIC(8,2) CHECK (SALARY > 29000),  
6  PRIMARY KEY(ID),  
7  FOREIGN KEY (DEPT_NAME) REFERENCES DEPARTMENT(DEPT_NAME)  
8  ON DELETE SET NULL  
9  );
```

Table created.

3.

```
SQL> INSERT INTO department values ('Biology','Watson','90000');
```

1 row created.

4.

```
SQL> CREATE OR REPLACE TRIGGER display_salary_changes  
2  BEFORE UPDATE ON instructor  
3  FOR EACH ROW  
4  WHEN (NEW.ID = OLD.ID)  
5  DECLARE  
6  sal_diff NUMBER;  
7  BEGIN  
8  sal_diff := :NEW.salary - :OLD.salary;  
9  dbms_output.put_line('Old salary: '|| :OLD.salary);  
10 dbms_output.put_line('New salary: '|| :NEW.salary);  
11 dbms_output.put_line('Salary difference: '||sal_diff);  
12 END;  
13 /
```

Trigger created.

5.

```
SQL> DECLARE
  2 total_rows number(2);
  3 BEGIN
  4 UPDATE instructor
  5 SET salary = salary + 5000;
  6 IF sql%notfound THEN
  7 dbms_output.put_line('no instructors updated');
  8 ELSIF sql%found THEN
  9 total_rows := sql%rowcount;
 10 dbms_output.put_line(total_rows||' instructors updated ');
 11 END IF ;
 12 END;
 13 /
no instructors updated

PL/SQL procedure successfully completed.
```


Experiment-16

AIM: Write PL/SQL program to implement Cursor on table.

1.

```
SQL> CREATE TABLE customers(  
  2 ID NUMBER PRIMARY KEY,  
  3 NAME VARCHAR2(20) NOT NULL,  
  4 AGE NUMBER,  
  5 ADDRESS VARCHAR2(20),  
  6 SALARY NUMERIC(20,2)  
  7 );
```

Table created.

2.

```
SQL> INSERT INTO customers VALUES(1,'Ramesh',23,'Allabad',25000);  
  
1 row created.
```

3.

```
SQL> INSERT INTO customers VALUES(2,'Suresh',22,'Kanpur',27000);  
  
1 row created.
```

4.

```
SQL> INSERT INTO customers VALUES(3,'Mahesh',24,'Ghaziabad',29000);  
  
1 row created.
```

5.

```
SQL> DECLARE  
  2 total_rows number(2);  
  3 BEGIN  
  4 UPDATE customers  
  5 SET salary = salary + 5000;  
  6 IF sql%notfound THEN  
  7 dbms_output.put_line('no customers updated');  
  8 ELSIF sql%found THEN  
  9 total_rows := sql%rowcount;  
 10 dbms_output.put_line(total_rows||' customers updated ');  
 11 END IF;  
 12 END;  
 13 /  
3 customers updated  
  
PL/SQL procedure successfully completed.
```

6.

```
SQL> DECLARE
  2  c_id customers.id%type;
  3  c_name customers.name%type;
  4  c_addr customers.address%type;
  5  CURSOR c_customers is
  6  SELECT id,name,address FROM customers;
  7  BEGIN
  8  OPEN c_customers;
  9  LOOP
 10  FETCH c_customers into c_id,c_name,c_addr;
 11  EXIT WHEN c_customers%notfound;
 12  dbms_output.put_line(c_id||' '||c_name||' '||c_addr);
 13  END LOOP;
 14  CLOSE c_customers;
 15  END;
 16  /
1 Ramesh Allabad
2 Suresh Kanpur
3 Mahesh Ghaziabad

PL/SQL procedure successfully completed.
```