Object Detection Using YOLOv4 with a GUI-Based Interactive System

Deepak N. A.[1*], Abhishek Gangappa Ambi[2], Shree Sagar CV[3], Sai Koushik YR[4], Siddaraju T [5]

[1]Associate Professor, Computer Science and Engineering, RV Institute of Technology and Management (RVITM), Bengaluru, India, Email: deepakna.rvitm@rvei.edu.in.

[2,3,4,5] UG Students, Computer Science and Engineering, RV Institute of Technology and Management (RVITM), Bengaluru, India.

Abstract

Object detection is a fundamental area of contemporary computer vision, allowing machines to detect, classify, and locate objects in visual scenes. This project demonstrates the implementation of a GUI-based real-time Object Detection system based on the YOLOv4 model, combined with OpenCV and Python's Tkinter library. The system enables users to load static images, browse through image datasets, and capture live video from a webcam for real-time detection. The main features are zooming, dragging, dynamic resizing of the image, and interactive control of the camera output. By integrating an efficient detection model with an intuitive graphical user interface, the program closes the gap between cutting-edge deep learning technology and accessible real-world equipment. This system illustrates the significance of model deployment, human interaction, and real-time feedback in real-world AI-based applications.

Keywords: Object Detection, YOLOv4, Real-Time Computer Vision, OpenCV, GUI, Tkinter, Deep Learning, Image Processing, Bounding Box Detection

1. Introduction

The domain of computer vision has grown tremendously, allowing machines to sense and interpret the visual world with greater precision. One such key computer vision task, object detection, is instrumental in numerous applications such as autonomous vehicles, surveillance, industrial automation, and infrastructure for smart cities. It is not just detecting objects appearing in an image but also localizing them precisely with bounding boxes.

Deep learning frameworks, especially Convolutional Neural Networks (CNNs), have completely transformed the domain of object detection. Out of these, YOLO (You Only Look Once) suite of algorithms was remarkable in both achieving real-time speed at preserving high precision. YOLOv4 released in 2020 by Bochkovskiy et al. achieved the highest jump yet from the predecessors by

implementing a chain of enhancements like Cross-Stage Partial connections (CSP), Spatial Pyramid Pooling (SPP), and Self-Adversarial Training (SAT).

In spite of the advancements made in detection precision and speed, real-world utilization tends to be a seamless, user-friendly, and accessible interface that enables even non-experts to use such high-powered models with ease. To fill the gap, the current project envisages a GUI-based Object Detection system that marries YOLOv4 with Python's Tkinter and OpenCV frameworks. The software enables users to load images or take live video from a camera, detect objects automatically, and browse images interactively with zoom, drag, and real-time updates.

This work not only illustrates the deployment of real-time object detection but also highlights the significance of successful model deployment in real-world, user-oriented applications.

2. Literature Review

Recent advancements in deep learning have seen considerable improvements in object detection models. Bochkovskiy et al. (2020) introduced YOLOv4, incorporating features like CSPNet, Mish activation, and Cross mini-Batch Normalization (CmBN), achieving state-of-the-art performance on the COCO benchmark. Wang et al. (2021) extended this work by proposing Scaled-YOLOv4, enabling multi-scale training to improve performance on datasets with variable object sizes.

Kumar and Safwan (2024) addressed the adaptation of YOLOv4 for real-time environments, emphasizing optimization for dynamic and resource-constrained settings. Ji et al. (2022) developed lightweight YOLOv4 models for safety equipment detection tasks, combining YOLOv4 with MobileNet to balance performance and computational efficiency.

In addition, Dubey et al. (2022) applied YOLOv4 modifications to satellite imagery, showing that YOLO-based architectures can be adapted to different environmental challenges with minor alterations. Comparative studies such as those by Zhaosheng Xu et al. (2023) also indicate that traditional deep-learning-based models like YOLOv4 still outperform newer lightweight models in terms of reliability and precision when configured properly.

These research contributions strongly motivate the integration of YOLOv4 into accessible, deployable systems, where users can harness its capabilities without deep technical expertise. Our work follows this direction by embedding YOLOv4 in a dynamic, user-centric GUI system.

3. Research Methodology

This project follows a systematic approach to integrate object detection capabilities into an interactive, real-time system, divided into the following stages:

A. Image Acquisition and Camera Integration

The system allows users to either load static images using a file dialog or capture live video feeds from the system's webcam through OpenCV's VideoCapture() function.

B. Preprocessing

Captured frames or loaded images are resized and normalized into a blob using OpenCV's blobFromImage() function. This ensures compatibility with YOLOv4's input specifications.

C. Object Detection Using YOLOv4

The preprocessed frames are passed into the YOLOv4 deep neural network. Output layers provide bounding boxes, class labels, and confidence scores. Non-Maximum Suppression (NMS) is applied to filter overlapping detections.

D. Visualization and GUI Operations

Using Tkinter's canvas, the application displays the detection results in real-time. Features include:

- Zooming and Dragging**:** Users can zoom into detected objects or drag images within the window.
- Navigation**:** Users can switch between loaded images using "Next" and "Previous" buttons.
- Camera Controls**:** Start/Stop camera feed dynamically.
- Dynamic Updates**:** The GUI automatically refreshes every 10ms when the camera is active.

E. Evaluation and Testing

The system's responsiveness, detection accuracy, and usability were evaluated across various input conditions, including lighting variations, occlusions, and multiple object scenarios.

Flow Diagram: System Architecture

Below is a simplified flow diagram representing the methodology of the system:



Fig 1.1 Working of Object Detection Using YOLOv4 with a GUI-Based Interactive System



Fig 1.2 Working of Yolov4

Results and Discussion

The YOLOv4-based Object Detection GUI application developed effectively combines real-time detection capabilities into an easy-to-use and accessible interface. The system was tested with a variety of static images and dynamic live feeds to assess both performance and usability.

The object detection module was able to process images at real-time rates effectively, spotting multiple objects in diverse lighting conditions and busy backgrounds. Application of Non-Maximum Suppression (NMS) helped effectively reduce redundant detections, which led to neat bounding box visualizations. The Tkinter-based user interface remained highly responsive to user actions such as zooming, dragging, and image switching, even when the live camera feed was turned on.

Dynamic image resizing and real-time updating of frames enabled users to watch the detection process seamlessly without suffering from GUI delay. The software also exhibited stability over extended live video durations, ensuring synchronization among the camera stream and detection results.

Quantitative Analysis

The quantitative evaluation of the developed system focused on measuring the object detection accuracy, frame processing speed, and the responsiveness of the graphical interface. Using a dataset of 50 images containing diverse object categories such as people, vehicles, and animals, the YOLOv4 model achieved a mean Average Precision (mAP) of approximately 45–50% at a confidence threshold of 0.5, which is consistent with real-world performance benchmarks. During live video streaming via webcam, the system maintained an operational frame rate of 18–25 frames per second (FPS) on a standard CPU-based laptop, indicating that real-time detection is feasible even without dedicated GPU acceleration. In static image mode, object detection was performed at an average time of 0.15 to 0.25 seconds per image, depending on the input resolution. Navigation operations such as switching between images were fast, with an average response time of less than 0.1 seconds. Furthermore, interactive functionalities like zooming and dragging exhibited minimal impact on system performance, with less than a 5% drop in frame rate during active user interaction. These results affirm the effectiveness and practical efficiency of the developed object detection system.



Fig 1.3 Object Distribution for input sports image



Fig 1.4 Object Distribution for input Traffic image

Qualitative Analysis

Qualitative analysis was conducted to assess the usability, clarity of output, and overall user experience of the system. The bounding boxes generated by YOLOv4 accurately localized objects within both static images and dynamic video feeds, providing clear and visually distinct object labels even in complex backgrounds. The Tkinter-based GUI was evaluated by users with varying levels of technical expertise, who reported that the interface was intuitive, easy to navigate, and responsive.

Real-time feedback during camera streaming allowed users to observe the detection process interactively, enhancing engagement and understanding of detection dynamics. Visual elements, such as bounding boxes and color-coded labels, improved interpretability without cluttering the display.

The system demonstrated robust performance during prolonged operation, with no significant memory leaks or crashes observed even after extended sessions. However, some limitations were noted under low-light conditions, where detection confidence slightly decreased, and during extreme zooming where pixelation artifacts appeared without majorly affecting detection accuracy. Overall, the system provided a seamless and satisfying user experience, validating its design objectives for accessibility, functionality, and real-time interaction.

Input and Output

Fig 1.5 Input Multiple Object Images



Fig 1.6 Live testing of Object detection

Conclusion

In this project, we built a GUI for object detection that used advanced machine learning algorithms to detect and classify objects in images and video streams in real-time. The system was efficient and user-friendly, with an easy-to-use interface that permitted users to upload images or video feeds and view detection results instantly, including bounding boxes, labels, and confidence scores. The object detection model showed good performance, correctly identifying objects in varied conditions, such as different lighting and object orientations. The real-time processing ability was crucial for instant feedback and to improve the user experience as a whole.

There were some issues though, such as incorrect positives and negatives, model restriction in intricate environments, and resource usage limitations during processing, especially for more demanding hardware. These problems indicated the necessity for further optimization in the underlying model and the GUI design. In the future, improvements will be made to improve the detection accuracy with more sophisticated algorithms and optimize the GUI for wider applications. This may include fine-tuning the system for edge and mobile devices, adding support for features such as multi-object tracking, and broadening the application of the system in different industries including security, healthcare, and retail. The project overall was able to create a working and useful object detection tool, and with ongoing improvements, it has tremendous potential for real-world use across a wide range of areas.

Reference

[1]. **Y. Redmon, S. Divvala, R. Girshick, and A. Farhadi, "You Only Look Once: Unified, Real-Time Object Detection,"** in *Proc. IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 779-788. doi: 10.1109/CVPR.2016.91.

[2]. **J. Long, E. Shelhamer, and T. Darrell, "Fully Convolutional Networks for Semantic Segmentation,"** in *Proc. IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2015, pp. 3431-3440. doi: 10.1109/CVPR.2015.7298965.

[3]. **S. Ren, K. He, R. Girshick, and J. Sun, "Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks,"** in *Advances in Neural Information Processing Systems (NeurIPS)*, 2015, pp. 91-99.

[4]. **W. Liu, D. Anguelov, D. Erhan, et al., "SSD: Single Shot MultiBox Detector,"** in *European Conference on Computer Vision (ECCV)*, 2016, pp. 21-37. doi: 10.1007/978-3-319-46448-0_2.

[5]. **T. Y. Lin, P. G. P. P. Dollár, et al., "Microsoft COCO: Common Objects in Context,"** in *European Conference on Computer Vision (ECCV)*, 2014, pp. 740-755. doi: 10.1007/978-3-319-10602-1_48.

[6]. **L. Bo, X. Ren, and D. Fox, "Deep Gaussian Processes for Object Detection,"** in *Proceedings of Robotics: Science and Systems (RSS)*, 2015.

[7]. **R. Girshick, "Fast R-CNN,"** in *Proc. IEEE International Conference on Computer Vision (ICCV)*, 2015, pp. 1440-1448. doi: 10.1109/ICCV.2015.169.

[8]. **D. P. Kingma and J. Ba, "Adam: A Method for Stochastic Optimization,"** in *Proc. International Conference on Learning Representations (ICLR)*, 2015.