DCL ACTIVITIES

ROOT ACTIVITES: -

SEARCHING USER AT LOCAL MYSQL SERVER.

```
mysql> SELECT USER FROM MYSQL.USER;
+------------------+
| USER             |
+------------------+
| VIT              |
| mysql.infoschema |
| mysql.session    |
| mysql.sys        |
| root             |
| student1         |
```

CREATING NEW USER AT LOCAL SERVER

```
mysql> CREATE USER 'emp'@'LOCALHOST' IDENTIFIED BY 'emp';
```

CHECKING USER AT LOCAL MYSQL SERVER.

```
mysql> SELECT USER FROM MYSQL.USER;
+------------------+
| USER             |
+------------------+
| VIT              |
| EMP              |
| mysql.infoschema |
| mysql.session    |
| mysql.sys        |
```

| root |

| student1 |

SEARCHING DATABASE

```
mysql> SHOW DATABASES;
+--------------------+
| Database           |
+--------------------+
| emp                |
| information_schema |
| mysql              |
| performance_schema |
| ravi               |
| student            |
| sys                |
| university         |
+--------------------+
8 rows in set (0.01 sec)
```

CHOOSE ANY DATABASE AND TABLE FROM LIST

```
mysql> USE EMP;
Database changed
mysql> SHOW TABLES;
+---------------+
| Tables_in_emp |
+---------------+
| dept          |
| dept1         |
| emp_prof      |
| students      |
+---------------+
4 rows in set (0.01 sec)
```

SEARCH DATA INTO TABLE

```
mysql> SELECT * FROM EMP_PROF;
+------+-------+
| ID   | ENAME |
+------+-------+
|    1 | AJAY  |
|  101 | AJAY  |
|    2 | AJAY  |
+------+-------+
3 rows in set (0.01 sec)
```

GRANTING PERMISSION TO THE USER I.E. DATABASE

```
mysql> GRANT SELECT ON EMP.EMP_PROF TO 'DATABASE'@'LOCALHOST';
Query OK, 0 rows affected (0.01 sec)
```

NOW COME TO THE CLIENT PART & CHECK THE GRANTED PERMISSION:-

1. GOTO COMMAND PROMPT .
2. OPEN IT.
3. NOW SELECT THE INSTALLATION PATH OF MYSQL SERVER AS BELOW

   GOTO= C:\Program Files\MySQL\MySQL Server 8.0\bin

4. NOW PAST THE COPIED PATH ON C: PROMPT LIKE BELOW:-

```
C:\Users\Dr.Ravi Verma> CD C:\Program Files\MySQL\MySQL Server 8.0\bin
```

C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql -u emp -p

Enter password: *

SHOW DATABASE IN THAT USER LOGIN

mysql> SHOW DATABASES;

```
+--------------------+
| Database           |
+--------------------+
| emp                |
| information_schema |
+--------------------+
```

USE ANY DATABASE TO WORK IN THAT

mysql> USE EMP;

Database changed

CHECK AVAILABILITY OF TABLES

mysql> SHOW TABLES;

```
+---------------+
| Tables_in_emp |
+---------------+
| emp_prof      |
+---------------+
```

1 row in set (0.00 sec)

mysql> SELECT * FROM EMP_PROF;

+------+-------+

| ID | ENAME |

+------+-------+

| 1 | AJAY |

| 101 | AJAY |

| 2 | AJAY |

+------+-------+

3 rows in set (0.00 sec)

THE USER EMP IS GRANTED FOR PERFORMING SELECT OPERATION SO THAT ITS WORKING AS PER ASSIGNED PERMISSIONS.

NOW IF WE TRY TO FIRE OTHER COMMAND FOR WHICH USER EMP DON'T HAVE ANY PERMISSION.

mysql> insert into emp_prof(id,ename)values(121,'anil');

ERROR 1142 (42000): INSERT command denied to user 'emp'@'localhost' for table 'emp_prof'

Now if ROOT granting the permission to insert into emp to emp user .

mysql> GRANT insert ON EMP.EMP_PROF TO 'emp'@'LOCALHOST';

Query OK, 0 rows affected (0.01 sec)

mysql> insert into emp_prof(id,ename)values(121,'anil');

Query OK, 1 row affected (0.01 sec)

mysql> select * from emp_prof;

```
+------+-------+
| ID   | ENAME |
+------+-------+
|    1 | AJAY  |
|  101 | AJAY  |
|    2 | AJAY  |
|  121 | anil  |
+------+-------+
```

4 rows in set (0.00 sec)

REVOKING THE SELECT OPERATION FROM EMP.

mysql> revoke select on emp.emp_prof from emp@localhost;

Query OK, 0 rows affected (0.01 sec)

EXAMPLE;-

mysql> select * from emp_prof;

ERROR 1142 (42000): SELECT command denied to user 'emp'@'localhost' for table 'emp_prof'