# PRACTICAL -06 & 07



# BASIC IPV6 ADDRESSING WITH CISCO PACKET TRACER

**Aim:**

- To demonstrate IPV6 Addressing using Cisco Packet Tracer.

**Objective:**

- Configuring a router in order to enable communication between two IPV6 networks.

# PROCEDURE

- Start up Cisco Packet Tracer, and place a couple end devices of your choice.
- Form a LAN by connecting the devices with a switch; repeat to form a second LAN, then connect them both with a router.
- Open the Command Line Interface for the router, and enable IPV6 addressing.
- Set an IPV6 address for each port, and a separate local link address.
- Now, configure an IP for each device; this is made easier by the option to let the device automatically figure out the address by communicating with the router.
- Test whether the connection works by pinging a device from one LAN to another.

# IMPLEMENTATION OF ARP USING CISCO PACKET TRACER

**Aim:**

- To demonstrate ARP (Address Resolution Protocol) using Cisco Packet Tracer.

**Objective:**

- Configuring a setup involving switches, end devices and a server in order to demonstrate the working of the Address Resolution Protocol.

# PROCEDURE

- Start up Cisco Packet Tracer, and place a few end devices of your choice.
- Connect them all using a switch.
- For each of them: double-click the device, go to the Desktop tab, click on IP Configuration and set an IP.
- Make sure to give them all similar IPs – say, if an address is p.q.r.s, keep the 'p', 'q', and 'r' values equal for all 4 end devices.
- A LAN has now been formed.
- Double-click any two of the devices, go to the Command Prompt, and type 'arp -a'; this shows you the ARP table for that device.
- Ignore the 'no entries found' message for now. From any one device, ping another device in the LAN.
- Now, ping the first device with that other device's Command Prompt.
- Check the ARP tables of both tables using 'arp -a' again.