

```

#include<stdio.h>
struct node
{
int info;
struct node *next;
};
typedef struct node * nodeptr;
nodeptr p,list,temp;

nodeptr getnode();
void push(int);
void pop();
void display();

void main()
{
int c,i,x;
char ch;
do
{
printf("Menu\n");
printf("1. push \n 2. pop\n 3. display\n");
scanf(" %d",&c);
switch(c)
{
case 1: printf("enter the number\n");
scanf("%d",&x);
push(x);
break;
case 2: pop();
break;
case 3: display();
break;
}
printf("\ndo you want to continue\n");
scanf(" %c",&ch);
}while(ch!='n');
}

nodeptr getnode()
{
nodeptr p;
p=(nodeptr)malloc(sizeof(struct node));

```

```
return p;  
}
```

```
void push(int x)  
{  
    temp=getnode();  
    temp->info=x;  
    temp->next=list;  
    list=temp;  
    return;  
}
```

```
void pop()  
{  
    if(list==NULL)  
        printf("deletion not possible. No nodes existed\n");  
    else  
    {  
        p=list;  
        list=p->next;  
        p->next=NULL;  
        printf("Deleted node info value is %d",p->info);  
        free(p);  
    }  
}
```

```
void display()  
{  
    if(list==NULL)  
        printf("No nodes in the list\n");  
    p=list;  
    while(p!=NULL)  
    {  
        printf("%d\t",p->info);  
        p=p->next;  
    }  
}
```