# **Electrostatic Potential** and Capacitance

- 1. On moving a charge of 20 coulomb by 2 cm, 2 J of work is done, then the potential difference between the points is [2002]
  - (a) 0.1 V
- (b) 8V
- (c) 2V
- (d) 0.5 V.
- 2. If there are *n* capacitors in parallel connected to V volt source, then the energy stored is equal to
- (b)  $\frac{1}{2} nCV^2$
- (d)  $\frac{1}{2n}CV^2$
- Capacitance (in F) of a spherical conductor with 3. radius 1 m is [2002]
  - (a)  $1.1 \times 10^{-10}$
- (c)  $9 \times 10^{-9}$
- A sheet of aluminium foil of negligible thickness 4. is introduced between the plates of a capacitor. The capacitance of the capacitor [2003]
  - (a) decreases
  - (b) remains unchanged
  - (c) becomes infinite
  - (d) increases
- 5. A thin spherical conducting shell of radius R has a charge q. Another charge Q is placed at the centre of the shell. The electrostatic potential at a point P, a distance  $\frac{R}{2}$  from the centre of the

  - (a)  $\frac{2Q}{4\pi\epsilon_0 R}$  (b)  $\frac{2Q}{4\pi\epsilon_0 R} \frac{2q}{4\pi\epsilon_0 R}$
  - (c)  $\frac{2Q}{4\pi\varepsilon_{o}R} + \frac{q}{4\pi\varepsilon_{o}R}$  (d)  $\frac{(q+Q)2}{4\pi\varepsilon_{o}R}$

- The work done in placing a charge of  $8 \times 10^{-18}$ coulomb on a condenser of capacity 100 micro-farad is [2003]
  - (a)  $16 \times 10^{-32}$  joule
  - (b)  $3.1 \times 10^{-26}$  joule
  - (c)  $4 \times 10^{-10}$  joule
  - (d)  $32 \times 10^{-32}$  joule
- Two thin wire rings each having a radius R are placed at a distance d apart with their axes coinciding. The charges on the two rings are +qand -q. The potential difference between the centres of the two rings is [2005]

(a) 
$$\frac{q}{2\pi \in_0} \left[ \frac{1}{R} - \frac{1}{\sqrt{R^2 + d^2}} \right]$$

(b) 
$$\frac{qR}{4\pi \in_0 d^2}$$

(c) 
$$\frac{q}{4\pi \in_0} \left[ \frac{1}{R} - \frac{1}{\sqrt{R^2 + d^2}} \right]$$

- (d) zero
- 8. A parallel plate capacitor is made by stacking n equally spaced plates connected alternatively. If the capacitance between any two adjacent plates is 'C' then the resultant capacitance is


[2005]

- (a) (n+1) C
- (b) (n-1) C
- (c) nC
- A fully charged capacitor has a capacitance 'C'. It is discharged through a small coil of resistance wire embedded in a thermally insulated block of specific heat capacity 's' and mass 'm'. If the


temperature of the block is raised by ' $\Delta T$ ', the potential difference 'V' across the capacitance is [2005]

#### **Electrostatic Potential and Capacitance**

- Two insulating plates are both uniformly charged in such a way that the potential difference between them is  $V_2 - V_1 = 20$  V. (i.e., plate 2 is at a higher potential). The plates are separated by d = 0.1 m and can be treated as infinitely large. An electron is released from rest on the inner surface of plate 1. What is its speed when it hits plate 2?  $(e = 1.6 \times 10^{-19} \text{ C}, m_a = 9.11 \times 10^{-31} \text{ kg})$



- (a)  $2.65 \times 10^6 \,\text{m/s}$  (b)  $7.02 \times 10^{12} \,\text{m/s}$
- (c)  $1.87 \times 10^6 \,\mathrm{m/s}$
- (d)  $32 \times 10^{-19} \text{ m/s}$
- An electric charge  $10^{-3} \,\mu$  C is placed at the origin (0,0) of X-Y co-ordinate system. Two points Aand B are situated at  $(\sqrt{2}, \sqrt{2})$  and (2, 0)respectively. The potential difference between the points A and B will be [2007]
  - (a) 4.5 volts
- (b) 9 volts
- (c) Zero
- (d) 2 volt
- **12.** Charges are placed on the vertices of a square as shown. Let  $\vec{E}$  be the electric field and V the potential at the centre. If the charges on A and B are interchanged with those on D and C respectively, then [2007]



- E changes, V remains unchanged
- E remains unchanged, V changes

- (c) both  $\vec{E}$  and V change
- (d)  $\vec{E}$  and V remain unchanged
- The potential at a point x (measured in  $\mu$  m) due to some charges situated on the x-axis is given by  $V(x) = 20/(x^2 - 4)$  volt. The electric field E at  $x = 4 \mu \text{ m}$  is given by [2007]
  - (a) (10/9) volt/  $\mu$  m and in the +ve x direction
  - (b) (5/3) volt/ $\mu$  m and in the –ve x direction
  - (c) (5/3) volt/ $\mu$  m and in the +ve x direction
  - (d) (10/9) volt/  $\mu$  m and in the –ve x direction
- A parallel plate condenser with a dielectric of dielectric constant K between the plates has a capacity C and is charged to a potential V volt. The dielectric slab is slowly removed from between the plates and then reinserted. The net work done by the system in this process is [2007]
  - (a) zero
- zero (b)  $\frac{1}{2}(K-1) CV^2$   $\frac{CV^2(K-1)}{K}$  (d)  $(K-1) CV^2$

P-97

- A parallel plate capacitor with air between the plates has capacitance of 9 pF. The separation between its plates is 'd'. The space between the plates is now filled with two dielectrics. One of the dielectrics has dielectric constant  $k_1 = 3$  and

thickness  $\frac{d}{3}$  while the other one has dielectric

constant  $k_2 = 6$  and thickness  $\frac{2d}{3}$ . Capacitance of the capacitor is now [2008]

- (a) 1.8 pF
- (b) 45 pF
- (c) 40.5 pF
- (d) 20.25 pF
- Two points P and Q are maintained at the potentials of 10 V and -4 V, respectively. The work done in moving 100 electrons from P to Q
  - $9.60 \times 10^{-17}$ J
    - (b)  $-2.24 \times 10^{-16} \,\mathrm{J}$

  - (c)  $2.24 \times 10^{-16} \,\text{J}$  (d)  $-9.60 \times 10^{-17} \,\text{J}$
- Two positive charges of magnitude 'q' are placed, at the ends of a side (side 1) of a square of side '2a'. Two negative charges of the same magnitude are kept at the other corners. Starting from rest, if a charge Q moves from the middle of side 1 to the centre of square, its kinetic energy at the centre of square is [2011 RS]

P-98 Physics

(a) zero

(b) 
$$\frac{1}{4\pi\varepsilon_0} \frac{2qQ}{a} \left( 1 + \frac{1}{\sqrt{5}} \right)$$

(c) 
$$\frac{1}{4\pi\varepsilon_0} \frac{2qQ}{a} \left( 1 - \frac{2}{\sqrt{5}} \right)$$

(d) 
$$\frac{1}{4\pi\varepsilon_0} \frac{2qQ}{a} \left( 1 - \frac{1}{\sqrt{5}} \right)$$

18. This questions has statement-1 and statement-2. Of the four choices given after the statements, choose the one that best describes the two statements.

An insulating solid sphere of radius R has a uniformly positive charge density  $\rho$ . As a result of this uniform charge distribution there is a finite value of electric potential at the centre of the sphere, at the surface of the sphere and also at a point outside the sphere. The electric potential at infinite is zero. [2012]

**Statement -1** When a charge q is taken from the centre to the surface of the sphere its potential


energy changes by  $\frac{q\rho}{3\epsilon_0}$  .


**Statement -2** The electric field at a distance r (r < R) from the centre of the sphere is  $\frac{\rho r}{3\epsilon_0}$ .


- (a) Statement 1 is true, Statement 2 is true; Statement 2 is not the correct explanation of statement 1.
- (b) Statement 1 is true Statement 2 is false.
- (c) Statement 1 is false Statement 2 is true.
- (d) Statement 1 is true, Statement 2 is true, Statement 2 is the correct explanation of Statement 1
- 19. Assume that an electric field  $\vec{E} = 30x^2\hat{i}$  exists in space. Then the potential difference  $V_A V_O$ , where  $V_O$  is the potential at the origin and  $V_A$  the potential at x = 2 m is: [2014]
  - (a) 120 J/C
- (b) -120 J/C
- (c) -80 J/C
- (d) 80 J/C
- **20.** A parallel plate capacitor is made of two circular plates separated by a distance 5 mm and with a


dielectric of dialectric constant 2.2 between them. When the electric field in the dielectric is  $3 \times 10^4$  V/m the charge density of the positive plate will be close to: [2014]


- (a)  $6 \times 10^{-7} \text{ C/m}^2$  (b)  $3 \times 10^{-7} \text{ C/m}^2$
- (c)  $3 \times 10^4 \text{ C/m}^2$  (d)  $6 \times 10^4 \text{ C/m}^2$
- 21. In the given circuit, charge  $Q_2$  on the  $2\mu F$  capacitor changes as C is varied from  $1\mu F$  to  $3\mu F$ .  $Q_2$  as a function of 'C' is given properly by: (figures are drawn schematically and are not to scale) [2015]












22. A uniformly charged solid sphere of radius R has potential  $V_0$  (measured with respect to  $\infty$ ) on its surface. For this sphere the equipotential

### **Electrostatic Potential and Capacitance**

surfaces with potentials  $\frac{3V_0}{2}, \frac{5V_0}{4}, \frac{3V_0}{4}$  and

 $\frac{V_0}{4}$  have radius  $R_1$ ,  $R_2$ ,  $R_3$  and  $R_4$  respectively. Then [2015]

- (a)  $R_1 = 0$  and  $R_2 < (R_4 R_3)$
- (b)  $2R < R_4$
- (c)  $R_1 = 0$  and  $R_2 > (R_4 R_3)$
- (d)  $R_1 \neq 0$  and  $(R_2 R_1) > (R_4 R_3)$
- 23. A combination of capacitors is set up as shown in the figure. The magnitude of the electric field, due to a point charge Q (having a charge equal to the sum of the charges on the 4  $\,\mu$  F and 9  $\,\mu$  F capacitors), at a point distance 30 m from it, would equal: [2016]



- (a) 420 N/C
- (b) 480 N/C

P-99

- (c) 240 N/C
- (d) 360 N/C
- 24. A capacitance of 2μF is required in an electrical circuit across a potential difference of 1.0 kV. A large number of 1μF capacitors are available which can withstand a potential difference of not more than 300 V. The minimum number of capacitors required to achieve this is [2017]
  - (a) 24
- (b) 32
- (c) 2
- (d) 16

Answer Key														
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
(a)	(b)	(a)	(b)	(c)	(d)	(a)	(b)	(c)	(a)	(c)	(a)	(a)	(a)	(c)
16	17	18	19	20	21	22	23	24						
(c)	(d)	(c)	(c)	(a)	(d)	(a)	(a)	(b)						


## SOLUTIONS

1. (a) We know that  $\frac{W_{AB}}{q} = V_B - V_A$ 

$$V_B - V_A = \frac{2 \text{ J}}{20 \text{ C}} = 0.1 \text{ J/C} = 0.1 \text{ V}$$

**2. (b)** The equivalent capacitance of n identical capacitors of capacitance C is equal to nC. Energy stored in this capacitor

$$E = \frac{1}{2}(nC)V^2 = \frac{1}{2}nCV^2$$



Alternatively

Each capacitor has a potential difference

of *V* between the plates. So energy stored in each capacitor

$$=\frac{1}{2}CV^2.$$

: Energy stored in n capacitor

$$= \left\lceil \frac{1}{2}CV^2 \right\rceil \times n$$

**3. (a)** For an isolated sphere, the capacitance is given by

$$C = 4\pi \in_0 r = \frac{1}{9 \times 10^9} \times 1 = 1.1 \times 10^{-10} \,\mathrm{F}$$

**4. (b)** The capacitance of a parallel plate capacitor in which a metal plate of thickness t is inserted is given by

$$C = \frac{\varepsilon_o A}{d - t}$$
. Here  $t \to 0$  :  $C = \frac{\varepsilon_o A}{d}$ 

5. (c) Electric potential due to charge Q placed at the centre of the spherical shell at point P is



$$V_1 = \frac{1}{4\pi\varepsilon_o} \frac{Q}{R/2} = \frac{1}{4\pi\varepsilon_o} \frac{2Q}{R}$$

Electric potential due to charge q on the surface of the spherical shell at any point inside the shell is

$$V_2 = \frac{1}{4\pi\varepsilon_o} \frac{q}{R}$$

... The net electric potential at point P is


$$V=V_1+V_2=\frac{1}{4\pi\varepsilon_o}\,\frac{2Q}{R}+\frac{1}{4\pi\varepsilon_o}\,\frac{q}{R}$$

**6. (d)** The work done is stored as the potential energy. The potential energy stored in a capacitor is given by

$$U = \frac{1}{2} \frac{Q^2}{C} = \frac{1}{2} \times \frac{\left(8 \times 10^{-18}\right)^2}{100 \times 10^{-6}}$$

 $=32\times10^{-32}\,\mathrm{J}$ 





At (1) using, potential

$$(V_1) = V_{\text{self}} + V_{\text{due to (2)}}$$

$$\Rightarrow V_1 = \frac{1}{4\pi\varepsilon_0} \left[ \frac{q}{R} - \frac{q}{\sqrt{R^2 + d^2}} \right]$$

At (2) using potential

$$(V_2) = V_{\text{self}} + V_{\text{due to (1)}}$$

$$\Rightarrow V_2 = \frac{1}{4\pi\varepsilon_0} \left[ \frac{-q}{R} + \frac{q}{\sqrt{R^2 + d^2}} \right]$$

$$\Delta V = V_1 - V_2$$

$$= \frac{1}{4\pi\varepsilon_0} \left[ \frac{q}{R} + \frac{q}{R} - \frac{q}{\sqrt{R^2 + d^2}} - \frac{q}{\sqrt{R^2 + d^2}} \right]$$
$$= \frac{1}{2\pi\varepsilon_0} \left[ \frac{q}{R} - \frac{q}{\sqrt{R^2 + d^2}} \right]$$

**8. (b)** As n plates are joined, it means (n-1) combination joined in parallel.

 $\therefore$  resultant capacitance = (n-1) C


9. (c) Applying conservation of energy,

$$\frac{1}{2}CV^2 = m.s \,\Delta t; \quad V = \sqrt{\frac{2m.s.\Delta t}{C}}$$

**10.** (a)  $eV = \frac{1}{2}mv^2$ 

$$\Rightarrow v = \sqrt{\frac{2eV}{m}} = \sqrt{\frac{2 \times 1.6 \times 10^{-19} \times 20}{9.1 \times 10^{-31}}}$$

 $= 2.65 \times 10^6 \text{ m/s}$ 



The distance of point  $A(\sqrt{2}, \sqrt{2})$  from the origin,

 $OA = |\vec{r_1}| = \sqrt{(\sqrt{2})^2 + (\sqrt{2})^2} = \sqrt{4} = 2$ units. The distance of point B(2, 0) from the origin,

$$OB = |\vec{r_2}| = \sqrt{(2)^2 + (0)^2} = 2 \text{ units.}$$

Now, potential at A,  $V_A = \frac{1}{4\pi \in_0} \cdot \frac{Q}{(OA)}$ 


Potential at B, 
$$V_B = \frac{1}{4\pi \in_0} \cdot \frac{Q}{(OB)}$$

 $\therefore$  Potential difference between the points A and B is given by

$$\begin{split} V_A - V_B &= \frac{1}{4\pi \in_0} \cdot \frac{Q}{OA} - \frac{1}{4\pi \in_0} \cdot \frac{Q}{OB} \\ &= \frac{Q}{4\pi \in_0} \left( \frac{1}{OA} - \frac{1}{OB} \right) = \frac{Q}{4\pi \in_0} \left( \frac{1}{2} - \frac{1}{2} \right) \\ &= \frac{Q}{4\pi \in_0} \times 0 = 0. \end{split}$$

## Electrostatic Potential and Capacitance

As shown in the figure, the resultant electric fields before and after interchanging the charges will have the same magnitude, but opposite directions. Also, the potential will be same in both cases as it is a scalar quantity.



13. (a) Here,  $V(x) = \frac{20}{x^2}$  volt We know that  $E = -\frac{dV}{dx} = -\frac{d}{dx} \left( \frac{20}{x^2 - 4} \right)$ or,  $E = +\frac{40x}{(x^2-4)^2}$  $E = +\frac{40 \times 4}{(4^2 - 4)^2} = +\frac{160}{144} = +\frac{10}{9} \text{ volt} / \mu \text{m}.$ 

> Positive sign indicates that  $\vec{E}$  is in +ve xdirection.

The potential energy of a charged capacitor is given by  $U = \frac{Q^2}{2C}$ . If a dielectric slab is inserted between the plates, the energy is given by  $\frac{Q^2}{2KC}$ , where *K* is the dielectric constant.

Again, when the dielectric slab is removed slowly its energy increases to initial potential energy. Thus, work done is zero.

5. (c) 
$$K_2$$
  $=$   $C_1$   $C_2$ 

The given capacitance is equal to two capacitances connected in series where

$$C_1 = \frac{k_1 \in_0 A}{d/3} = \frac{3k_1 \in_0 A}{d}$$
$$= \frac{3 \times 3 \in_0 A}{d} = \frac{9 \in_0 A}{d}$$
and

$$\begin{split} C_1 &= \frac{k_2 \in_0 A}{2d/3} = \frac{3k_2 \in_0 A}{2d} \\ &= \frac{3 \times 6 \in_0 A}{2d} = \frac{9 \in_0 A}{d} \end{split}$$
 The equivalent capacitance  $C_{\text{eq}}$  is

$$\frac{1}{C_{\text{eq}}} = \frac{1}{C_1} + \frac{1}{C_2}$$

$$= \frac{d}{9 \in_0 A} + \frac{d}{9 \in_0 A} = \frac{2d}{9 \in_0 A}$$

$$\therefore C_{eq} = \frac{9}{2} \frac{\in_0 A}{d} = \frac{9}{2} \times 9 \ pF = 40.5 pF$$

16. (c) 
$$\frac{W_{PQ}}{q} = (V_Q - V_P)$$
$$\Rightarrow W_{PQ} = q(V_Q - V_P)$$
$$= (-100 \times 1.6 \times 10^{-19}) (-4 - 10)$$
$$= +2.24 \times 10^{-16} \text{J}$$


(d) Potential at point A.

$$V_A = \frac{2kq}{a} - \frac{2kq}{a\sqrt{5}}$$

 $\therefore$  (potential due to each  $q = \frac{kq}{q}$  and

potential due to each  $-q = \frac{-kq}{q\sqrt{5}}$ )

P-102 Physics



Potential at point. B,

$$V_B = 0$$

(  $\because$  Point *B* is equidistant from all the four charges)

:. Using work energy theorem,

$$(W_{AB})_{electric} = Q(V_A - V_B)$$

$$= \frac{2kqQ}{a} \left[ 1 - \frac{1}{\sqrt{5}} \right]$$

$$= \left( \frac{1}{4\pi\epsilon_0} \right) \frac{2Qq}{a} \left[ 1 - \frac{1}{\sqrt{5}} \right]$$


**18. (c)** The potential energy at the centre of the sphere

$$U_c = \frac{3}{2} \frac{KQq}{R}$$

The potential energy at the surface of the sphere

$$U_S = \frac{KqQ}{R}$$

Now change in the energy



Where  $Q = \rho . V = \rho . \frac{4}{3} \pi R^3$ 

$$\Delta U = \frac{2K}{3} \frac{\pi R^3 \rho q}{R}$$
$$\Delta U = \frac{2}{3} \times \frac{1}{4\pi \in_0} \frac{\pi R^3 \rho q}{R}$$

$$\Delta U = \frac{R^2 \rho q}{6 \in_0}$$

19. (c) Potential difference between any two points in an electric field is given by,

$$dV = -\overrightarrow{E}.\overrightarrow{dx}$$

$$\int_{V_O}^{V_A} dV = -\int_0^2 30x^2 dx$$

$$V_A - V_O = -[10x^3]_0^2 = -80J/C$$

**20.** (a) Electric field in presence of dielectric between the two plates of a parallel plate capaciator is given by,

$$E = \frac{\sigma}{K \varepsilon_0}$$

Then, charge density

$$σ = K ε0 E$$
= 2.2 × 8.85 × 10<sup>-12</sup> × 3 × 10<sup>4</sup>
≈ 6 × 10<sup>-7</sup> C/m<sup>2</sup>


=  $\frac{\sigma.s}{v}$  (Let surface area of plates = s)

$$= \frac{\sigma.s}{\frac{\sigma}{\lambda} \ln\left(1 + \frac{\lambda d}{K_0}\right)}$$

$$= s\lambda \cdot \frac{d}{d} \frac{1}{\ln\left(1 + \frac{\lambda d}{K_0}\right)} \quad (\because \text{ in vacuum } \varepsilon_0 = 1)$$

$$\frac{\lambda d}{d} = \sigma \cdot \left(1 - \sigma \cdot \frac{s}{\delta}\right)$$

$$c = \frac{\lambda d}{\ln\left(1 + \frac{\lambda d}{K_0}\right)} \cdot C_0 \quad \left(\text{here, } C_0 = \frac{s}{d}\right)$$



21. (d)


From figure, 
$$Q_2 = \frac{2}{2+1}Q = \frac{2}{3}Q$$

$$Q = E\left(\frac{C \times 3}{C+3}\right)$$

## **Electrostatic Potential and Capacitance**

 $\therefore Q_2 = \frac{2}{3} \left( \frac{3CE}{C+3} \right) = \frac{2CE}{C+3}$ 

Therefore graph d correctly dipicts.



22. (a) We know,  $V_0 = \frac{Kq}{R} = Vsurface$ 

Now, 
$$V_i = \frac{Kq}{2R^3} (3R^2 - r^2)$$
 [For  $r < R$ ]

At the centre of sphare r = 0. Here

$$V = \frac{3}{2}V_0$$

Now, 
$$\frac{5}{4} \frac{Kq}{R} = \frac{Kq}{2R^3} (3R^2 - r^2)$$

$$R_2 = \frac{R}{\sqrt{2}}$$

$$\frac{3}{4}\frac{Kq}{R} = \frac{Kq}{R^3}$$

$$\frac{1}{4}\frac{Kq}{R} = \frac{Kq}{R_4}$$

$$R_4 = 4R$$

Also,  $R_1 = 0$  and  $R_2 < (R_4 - R_3)$ 

-P-103

23. (a)  ${}^{4\mu F}_{9\mu F}$   $\Rightarrow$   ${}^{C_1 = 4\mu F}_{12\mu F} = C_P$ 

Charge on 
$$C_1$$
 is  $q_1 = \left\lceil \left( \frac{12}{4+12} \right) \times 8 \right\rceil \times 4 =$ 

24μc

The voltage across  $C_p$  is  $V_p = \frac{4}{4+12} \times 8 = 2v$ 

- ∴ Voltage across 9µF is also 2V
- $\therefore$  Charge on 9µF capacitor =  $9 \times 2 = 18\mu$ C
- $\therefore$  Total charge on 4  $\mu$ F and 9 $\mu$ F = 42 $\mu$ c

$$\therefore E = \frac{KQ}{r^2} = 9 \times 10^9 \times \frac{42 \times 10^{-6}}{30 \times 30}$$
$$= 420 \text{ NC}^{-1}$$

24. (b) To get a capacitance of 2μF arrangement of capacitors of capacitance 1μF as shown in figure 8 capacitors of 1μF in parallel with four such branches in series i.e., 32 such capacitors are required.

