

Week-4

B.Shashwath

250701697

1. 1-DP-Playing with Numbers:

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3. Write any efficient algorithm to find the possible ways.

Example 1:

Input: 6

Output: 6

Explanation: There are 6 ways to 6 represent number with 1 and 3

$1+1+1+1+1+1$

$3+3$

$1+1+1+3$

$1+1+3+1$

$1+3+1+1$

$3+1+1+1$

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

```

#include <stdio.h>

long long countWays(int n) {
    if (n <= 2) {
        return 1;
    }
    long long a = 1;
    long long b = 1;
    long long c = 1;
    long long current;

    for (int i = 3; i <= n; i++) {
        current = c + a;
        a = b;
        b = c;
        c = current;
    }

    return c;
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        printf("%lld\n", countWays(n));
    }
    return 0;
}

```

	Input	Expected	Got	
✓	6	6	6	✓
✓	25	8641	8641	✓
✓	100	24382819596721629	24382819596721629	✓

Passed all tests! ✓

2. 2-DP-Playing with chessboard:

Playing with Chessboard:

Ram is given with an $n \times n$ chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position ($n-1$, $n-1$) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is
Optimal path value: $1+2+8+7+1=19$

Input Format

First Line contains the integer n

The next n lines contain the $n \times n$ chessboard values

Output Format

Print Maximum monetary value of the path

```

#include <stdio.h>

long long maxPathSumOptimized(int n) {
    long long dp[n];
    int val;

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &val);

            if (i == 0 && j == 0) {
                dp[j] = val;
            } else if (i == 0) {
                dp[j] = dp[j - 1] + val;
            } else if (j == 0) {
                dp[j] = dp[j] + val;
            } else {
                long long max_prev = dp[j] > dp[j - 1] ? dp[j] : dp[j - 1];
                dp[j] = val + max_prev;
            }
        }
    }

    return dp[n - 1];
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        printf("%lld\n", maxPathSumOptimized(n));
    }
    return 0;
}

```

	Input	Expected	Got	
✓	3 1 2 4 2 3 4 8 7 1	19	19	✓
✓	3 1 3 1 1 5 1 4 2 1	12	12	✓
✓	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✓

Passed all tests! ✓

3. 3-DP-Longest Common Subsequence:

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	g	t	a	b	
s2	g	x	t	x	a	y	b

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab	2
azb	

```

#include <stdio.h>
#include <string.h>

#define MAX_LEN 1005

int max(int a, int b) {
    return (a > b) ? a : b;
}

int lcs(char *s1, char *s2) {
    int m = strlen(s1);
    int n = strlen(s2);

    int dp[m + 1][n + 1];
    for (int i = 0; i <= m; i++) {
        for (int j = 0; j <= n; j++) {
            if (i == 0 || j == 0) {
                dp[i][j] = 0;
            } else if (s1[i - 1] == s2[j - 1]) {
                dp[i][j] = 1 + dp[i - 1][j - 1];
            } else {
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
            }
        }
    }

    return dp[m][n];
}

int main() {
    char s1[MAX_LEN], s2[MAX_LEN];

    if (scanf("%s", s1) == 1 && scanf("%s", s2) == 1) {
        printf("%d\n", lcs(s1, s2));
    }

    return 0;
}

```

	Input	Expected	Got	
✓	aab azb	2	2	✓
✓	ABCD ABCD	4	4	✓

Passed all tests! ✓

4. 4-DP-Longest non-decreasing Subsequence:

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

```

#include <stdio.h>
int upper_bound(int arr[], int size, int key) {
    int low = 0, high = size;
    while (low < high) {
        int mid = low + (high - low) / 2;
        if (arr[mid] <= key) {
            low = mid + 1;
        } else {
            high = mid;
        }
    }
    return low;
}

int lengthOfLNDS(int nums[], int n) {
    if (n == 0) return 0;

    int tail[n];
    int length = 0;

    for (int i = 0; i < n; i++) {
        int idx = upper_bound(tail, length, nums[i]);
        tail[idx] = nums[i];
        if (idx == length) {
            length++;
        }
    }

    return length;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int nums[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }

    printf("%d\n", lengthOfLNDS(nums, n));

    return 0;
}

```

	Input	Expected	Got	
✓	9 -1 3 4 5 2 2 2 2 3	6	6	✓
✓	7 1 2 2 4 5 7 6	6	6	✓

Passed all tests! ✓