

Secure Hash Algorithm-1

The output of SHA-1 message digest is 160 bits in length, which is 32 bits more than MD5.

SHA is designed to be computationally infeasible to

- a) obtain the original message, given its message digest.**
- b) find two messages producing the same message digest.**

Working of SHA-1

Step 1 : Padding

Like MD5, the first step in SHA is add padding to the end of the original message in such a way that the length of the message is 64 bits short of a multiple of 512.

The padding bits are always added, even if the message is already 64 bits short of a multiple pf 512.

Working of SHA-1

Step 2 : Append Length

The length of the message excluding the length of the padding is now calculated and appended to the end of the padding as a 64 bit block.

Working of SHA-1

Step 3 : Divide the Input

The input message is now divided into blocks, each of length 512 bits. These blocks become the input to the message-digest processing logic.

Working of SHA-1

Step 4 : Initialize Chaining Variables

5 Chaining variables, A,B,C,D and E are initialized each of 32 bits.

In SHA, the variables A through D have the same values as they had in MD5, additionally, E is initialized as HEX C3 D2 E1 F0.

Working of SHA-1

Step 5 : Process Blocks

Step 5.1 : Copy the Chaining variables A-E into variables a-e. The combination of a-e, called abcde will be considered as a single register for storing the temporary intermediate as well as final results.

Working of SHA-1

Step 5 : Process Blocks

Step 5.2 : Divide the current 512 bit block into 16 sub blocks each consisting of 32 bits.

Working of SHA-1

Step 5 : Process Blocks

Step 5.3 : SHA has 4 rounds, each consisting of 20 steps.

Each round takes the current 512 bit block, the register abcde and a constant $K[t]$, t ranging from 0-79.

It then updates the contents of the register abcde using the SHA algorithm steps.

A major difference is the fact that we had 64 different constants defined as K in MD5, Here we have only 4 constants defined for $K[t]$. one used in each of the 4 rounds.

Working of SHA-1

Step 5 : Process Blocks


Step 5.3 :

Round	Value of t between	K[t] in Hexadecimal
1	1 and 19	5A 92 79 99
2	20 and 39	6E D9 EB A1
3	40 and 59	9F 1B BC DC
4	60 and 79	CA 62 C1 D6

Working of SHA-1

Step 5 : Process Blocks

Step 5.4 : SHA consists of 4 rounds, each consisting of 20 iterations. This makes it a total of 80 iterations.



Working of SHA-1

Step 5 : Process Blocks

Step 5.4 : Process P in each SHA-1 Round

Round	Process P
1	$(b \text{ AND } c) \text{ OR } ((\text{NOT } b) \text{ AND } (d))$
2	$b \text{ XOR } c \text{ XOR } d$
3	$(b \text{ AND } c) \text{ OR } (b \text{ AND } d) \text{ OR } (c \text{ AND } d)$
4	$(b \text{ AND } c) \text{ OR } ((\text{NOT } b) \text{ AND } (d))$

Working of SHA-1

Step 5 : Process Blocks

Step 5.4 : Calculation of $W[t]$

The values of $W[t]$ is calculated as follows:

For the first 16 words of W (i.e $t=0$ to $t=15$), the contents of the input message sub-block become the contents of $W[t]$ straightaway.

Working of SHA-1

Step 5 : Process Blocks

Step 5.4 : Calculation of $W[t]$

The values of $W[t]$ is calculated as follows:

For the first 16 words of W (i.e $t=0$ to $t=15$), the contents of the input message sub-block become the contents of $W[t]$ straightaway.

The remaining 64 values are calculated using the equation:

$$W[t] = s^{16} (W[t-16] \text{ XOR } W[t-14] \text{ XOR } W[t-8] \text{ XOR } W[t-3])$$

MD5 vs SHA-1

1. MD5 can create 128 bits long message digest while SHA1 generates 160 bits long message digest.
2. To discern the original message the attacker would need 2^{128} operations while using the MD5 algorithm. On the other hand, in SHA1 it will be 2^{160} which makes it quite difficult to find.
3. If the attacker wants to find the two messages having the same message digest, he would require 2^{64} operations for MD5 whereas 2^{80} for SHA1.
4. When it comes to security by the above-given fact SHA1 hold more points relative to MD5.
5. MD5 is faster than SHA1, but SHA1 is more complex as compared to MD5.