

1. Iteima R9500EVO (Rapier Loom) – Machine Specifications

Typical specifications of Iteima Group R9500EVO rapier loom include:

- Machine type: Rapier loom (weaving machine)
- Model: R9500EVO
- Weaving width: Wide range (industrial standard widths available up to large fabric widths)
- Weft insertion system: Single or double rapier system
- Weft selection: Electronic multi-color weft selection (up to several colors depending on configuration)
- Shedding system: Electronic dobby or cam motion system (optional configurations)
- Control system: Fully computerized touch-based EVOConsole system
- Connectivity: Wi-Fi, Bluetooth, IoT-ready smart monitoring system
- Drive system: Direct drive motor with optimized energy efficiency
- Lubrication system: Automatic centralized lubrication system
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic controlled let-off system
- Fabric density: Adjustable pick density control system
- Pattern capability: Plain, twill, satin, jacquard and complex woven structures
- Yarn compatibility: Cotton, polyester, wool, silk, technical yarns, blended yarns
- Automation level: High automation with digital production monitoring
- Production monitoring: MyWeave digital factory monitoring system
- Efficiency: High-speed weaving with low vibration and improved fabric quality
- Energy system: Energy-saving optimized mechanical design

2. Picanol OmniPlus-i Connect (Air-Jet Loom) – Machine Specifications

Typical specifications of Picanol OmniPlus-i Connect air-jet loom include:

- Machine type: Air-jet weaving machine (shuttleless loom)
- Model: OmniPlus-i Connect
- Weaving width: Approx. 190 cm to 400 cm (varies by configuration) ([Picanol](#))
- Weft insertion system: Air-jet system with main nozzle and relay nozzles
- Weft selection: Multi-color weft insertion (up to 8 colors depending on setup) ([Picanol](#))
- Control system: Fully computerized BlueBox electronic platform
- User interface: BlueTouch touchscreen display system
- Drive system: SUMO direct drive motor system
- Shed system: Electronic dobby/cam motion (configuration dependent)
- Weft insertion technology: High-speed air jet with optimized air consumption system
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic let-off system
- Fabric density: Programmable pick density control
- Pattern capability: Plain, twill, satin, jacquard, technical and industrial fabrics

- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: PicConnect IoT-based production monitoring system
- Automation level: Fully automated smart weaving system
- Energy system: Eco-efficient design with reduced air and power consumption
- Sensors: Integrated monitoring (climate, vibration, air usage, and warp/weft control) ([Textile Network](#))
- Safety system: CE-standard safety guards, emergency stop systems, light curtains

3. Toyota JAT910 (Air-Jet Loom) – Machine Specifications

Typical specifications of Toyota Industries Corporation JAT910 air-jet loom include:

- Machine type: Air-jet weaving machine (shuttleless loom)
- Model: JAT910
- Weaving width: Approx. 150 cm – 360+ cm (depending on configuration) ([Toyota Textile Machinery](#))
- Weft insertion system: High-speed air jet with main nozzle and auxiliary nozzles
- Weft selection: Multi-color weft insertion system (up to several colors depending on setup)
- Control system: Fully computerized electronic control system
- Operation panel: Digital touch control system with smart functions
- Drive system: High-efficiency direct drive motor system
- Shedding system: Electronic dobby / cam system (optional configurations)
- Let-off system: Electronic controlled let-off motion
- Take-up system: Electronic controlled fabric take-up system
- Air system: Optimized air consumption injection system (energy-saving design)
- Fabric density: Programmable pick density control
- Pattern capability: Plain, twill, satin, jacquard, technical fabrics
- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: IoT-based factory management system (FACT-plus)
- Sensors: Real-time weft insertion detection system (i-SENSOR technology)
- Automation level: Fully automated smart weaving system
- Efficiency: High-speed weaving with reduced vibration and improved stability ([Toyota Industries](#))
- Energy system: Reduced air consumption and power-saving technology

4. Dornier P2 (Rapier Loom) – Machine Specifications

Typical specifications of Lindauer Dornier GmbH P2 rapier loom include:

- Machine type: Rapier weaving machine (shuttleless loom)
- Model: P2
- Weaving width: Approx. 150 cm – 540 cm (depending on configuration) ([Wilhelm Technology & Projects](#))
- Weft insertion system: Positive controlled double rapier system
- Weft insertion speed: Up to approx. 600 picks/min (high-speed production) ([Lindauer DORNIER GmbH](#))
- Weft selection: Up to 16 color weft insertion system
- Control system: Fully computerized electronic control system (advanced modular platform)

- Shedding system: Cam, dobby (up to 24 shafts), or jacquard compatible
- Drive system: High-efficiency direct drive system
- Shed geometry: Optimized positive shed formation system
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic controlled let-off system
- Machine structure: Highly rigid modular frame design for stability
- Fabric density: Programmable pick density control system
- Pattern capability: Plain, twill, satin, jacquard, complex technical structures
- Yarn compatibility: Cotton, polyester, silk, wool, glass fiber, carbon fiber, aramid
- Automation level: High automation with smart monitoring and production control
- Monitoring system: Digital machine diagnostics and production tracking
- Application: Fashion fabrics, home textiles, upholstery, and technical textiles

5. Tsudakoma ZAX (Air-Jet Loom) – Machine Specifications

Typical specifications of Tsudakoma Corporation ZAX series air-jet loom include:

- Machine type: Air-jet weaving machine (shuttleless loom)
- Model series: ZAX (e.g., ZAX9100, ZAX9200i, ZAX001neo)
- Weaving width: Approx. 150 cm – 360+ cm (varies by model and fabric type) ([Heng Feng Textile Machinery](#))
- Weft insertion system: High-speed air-jet system with main nozzle and relay nozzles
- Weft selection: Multi-color weft insertion system (up to 8 colors depending on configuration)
- Control system: Fully computerized electronic control system with Weave Navigation system
- Operation panel: Large digital touchscreen (Weave Navigation® system in advanced models)
- Drive system: Direct drive motor system for stable high-speed operation
- Shedding system: Electronic dobby or cam motion (model dependent)
- Air system: Optimized air consumption system for energy saving
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic let-off system
- Fabric density: Programmable pick density control system
- Pattern capability: Plain, twill, satin, jacquard, and technical fabrics
- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: Digital production monitoring and machine diagnostics (IoT-ready in newer models)
- Automation level: Fully automated high-speed weaving system
- Efficiency: High-speed weaving with reduced vibration and improved fabric quality ([Wikipedia](#))
- Energy system: Energy-saving design with reduced air and power consumption

6. Iteima A9500 (Air-Jet Loom) – Machine Specifications

Typical specifications of Iteima Group A9500 air-jet loom include:

- Machine type: Air-jet weaving machine (shuttleless loom)
- Model: A9500 (A9500 EVO / A9500 platform series)

- Weaving width: Wide range (commonly approx. 190 cm – 360+ cm depending on configuration)
- Weft insertion system: High-speed air-jet system with main nozzle and relay nozzles
- Weft selection: Multi-color weft insertion system (typically up to 8 colors depending on setup)
- Control system: Fully computerized electronic control system (EVOConsole platform)
- Operation interface: Touchscreen digital console with IoT connectivity
- Drive system: High-efficiency direct drive motor system
- Shedding system: Electronic dobby or cam motion system (model dependent)
- Air system: Optimized pneumatic platform for controlled air consumption
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic controlled let-off system
- Fabric density: Programmable pick density control system
- Pattern capability: Plain, twill, satin, jacquard, and technical fabric structures
- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: Smart factory monitoring (MyWeave / IoT-based systems)
- Automation level: Fully automated high-speed weaving system
- Efficiency: High productivity with reduced vibration and stable fabric quality
- Energy system: Energy-saving air consumption optimization technology

7. Picanol OptiMax-i Connect (Rapier Loom) – Machine Specifications

Typical specifications of Picanol OptiMax-i Connect rapier loom include:

- Machine type: Rapier weaving machine (shuttleless loom)
- Model: OptiMax-i Connect
- Weaving width: Approx. 190 cm – 540 cm (depending on configuration) ([Picanol](#))
- Weft insertion system: Guided gripper / free flight rapier system
- Weft selection: Up to 12 color weft insertion capability ([Textile World Asia](#))
- Control system: BlueBox computerized electronic control platform
- Operation interface: BlueTouch touchscreen system
- Drive system: Sumo energy-efficient direct drive motor system
- Shedding system: Electronic dobby / cam / jacquard compatible
- Shed geometry: Optimized shed design for reduced warp stress
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic controlled let-off system
- Fabric density: Programmable pick density control
- Pattern capability: Plain, twill, satin, jacquard, technical fabrics
- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: IoT-based smart monitoring and production control
- Automation level: Fully computerized high-performance weaving system
- Efficiency: High-speed production with energy-saving design
- Maintenance system: Modular design for easy servicing and upgrades

8. Toyota JAT810 (Air-Jet Loom) – Machine Specifications

Typical specifications of Toyota JAT810 air-jet loom include:

- Machine type: Air-jet weaving machine (shuttleless loom)

- Model: JAT810
- Weaving width: Approx. 140 cm – 390 cm (depending on configuration) ([Toyota Industries](#))
- Weft insertion system: High-speed air-jet system with main nozzle and sub nozzles
- Weft selection: Multi-color weft insertion system (up to 4–8 colors depending on setup)
- Control system: Fully computerized electronic control system with function panel
- Operation system: Advanced digital function panel with factory monitoring support (FACT system)
- Drive system: Energy-efficient motor drive system
- Shedding system: Negative cam, positive cam, crank, dobby, and electronic shedding options ([Toyota Industries](#))
- Air system: Optimized air-saving system with reduced air consumption technology
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic controlled let-off system
- Fabric density: Programmable pick density control system
- Pattern capability: Plain, twill, satin, dobby, jacquard (depending on configuration)
- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: FACT system + production monitoring (P-monitor system)
- Automation level: Fully automated high-speed weaving system
- Efficiency: High productivity with reduced air consumption and improved stability
- Energy system: Energy-saving air jet technology (up to ~20% air reduction) ([IGES](#))

9. Saurer Air-Jet Loom – Machine Specifications

Typical specifications of Saurer air-jet loom include:

- Machine type: Air-jet weaving machine (shuttleless loom)
- Weaving width: Approx. 190 cm – 360+ cm (depending on model configuration)
- Weft insertion system: High-speed compressed air system with main nozzle and relay (sub) nozzles
- Weft selection: Multi-color weft insertion system (typically up to 4–8 colors depending on model)
- Control system: Fully computerized electronic control system with smart monitoring interface
- Drive system: Energy-efficient direct drive motor system
- Shedding system: Electronic dobby or cam motion system (model dependent)
- Air system: Optimized air consumption system for reduced energy usage
- Fabric take-up: Electronic controlled take-up system
- Warp let-off: Electronic controlled let-off system
- Fabric density: Programmable pick density control system
- Pattern capability: Plain, twill, satin, jacquard, and technical woven structures
- Yarn compatibility: Cotton, polyester, viscose, wool, blended and technical yarns
- Monitoring system: Digital production monitoring and machine diagnostic system (smart factory ready)
- Automation level: High automation with intelligent control system
- Efficiency: High-speed weaving with stable performance and reduced downtime
- Maintenance system: Modular design for easier servicing and reduced maintenance time

10. Stäubli SX PRO (Jacquard Machine) – Machine Specifications

Typical specifications of Stäubli SX PRO electronic Jacquard machine include:

- Machine type: Electronic Jacquard shedding machine
- Model: SX PRO
- Application: Air-jet, rapier, and water-jet weaving machines
- Hook capacity: Up to **2,688 hooks**
- Control system: Independent TC8 electronic Jacquard controller
- Electronic system: NOEMI electronic architecture for data transmission and hook selection
- Hook selection system: MX PRO module system
- Drive system: Electronic shedding control system
- Power system: Integrated power supply inside Jacquard head
- Installation: Compact design for easy installation in weaving machines
- Fabric compatibility: Flat fabrics, terry fabrics, upholstery, silk, apparel, technical textiles
- Pattern capability: Complex jacquard designs, multi-layer woven structures
- Data transmission: High-speed digital pattern data transfer system
- Maintenance system: Low-maintenance, lubricated-for-life components
- Energy efficiency: Low-friction design reduces energy consumption
- Ventilation system: Optimized cooling and dust protection system
- Machine structure: Robust modular construction for industrial use

❖ **References:**

1. [Toyota JAT910 Air-Jet Loom Specifications](#)
2. [Toyota Weaving Machinery Official Site](#)
3. [Itama R9500EVO Rapier Loom](#)
4. [Itama A9500EVO Air-Jet Loom](#)
5. [Picanol OmniPlus-i Connect Air-Jet Loom](#)
6. [Picanol OptiMax-i Rapier Loom](#)
7. [Dornier P2 Rapier Weaving Machine](#)
8. [Dornier A2 Air-Jet Weaving Machine](#)
9. [Tsudakoma ZAX Air-Jet Loom](#)
10. [Stäubli Jacquard Weaving Machines](#)
11. [SMIT GS980 Rapier Loom](#)
12. [Karl Mayer Technical Textile Machines](#)
13. [Toyota JAT810 Air-Jet Loom](#)
14. [Toyota LWT810 Water-Jet Loom](#)
15. [Picanol TerryMax-i Weaving Machine](#)
16. [Picanol TERRYplus Summum](#)
17. [Dornier Weaving Machines Official Site](#)
18. [Itama Weaving Machines Official Site](#)
19. [Picanol Weaving Machines Official Site](#)
20. [Toyota Air & Water Jet Looms](#)
21. [Textile Today – Leading Weaving Machines in 2025](#)
22. [Textile School – Top Weaving Machinery Manufacturers](#)
23. [Textile World – Weaving Machine Technology Update](#)
24. [Sulzer Projectile & Itama Air-Jet Loom Specifications](#)
25. [Zaman Textile Weaving Machinery Details](#)