

NEHvigation

Singapore ERP & Toll Route Optimizer 1.0 Technical Overview

Comprehensive System Architecture, Tech Stack, & Algorithmic Logic Documentation

1. Executive Summary & Problem Statement

Driving in Singapore involves navigating a dense network of Electronic Road Pricing (ERP) gantries across expressways (CTE, PIE, AYE, KPE, MCE, ECP) and arterial roads (Central Business District, Orchard, Bugis). Toll rates fluctuate dynamic based on time-of-day, vehicle classification, and traffic congestion schedules.

Conventional navigation software (e.g., standard Google Maps or Waze) evaluates routes primarily based on travel time or distance. They frequently fail to address the total cost of ownership per trip, often routing drivers through high-fee ERP gantries to save 1-2 minutes, or taking indirect detours that consume significantly more fuel than the toll avoided.

NEHvigation solves this by providing a unified Singapore Toll & Energy Optimizer. It evaluates live and scheduled LTA ERP gantry rates, calculates vehicle-specific fuel/EV consumption with urban traffic idling adjustments, calculates total monetary cost per route option, and automatically identifies the most cost-effective path.

2. Key Functional Capabilities

- Real-Time LTA ERP Gantry Matching:** Leverages spatial buffer queries (~80m radius) via Turf.js to identify every ERP gantry crossed along alternative route options.
- Dynamic Time-Window Schedules:** Supports Live SG Time, Morning Peak (08:30), Evening Peak (18:30), or Custom departure times/days to predict toll fees accurately.
- Vehicle & Fuel Efficiency Engine:** Features presets for vehicles (e.g., Skoda Yeti 10.4 km/L, Hyundai Ioniq 5 EV 17.5 kWh/100km, Goods Vehicles, Taxis, Motorcycles) plus custom rate inputs.
- Traffic Score & Speed Multiplier Engine:** Evaluates real-time average speed (km/h) to categorize traffic conditions into 5 distinct speed tiers, applying dynamic fuel consumption multipliers (up to +35% for heavy crawling congestion).
- Intersection & Traffic Light Penalty:** Tracks traffic light density along route segments, adding stop-start idling overhead (~20ml fuel or 0.005 kWh EV penalty per traffic light).
- Composite Route Recommendation:** Computes a multi-variable composite score weighing travel duration, distance, ERP tolls (\$1.00 = 5 pts), fuel cost, and traffic light delays to auto-select the "Best Value Route".
- Seamless Google Maps Handoff:** Deep-links optimized routes with precise numerical lat/lng waypoints directly into native mobile Google Maps without URL parsing errors.

3. Technical Stack & Dependencies

Layer / Component	Technology / Library	Purpose & Implementation
Framework	Next.js 16 (App Router)	Full-stack React 19 app with API routes & SSR
Language	TypeScript 5	End-to-end type safety & structured models
Styling	Tailwind CSS v4	Dark-theme responsive design for OLED & mobile
Authentication	NextAuth.js v5 + Google OAuth	Secure whitelisted email access control
Maps & Geocoding	@react-google-maps/api	Google Places Autocomplete & Directions API
Geospatial Engine	@turf/turf & @mapbox/polyline	Polyline decoding & spatial gantry buffering
PDF Generator	jsPDF	Dynamic architecture & reporting document compilation

4. Core Architectural Logics & Algorithms

- i2½A. Spatial Buffer Gantry Detection Algorithm:** When candidate routes are received from Google Directions API, polylines are decoded into coordinate arrays. Turf.js constructs spatial line-buffers (~80m). Gantry coordinates are checked against these buffers to determine exact gantry hits per route.
- i2½B. LTA Rate Schedule Matrix:** ERP toll rates are retrieved based on gantry IDs, vehicle type, day of week, and time window. The engine automatically checks if the departure falls into active operating windows (e.g. 07:00-09:30 CTE inbound) or off-peak zero-rate periods.
- i2½C. Traffic Score & Speed Factor Logic:** Derives average speed (km/h) = Distance / Duration. Categorizes traffic into 5 speed tiers: <20 km/h (Heavy Congestion, 1.35x fuel multiplier), 20i2½35 km/h (Slow Traffic, 1.20x), 35i2½50 km/h (Moderate, 1.10x), 50i2½80 km/h (Optimal Cruising, 1.00x), and >80 km/h (Expressway Drag, 1.05x).
- i2½D. Fuel, Energy & Intersection Cost Logic:** Calculates distance-based fuel/EV usage using: Energy = (Distance / Efficiency) i2½ SpeedFactor + TrafficLightStopPenalty (~20ml fuel/0.005 kWh per intersection). Total Cost = ERP Toll (\$) + [Energy Consumed i2½ Fuel Price (\$/L or \$/kWh)].
- i2½E. Composite Route Optimization Score:** Computes a weighted scoring penalty: CompositeScore = (DurationMin i2½ 1.0) + (TrafficLightScore i2½ 0.5) + (DistanceKm i2½ 0.1) + (ERPTollFee i2½ 5.0) + (FuelLiters i2½ 10.0). The route with the lowest composite score is highlighted as the winner.
- i2½F. Mobile GPS & Deep-Linking Optimization:** Geolocation utilizes a 2-phase fallback mechanism (3.5s high-accuracy fix fallback to network cell-triangulation) for fast response times. Google Maps URLs utilize strict numeric coordinates (lat,lng) to prevent mobile app string-parsing errors.
- i2½G. Whitelist Authorization Security:** NextAuth middleware verifies user credentials against an authorized whitelist. Unapproved users are redirected to a branded access restriction view ("Access Denied! Reach out to Shaunneh").