ClockMaster User Guide



November 6, 2019

Group 4

Pedro Santos, nº93892

Sara Soares, nº87737

Professor José Teixeira de Sousa





Contents

1	Introduction	7
2	Block Diagram	8
3	Peripherals	8
	3.1 Peripherals used	9
4	Instructions	9
	4.1 Clock	9
	4.2 Counter	9
	4.3 Timer	9
5	Implementation Results	9
6	Conclusions	9



List of Tables





List of Figures

1	Basys 2 board	7
2	Block diagram	8





1 Introduction

The Basys2 Figure 1, board is a circuit design and implementation platform that anyone can use to gain experience building real digital circuits. Built around a Xilinx Spartan-3E Field Programmable Gate Array and a Atmel AT90USB2 USB controller, the Basys2 board provides complete, ready-to-use hardware suitable for hosting circuits ranging from basic logic devices to complex controllers.



Figure 1: Basys 2 board

Our project uses the Basys2 to make a clock with some features. We propose to use 7 segment dislay as output and the push buttons to set the time and navigate through the menus.



2 Block Diagram




Figure 2: Block diagram

3 Peripherals

The Basys2 has manny peripherals options such as: -7 segments display -on/off switch -push buttons -VGA port -PS/2 port -6-pin headers



3.1 Peripherals used

The peripherals that we will de using are the 7 segments display and the push buttons.

4 Instructions

4.1 Clock

The ClockMaster will have the function to show the time in the 7 segment dislay. With the help of the push buttons we will be able to set the time correctly.

4.2 Counter

The Counter is a feature that we can set a desired value and counts until reach that value.

4.3 Timer

This feature use a previously entered value and stop counting when it reaches 0.

5 Implementation Results

6 Conclusions