

ULPF Final Prototype

One schema. Any supported perimeter device. Zero forensic data loss.

5 adapters

Offline core

Phase 5 gate passed

10

stored events in preview

5

DENY vendors

33.4

events/sec local benchmark

51.3ms

p95 latency

Field trace sample

- @timestamp ← ['date', 'time', 'tz']
- destination.ip ← dstip
- destination.port ← dstport
- event.action ← action
- event.category ← default
- event.severity ← level

Validation: PASS · Raw SHA-256 retained

Unified Event Explorer · filter: event.action = DENY

timestamp	vendor	product	source	destination	port	protocol	action	parser
2026-08-26T11:31:00	Generic	RFC5424 Syslog	10.0.0.25	203.0.113.80	22	TCP	DENY	1.0.0
2026-08-26T11:31:00	SyntheticVendor	EdgeFirewall	10.0.0.25	203.0.113.80	22	TCP	DENY	1.0.0
2026-08-26T11:31:00	Palo Alto Networks	PAN-OS	10.0.0.25	203.0.113.80	22	TCP	DENY	1.0.0
2026-08-26T11:31:00	Cisco	ASA	10.0.0.25	203.0.113.80	22	TCP	DENY	1.0.0
2026-08-26T11:31:00	Fortinet	FortiGate	10.0.0.25	203.0.113.80	22	TCP	DENY	1.0.0

RAW

```
date=2026-08-26 time=17:00:00
tz="+0530" devname="FGT-EDGE-01"
devid="FG100FTK000000001"
logid="0000000013" type="traffic"
subtype="forward" level="notice"
vd="root" srcip=10.0.0.5
srcport=52134 srcintf="port2"
dstip=8.8.
```

PARSED

```
{
  "action": "accept",
  "date": "2026-08-26",
  "devid": "FG100FTK000000001",
  "devname": "FGT-EDGE-01",
  "dstcountry": "United States",
  "dstintf": "wan1",
  "dstip": "8.8.8.8",
  "dstport": "443",
  "duration": "3",
  "level": "notice".
```

NORMALIZED

```
{
  "event": {
    "action": "ALLOW",
    "category": "network",
    "severity": "NOTICE",
    "type": "connection"
  },
  "source": {
    "ip": "10.0.0.5",
    "port": 52134
  }
}
```

Judge story: different vendor log languages enter one deterministic pipeline, become one universal schema, and still retain exact forensic raw evidence with parser/mapping provenance.

Claim guardrail: benchmark is a reproducible local prototype baseline, not a production scale claim.