JAVA

ASSIGNMENT

BY : SHAURYA PUNDIR   TO:-Mr. AMIT KUMAR


eclipse-workspace - JavaCode/src/Termwork/MMAINN.java - Eclipse IDE
package Termwork;
import java.util.*;
public class MMAINN {
public static void main(String[] args)
{
Scanner sc=new Scanner(System.in);
int x=sc.nextInt();
int sum =0;
while(x>0)
{
sum=sum+x;
x=sc.nextInt();
}
System.out.println(sum);
}
}
Writable
Smart Insert
17 : 33 : 279


eclipse-workspace - JavaCode/src/LAB/areamain.java - Eclipse IDE
package LAB;
import java.util.*;
class area
{
void area(int l,int b)
{
System.out.println("The area of rect is:"+l*b);
}
void area(int r)
{
System.out.println("The area of circle is:"+(3.14*r*r));
}
}
public class areamain {
public static void main(String[] args) {
int r,l,b;
Scanner sc=new Scanner (System.in);
System.out.println("Enter the value of r");
r=sc.nextInt();
System.out.println("Enter the value of l");
l=sc.nextInt();
System.out.println("Enter the value of b");
b=sc.nextInt();
area a=new area();
a.area(l,b);
a.area(r);
}
}
Resource leak: 'sc' is never closed
Writable
Smart Insert
21 : 24 [115]


eclipse-workspace - JavaCode/src/LAB/sphere.java - Eclipse IDE
package LAB;
import java.util.Scanner;
class solu
{
void spheree(int r)
{
}
void spheree(float r)
{
}
}
public class sphere {
public static void main(String[] args)
{
int r;
Scanner sc=new Scanner (System.in);
System.out.println("Enter the value of r");
r=sc.nextInt();
solu s=new solu();
}
}
Writable
Smart Insert
11 : 26 : 116


eclipse-workspace - JavaCode/src/LAB/AcessAnimal.java - Eclipse IDE
System.out.println(getName()+" is eating food");
}
}
class Dog extends Animal {
public Dog(String name) {
super(name); // Call the constructor of the Animal class
}
// Implementing the abstract method for Dog
@Override
public void makeSound() {
System.out.println(getName() + " says: Bark");
}
}
class Cat extends Animal {
public Cat(String name) {
super(name); // Call the constructor of the Animal class
}
// Implementing the abstract method for Cat
@Override
public void makeSound() {
System.out.println(getName() + " says: Meow");
}
}
public class AcessAnimal {
public static void main(String[] args) {
Animal dog = new Dog("Buddy");
dog.makeSound(); // Output: Buddy says: Bark
dog.eat(); //Output: Buddy is eating food
Animal cat = new Cat("Whiskers");
cat.makeSound(); // Output: Whiskers says: Meow
cat.eat(); //Output: Buddy is eating food
}
}
Writable
Smart Insert
43 : 14 : 1021



```java
package LAB;

abstract class Animal {
    // Field for the name of the animal
    private String name;

    // Constructor to set the name of the animal
    public Animal(String name) {
        this.name = name;
    }

    // Abstract method makeSound
    public abstract void makeSound();

    // Concrete method to get the name of the animal
    public String getName() {
        return name;
    }

    public void eat() {
        System.out.println(getName()+" is eating food");
    }
}

class Dog extends Animal {
    public Dog(String name) {
        super(name); // Call the constructor of the Animal class
    }

    // Implementing the abstract method for Dog
    @Override
    public void makeSound() {
        System.out.println(getName() + " says: Bark");
    }
}

class Cat extends Animal {
    public Cat(String name) {
        super(name); // Call the constructor of the Animal class
    }
```



```java
package Termwork;
import java.util.ArrayList;

public class AlternateElements {

    public static List<Integer> alternate(List<Integer> list1, List<Integer> list2) {
        List<Integer> result = new ArrayList<>();
        int size1 = list1.size();
        int size2 = list2.size();
        int maxSize = Math.max(size1, size2);

        for (int i = 0; i < maxSize; i++) {
            if (i < size1)
                result.add(list1.get(i));
            if (i < size2)
                result.add(list2.get(i));
        }

        return result;
    }

    public static void main(String[] args) {
        List<Integer> list1 = new ArrayList<>();
        list1.add(1);
        list1.add(2);
        list1.add(3);
        list1.add(4);
        list1.add(5);

        List<Integer> list2 = new ArrayList<>();
        list2.add(6);
        list2.add(7);
        list2.add(8);
        list2.add(9);
        list2.add(10);
        list2.add(11);
        list2.add(12);

        List<Integer> result = alternate(list1, list2);
        System.out.println(result);
```



eclipse-workspace - JavaCode/src/multiple/ThrowExample.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Package Explorer
JavaCode
package-inf... p3uppermain... main703.java areamain.java sphere.java AcessAnimal... ThrowExample... AlternateEle...
package multiple;
public class ThrowExample {
static void checkAge(int age) throws Exception
{
if (age < 18) {
// Throw an ArithmeticException if the age is less than 18
throw new Exception("Access denied - "
+ "You must be at least 18 years old.");
} else {
System.out.println("Access granted - You are old enough!");
}
}
public static void main(String[] args) {
try {
checkAge(10); // This will throw an ArithmeticException
} catch (Exception e) {
System.out.println("Exception caught in main: "+e);
}
}
}
Writable
Smart Insert
4 : 51 : 100



eclipse-workspace - JavaCode/src/Termwork/ArrayDemo.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Package Explorer
JavaCode
p3uppermain... main703.java areamain.java sphere.java AcessAnimal... ThrowExample... ArrayDemo.java AlternateEle...
package Termwork;
import java.util.Arrays;
class ArrayDemo {
// Overloaded arrayFunc method to find pairs with a specific sum
void arrayFunc(int[] array, int target) {
System.out.println("Pairs of elements whose sum is " + target + " are:");
for (int i = 0; i < array.length; i++) {
for (int j = i + 1; j < array.length; j++) {
if (array[i] + array[j] == target) {
System.out.println(array[i] + " + " + array[j] + " = " + target);
}
}
}
}
void arrayFunc(int[] A, int p, int[] B, int q) {
int[] merged = new int[p + q];
int i = 0, j = 0, k = 0;
// Merge the two arrays
while (i < p && j < q) {
if (A[i] < B[j]) {
merged[k++] = A[i++];
} else {
merged[k++] = B[j++];
}
}
// Copy remaining elements from A
while (i < p) {
merged[k++] = A[i++];
}
// Copy remaining elements from B
while (j < q) {
merged[k++] = B[j++];
}
Writable
Smart Insert
52 : 1 : 1434


eclipse-workspace - JavaCode/src/Termwork/Bankk.java - Eclipse IDE
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToDisplay) {
account.displayInfo();
}
}
break;
case 2:
System.out.print("Enter account number: ");
int accNumberToDeposit = scanner.nextInt();
System.out.print("Enter amount to deposit: ");
double depositAmount = scanner.nextDouble();
scanner.nextLine(); // Consume newline
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToDeposit) {
account.deposit(depositAmount);
account.displayInfo();
}
}
break;
case 3:
System.out.print("Enter account number: ");
int accNumberToWithdraw = scanner.nextInt();
System.out.print("Enter amount to withdraw: ");
double withdrawAmount = scanner.nextDouble();
scanner.nextLine(); // Consume newline
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToWithdraw) {
account.withdraw(withdrawAmount);
account.displayInfo();
}
}
break;
case 4:
System.out.print("Enter account number: ");
int accNumberToChangeAddress = scanner.nextInt();
scanner.nextLine(); // Consume newline
System.out.print("Enter new address: ");
String newAddress = scanner.nextLine();
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToChangeAddress) {
Writable
Smart Insert
8 : 49 : 144


eclipse-workspace - JavaCode/src/Termwork/Bankk.java - Eclipse IDE
}
}
break;
case 3:
System.out.print("Enter account number: ");
int accNumberToWithdraw = scanner.nextInt();
System.out.print("Enter amount to withdraw: ");
double withdrawAmount = scanner.nextDouble();
scanner.nextLine(); // Consume newline
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToWithdraw) {
account.withdraw(withdrawAmount);
account.displayInfo();
}
}
break;
case 4:
System.out.print("Enter account number: ");
int accNumberToChangeAddress = scanner.nextInt();
scanner.nextLine(); // Consume newline
System.out.print("Enter new address: ");
String newAddress = scanner.nextLine();
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToChangeAddress) {
account.changeAddress(newAddress);
account.displayInfo();
}
}
break;
case 5:
continueOperations = false;
break;
default:
System.out.println("Invalid choice, please try again.");
}
}
scanner.close();
}
}
Writable
Smart Insert
8 : 49 : 144


eclipse-workspace - JavaCode/src/LAB/Employee.java - Eclipse IDE
package LAB;
/* Design a class named Employee with private fields for name, ID, and salary. Provide public setter and getter me
import java.util.*;
public class Employee
{
private int ID,Salary;
private String Name;
public Employee(int id,String N,int salary)
{
ID=id;
Name=N;
Salary=salary;
}
void disp()
{
System.out.println(" "+ID+" "+Name+" "+Salary);
}
}
class MAINEmployee
{
public static void main(String[] args)
{
Employee e1=new Employee(1234,"Shaurya Pundir",80000);
e1.disp();
}
}


eclipse-workspace - JavaCode/src/LAB/areamain.java - Eclipse IDE
package LAB;
import java.util.*;
class area
void area(int l,int b)
{
System.out.println("The area of rect is:"+l*b);
}
void area(int r)
{
System.out.println("The area of circle is:"+(3.14*r*r));
}
}
public class areamain {
public static void main(String[] args) {
int r,l,b;
Scanner sc=new Scanner (System.in);
System.out.println("Enter the value of r");
r=sc.nextInt();
System.out.println("Enter the value of l");
l=sc.nextInt();
System.out.println("Enter the value of b");
b=sc.nextInt();
area a=new area();
a.area(l,b);
a.area(r);
}
}



eclipse-workspace - JavaCode/src/LAB/dynamic.java - Eclipse IDE
package LAB;
class a
{
void shaurya()
{
System.out.println("shaurya got placement");
}
}
class b extends a
{
void shaurya()
{
System.out.println("package of 10000");
}
}
public class dynamic
{
public static void main(String[] args)
{
a obj = new b();
obj.shaurya();
}
}



eclipse-workspace - JavaCode/src/LAB/AcessAnimal.java - Eclipse IDE
package LAB;
abstract class Animal {
// Field for the name of the animal
private String name;
// Constructor to set the name of the animal
public Animal(String name) {
this.name = name;
}
// Abstract method makeSound
public abstract void makeSound();
// Concrete method to get the name of the animal
public String getName() {
return name;
}
public void eat() {
System.out.println(getName()+" is eating food");
}
}
class Dog extends Animal {
public Dog(String name) {
super(name); // Call the constructor of the Animal class
}
// Implementing the abstract method for Dog
@Override
public void makeSound() {
System.out.println(getName() + " says: Bark");
}
}
class Cat extends Animal {
public Cat(String name) {
super(name); // Call the constructor of the Animal class
}


eclipse-workspace - JavaCode/src/LAB/AcessAnimal.java - Eclipse IDE
System.out.println(getName()+" is eating food");
}
}
class Dog extends Animal {
public Dog(String name) {
super(name); // Call the constructor of the Animal class
}
// Implementing the abstract method for Dog
@Override
public void makeSound() {
System.out.println(getName() + " says: Bark");
}
}
class Cat extends Animal {
public Cat(String name) {
super(name); // Call the constructor of the Animal class
}
// Implementing the abstract method for Cat
@Override
public void makeSound() {
System.out.println(getName() + " says: Meow");
}
}
public class AcessAnimal {
public static void main(String[] args) {
Animal dog = new Dog("Buddy");
dog.makeSound(); // Output: Buddy says: Bark
dog.eat(); //Output: Buddy is eating food
Animal cat = new Cat("Whiskers");
cat.makeSound(); // Output: Whiskers says: Meow
cat.eat(); //Output: Buddy is eating food
}
}


eclipse-workspace - JavaCode/src/Termwork/ArrayDemo.java - Eclipse IDE
while (i < p) {
merged[k++] = A[i++];
}
// Copy remaining elements from B
while (j < q) {
merged[k++] = B[j++];
}
// Fill A with the first p smallest elements
for (i = 0; i < p; i++) {
A[i] = merged[i];
}
// Fill B with the remaining elements
for (j = 0; j < q; j++) {
B[j] = merged[p + j];
}
}
public static void main(String[] args) {
ArrayDemo demo = new ArrayDemo();
int[] numbers = {4, 6, 5, -10, 8, 5, 20};
int target = 10;
demo.arrayFunc(numbers, target);
int[] A = { 1, 5, 6, 7, 8, 10 };
int[] B = { 2, 4, 9 };
int p = A.length;
int q = B.length;
demo.arrayFunc(A, p, B, q);
System.out.println("Sorted Arrays:");
System.out.println("A: " + Arrays.toString(A));
System.out.println("B: " + Arrays.toString(B));
}
}


eclipse-workspace - JavaCode/src/LAB/ExceptionMain.java - Eclipse IDE
package LAB;
import java.io.BufferedReader;
public class ExceptionMain {
public static String isEven(int number) {
return number%2==0?"Even":"Odd";
}
public static void main(String[] args)throws Exception{
InputStreamReader isr = new InputStreamReader(System.in);
BufferedReader br = new BufferedReader(isr);
// try {
System.out.println("Enter any number: ");
int x = Integer.parseInt(br.readLine());
System.out.println("HI");
System.out.println(x+" is a "+isEven(x)+" number");
}
catch(Exception e)
{
System.out.println(e);
}
}
Writable
Smart Insert
24 : 12 : 701

eclipse-workspace - JavaCode/src/LAB/Filehandling.java - Eclipse IDE
package LAB;
import java.util.*;
public class Filehandling {
public static void main(String[] args) {
File dir =new File("LAB");
dir.mkdir();
File file = new File("LAB\\SS.txt");
try {
if (file.createNewFile()) {
System.out.println("File created at"+ file.getAbsolutePath());
} else {
System.out.println("File already exists at"+ file.getAbsolutePath());
}
} catch (IOException e) {
System.out.println("Error found in creating the file");
}
try {
FileWriter writer = new FileWriter(file);
writer.write("Hi bla bla bla bkan");
writer.close();
} catch (IOException e) {
System.out.println("Error found in writing the file");
}
try {
FileReader r = new FileReader(file);
int ch;
while ((ch = r.read()) != -1) {
System.out.print((char) ch);
}
r.close();
} catch (IOException e) {
System.out.println("Error found in reading the file");
}
}
}
Writable
Smart Insert
10 : 45 : 250


eclipse-workspace - JavaCode/src/LAB/Filehandling.java - Eclipse IDE
package LAB;
import java.util.*;
public class Filehandling {
public static void main(String[] args) {
File dir =new File("LAB");
dir.mkdir();
File file = new File("LAB\\SS.txt");
try {
if (file.createNewFile()) {
System.out.println("File created at"+ file.getAbsolutePath());
} else {
System.out.println("File already exists at"+ file.getAbsolutePath());
}
} catch (IOException e) {
System.out.println("Error found in creating the file");
}
try {
FileWriter writer = new FileWriter(file);
writer.write("Hi Bla bla bla bkam");
writer.close();
} catch (IOException e) {
System.out.println("Error found in writing the file");
}
try {
FileReader r = new FileReader(file);
int ch;
while ((ch = r.read()) != -1) {
System.out.print((char) ch);
}
r.close();
} catch (IOException e) {
System.out.println("Error found in reading the file");
}
}
}
Writable
Smart Insert
27 : 67 : 881


eclipse-workspace - JavaCode/src/LAB/EmployeeMain.java - Eclipse IDE
package LAB;
import java.util.*;
class Emp
{
String name;
int eid,deptid;
void display(String name,int eid,int deptid)
{
this.name=name;
this.eid=eid;
this.deptid=deptid;
try
{
if(!(name.charAt(0)>=65 && name.charAt(0)<=90))
{
throw new ArithmeticException("The first letter is not Capital");
}
}
catch(Exception e)
{
System.out.println(e);
}
try
{
if(!(eid>=2001 && eid<=5001))
{
throw new Exception("The employee id id not in range of 2001 - 5001.");
}
}
catch(Exception e)
{
System.out.println(e);
}
try
{
if(!(deptid>=1 && deptid<=5))
Writable
Smart Insert
53 : 1 : 898



eclipse-workspace - JavaCode/src/LAB/InterfaceMain.java - Eclipse IDE
package LAB;
import java.util.*;
interface Demo
{
void volume();
}
class Cone implements Demo
{
double r,h,v;
Cone(double r,double h)
{
this.r=r;
this.h=h;
}
public void volume()
{
v=(float) (0.5*3.14*(r*r*h));
System.out.println("Volume of Cone:"+v);
}
}
class Hemisphere implements Demo
{
double r,v;
Hemisphere(double r)
{
this.r=r;
}
public void volume()
{
v=(double) (0.6666*3.14*(r*r*r));
System.out.println("Volume of Hemisphere:"+v);
}
}
class Cylinder implements Demo



eclipse-workspace - JavaCode/src/LAB/InterfaceMain.java - Eclipse IDE
Hemisphere(double r)
{
this.r=r;
}
public void volume()
{
v=(double) (0.6666*3.14*(r*r*r));
System.out.println("Volume of Hemisphere:"+v);
}
}
class Cylinder implements Demo
{
double r,h,v;
Cylinder(double r,double h)
{
this.r=r;
this.h=h;
}
public void volume()
{
v=(double) (3.14*(r*r*h));
System.out.println("Volume of Hemisphere:"+v);
}
}
public class interfaceMain {
public static void main(String[] args) {
Cone c=new Cone(3.0,1.0);
c.volume();
Hemisphere h=new Hemisphere(4.0);
h.volume();
Cylinder c1=new Cylinder(4.0,1.0);
c1.volume();
}
}


eclipse-workspace - JavaCode/src/Chapter1/sqrtt.java - Eclipse IDE
package Chapter1;
import java.util.*;
public class sqrtt {
public static void main(String[] args)
{
Scanner sc=new Scanner(System.in);
int flag=0,pos=0;
int [] Books= {100,101,102,103,104,105,106,107,108,109,110,111,112,113,114};
System.out.println("Enter the book id to find: ");
int x=sc.nextInt();
for(int i: Books)
{
pos+=1;
if(i==x)
{
System.out.println("Book present in "+pos);
flag=1;
}
}
if(flag==0)
{
System.out.println("Book not found");
}
}
}
Writable
Smart Insert
1 : 1 : 0

eclipse-workspace - JavaCode/src/Chapter1/squareroot.java - Eclipse IDE
package Chapter1;
import java.util.*;
public class squareroot {
public static void main(String[] args) {
// TODO Auto-generated method stub
Scanner sc=new Scanner(System.in);
System.out.println("Enter a number :");
int x=sc.nextInt();
for(int i=1;i<x/2;i++)
{
if((i*i)==x)
{
System.out.println("Square root of number "+x+" is:"+i);
}
}
}
}
Writable
Smart Insert
1 : 1 : 0


eclipse-workspace - JavaCode/src/Chapter1/sum.java - Eclipse IDE
package Chapter1;
import java.util.*;
public class sum {
public static void main(String args[])
{
int x,s=0,d; //Sum of digit of x
Scanner sc=new Scanner(System.in);
System.out.println("Enter a number:");
x=sc.nextInt();
while(x!=0)
{
d=x%10;
s=s+d;
x=x/10;
}
System.out.println("The sum of digit of number is: "+s);
}
}


eclipse-workspace - JavaCode/src/Chapter1/Test.java - Eclipse IDE
package Chapter1;
public class Test {
int x,y;
public Test(int x,int y)
{
this.x=x;
this.y=y;
}
boolean equalTo(Test obj)
{
if(obj.x==x && obj.y==y)
{
return true;
}
else
return false;
}
}
class Testobj
{
public static void main(String[] args)
{
Test t1=new Test(10,20);
Test t2=new Test(10,20);
Test t3=new Test(-10,-20);
System.out.println("t1==t2:"+t1.equalTo(t2));
System.out.println("t1==t3:"+t1.equalTo(t3));
}
}


eclipse-workspace - JavaCode/src/LAB/areamain.java - Eclipse IDE
package LAB;
import java.util.*;
class area{
void area(int l,int b)
{
System.out.println("The area of rect is:"+l*b);
}
void area(int r)
{
System.out.println("The area of circle is:"+(3.14*r*r));
}
}
public class areamain {
public static void main(String[] args) {
int r,l,b;
Scanner sc=new Scanner (System.in);
System.out.println("Enter the value of r");
r=sc.nextInt();
System.out.println("Enter the value of l");
l=sc.nextInt();
System.out.println("Enter the value of b");
b=sc.nextInt();
area a=new area();
a.area(l,b);
a.area(r);
}
}


eclipse-workspace - JavaCode/src/LAB/Counter.java - Eclipse IDE
package LAB;
public class Counter
{
static int n=0;
public Counter()
{
n+=1;
}
void disp()
{
System.out.println("The number of times the instance created is :"+n);
}
}
class Countmain
{
public static void main(String args[])
{
Counter c1=new Counter();
Counter c2=new Counter();
Counter c3=new Counter();
c3.disp();
}
}



eclipse-workspace - JavaCode/src/LAB/Employee.java - Eclipse IDE
package LAB;
/* Design a class named Employee with private fields for name, ID, and salary. Provide public setter and getter me
import java.util.*;
public class Employee
{
private int ID,Salary;
private String Name;
public Employee(int id,String N,int salary)
{
ID=id;
Name=N;
Salary=salary;
}
void disp()
{
System.out.println(" "+ID+" "+Name+" "+Salary);
}
}
class MAINEmployee
{
public static void main(String[] args)
{
Employee e1=new Employee(1234,"Shaurya Pundir",80000);
e1.disp();
}
}



eclipse-workspace - JavaCode/src/LAB/MyCalculateMain.java - Eclipse IDE
}
else
{
this.n=n;
this.exp=exp;
double num=Math.pow(n,exp);
return (int)num;
}
}
}
public class MyCalculateMain {
public static void main(String[] args) throws Exception
{
MyCalculate obj=new MyCalculate();
Scanner sc=new Scanner(System.in);
System.out.print("Enter the value of number and the exponent:");
try
{
int n=sc.nextInt();
int exp=sc.nextInt();
int a=obj.power(n,exp);
System.out.println(n+"^"+exp+"="+a);
}
catch(Exception e)
{
System.out.println(e);
e.printStackTrace();
}
finally
{
System.out.println("Program Terminated");
}
}
}


eclipse-workspace - JavaCode/src/LAB/MyDialogue.java - Eclipse IDE
package LAB;
import javax.swing.*;
public class MyDialogue
{
MyDialogue()
{
JDialog d=new JDialog();
d.setTitle("Simple Dialog");
d.setSize(200,150);
d.setVisible(true);
}
public static void main(String[] args) {
MyDialogue dd=new MyDialogue();
}
}
Writable
Smart Insert


eclipse-workspace - JavaCode/src/LAB/MyFrame.java - Eclipse IDE
package LAB;
import javax.swing.JFrame;
public class MyFrame extends JFrame
{
public MyFrame()
{
setTitle("Shaurya App");
setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
setSize(480,480);
setLocation(100,100);
setVisible(true);
}
public static void main(String[] args)
{
MyFrame d=new MyFrame();
}
}
Writable
Smart Insert


eclipse-workspace - JavaCode/src/LAB/MyJPanelDemo.java - Eclipse IDE
package LAB;
import java.awt.*;
public class MyJPanelDemo extends JFrame
{
public MyJPanelDemo()
{
JPanel obj;
setTitle("JPanel Demo");
setVisible(true);
setSize(300,200);
//Create a JPanel
obj = new JPanel();
//set the color of a JPanel
obj.setBackground(Color.green);
//Adding a jpanel to the JFrame
add(obj);
}
public static void main(String[] args) {
// TODO Auto-generated method stub
MyJPanelDemo jP = new MyJPanelDemo();
}
}


eclipse-workspace - JavaCode/src/LAB/p1.java - Eclipse IDE
package LAB;
import java.util.*;
public class p1 {
public int Price;
public String Author, Title;
public p1() {
Price = 100;
Author = "Shaurya";
Title = "50 Shades of Grey";
}
void display() {
System.out.println("Title: " + Title);
System.out.println("Author: " + Author);
System.out.println("Price: " + Price);
}
public static void main(String[] args) {
p1 book = new p1(); // Creating an object of class p1
book.display(); // Calling the display method on the object
}
}


eclipse-workspace - JavaCode/src/LAB/p2.java - Eclipse IDE
package LAB;
import java.util.*;
public class p2
{
private int Price;
private String Author, Title;
public p2()
{
Author = "Yogesh";
Title = "XXX";
Price = 1000;
}
public p2(int x)
{
Author = "Shaurya";
Title = "50 Shades of Grey";
}
void display() {
System.out.println("Title: " + Title);
System.out.println("Author: " + Author);
System.out.println("Price: " + Price);
}
public static void main(String[] args) {
p2 book = new p2(); // Creating an object of class p1
p2 book2= new p2(5);
book.display(); // Calling the display method on the object
book2.display();
}
}
Writable
Smart Insert
1 : 1 : 0


eclipse-workspace - JavaCode/src/LAB/pallindrome.java - Eclipse IDE
package LAB;
import java.util.*;
class p
{
boolean pwork(String str)
{
String rev="";
for(int i=str.length()-1;i>=0;i++)
{
char ch=str.charAt(i);
rev+=ch;
}
return str.equals(rev);
}
}
public class pallindrome {
public static void main(String[] args)
{
p p1=new p();
System.out.println("Enter the string :");
Scanner sc=new Scanner(System.in);
String x=sc.nextLine();
if(p1.pwork(x)==true)
{
System.out.println("The strings are pallindrome");
}
else
{
System.out.println("The strings is not pallindrome");
}
}
}
Writable
Smart Insert
24 : 29 : 444


eclipse-workspace - JavaCode/src/LAB26/p3uppermain.java - Eclipse IDE
package LAB26;
import java.util.*;
class p {
String s;
p(String st) {
s = st;
}
String convert() {
StringBuilder result = new StringBuilder();
for (int i = 0; i < s.length(); i++) {
char ch = s.charAt(i);
if (ch >= 'A' && ch <= 'Z') {
result.append(Character.toLowerCase(ch));
} else if (ch >= 'a' && ch <= 'z') {
result.append(Character.toUpperCase(ch));
} else {
result.append(ch);
}
}
return result.toString();
}
}
public class p3uppermain {
static Scanner sc = new Scanner(System.in);
public static void main(String[] args) {
System.out.println("Enter the string:");
String s = sc.nextLine();
p p1 = new p(s);
String n = p1.convert();
System.out.println("The new string is: " + n);
}
}


eclipse-workspace - JavaCode/src/LAB26/ShapeMain.java - Eclipse IDE
package LAB26;
abstract class Shape
{
int l,b,e;
float r;
Shape(int a,int b)
{
l=a;
this.b=b;
}
Shape(int c)
{
this.e=e;
}
Shape(float r)
{
this.r=r;
}
abstract void area();
// abstract void square_area();
// abstract void circle_area();
}
class Rectangle extends Shape
{
Rectangle(int a1 ,int b1)
{
super(a1,b1);
}
void area()
{
System.out.println("The area of rectangle is: "+l*b);
}
}
class Square extends Shape
{
Square(int a)
{
super(a);


eclipse-workspace - JavaCode/src/LAB26/ShapeMain.java - Eclipse IDE
}
}
class Square extends Shape
{
Square(int a)
{
super(a);
}
void area()
{
System.out.println("The are of square is :"+a*a);
}
}
class Circle extends Shape
{
Circle(float a)
{
super(a);
}
void area()
{
System.out.println("The arc of square is :"+2*3.14*r);
}
}
public class ShapeMain {
public static void main(String[] args)
{
Rectangle r=new Rectangle(10,5);
Square s=new Square(10);
Circle c=new Circle((float) 7.0);
r.area();
s.area();
c.area();
}
}


eclipse-workspace - JavaCode/src/LAB26/TemperatureMain.java - Eclipse IDE
package LAB26;
import java.util.Scanner;
abstract class Temperature {
double temp;
void settemp(double temp1) {
temp = temp1;
}
abstract void changetemp();
}
class Faren_to_Celci extends Temperature {
Faren_to_Celci(double a) {
this.settemp(a);
}
void changetemp() {
temp = (5.0 / 9) * (temp - 32);
this.settemp(temp);
System.out.println("Fahrenheit to Celsius: " + temp);
}
}
class Celci_to_Faren extends Temperature {
Celci_to_Faren(double a) {
this.settemp(a);
}
void changetemp() {
temp = (9.0 / 5) * temp + 32;
this.settemp(temp);
System.out.println("Celsius to Fahrenheit: " + temp);
}
}
public class TemperatureMain {
public static void main(String[] args) {


eclipse-workspace - JavaCode/src/LAB26/TemperatureMain.java - Eclipse IDE
temp = (5.0 / 9) * (temp - 32);
this.settemp(temp);
System.out.println("Fahrenheit to Celsius: " + temp);
}
}
class Celci_to_Faren extends Temperature {
Celci_to_Faren(double a) {
this.settemp(a);
}
void changetemp() {
temp = (9.0 / 5) * temp + 32;
this.settemp(temp);
System.out.println("Celsius to Fahrenheit: " + temp);
}
}
public class TemperatureMain {
public static void main(String[] args) {
Scanner sc = new Scanner(System.in);
// Convert Fahrenheit to Celsius
System.out.print("Enter temperature in Fahrenheit: ");
double fahrenheit = sc.nextDouble();
Faren_to_Celci farenToCelci = new Faren_to_Celci(fahrenheit);
farenToCelci.changetemp();
// Convert Celsius to Fahrenheit
System.out.print("Enter temperature in Celsius: ");
double celsius = sc.nextDouble();
Celci_to_Faren celciToFaren = new Celci_to_Faren(celsius);
celciToFaren.changetemp();
sc.close();
}
}


eclipse-workspace - JavaCode/src/LAB26/VolumeCalculator.java - Eclipse IDE
package LAB26;
import java.util.Scanner;
// Define the interface
interface Shapee {
void displayVolume();
}
// Class for Cone
class Cone implements Shapee {
private double radius;
private double height;
Cone(double radius, double height) {
this.radius = radius;
this.height = height;
}
@Override
public void displayVolume() {
double volume = (Math.PI * radius * radius * height) / 3;
System.out.println("Volume of the Cone: " + volume);
}
}
// Class for Hemisphere
class Hemisphere implements Shapee {
private double radius;
Hemisphere(double radius) {
this.radius = radius;
}
@Override
public void displayVolume() {
double volume = (2 * Math.PI * Math.pow(radius, 3)) / 3;
System.out.println("Volume of the Hemisphere: " + volume);
}
}


eclipse-workspace - JavaCode/src/LAB26/VolumeCalculator.java - Eclipse IDE
// Class for Cylinder
class Cylinder implements Shapee {
private double radius;
private double height;
Cylinder(double radius, double height) {
this.radius = radius;
this.height = height;
}
@Override
public void displayVolume() {
double volume = Math.PI * radius * radius * height;
System.out.println("Volume of the Cylinder: " + volume);
}
}
public class VolumeCalculator {
public static void main(String[] args) {
Scanner scanner = new Scanner(System.in);
// Get dimensions for Cone
System.out.print("Enter radius of the cone: ");
double coneRadius = scanner.nextDouble();
System.out.print("Enter height of the cone: ");
double coneHeight = scanner.nextDouble();
Cone cone = new Cone(coneRadius, coneHeight);
// Get dimensions for Hemisphere
System.out.print("Enter radius of the hemisphere: ");
double hemisphereRadius = scanner.nextDouble();
Hemisphere hemisphere = new Hemisphere(hemisphereRadius);
// Get dimensions for Cylinder
System.out.print("Enter radius of the cylinder: ");
double cylinderRadius = scanner.nextDouble();
System.out.print("Enter height of the cylinder: ");
double cylinderHeight = scanner.nextDouble();
Cylinder cylinder = new Cylinder(cylinderRadius, cylinderHeight);


eclipse-workspace - JavaCode/src/multiple/ThrowExample.java - Eclipse IDE
package multiple;
public class ThrowExample {
static void checkAge(int age) throws Exception
{
if (age < 18) {
// Throw an ArithmeticException if the age is less than 18
throw new Exception("Access denied - "
+ "You must be at least 18 years old.");
} else {
System.out.println("Access granted - You are old enough!");
}
}
public static void main(String[] args) {
try {
checkAge(10); // This will throw an ArithmeticException
} catch (Exception e) {
System.out.println("Exception caught in main: "+e);
}
}
}


eclipse-workspace - JavaCode/src/multiple/Truck.java - Eclipse IDE
package multiple;
public interface Truck extends Vehicle {
default void start()
{
Vehicle.super.start();
System.out.println("Truck is starting");
}
}


eclipse-workspace - JavaCode/src/multiple/Vehicle.java - Eclipse IDE
package multiple;
import java.util.*;
public interface Vehicle {
default void start()
{
System.out.println("Vehicle is starting");
}
}



eclipse-workspace - JavaCode/src/Termwork/p5main.java - Eclipse IDE
package Termwork;
import java.util.*;
public class p5main {
public static void main(String[] args) {
Scanner sc=new Scanner(System.in);
String s=sc.next();
StringBuilder sb=new StringBuilder(s);
for(int i=0;i<sb.length();i++)
{
if(sb.charAt(i)=='a' || sb.charAt(i)=='e' || sb.charAt(i)=='i' || sb.charAt(i)=='o' ||sb.charAt(i)==
{
sb.deleteCharAt(i);
i--;
}
}
System.out.println("The new string is:"+sb);
}
}
Writable
Smart Insert
15 : 17 : 399



eclipse-workspace - JavaCode/src/Termwork/ProducerConsumerMain.java - Eclipse IDE
package Termwork;
class SharedBuffer {
private int data;
private boolean hasData = false;
// Producer method
public synchronized void produce(int value) throws InterruptedException {
while (hasData) {
wait(); // Wait until the data is consumed
}
data = value;
hasData = true;
System.out.println("Produced: " + data);
notify(); // Notify the consumer that new data is available
}
// Consumer method
public synchronized void consume() throws InterruptedException {
while (!hasData) {
wait(); // Wait until new data is produced
}
System.out.println("Consumed: " + data);
hasData = false;
notify(); // Notify the producer that the data has been consumed
}
}
class Producer extends Thread {
private SharedBuffer buffer;
public Producer(SharedBuffer buffer) {
this.buffer = buffer;
}
@Override
public void run() {
for (int i = 1; i <= 10; i++) {
try {
buffer.produce(i);
Thread.sleep(100); // Simulate time taken to produce a value
Writable
Smart Insert
8 : 26 : 232


eclipse-workspace - JavaCode/src/Termwork/ProducerConsumerMain.java - Eclipse IDE
Thread.sleep(100); // Simulate time taken to produce a value
} catch (InterruptedException e) {
e.printStackTrace();
}
}
}
}
class Consumer extends Thread {
private SharedBuffer buffer;
public Consumer(SharedBuffer buffer) {
this.buffer = buffer;
}
@Override
public void run() {
for (int i = 1; i <= 10; i++) {
try {
buffer.consume();
Thread.sleep(150); // Simulate time taken to consume a value
} catch (InterruptedException e) {
e.printStackTrace();
}
}
}
}
public class ProducerConsumerMain {
public static void main(String[] args) {
SharedBuffer buffer = new SharedBuffer();
Producer producer = new Producer(buffer);
Consumer consumer = new Consumer(buffer);
producer.start();
consumer.start();
try {
producer.join();
Writable
Smart Insert
8 : 26 : 232

eclipse-workspace - JavaCode/src/Termwork/ProducerConsumerMain.java - Eclipse IDE
class Consumer extends Thread {
private SharedBuffer buffer;
public Consumer(SharedBuffer buffer) {
this.buffer = buffer;
}
@Override
public void run() {
for (int i = 1; i <= 10; i++) {
try {
buffer.consume();
Thread.sleep(150); // Simulate time taken to consume a value
} catch (InterruptedException e) {
e.printStackTrace();
}
}
}
}
public class ProducerConsumerMain {
public static void main(String[] args) {
SharedBuffer buffer = new SharedBuffer();
Producer producer = new Producer(buffer);
Consumer consumer = new Consumer(buffer);
producer.start();
consumer.start();
try {
producer.join();
consumer.join();
} catch (InterruptedException e) {
e.printStackTrace();
}
}
}
Writable
Smart Insert
8 : 26 : 232


eclipse-workspace - JavaCode/src/Termwork/p1main.java - Eclipse IDE
package Termwork;
public class p1main {
public static void main(String[] args) {
int n=args.length;
if(n<4)
{
System.out.println("The details are not sufficient");
}
else
{
System.out.println("Name:"+args[0]);
System.out.println("University Roll No :"+args[1]);
System.out.println("Course:"+args[2]);
System.out.println("Semester : "+args[3]);
}
}
}


eclipse-workspace - JavaCode/src/Termwork/p4main.java - Eclipse IDE
package Termwork;
import java.util.*;
public class p4main {
public static void main(String[] args) {
Scanner sc = new Scanner(System.in);
String s = sc.next();
int count = 0;
for (int i = 0; i < s.length() - 2; i++) { // Ensure there's room for "0(1+)0"
if (s.charAt(i) == '0') {
for (int j = i + 1; j < s.length() - 1; j++) {
if (s.charAt(j) == '1') {
for (int k = j + 1; k < s.length(); k++) {
if (s.charAt(k) == '0') {
count++;
i = k - 1; // Move i to k-1 to avoid counting overlapping patterns
break;
}
}
break;
}
}
}
}
System.out.println(s + "-count=" + count);
}
}



eclipse-workspace - JavaCode/src/Termwork/p5main.java - Eclipse IDE
package Termwork;
import java.util.*;
public class p5main {
public static void main(String[] args) {
Scanner sc=new Scanner(System.in);
String s=sc.next();
StringBuilder sb=new StringBuilder(s);
for(int i=0;i<sb.length();i++)
{
if(sb.charAt(i)=='a' || sb.charAt(i)=='e' || sb.charAt(i)=='i' || sb.charAt(i)=='o' ||sb.charAt(i)==
{
sb.deleteCharAt(i);
i--;
}
}
System.out.println("The new string is:"+sb);
}
}



eclipse-workspace - JavaCode/src/LAB/main703.java - Eclipse IDE
package LAB;
import java.util.*;
class converte {
void arrayF(int a[]) {
int p;
for (int i = 0; i < a.length; i++) {
for (int j = i + 1; j < a.length; j++) {
if (a[i] > a[j]) {
p = a[i];
a[i] = a[j];
a[j] = p;
}
}
}
System.out.println("The sorted array is:");
for (int i = 0; i < a.length; i++) {
System.out.print(a[i] + " ");
}
System.out.println();
}
void arrayF(int a[], int b) {
int arr[] = new int[a.length + 1];
for (int i = 0; i < a.length; i++) {
arr[i] = a[i];
}
arr[a.length] = b;
System.out.println("The array with added element is:");
for (int i = 0; i < arr.length; i++) {
System.out.print(arr[i] + " ");
}
System.out.println();
}
}
public class main703 {
public static void main(String[] args)
{
int n;


eclipse-workspace - JavaCode/src/LAB/main703.java - Eclipse IDE
void arrayF(int a[], int b) {
int arr[] = new int[a.length + 1];
for (int i = 0; i < a.length; i++) {
arr[i] = a[i];
}
arr[a.length] = b;
System.out.println("The array with added element is:");
for (int i = 0; i < arr.length; i++) {
System.out.print(arr[i] + " ");
}
System.out.println();
}
}
public class main703 {
public static void main(String[] args)
{
int n;
Scanner sc=new Scanner (System.in);
System.out.println("Enter the value of n");
n=sc.nextInt();
int arr[]=new int[n] ;
System.out.println("Enter the Value in array");
for(int i=0;i<n;i++)
{
arr[i]=sc.nextInt();
}
System.out.println("Enter the value of b");
int b=sc.nextInt();
converto c1=new converto();
c1.arrayF(arr);
c1.arrayF(arr,b);
}
}
Writable
Smart Insert
40 : 15 : 1080

eclipse-workspace - JavaCode/src/Termwork/ArrayDemo.java - Eclipse IDE
JavaCode/src/multiple/ThrowExample.java
while (i < p) {
merged[k++] = A[i++];
}
// Copy remaining elements from B
while (j < q) {
merged[k++] = B[j++];
}
// Fill A with the first p smallest elements
for (i = 0; i < p; i++) {
A[i] = merged[i];
}
// Fill B with the remaining elements
for (j = 0; j < q; j++) {
B[j] = merged[p + j];
}
}
public static void main(String[] args) {
ArrayDemo demo = new ArrayDemo();
int[] numbers = {4, 6, 5, -10, 8, 5, 20};
int target = 10;
demo.arrayFunc(numbers, target);
int[] A = { 1, 5, 6, 7, 8, 10 };
int[] B = { 2, 4, 9 };
int p = A.length;
int q = B.length;
demo.arrayFunc(A, p, B, q);
System.out.println("Sorted Arrays:");
System.out.println("A: " + Arrays.toString(A));
System.out.println("B: " + Arrays.toString(B));
}
}
Writable
Smart Insert
52 : 1 : 1434



eclipse-workspace - JavaCode/src/Termwork/Bankk.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Package Explorer
JavaCode
main703.java
areamain.java
sphere.java
AcessAnimal...
ThrowExample...
Bankk.java
ArrayDemo.java
AlternateEle...
package Termwork;
import java.util.ArrayList;
class Bankk {
private static int nextAccountNumber = 1001;
private String name;
private String address;
private int accountNumber;
private double balance;
// Constructor to initialize the bank account
public Bankk(String name, String address, double initialBalance) {
this.name = name;
this.address = address;
this.accountNumber = nextAccountNumber++;
this.balance = initialBalance;
}
// Method to display account information
public void displayInfo() {
System.out.println("Account Number: " + accountNumber);
System.out.println("Name: " + name);
System.out.println("Address: " + address);
System.out.println("Balance: " + balance);
}
// Method to deposit amount
public void deposit(double amount) {
if (amount > 0) {
balance += amount;
System.out.println("Deposited: " + amount);
} else {
System.out.println("Invalid deposit amount");
}
}
// Method to withdraw amount
public void withdraw(double amount) {
Writable
Smart Insert
8 : 49 : 144



eclipse-workspace - JavaCode/src/Termwork/Bankk.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Package Explorer
JavaCode
main703.java
areamain.java
sphere.java
AcessAnimal...
ThrowExample...
Bankk.java
ArrayDemo.java
AlternateEle...
// Method to withdraw amount
public void withdraw(double amount) {
if (amount > 0 && amount <= balance) {
balance -= amount;
System.out.println("Withdrawn: " + amount);
} else {
System.out.println("Invalid or insufficient amount for withdrawal");
}
}
// Method to change address
public void changeAddress(String newAddress) {
address = newAddress;
System.out.println("Address updated to: " + newAddress);
}
// Getters for account number and name (for identifying accounts)
public int getAccountNumber() {
return accountNumber;
}
public String getName() {
return name;
}
public static void main(String[] args) {
Scanner scanner = new Scanner(System.in);
ArrayList<Bankk> bankAccounts = new ArrayList<>();
// Enter the number of depositors
System.out.print("Enter the number of depositors: ");
int numDepositors = scanner.nextInt();
scanner.nextLine(); // Consume newline
// Enter information for each depositor
for (int i = 0; i < numDepositors; i++) {
System.out.print("Enter name of depositor: ");
String name = scanner.nextLine();
System.out.print("Enter address of depositor: ");
String address = scanner.nextLine();
Writable
Smart Insert
8 : 49 : 144


eclipse-workspace - JavaCode/src/Termwork/Bankk.java - Eclipse IDE
// Enter information for each depositor
for (int i = 0; i < numDepositors; i++) {
System.out.print("Enter name of depositor: ");
String name = scanner.nextLine();
System.out.print("Enter address of depositor: ");
String address = scanner.nextLine();
System.out.print("Enter initial balance: ");
double balance = scanner.nextDouble();
scanner.nextLine(); // Consume newline
Bankk account = new Bankk(name, address, balance);
bankAccounts.add(account);
System.out.println("Account created with account number: " + account.getAccountNumber());
}
// Perform operations
boolean continueOperations = true;
while (continueOperations) {
System.out.println("\nChoose an operation:");
System.out.println("1. Display information of a depositor");
System.out.println("2. Deposit amount");
System.out.println("3. Withdraw amount");
System.out.println("4. Change address");
System.out.println("5. Exit");
int choice = scanner.nextInt();
scanner.nextLine(); // Consume newline
switch (choice) {
case 1:
System.out.print("Enter account number: ");
int accNumberToDisplay = scanner.nextInt();
scanner.nextLine(); // Consume newline
for (Bankk account : bankAccounts) {
if (account.getAccountNumber() == accNumberToDisplay) {
account.displayInfo();
}
}
break;


eclipse-workspace - JavaCode/src/LAB/EmployeeMain.java - Eclipse IDE
package LAB;
import java.util.*;
class Emp
{
String name;
int eid,deptid;
void display(String name,int eid,int deptid)
{
this.name=name;
this.eid=eid;
this.deptid=deptid;
try
{
if(!(name.charAt(0)>=65 && name.charAt(0)<=90))
{
throw new ArithmeticException("The first letter is not Capital");
}
}
catch(Exception e)
{
System.out.println(e);
}
try
{
if(!(eid>=2001 && eid<=5001))
{
throw new Exception("The employee id id not in range of 2001 - 5001.");
}
}
catch(Exception e)
{
System.out.println(e);
}
try
{
if(!(deptid>=1 && deptid<=5))


eclipse-workspace - JavaCode/src/LAB/EmployeeMain.java - Eclipse IDE
{
throw new Exception("The employee id id not in range of 2001 - 5001.");
}
}
catch(Exception e)
{
System.out.println(e);
}
try
{
if(!(deptid>=1 && deptid<=5))
{
throw new Exception("The dept id is not in the rage of 1 - 5.");
}
}
catch(Exception e)
{
System.out.println(e);
}
System.out.println("Name :"+name +"\nEmp id: "+eid+"\nDept ID: "+deptid);
}
}
public class EmployeeMain {
public static void main(String[] args)
{
Scanner sc=new Scanner(System.in);
System.out.println("Enter the Employee name ,Employee id and Department ID:");
String name=sc.next();
int eid=sc.nextInt();
int deptid=sc.nextInt();
Emp e=new Emp();
e.display(name,eid,deptid);
}
}
Writable
Smart Insert
7 : 17 : 66


eclipse-workspace - JavaCode/src/Termwork/AlternateElements.java - Eclipse IDE
package Termwork;
import java.util.ArrayList;
public class AlternateElements {
public static List<Integer> alternate(List<Integer> list1, List<Integer> list2) {
List<Integer> result = new ArrayList<>();
int size1 = list1.size();
int size2 = list2.size();
int maxSize = Math.max(size1, size2);
for (int i = 0; i < maxSize; i++) {
if (i < size1)
result.add(list1.get(i));
if (i < size2)
result.add(list2.get(i));
}
return result;
}
public static void main(String[] args) {
List<Integer> list1 = new ArrayList<>();
list1.add(1);
list1.add(2);
list1.add(3);
list1.add(4);
list1.add(5);
List<Integer> list2 = new ArrayList<>();
list2.add(6);
list2.add(7);
list2.add(8);
list2.add(9);
list2.add(10);
list2.add(11);
list2.add(12);
List<Integer> result = alternate(list1, list2);
System.out.println(result);
Writable
Smart Insert
6 : 1 : 108


eclipse-workspace - JavaCode/src/Termwork/ArrayDemo.java - Eclipse IDE
package Termwork;
import java.util.Arrays;
class ArrayDemo {
// Overloaded arrayFunc method to find pairs with a specific sum
void arrayFunc(int[] array, int target) {
System.out.println("Pairs of elements whose sum is " + target + " are:");
for (int i = 0; i < array.length; i++) {
for (int j = i + 1; j < array.length; j++) {
if (array[i] + array[j] == target) {
System.out.println(array[i] + " + " + array[j] + " = " + target);
}
}
}
}
void arrayFunc(int[] A, int p, int[] B, int q) {
int[] merged = new int[p + q];
int i = 0, j = 0, k = 0;
// Merge the two arrays
while (i < p && j < q) {
if (A[i] < B[j]) {
merged[k++] = A[i++];
} else {
merged[k++] = B[j++];
}
}
// Copy remaining elements from A
while (i < p) {
merged[k++] = A[i++];
}
// Copy remaining elements from B
while (j < q) {
merged[k++] = B[j++];
}
Writable
Smart Insert
34 : 10 : 1040


eclipse-workspace - JavaCode/src/JButtonExample1.java - Eclipse IDE
import javax.swing.*;
public class JButtonExample1 {
public static void main(String[] args) {
// Create a new JFrame
JFrame frame = new JFrame("JButton Example");
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
frame.setSize(400, 400);
frame.setLayout(new FlowLayout());
// JButton with no text or icon
JButton button1 = new JButton();
button1.setText("Submit");
button1.setToolTipText("This is Submit Button");
frame.add(button1);
// JButton with text
JButton button2 = new JButton("Reset");
button2.setToolTipText("This is a Reset Button");
frame.add(button2);
// Configure JButton using various methods
button1.setVerticalTextPosition(SwingConstants.BOTTOM);
button1.setHorizontalTextPosition(SwingConstants.CENTER);
button2.setVerticalTextPosition(SwingConstants.BOTTOM);
button2.setHorizontalTextPosition(SwingConstants.CENTER);
// button1.setMargin(new Insets(10, 10, 10, 10));
// button1.setEnabled(true);
// button1.setContentAreaFilled(true);
// button1.setBorderPainted(true);
// Make the frame visible
frame.setVisible(true);
}
}
Writable
Smart Insert
13 : 40 : 397


eclipse-workspace - JavaCode/src/Chapter1/p2.java - Eclipse IDE
package Chapter1;
import java.util.*;
public class p2
{
public static void main(String args[])
{
Scanner sc=new Scanner(System.in);
int num,i,count=0;
System.out.println("Enter the number :");
num=sc.nextInt();
for(i=2;i<=num;i++)
{
for(int j=2;j<=i;j++)
{
if(i%j==0)
{
count++;
}
}
if(count==1)
{
System.out.println(i);
}
count=0;
}
}
}


eclipse-workspace - JavaCode/src/Chapter1/p3.java - Eclipse IDE
package Chapter1;
import java.util.Scanner;
public class p3 {
public static void main(String[] args) {
int x,s=0,d; //rev of digit of x
Scanner sc=new Scanner(System.in);
System.out.println("Enter a number:");
x=sc.nextInt();
while(x!=0)
{
d=x%10;
s=s*10+d;
x=x/10;
}
System.out.println("The reverse of number is: "+s);
}
}


eclipse-workspace - JavaCode/src/Chapter1/Program1.java - Eclipse IDE
package Chapter1;
public class Program1
{
public static void main(String args[])
{
int i,count=0;
for(i=2;i<=50;i++)
{
for(int j=2;j<i;j++)
{
if(i%j==0)
{
count++;
}
}
if(count==0)
{
System.out.println(i);
}
count=0;
}
}
}


eclipse-workspace - JavaCode/src/LAB/Main.java - Eclipse IDE
package LAB;
interface A
{
void speak();
}
interface one extends A
{
void name();
}
interface two extends A
{
void type();
}
class B implements one,two
{
public void speak()
{
System.out.println("Fuck");
}
public void name()
{
System.out.println("Hes");
}
@Override
public void type() {
System.out.println("Animal");
}
}
public class Main {
public static void main(String[] args) {
B ob =new B();
ob.speak();
ob.name();
ob.type();
}
}


eclipse-workspace - JavaCode/src/LAB/Main.java - Eclipse IDE
package LAB;
interface A
{
void speak();
}
interface one extends A
{
void name();
}
interface two extends A
{
void type();
}
class B implements one,two
{
public void speak()
{
System.out.println("Fuck");
}
public void name()
{
System.out.println("Hen");
}
@Override
public void type() {
System.out.println("Animal");
}
}
public class Main {
public static void main(String[] args) {
B ob =new B();
ob.speak();
ob.name();
ob.type();
}
}
Writable
Smart Insert
38 : 6 : 500


eclipse-workspace - JavaCode/src/LAB/mainvowels.java - Eclipse IDE
package LAB;
import java.util.*;
class vowels
{
int countvowels(String str)
{
int count = 0;
for (int i = 0; i < str.length(); i++) { // Corrected loop condition
char ch = str.charAt(i);
if (ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u') {
count += 1;
}
}
return count;
}
}
public class mainvowels
{
public static void main(String args[])
{
vowels v1=new vowels();
int co;
Scanner sc = new Scanner(System.in);
System.out.println("Enter the string:");
String x = sc.nextLine();
co = v1.countvowels(x);
System.out.println("No of vowels in " + x + " is: " + co); // Added space after "in"
}
}
Writable
Smart Insert
10 : 58 : 290


eclipse-workspace - JavaCode/src/LAB/MyCalculateMain.java - Eclipse IDE
package LAB;
import java.util.*;
class MyCalculate
{
int n,exp;
int power(int n,int exp) throws Exception
{
if(n<0 || exp<0)
{
throw new Exception("The number n & e shoulbe non negative");
}
else
{
this.n=n;
this.exp=exp;
double num=Math.pow(n,exp);
return (int)num;
}
}
}
public class MyCalculateMain {
public static void main(String[] args) throws Exception
{
MyCalculate obj=new MyCalculate();
Scanner sc=new Scanner(System.in);
System.out.print("Enter the value of number and the exponent:");
try
{
int n=sc.nextInt();
int exp=sc.nextInt();
int a=obj.power(n,exp);
System.out.println(n+"^"+exp+"="+a);
}
catch(Exception e)
{
Writable
Smart Insert
24 : 1 : 391

eclipse-workspace - JavaCode/src/LAB/PallindromeMain.java - Eclipse IDE
package LAB;
import java.io.File;
public class PallindromeMain {
public static boolean isPalindrome(String word) {
StringBuilder reversed = new StringBuilder(word).reverse();
return word.equalsIgnoreCase(reversed.toString());
}
public static void main(String[] args) {
File file = new File("pallin.txt");
try {
if (file.createNewFile()) {
System.out.println("File is Created");
} else {
System.out.println("There was a problem while creating the file");
}
} catch (IOException e) {
System.out.println("Exception caught in creating the file ");
e.printStackTrace();
}
try {
FileWriter writer = new FileWriter(file);
writer.write("Hello madam how are you");
writer.close();
} catch (IOException e) {
System.out.println("Error found in writing the file");
e.printStackTrace();
}
try {
FileReader fileReader = new FileReader(file);
BufferedReader bufferedReader = new BufferedReader(fileReader);
String line;
int palindromeCount = 0;
while ((line = bufferedReader.readLine()) != null)
Writable
Smart Insert
32 : 12 : 978


eclipse-workspace - JavaCode/src/LAB/PallindromeMain.java - Eclipse IDE
}

try {
FileWriter writer = new FileWriter(file);
writer.write("Hello madam how are you");
writer.close();

} catch (IOException e) {
System.out.println("Error found in writing the file");
e.printStackTrace();
}

try {
FileReader fileReader = new FileReader(file);
BufferedReader bufferedReader = new BufferedReader(fileReader);
String line;
int palindromeCount = 0;
while ((line = bufferedReader.readLine()) != null)
{
String[] words = line.split("\\s+");
for (String word : words) {
if (isPalindrome(word)) {
palindromeCount++;
}
}
}
bufferedReader.close();
System.out.println("Number of palindrome words: " + palindromeCount);

} catch (IOException e) {
System.out.println("Error found in reading the file");
e.printStackTrace();
}
}
}

//write a java prog to create a interface and make classes cone,clinder and hemisphere that implements the interfa
/*write a java file handlinf prog to count and display thr no of pallindrome present in thr text file*/
Writable
Smart Insert
32 : 12 : 978

eclipse-workspace - JavaCode/src/LAB/Threadmain.java - Eclipse IDE
package LAB;

class ThreadCount extends Thread
{
private int threadno;
public ThreadCount(int threadno)
{
this.threadno=threadno;
}
public void run()
{
try {
countThread();
} catch (InterruptedException e) {
e.printStackTrace();
}
}
public void countThread() throws InterruptedException
{
for(int i=0;i<5;i++)
{
Thread.sleep(500);
System.out.println("Thread No."+threadno+"iteration"+i);
}
}
}

/*write a java file handlinf prog to count and display thr no of pallindrome present in thr text file*/
public class Threadmain {

public static void main(String[] args) throws InterruptedException
{
long startTime=System.currentTimeMillis();
for(int i=0;i<10;i++)
{
ThreadCount t1=new ThreadCount(i);
t1.start();
}
Thread.sleep(3000);
Writable
Smart Insert
1 : 1 : 0


eclipse-workspace - JavaCode/src/LAB/Threadmain.java - Eclipse IDE
public void run()
{
try {
countThread();
} catch (InterruptedException e) {
e.printStackTrace();
}
}
public void countThread() throws InterruptedException
{
for(int i=0;i<5;i++)
{
Thread.sleep(500);
System.out.println("Thread No."+threadno+"Iteration"+i);
}
}
}
/*write a java file handlint prog to count and display thr no of pallindrome present in thr text file*/
public class Threadmain {
public static void main(String[] args) throws InterruptedException
{
long startTime=System.currentTimeMillis();
for(int i=0;i<10;i++)
{
ThreadCount t1=new ThreadCount(i);
t1.start();
}
Thread.sleep(3000);
System.out.println("Main thread is exiting.....");
long endTime=System.currentTimeMillis();
System.out.println("Time taken:"+(endTime-startTime)/1000+" seconds");
}
}


eclipse-workspace - JavaCode/src/LAB26/VolumeCalculator.java - Eclipse IDE
@Override
public void displayVolume() {
double volume = Math.PI * radius * radius * height;
System.out.println("Volume of the Cylinder: " + volume);
}
}
public class VolumeCalculator {
public static void main(String[] args) {
Scanner scanner = new Scanner(System.in);
// Get dimensions for Cone
System.out.print("Enter radius of the cone: ");
double coneRadius = scanner.nextDouble();
System.out.print("Enter height of the cone: ");
double coneHeight = scanner.nextDouble();
Cone cone = new Cone(coneRadius, coneHeight);
// Get dimensions for Hemisphere
System.out.print("Enter radius of the hemisphere: ");
double hemisphereRadius = scanner.nextDouble();
Hemisphere hemisphere = new Hemisphere(hemisphereRadius);
// Get dimensions for Cylinder
System.out.print("Enter radius of the cylinder: ");
double cylinderRadius = scanner.nextDouble();
System.out.print("Enter height of the cylinder: ");
double cylinderHeight = scanner.nextDouble();
Cylinder cylinder = new Cylinder(cylinderRadius, cylinderHeight);
// Display volumes
System.out.println();
cone.displayVolume();
hemisphere.displayVolume();
cylinder.displayVolume();
scanner.close();
}
}


eclipse-workspace - JavaCode/src/multiple/Car.java - Eclipse IDE
package multiple;
public interface Car extends Vehicle
{
default void start()
{
Vehicle.super.start();
System.out.println("Car is startting");
}
}


eclipse-workspace - JavaCode/src/multiple/Hybrid.java - Eclipse IDE
package multiple;
public class Hybrid implements Car ,Truck {
public void start()
{
System.out.println("Hybrid class ");
Car.super.start();
Truck.super.start();
}
}


eclipse-workspace - JavaCode/src/multiple/mainclass.java - Eclipse IDE
package multiple;
public class mainclass {
public static void main(String args[])
{
Hybrid h= new Hybrid ();
h.start();
}
}
Writable
Smart Insert
10 : 1 : 140


eclipse-workspace - JavaCode/src/Termwork/VowelCounterApp.java - Eclipse IDE
package Termwork;
import java.awt.event.*;
public class VowelCounterApp implements ActionListener {
JFrame frame = new JFrame("Shaurya");
JButton button = new JButton("Count Number of Vowels");
JTextField f1 = new JTextField();
JTextField f2 = new JTextField();
public VowelCounterApp() {
frame.setSize(400, 400);
f1.setBounds(50, 40, 150, 20);
f2.setBounds(50, 70, 150, 20);
button.setBounds(50, 130, 95, 30);
button.addActionListener(this);
frame.add(button);
frame.add(f1);
frame.add(f2);
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
frame.setLayout(null);
frame.setVisible(true);
}
public void actionPerformed(ActionEvent e) {
String s1 = f1.getText();
int count = 0;
try {
for (int i = 0; i < s1.length(); i++) {
if (s1.charAt(i) == 'a' || s1.charAt(i) == 'e' || s1.charAt(i) == 'i' || s1.charAt(i) == 'o'
|| s1.charAt(i) == 'u') {
count++;
}
}
String s = "" + count;
f2.setText(s);
} catch (Exception ex) {
f2.setText(ex.toString());
}
}
Writable
Smart Insert
41 : 1 : 1314


eclipse-workspace - JavaCode/src/Termwork/SwapPairs.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Package Explorer
ThrowExample... ProducerCon... p5main.java RemoveEvenLe... SwapPairs.java VowelCounter... Vehicle.java Truck.java
package Termwork;
import java.util.ArrayList;
public class SwapPairs {
public static void swapPairs(ArrayList<String> list) {
for (int i = 0; i < list.size() - 1; i += 2) {
// Swap the elements at indices i and i+1
String temp = list.get(i);
list.set(i, list.get(i + 1));
list.set(i + 1, temp);
}
}
public static void main(String[] args) {
ArrayList<String> list1 = new ArrayList<>();
list1.add("four");
list1.add("score");
list1.add("and");
list1.add("seven");
list1.add("years");
list1.add("ago");
System.out.println("Original list: " + list1);
swapPairs(list1);
System.out.println("List after swapping pairs: " + list1);
ArrayList<String> list2 = new ArrayList<>();
list2.add("to");
list2.add("be");
list2.add("or");
list2.add("not");
list2.add("to");
list2.add("be");
list2.add("hamlet");
System.out.println("Original list: " + list2);
swapPairs(list2);
System.out.println("List after swapping pairs: " + list2);
Writable
Smart Insert
38 : 38 : 1094


eclipse-workspace - JavaCode/src/Termwork/p3main.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Package Explorer
ProducerCon... p3main.java p5main.java RemoveEvenLe... SwapPairs.java VowelCounter... Vehicle.java Truck.java
Here, 7 is the saddle point because it is the minimum element in its row and maximum element in its column.
*/
public class p3main {
public static void main(String[] args) {
int[][] matrix = {
{1, 2, 3},
{4, 5, 6},
{7, 8, 9}
};
findSaddlePoint(matrix);
}
public static void findSaddlePoint(int[][] matrix) {
int rows = matrix.length;
int cols = matrix[0].length;
for (int i = 0; i < rows; i++) {
int minRowValue = matrix[i][0];
int minColIndex = 0;
// Find the minimum element in the current row
for (int j = 1; j < cols; j++) {
if (matrix[i][j] < minRowValue) {
minRowValue = matrix[i][j];
minColIndex = j;
}
}
boolean isSaddlePoint = true;
// Check if the found minimum element is the maximum in its column
for (int k = 0; k < rows; k++) {
if (matrix[k][minColIndex] > minRowValue) {
isSaddlePoint = false;
break;
}
}
// If it is a saddle point, print its coordinates
Writable
Smart Insert
17 : 9 : 584


eclipse-workspace - JavaCode/src/Termwork/p2main.java - Eclipse IDE
package Termwork;
import java.util.Scanner;
public class p2main {
public static void main(String[] args) {
Scanner sc = new Scanner(System.in);
System.out.println("Enter the value of the nums variable");
int n = sc.nextInt();
// Convert the integer to a string
String s = Integer.toString(n);
// Replace all '0' characters with '1' and store the result
s = s.replace('0', '1');
// Convert the modified string back to an integer
int m = Integer.parseInt(s);
// Print the result
System.out.println("The new number is: " + m);
}
}
Writable
Smart Insert