



Machine Learning

Recommen der ~~Systems~~ Problem formulation

Example: Predicting movie ratings

User rates movies using one to five stars



Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last				
Romance forever				
Cute puppies of love				
Nonstop car chases				
Swords vs. karate				

n_u = no. users

n_m = no. movies

$r(i, j)$ = 1 if user j has rated movie i

$y^{(i, j)}$ = rating given by user j to movie i

(defined only if $r(i, j) = 1$)

In our notation, $r(i, j) = 1$ if user j has rated movie i , and $y^{(i, j)}$ is his rating on that movie. Consider the following example (no. of movies $n_m = 2$, no. of users $n_u = 3$):


.	User 1	User 2	User 3
Movie 1	0	1	?
Movie 2	?	5	5

What is $r(2, 1)$? How about $y^{(2, 1)}$?

- ☐ $r(2, 1) = 0, y^{(2, 1)} = 1$
- ☐ $r(2, 1) = 1, y^{(2, 1)} = 1$
- ☒ $r(2, 1) = 0, y^{(2, 1)} = \text{undefined}$

Correct Response

- ☐ $r(2, 1) = 1, y^{(2, 1)} = \text{undefined}$



Machine Learning

Recommen der ~~System-based~~ content-based recommendati ons

Content-based recommender systems

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	4	0	?
Nonstop car chases	0	0	5	3
Swords & karate	?	?	?	?

For each user u , learn a parameter μ_u

user u as rating movie with stars.

0.1

1.0

0.9

Predict

Problem formulation

$r(i, j) = 1$ if user i has rated movie j (0 otherwise)

$y^{(i,j)}$ = rating by user i on movie j (if defined)

$\theta^{(j)}$ = parameter vector for user j

$x^{(i)}$ = feature vector for movie i

For user j , movie i , predicted rating: $\theta^{(j)T} x^{(i)}$

$m^{(j)}$ = no. of movies rated by user j

To learn $\theta^{(j)}$:

Optimization objective:

To learn $\theta^{(j)}$ (parameter for user j):

$$\min_{\theta^{(j)}} \frac{1}{2} \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{k=1}^n (\theta_k^{(j)})^2$$

To learn $\theta^{(1)}, \theta^{(2)}, \dots, \theta^{(n_u)}$:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

Optimization algorithm:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

Gradient descent update:

$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} \quad (\text{for } k = 0)$$

$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \left(\sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} + \lambda \theta_k^{(j)} \right) \quad (\text{for } k \neq 0)$$



Machine Learning

Recommen der ~~Systems~~ Collaborati ve filtering

Problem motivation

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	x_1 (romance)	x_2 (action)
Love at last	5	5	0	0	0.9	0
Romance forever	5	?	?	0	1.0	0.01
Cute puppies of love	?	4	0	?	0.99	0
Nonstop car chases	0	0	5	4	0.1	1.0
Swords vs. karate	0	0	5	?	0	0.9

Problem motivation

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	x_1 (romance)	x_2 (action)
Love at last	5	5	0	0	?	?
Romance forever	5	?	?	0	?	?
Cute puppies of love	?	4	0	?	?	?
Nonstop car chases	0	0	5	4	?	?
Swords vs. karate	$\theta^{(1)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}$	$\theta^{(2)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}$	$\theta^{(3)} = \begin{bmatrix} 5 \\ 0 \\ 5 \end{bmatrix}$	$\theta^{(4)} = \begin{bmatrix} ? \\ 0 \\ 5 \end{bmatrix}$	$\begin{bmatrix} 0 \\ 0 \\ 5 \end{bmatrix}$	$\begin{bmatrix} ? \\ ? \\ ? \end{bmatrix}$

Consider the following movie ratings:

.	User 1	User 2	User 3	(romance)
Movie 1	0	1.5	2.5	?

Note that there is only one feature x_1 . Suppose that:

$$\theta^{(1)} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \theta^{(2)} = \begin{bmatrix} 0 \\ 3 \end{bmatrix}, \theta^{(3)} = \begin{bmatrix} 0 \\ 5 \end{bmatrix}$$

What would be a reasonable value for $x_1^{(1)}$ (the value denoted "?" in the table above)?

☒ 0.5

Correct Response

☐ 1

☐ 2

☐ Any of these values would be equally reasonable.

Optimization algorithm

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$, to learn $\theta^{(i)}$:

$$\min_{x^{(i)}} \frac{1}{2} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{k=1}^n (x_k^{(i)})^2$$

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$, to learn $x^{(1)}, \dots, x^{(n_m)}$:

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2$$

Collaborative filtering

Given $x^{(1)}, \dots, x^{(n_m)}$ (and movie ratings),
can estimate $\theta^{(1)}, \dots, \theta^{(n_u)}$

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$,
can estimate $x^{(1)}, \dots, x^{(n_m)}$


Suppose you use gradient descent to minimize:

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2$$

Which of the following is a correct gradient descent update rule for $i \neq 0$?

- ☐ $x_k^{(i)} := x_k^{(i)} + \alpha \left(\sum_{j:r(i,j)=1} \left((\theta^{(j)})^T (x^{(i)}) - y^{(i,j)} \right) \theta_k^{(j)} \right)$
- ☐ $x_k^{(i)} := x_k^{(i)} - \alpha \left(\sum_{j:r(i,j)=1} \left((\theta^{(j)})^T (x^{(i)}) - y^{(i,j)} \right) \theta_k^{(j)} \right)$
- ☐ $x_k^{(i)} := x_k^{(i)} + \alpha \left(\sum_{j:r(i,j)=1} \left((\theta^{(j)})^T (x^{(i)}) - y^{(i,j)} \right) \theta_k^{(j)} + \lambda x_k^{(i)} \right)$
- ☒ $x_k^{(i)} := x_k^{(i)} - \alpha \left(\sum_{j:r(i,j)=1} \left((\theta^{(j)})^T (x^{(i)}) - y^{(i,j)} \right) \theta_k^{(j)} + \lambda x_k^{(i)} \right)$

Correct Response



Machine Learning

Recommen
der
~~Systems~~
Collaborative
filtering
algorithm

Collaborative filtering optimization objective

Given $x^{(1)}, \dots, x^{(n_m)}$, estimate $\theta^{(1)}, \dots, \theta^{(n_u)}$:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$, estimate $x^{(1)}, \dots, x^{(n_m)}$:

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2$$

Minimizing $x^{(1)}, \dots, x^{(n_m)}$ and $\theta^{(1)}, \dots, \theta^{(n_u)}$ simultaneously:

$$J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)}) = \frac{1}{2} \sum_{(i,j):r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

$$\min_{\substack{x^{(1)}, \dots, x^{(n_m)} \\ \theta^{(1)}, \dots, \theta^{(n_u)}}} J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)})$$

Collaborative filtering algorithm

1. Initialize $x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)}$ to small random values.

2. Minimize $J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)})$ using gradient descent (or an advanced optimization algorithm). E.g. for every $j = 1, \dots, n_u, i = 1, \dots, n_m$

$$x_k^{(i)} := x_k^{(i)} - \alpha \left(\sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) \theta_k^{(j)} + \lambda x_k^{(i)} \right)$$


$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \left(\sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} + \lambda \theta_k^{(j)} \right)$$

3. For a user with parameters θ and a movie with (learned) features x , predict a star rating of $\theta^T x$.

In the algorithm we described, we initialized $x^{(1)}, \dots, x^{(n_m)}$ and $\theta^{(1)}, \dots, \theta^{(n_u)}$ to small random values. Why is this?

- ☐ This step is optional. Initializing to all 0's would work just as well.
- ☐ Random initialization is always necessary when using gradient descent on any problem.
- ☐ This ensures that $x^{(i)} \neq \theta^{(j)}$ for any i, j .
- ☒ This serves as symmetry breaking (similar to the random initialization of a neural network's parameters) and ensures the algorithm learns features $x^{(1)}, \dots, x^{(n_m)}$ that are different from each other.

Correct Response



Machine Learning

Recommen
der
~~Systemization:~~
Low rank
matrix
factorization

Collaborative filtering

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	4	0	?
Nonstop car chases	0	0	5	4
Swords vs. karate	0	0	5	?

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 \\ 5 & ? & ? & 0 \\ ? & 4 & 0 & ? \\ 0 & 0 & 5 & 4 \\ 0 & 0 & 5 & 0 \end{bmatrix}$$

Collaborative filtering

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 \\ 5 & ? & ? & 0 \\ ? & 4 & 0 & ? \\ 0 & 0 & 5 & 4 \\ 0 & 0 & 5 & 0 \end{bmatrix}$$

Predicted

$$\begin{bmatrix} \text{ratings} & (\theta^{(1)})^T(x^{(1)}) & (\theta^{(2)})^T(x^{(1)}) & \dots & (\theta^{(n_u)})^T(x^{(1)}) \\ (\theta^{(1)})^T(x^{(2)}) & (\theta^{(2)})^T(x^{(2)}) & \dots & (\theta^{(n_u)})^T(x^{(2)}) \\ \vdots & \vdots & \vdots & \vdots \\ (\theta^{(1)})^T(x^{(n_m)}) & (\theta^{(2)})^T(x^{(n_m)}) & \dots & (\theta^{(n_u)})^T(x^{(n_m)}) \end{bmatrix}$$

Let $X = \begin{bmatrix} - & (x^{(1)})^T & - \\ & \vdots & \\ - & (x^{(n_m)}) & - \end{bmatrix}$, $\Theta = \begin{bmatrix} - & (\theta^{(1)})^T & - \\ & \vdots & \\ - & (\theta^{(n_u)}) & - \end{bmatrix}$.

What is another way of writing the following:

$$\begin{bmatrix} (x^{(1)})^T (\theta^{(1)}) & \dots & (x^{(1)})^T (\theta^{(n_u)}) \\ \vdots & \ddots & \vdots \\ (x^{(n_m)})^T (\theta^{(1)}) & \dots & (x^{(n_m)})^T (\theta^{(n_u)}) \end{bmatrix}$$

☐ $X\Theta$

☐ $X^T\Theta$

☒ $X\Theta^T$

Correct Response

☐ $\Theta^T X^T$

Finding related movies

For each product i , we learn a feature vector $x^{(i)} \in \mathbb{R}^n$.

.

How to find movies related to movie i ?

5 most similar movies to movie i :

Find the 5 movies j with the smallest $\|x^{(i)} - x^{(j)}\|$.



Machine Learning

Recommen
der
~~System~~
Implementation detail:
Mean
normalization

Users who have not rated any movies

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	Eve (5)
Love at last	5	5	0	0	?
Romance forever	5	?	?	0	?
Cute puppies of love	?	4	0	?	?
Nonstop car chases	0	0	5	4	?
Swords vs. karate	0	0	5	?	?

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix}$$

$$\min_{\theta^{(1)}, \dots, \theta^{(n_m)}} \frac{1}{2} \sum_{(i,j): r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

Mean Normalization:

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix} \quad \mu = \begin{bmatrix} 2.5 \\ 2.5 \\ 2 \\ 2.25 \\ 1.25 \end{bmatrix} \rightarrow Y = \begin{bmatrix} 2.5 & 2.5 & -2.5 & -2.5 & ? \\ 2.5 & ? & ? & -2.5 & ? \\ ? & 2 & -2 & ? & ? \\ -2.25 & -2.25 & 2.75 & 1.75 & ? \\ -1.25 & -1.25 & 3.75 & -1.25 & ? \end{bmatrix}$$

For user j , on movie predict:

User 5 (Eve):

We talked about mean normalization. However, unlike some other applications of feature scaling, we did not scale the movie ratings by dividing by the range (max – min value). This is because:

- ☐ This sort of scaling is not useful when the value being predicted is real-valued.
- ☒ All the movie ratings are already comparable (e.g., 0 to 5 stars), so they are already on similar scales.

Correct Response

- ☐ Subtracting the mean is mathematically equivalent to dividing by the range.
- ☐ This makes the overall algorithm significantly more computationally efficient.