

Contents

Biography	xxxi
Preface.....	xxxiii

PART 1 INTRODUCTION

CHAPTER 1	Statistical Machine Learning	3
1.1	Types of Learning	3
1.2	Examples of Machine Learning Tasks	4
1.2.1	Supervised Learning	4
1.2.2	Unsupervised Learning	5
1.2.3	Further Topics	6
1.3	Structure of This Textbook	8

PART 2 STATISTICS AND PROBABILITY

CHAPTER 2	Random Variables and Probability Distributions	11
2.1	Mathematical Preliminaries	11
2.2	Probability	13
2.3	Random Variable and Probability Distribution	14
2.4	Properties of Probability Distributions	16
2.4.1	Expectation, Median, and Mode	16
2.4.2	Variance and Standard Deviation	18
2.4.3	Skewness, Kurtosis, and Moments	19
2.5	Transformation of Random Variables	22
CHAPTER 3	Examples of Discrete Probability Distributions	25
3.1	Discrete Uniform Distribution	25
3.2	Binomial Distribution	26
3.3	Hypergeometric Distribution.....	27
3.4	Poisson Distribution	31
3.5	Negative Binomial Distribution	33
3.6	Geometric Distribution.....	35
CHAPTER 4	Examples of Continuous Probability Distributions	37
4.1	Continuous Uniform Distribution	37
4.2	Normal Distribution.....	37
4.3	Gamma Distribution, Exponential Distribution, and Chi-Squared Distribution	41
4.4	Beta Distribution	44
4.5	Cauchy Distribution and Laplace Distribution	47
4.6	t -Distribution and F -Distribution	49

CHAPTER 5	Multidimensional Probability Distributions	51
5.1	Joint Probability Distribution	51
5.2	Conditional Probability Distribution	52
5.3	Contingency Table	53
5.4	Bayes' Theorem	53
5.5	Covariance and Correlation	55
5.6	Independence	56
CHAPTER 6	Examples of Multidimensional Probability Distributions	61
6.1	Multinomial Distribution	61
6.2	Multivariate Normal Distribution	62
6.3	Dirichlet Distribution	63
6.4	Wishart Distribution	70
CHAPTER 7	Sum of Independent Random Variables	73
7.1	Convolution	73
7.2	Reproductive Property	74
7.3	Law of Large Numbers	74
7.4	Central Limit Theorem	77
CHAPTER 8	Probability Inequalities	81
8.1	Union Bound	81
8.2	Inequalities for Probabilities	82
	8.2.1 Markov's Inequality and Chernoff's Inequality	82
	8.2.2 Cantelli's Inequality and Chebyshev's Inequality ..	83
8.3	Inequalities for Expectation	84
	8.3.1 Jensen's Inequality	84
	8.3.2 Hölder's Inequality and Schwarz's Inequality	85
	8.3.3 Minkowski's Inequality	86
	8.3.4 Kantorovich's Inequality	87
8.4	Inequalities for the Sum of Independent Random Vari- ables	87
	8.4.1 Chebyshev's Inequality and Chernoff's Inequality	88
	8.4.2 Hoeffding's Inequality and Bernstein's Inequality	88
	8.4.3 Bennett's Inequality	89
CHAPTER 9	Statistical Estimation	91
9.1	Fundamentals of Statistical Estimation	91
9.2	Point Estimation	92
	9.2.1 Parametric Density Estimation	92
	9.2.2 Nonparametric Density Estimation	93
	9.2.3 Regression and Classification	93

	9.2.4	Model Selection	94
9.3		Interval Estimation	95
	9.3.1	Interval Estimation for Expectation of Normal Samples	95
	9.3.2	Bootstrap Confidence Interval	96
	9.3.3	Bayesian Credible Interval	97
CHAPTER 10		Hypothesis Testing	99
	10.1	Fundamentals of Hypothesis Testing	99
	10.2	Test for Expectation of Normal Samples	100
	10.3	Neyman-Pearson Lemma	101
	10.4	Test for Contingency Tables	102
	10.5	Test for Difference in Expectations of Normal Samples ..	104
		10.5.1 Two Samples without Correspondence	104
		10.5.2 Two Samples with Correspondence	105
	10.6	Nonparametric Test for Ranks	107
		10.6.1 Two Samples without Correspondence	107
		10.6.2 Two Samples with Correspondence	108
	10.7	Monte Carlo Test	108

PART 3 GENERATIVE APPROACH TO STATISTICAL PATTERN RECOGNITION

CHAPTER 11		Pattern Recognition via Generative Model Estimation	113
	11.1	Formulation of Pattern Recognition	113
	11.2	Statistical Pattern Recognition	115
	11.3	Criteria for Classifier Training	117
		11.3.1 MAP Rule	117
		11.3.2 Minimum Misclassification Rate Rule	118
		11.3.3 Bayes Decision Rule	119
		11.3.4 Discussion	121
	11.4	Generative and Discriminative Approaches	121
CHAPTER 12		Maximum Likelihood Estimation	123
	12.1	Definition	123
	12.2	Gaussian Model	125
	12.3	Computing the Class-Posterior Probability	127
	12.4	Fisher's Linear Discriminant Analysis (FDA)	130
	12.5	Hand-Written Digit Recognition	133
		12.5.1 Preparation	134
		12.5.2 Implementing Linear Discriminant Analysis	135
		12.5.3 Multiclass Classification	136
CHAPTER 13		Properties of Maximum Likelihood Estimation	139

13.1	Consistency	139
13.2	Asymptotic Unbiasedness	140
13.3	Asymptotic Efficiency	141
	13.3.1 One-Dimensional Case	141
	13.3.2 Multidimensional Cases	141
13.4	Asymptotic Normality	143
13.5	Summary	145
CHAPTER 14	Model Selection for Maximum Likelihood Estimation	147
14.1	Model Selection	147
14.2	KL Divergence	148
14.3	AIC	150
14.4	Cross Validation	154
14.5	Discussion	154
CHAPTER 15	Maximum Likelihood Estimation for Gaussian Mixture Model	157
15.1	Gaussian Mixture Model	157
15.2	MLE	158
15.3	Gradient Ascent Algorithm	161
15.4	EM Algorithm	162
CHAPTER 16	Nonparametric Estimation	169
16.1	Histogram Method	169
16.2	Problem Formulation	170
16.3	KDE	174
	16.3.1 Parzen Window Method	174
	16.3.2 Smoothing with Kernels	175
	16.3.3 Bandwidth Selection	176
16.4	NNDE	178
	16.4.1 Nearest Neighbor Distance	178
	16.4.2 Nearest Neighbor Classifier	179
CHAPTER 17	Bayesian Inference	185
17.1	Bayesian Predictive Distribution	185
	17.1.1 Definition	185
	17.1.2 Comparison with MLE	186
	17.1.3 Computational Issues	188
17.2	Conjugate Prior	188
17.3	MAP Estimation	189
17.4	Bayesian Model Selection	193
CHAPTER 18	Analytic Approximation of Marginal Likelihood	197
18.1	Laplace Approximation	197
	18.1.1 Approximation with Gaussian Density	197

	18.1.2 Illustration.....	199
	18.1.3 Application to Marginal Likelihood Approximation	200
	18.1.4 Bayesian Information Criterion (BIC)	200
18.2	Variational Approximation	202
	18.2.1 Variational Bayesian EM (VBEM) Algorithm.....	202
	18.2.2 Relation to Ordinary EM Algorithm.....	203
CHAPTER 19	Numerical Approximation of Predictive Distribution	205
19.1	Monte Carlo Integration.....	205
19.2	Importance Sampling	207
19.3	Sampling Algorithms	208
	19.3.1 Inverse Transform Sampling	208
	19.3.2 Rejection Sampling	212
	19.3.3 Markov Chain Monte Carlo (MCMC) Method	214
CHAPTER 20	Bayesian Mixture Models	221
20.1	Gaussian Mixture Models.....	221
	20.1.1 Bayesian Formulation.....	221
	20.1.2 Variational Inference.....	223
	20.1.3 Gibbs Sampling	228
20.2	Latent Dirichlet Allocation (LDA).....	229
	20.2.1 Topic Models.....	230
	20.2.2 Bayesian Formulation.....	231
	20.2.3 Gibbs Sampling	232
 PART 4 DISCRIMINATIVE APPROACH TO STATISTICAL MACHINE LEARNING		
CHAPTER 21	Learning Models	237
21.1	Linear-in-Parameter Model.....	237
21.2	Kernel Model	239
21.3	Hierarchical Model.....	242
CHAPTER 22	Least Squares Regression	245
22.1	Method of LS.....	245
22.2	Solution for Linear-in-Parameter Model	246
22.3	Properties of LS Solution.....	250
22.4	Learning Algorithm for Large-Scale Data	251
22.5	Learning Algorithm for Hierarchical Model	252
CHAPTER 23	Constrained LS Regression	257
23.1	Subspace-Constrained LS.....	257
23.2	ℓ_2 -Constrained LS	259

23.3	Model Selection	262
CHAPTER 24	Sparse Regression	267
24.1	ℓ_1 -Constrained LS	267
24.2	Solving ℓ_1 -Constrained LS	268
24.3	Feature Selection by Sparse Learning	272
24.4	Various Extensions	272
24.4.1	Generalized ℓ_1 -Constrained LS	273
24.4.2	ℓ_p -Constrained LS	273
24.4.3	$\ell_1 + \ell_2$ -Constrained LS.....	274
24.4.4	$\ell_{1,2}$ -Constrained LS.....	276
24.4.5	Trace Norm Constrained LS	278
CHAPTER 25	Robust Regression	279
25.1	Nonrobustness of ℓ_2 -Loss Minimization	279
25.2	ℓ_1 -Loss Minimization	280
25.3	Huber Loss Minimization.....	282
25.3.1	Definition	282
25.3.2	Stochastic Gradient Algorithm	283
25.3.3	Iteratively Reweighted LS.....	283
25.3.4	ℓ_1 -Constrained Huber Loss Minimization	286
25.4	Tukey Loss Minimization	290
CHAPTER 26	Least Squares Classification	295
26.1	Classification by LS Regression.....	295
26.2	0/1-Loss and Margin.....	297
26.3	Multiclass Classification.....	300
CHAPTER 27	Support Vector Classification	303
27.1	Maximum Margin Classification	303
27.1.1	Hard Margin Support Vector Classification	303
27.1.2	Soft Margin Support Vector Classification	305
27.2	Dual Optimization of Support Vector Classification	306
27.3	Sparseness of Dual Solution.....	308
27.4	Nonlinearization by Kernel Trick.....	311
27.5	Multiclass Extension	312
27.6	Loss Minimization View.....	314
27.6.1	Hinge Loss Minimization.....	315
27.6.2	Squared Hinge Loss Minimization	316
27.6.3	Ramp Loss Minimization.....	318
CHAPTER 28	Probabilistic Classification	321
28.1	Logistic Regression	321
28.1.1	Logistic Model and MLE	321
28.1.2	Loss Minimization View	324

28.2	LS Probabilistic Classification	325
CHAPTER 29	Structured Classification	329
29.1	Sequence Classification	329
29.2	Probabilistic Classification for Sequences	330
29.2.1	Conditional Random Field	330
29.2.2	MLE	333
29.2.3	Recursive Computation	333
29.2.4	Prediction for New Sample	336
29.3	Deterministic Classification for Sequences	337
 PART 5 FURTHER TOPICS		
CHAPTER 30	Ensemble Learning	343
30.1	Decision Stump Classifier	343
30.2	Bagging	344
30.3	Boosting	346
30.3.1	Adaboost	348
30.3.2	Loss Minimization View	348
30.4	General Ensemble Learning	354
CHAPTER 31	Online Learning	355
31.1	Stochastic Gradient Descent	355
31.2	Passive-Aggressive Learning	356
31.2.1	Classification	357
31.2.2	Regression	358
31.3	Adaptive Regularization of Weight Vectors (AROW)	360
31.3.1	Uncertainty of Parameters	360
31.3.2	Classification	361
31.3.3	Regression	362
CHAPTER 32	Confidence of Prediction	365
32.1	Predictive Variance for ℓ_2 -Regularized LS	365
32.2	Bootstrap Confidence Estimation	367
32.3	Applications	368
32.3.1	Time-series Prediction	368
32.3.2	Tuning Parameter Optimization	369
CHAPTER 33	Semisupervised Learning	375
33.1	Manifold Regularization	375
33.1.1	Manifold Structure Brought by Input Samples ...	375
33.1.2	Computing the Solution	377
33.2	Covariate Shift Adaptation	378
33.2.1	Importance Weighted Learning	378

33.2.2	Relative Importance Weighted Learning	382
33.2.3	Importance Weighted Cross Validation	382
33.2.4	Importance Estimation	383
33.3	Class-balance Change Adaptation	385
33.3.1	Class-balance Weighted Learning.....	385
33.3.2	Class-balance Estimation	386
CHAPTER 34	Multitask Learning	391
34.1	Task Similarity Regularization.....	391
34.1.1	Formulation	391
34.1.2	Analytic Solution.....	392
34.1.3	Efficient Computation for Many Tasks	393
34.2	Multidimensional Function Learning	394
34.2.1	Formulation	394
34.2.2	Efficient Analytic Solution.....	397
34.3	Matrix Regularization.....	397
34.3.1	Parameter Matrix Regularization	397
34.3.2	Proximal Gradient for Trace Norm Regularization	400
CHAPTER 35	Linear Dimensionality Reduction	405
35.1	Curse of Dimensionality	405
35.2	Unsupervised Dimensionality Reduction	407
35.2.1	PCA	407
35.2.2	Locality Preserving Projection	410
35.3	Linear Discriminant Analyses for Classification.....	412
35.3.1	Fisher Discriminant Analysis.....	413
35.3.2	Local Fisher Discriminant Analysis.....	414
35.3.3	Semisupervised Local Fisher Discriminant Analysis	417
35.4	Sufficient Dimensionality Reduction for Regression.....	419
35.4.1	Information Theoretic Formulation	419
35.4.2	Direct Derivative Estimation	422
35.5	Matrix Imputation	425
CHAPTER 36	Nonlinear Dimensionality Reduction	429
36.1	Dimensionality Reduction with Kernel Trick.....	429
36.1.1	Kernel PCA	429
36.1.2	Laplacian Eigenmap	433
36.2	Supervised Dimensionality Reduction with Neural Networks	435
36.3	Unsupervised Dimensionality Reduction with Autoencoder	436
36.3.1	Autoencoder.....	436

36.3.2	Training by Gradient Descent	437
36.3.3	Sparse Autoencoder	439
36.4	Unsupervised Dimensionality Reduction with Restricted Boltzmann Machine	440
36.4.1	Model	441
36.4.2	Training by Gradient Ascent.....	442
36.5	Deep Learning	446
CHAPTER 37	Clustering	447
37.1	k -Means Clustering	447
37.2	Kernel k -Means Clustering.....	448
37.3	Spectral Clustering	449
37.4	Tuning Parameter Selection	452
CHAPTER 38	Outlier Detection	457
38.1	Density Estimation and Local Outlier Factor	457
38.2	Support Vector Data Description	458
38.3	Inlier-Based Outlier Detection	464
CHAPTER 39	Change Detection	469
39.1	Distributional Change Detection.....	469
39.1.1	KL Divergence	470
39.1.2	Pearson Divergence	470
39.1.3	L_2 -Distance	471
39.1.4	L_1 -Distance	474
39.1.5	Maximum Mean Discrepancy (MMD)	476
39.1.6	Energy Distance.....	477
39.1.7	Application to Change Detection in Time Series ..	477
39.2	Structural Change Detection	478
39.2.1	Sparse MLE	478
39.2.2	Sparse Density Ratio Estimation	482
References		485
Index		491

List of Figures

Fig. 1.1	Regression.	5
Fig. 1.2	Classification.	5
Fig. 1.3	Clustering.	6
Fig. 1.4	Outlier detection.	6
Fig. 1.5	Dimensionality reduction.	7
Fig. 2.1	Combination of events.	12
Fig. 2.2	Examples of probability mass function. Outcome of throwing a fair six-sided dice (discrete uniform distribution $U\{1, 2, \dots, 6\}$).	14
Fig. 2.3	Example of probability density function and its cumulative distribution function.	15
Fig. 2.4	Expectation is the average of x weighted according to $f(x)$, and median is the 50% point both from the left-hand and right-hand sides. α -quantile for $0 \leq \alpha \leq 1$ is a generalization of the median that gives the $100\alpha\%$ point from the left-hand side. Mode is the maximizer of $f(x)$.	16
Fig. 2.5	Income distribution. The expectation is 62.1 thousand dollars, while the median is 31.3 thousand dollars.	17
Fig. 2.6	Skewness.	20
Fig. 2.7	Kurtosis.	20
Fig. 2.8	Taylor series expansion at the origin.	21
Fig. 2.9	One-dimensional change of variables in integration. For multidimensional cases, see Fig. 4.2.	23
Fig. 3.1	Probability mass functions of binomial distribution $\text{Bi}(n, p)$.	26
Fig. 3.2	Sampling from a bag. The bag contains N balls which consist of $M < N$ balls labeled as “A” and $N - M$ balls labeled as “B.” n balls are sampled from the bag, which consists of x balls labeled as “A” and $n - x$ balls labeled as “B.”	27
Fig. 3.3	Sampling with and without replacement. The sampled ball is returned to the bag before the next ball is sampled in sampling with replacement, while the next ball is sampled without returning the previously sampled ball in sampling without replacement.	28
Fig. 3.4	Probability mass functions of hypergeometric distribution $\text{HG}(N, M, n)$.	29
Fig. 3.5	Probability mass functions of $\text{Bi}(n, M/N)$ and $\text{HG}(N, M, n)$ for $N = 100$, $M = 90$, and $n = 90$.	29
Fig. 3.6	Probability mass functions of Poisson distribution $\text{Po}(\lambda)$.	34
Fig. 3.7	Probability mass functions of negative binomial distribution $\text{NB}(k, p)$.	34
Fig. 3.8	Probability mass functions of geometric distribution $\text{Ge}(p)$.	35
Fig. 4.1	Gaussian integral.	39
Fig. 4.2	Two-dimensional change of variables in integration.	40
Fig. 4.3	Probability density functions of normal density $N(\mu, \sigma^2)$.	40
Fig. 4.4	Standard normal distribution $N(0, 1)$. A random variable following $N(0, 1)$ is included in $[-1, 1]$ with probability 68.27%, in $[-2, 2]$ with probability 95.45%, and in $[-3, 3]$ with probability 99.73%.	41

Fig. 4.5	Gamma function. $\Gamma(\alpha + 1) = \alpha!$ holds for non-negative integer α , and the gamma function smoothly interpolates the factorials.	42
Fig. 4.6	Probability density functions of gamma distribution $\text{Ga}(\alpha, \lambda)$.	43
Fig. 4.7	Probability density functions of beta distribution $\text{Be}(\alpha, \beta)$.	46
Fig. 4.8	Probability density functions of Cauchy distribution $\text{Ca}(a, b)$, Laplace distribution $\text{La}(a, b)$, and normal distribution $N(a, b^2)$.	48
Fig. 4.9	Probability density functions of t -distribution $t(d)$, Cauchy distribution $\text{Ca}(0, 1)$, and normal distribution $N(0, 1)$.	49
Fig. 4.10	Probability density functions of F -distribution $F(d, d')$.	50
Fig. 5.1	Correlation coefficient $\rho_{x,y}$. Linear relation between x and y can be captured.	57
Fig. 5.2	Correlation coefficient for nonlinear relations. Even when there is a nonlinear relation between x and y , the correlation coefficient can be close to zero if the probability distribution is symmetric.	58
Fig. 5.3	Example of x and y which are uncorrelated but dependent.	59
Fig. 6.1	Probability density functions of two-dimensional normal distribution $N(\boldsymbol{\mu}, \boldsymbol{\Sigma})$ with $\boldsymbol{\mu} = (0, 0)^\top$.	64
Fig. 6.2	Eigenvalue decomposition.	65
Fig. 6.3	Contour lines of the normal density. The principal axes of the ellipse are parallel to the eigenvectors of variance-covariance matrix $\boldsymbol{\Sigma}$, and their length is proportional to the square root of the eigenvalues.	66
Fig. 6.4	Probability density functions of Dirichlet distribution $\text{Dir}(\boldsymbol{\alpha})$. The center of gravity of the triangle corresponds to $x^{(1)} = x^{(2)} = x^{(3)} = 1/3$, and each vertex represents the point that the corresponding variable takes one and the others take zeros.	69
Fig. 6.5	Vectorization operator and Kronecker product.	71
Fig. 7.1	Arithmetic mean, geometric mean, and harmonic mean.	76
Fig. 7.2	Law of large numbers.	77
Fig. 7.3	Central limit theorem. The solid lines denote the normal densities.	78
Fig. 8.1	Markov's inequality.	83
Fig. 8.2	Chebyshev's inequality.	84
Fig. 8.3	Convex function and tangent line.	85
Fig. 8.4	$h(u) = (1 + u) \log(1 + u) - u$ and $g(u) = \frac{u^2}{2+2u/3}$.	90
Fig. 9.1	Confidence interval for normal samples.	96
Fig. 9.2	Bootstrap resampling by sampling with replacement.	97
Fig. 10.1	Critical region and critical value.	101
Fig. 11.1	Hand-written digit image and its vectorization.	114
Fig. 11.2	Constructing a classifier is equivalent to determine a discrimination function, decision regions, and decision boundaries.	115

Fig. 11.3	Dimensionality reduction onto a two-dimensional subspace by principal component analysis (see Section 35.2.1).	116
Fig. 11.4	Illustration of hand-written digit samples in the pattern space.	117
Fig. 11.5	MAP rule.	118
Fig. 11.6	Minimum misclassification rate rule.	119
Fig. 12.1	Likelihood equation, setting the derivative of the likelihood to zero, is a necessary condition for the maximum likelihood solution but is not a sufficient condition in general.	124
Fig. 12.2	Log function is monotone increasing.	125
Fig. 12.3	Formulas for vector and matrix derivatives [80].	126
Fig. 12.4	MATLAB code for MLE with one-dimensional Gaussian model.	128
Fig. 12.5	Example of MLE with one-dimensional Gaussian model.	128
Fig. 12.6	Orthogonal projection.	130
Fig. 12.7	Mahalanobis distance having hyperellipsoidal contours.	130
Fig. 12.8	Linear discriminant analysis.	132
Fig. 12.9	When the classwise sample ratio n_1/n_2 is changed.	132
Fig. 12.10	When the classwise sample distributions are rotated.	133
Fig. 12.11	Matrix and third tensor.	134
Fig. 12.12	Misclassified test patterns.	136
Fig. 12.13	MATLAB code for multiclass classification by FDA.	137
Fig. 12.14	Confusion matrix for 10-class classification by FDA. The correct classification rate is $1798/2000 = 89.9\%$.	138
Fig. 13.1	Bias-variance decomposition of expected squared error.	140
Fig. 13.2	MATLAB code for illustrating asymptotic normality of MLE.	145
Fig. 13.3	Example of asymptotic normality of MLE.	145
Fig. 14.1	Model selection. Too simple model may not be expressive enough to represent the true probability distribution, while too complex model may cause unreliable parameter estimation.	148
Fig. 14.2	For nested models, log-likelihood is monotone nondecreasing as the model complexity increases.	150
Fig. 14.3	AIC is the sum of the negative log-likelihood and the number of parameters.	151
Fig. 14.4	Big-o and small-o notations.	152
Fig. 14.5	Cross validation.	154
Fig. 14.6	Algorithm of likelihood cross validation.	155
Fig. 15.1	MLE for Gaussian model.	158
Fig. 15.2	Example of Gaussian mixture model: $q(x) = 0.4N(x; -2, 1.5^2) + 0.2N(x; 2, 2^2) + 0.4N(x; 3, 1^2)$.	159
Fig. 15.3	Schematic of gradient ascent.	161
Fig. 15.4	Algorithm of gradient ascent.	161
Fig. 15.5	Step size ε in gradient ascent. The gradient flow can overshoot the peak if ε is large, while gradient ascent is slow if ε is too small.	162
Fig. 15.6	EM algorithm.	163

Fig. 15.7	Maximizing the lower bound $b(\theta)$ of the log-likelihood $\log L(\theta)$.	164
Fig. 15.8	Jensen's inequality for $m = 2$. \log is a concave function.	164
Fig. 15.9	MATLAB code of EM algorithm for Gaussian mixture model.	166
Fig. 15.10	Example of EM algorithm for Gaussian mixture model. The size of ellipses is proportional to the mixing weights $\{w_\ell\}_{\ell=1}^m$.	167
Fig. 16.1	Examples of Gaussian MLE.	170
Fig. 16.2	Example of histogram method.	170
Fig. 16.3	MATLAB code for inverse transform sampling (see Section 19.3.1) for probability density function shown in Fig. 16.1(b). The bottom function should be saved as "myrand.m."	171
Fig. 16.4	Choice of bin width in histogram method.	171
Fig. 16.5	Notation of nonparametric methods.	172
Fig. 16.6	Probability P approximated by the size of rectangle.	172
Fig. 16.7	Normalized variance of binomial distribution.	173
Fig. 16.8	Parzen window method.	174
Fig. 16.9	Example of Parzen window method.	175
Fig. 16.10	Example of Gaussian KDE. Training samples are the same as those in Fig. 16.9.	176
Fig. 16.11	Choice of kernel bandwidth h in KDE.	177
Fig. 16.12	MATLAB code for Gaussian KDE with bandwidth selected by likelihood cross validation. A random number generator "myrand.m" shown in Fig. 16.3 is used.	177
Fig. 16.13	Example of Gaussian KDE with bandwidth selected by likelihood cross validation.	178
Fig. 16.14	MATLAB code for NNDE with the number of nearest neighbors selected by likelihood cross validation. A random number generator "myrand.m" shown in Fig. 16.3 is used.	179
Fig. 16.15	Example of NNDE with the number of nearest neighbors selected by likelihood cross validation.	180
Fig. 16.16	Example of nearest neighbor classifier.	181
Fig. 16.17	Algorithm of cross validation for misclassification rate.	182
Fig. 16.18	MATLAB code for k -nearest neighbor classifier with k chosen by cross validation. The bottom function should be saved as "knn.m."	183
Fig. 16.19	Confusion matrix for 10-class classification by k -nearest neighbor classifier. $k = 1$ was chosen by cross validation for misclassification rate. The correct classification rate is $1932/2000 = 96.6\%$.	183
Fig. 17.1	Bayes vs. MLE. The maximum likelihood solution \hat{p}_{ML} is always confined in the parametric model $q(\mathbf{x}; \theta)$, while the Bayesian predictive distribution $\hat{p}_{\text{Bayes}}(\mathbf{x})$ generally pops out from the model.	187
Fig. 17.2	MAP estimation.	190
Fig. 17.3	Example of MLE for Gaussian model. When the number of training samples, n , is small, MLE tends to overfit the samples.	190
Fig. 17.4	MATLAB code for penalized MLE with one-dimensional Gaussian model.	192
Fig. 17.5	Example of MAP estimation with one-dimensional Gaussian model.	192

Fig. 17.6	MATLAB code for empirical Bayes.	195
Fig. 17.7	Example of empirical Bayes.	195
Fig. 18.1	Laplace approximation.	199
Fig. 19.1	Numerical computation of π by Monte Carlo integration.	206
Fig. 19.2	MATLAB code for numerically computing π by Monte Carlo integration.	207
Fig. 19.3	MATLAB code for importance sampling.	208
Fig. 19.4	Examples of probability density function $p(\theta)$ and its cumulative distribution function $P(\theta)$. Cumulative distribution function is monotone nondecreasing and satisfies $\lim_{\theta \rightarrow -\infty} P(\theta) = 0$ and $\lim_{\theta \rightarrow \infty} P(\theta) = 1$.	209
Fig. 19.5	Inverse transform sampling.	209
Fig. 19.6	$\theta \leq \theta'$ implies $P(\theta) \leq P(\theta')$.	210
Fig. 19.7	Laplace distribution.	211
Fig. 19.8	MATLAB code for inverse transform sampling.	211
Fig. 19.9	Example of inverse transform sampling for Laplace distribution.	212
Fig. 19.10	Algorithm of rejection sampling.	212
Fig. 19.11	Illustration of rejection sampling when the proposal distribution is uniform.	213
Fig. 19.12	MATLAB code for rejection sampling.	214
Fig. 19.13	Example of rejection sampling.	214
Fig. 19.14	Computational efficiency of rejection sampling. (a) When the upper bound of the probability density, κ , is small, proposal points are almost always accepted and thus rejection sampling is computationally efficient. (b) When κ is large, most of the proposal points will be rejected and thus rejection sampling is computationally expensive.	215
Fig. 19.15	Random walk.	216
Fig. 19.16	MATLAB code for Metropolis-Hastings sampling. The bottom function should be saved as “pdf.m.”	217
Fig. 19.17	Example of Metropolis-Hastings sampling.	218
Fig. 19.18	MATLAB code for Gibbs sampling.	219
Fig. 19.19	Example of Gibbs sampling.	220
Fig. 20.1	Variational Bayesian formulation of Gaussian mixture model.	223
Fig. 20.2	VBEM algorithm for Gaussian mixture model. $(\alpha_0, \beta_0, \mathbf{W}_0, \nu_0)$ are hyperparameters.	225
Fig. 20.3	MATLAB code of VBEM algorithm for Gaussian mixture model.	226
Fig. 20.4	Example of VBEM algorithm for Gaussian mixture model. The size of ellipses is proportional to the mixing weights $\{w_\ell\}_{\ell=1}^m$. A mixture model of five Gaussian components is used here, but three components have mixing coefficient close to zero and thus they are almost eliminated.	227
Fig. 20.5	MATLAB code of collapsed Gibbs sampling for Gaussian mixture model.	229
Fig. 20.6	Example of collapsed Gibbs sampling for Gaussian mixture model. A mixture model of five Gaussian components is used here, but only two components remain and no samples belong to the remaining three components.	230
Fig. 21.1	Linear-in-input model cannot approximate nonlinear functions.	238

Fig. 21.2	Multidimensional basis functions. The multiplicative model is expressive, but the number of parameters grows exponentially in input dimensionality. On the other hand, in the additive model, the number of parameters grows only linearly in input dimensionality, but its expression power is limited.	239
Fig. 21.3	Gaussian kernel with bandwidth h and center c .	240
Fig. 21.4	One-dimensional Gaussian kernel model. Gaussian functions are located at training input samples $\{\mathbf{x}_i\}_{i=1}^n$ and their height $\{\theta_i\}_{i=1}^n$ is learned.	241
Fig. 21.5	Two-dimensional Gaussian kernel model. The curse of dimensionality is mitigated by only approximating the learning target function in the vicinity of training input samples.	241
Fig. 21.6	Sigmoidal function.	242
Fig. 21.7	Hierarchical model as a three-layered network.	243
Fig. 22.1	Generalized inverse.	247
Fig. 22.2	Singular value decomposition.	248
Fig. 22.3	MATLAB code for LS regression.	249
Fig. 22.4	Example of LS regression with sinusoidal basis functions $\phi(x) = (1, \sin \frac{x}{2}, \cos \frac{x}{2}, \sin \frac{2x}{2}, \cos \frac{2x}{2}, \dots, \sin \frac{15x}{2}, \cos \frac{15x}{2})^\top$.	249
Fig. 22.5	Geometric interpretation of LS method for linear-in-parameter model. Training output vector \mathbf{y} is projected onto the range of Φ , denoted by $\mathcal{R}(\Phi)$, for denoising purposes.	251
Fig. 22.6	Algorithm of stochastic gradient descent for LS regression with a linear-in-parameter model.	252
Fig. 22.7	MATLAB code of stochastic gradient descent for LS regression with the Gaussian kernel model.	253
Fig. 22.8	Example of stochastic gradient descent for LS regression with the Gaussian kernel model. For $n = 50$ training samples, the Gaussian bandwidth is set at $h = 0.3$.	254
Fig. 22.9	Gradient descent for nonlinear models. The training squared error J_{LS} is nonconvex and there exist multiple local optimal solutions in general.	254
Fig. 22.10	MATLAB code for error back-propagation algorithm.	255
Fig. 22.11	Example of regression by error back-propagation algorithm.	255
Fig. 23.1	Examples of LS regression for linear-in-parameter model when the noise level in training output is high. Sinusoidal basis functions $\{1, \sin \frac{x}{2}, \cos \frac{x}{2}, \sin \frac{2x}{2}, \cos \frac{2x}{2}, \dots, \sin \frac{15x}{2}, \cos \frac{15x}{2}\}$ are used in ordinary LS, while its subset $\{1, \sin \frac{x}{2}, \cos \frac{x}{2}, \sin \frac{2x}{2}, \cos \frac{2x}{2}, \dots, \sin \frac{5x}{2}, \cos \frac{5x}{2}\}$ is used in the subspace-constrained LS method.	258
Fig. 23.2	Constraint in parameter space.	258
Fig. 23.3	MATLAB code for subspace-constrained LS regression.	259
Fig. 23.4	Parameter space in ℓ_2 -constrained LS.	259
Fig. 23.5	Lagrange dual problem.	260
Fig. 23.6	MATLAB code of ℓ_2 -constrained LS regression for Gaussian kernel model.	262
Fig. 23.7	Example of ℓ_2 -constrained LS regression for Gaussian kernel model. The Gaussian bandwidth is set at $h = 0.3$, and the regularization parameter is set at $\lambda = 0.1$.	262

Fig. 23.8	Parameter space in generalized ℓ_2 -constrained LS.	263
Fig. 23.9	Examples of ℓ_2 -constrained LS with the Gaussian kernel model for different Gaussian bandwidth h and different regularization parameter λ .	263
Fig. 23.10	MATLAB code of cross validation for ℓ_2 -constrained LS regression.	264
Fig. 23.11	Example of cross validation for ℓ_2 -constrained LS regression. The cross validation error for all Gaussian bandwidth h and regularization parameter λ is plotted, which is minimized at $(h, \lambda) = (0.3, 0.1)$. See Fig. 23.9 for learned functions.	265
Fig. 23.12	Matrix inversion lemma.	265
Fig. 24.1	Parameter space in ℓ_1 -constrained LS.	268
Fig. 24.2	The solution of ℓ_1 -constrained LS tends to be on one of the coordinate axes, which is a sparse solution.	269
Fig. 24.3	Alternating direction method of multipliers.	270
Fig. 24.4	MATLAB code of ℓ_1 -constrained LS by ADMM for Gaussian kernel model.	271
Fig. 24.5	Example of ℓ_1 -constrained LS for Gaussian kernel model. 38 out of 50 parameters are zero.	271
Fig. 24.6	Unit ℓ_p -balls.	274
Fig. 24.7	Properties of ℓ_p -constraint.	275
Fig. 24.8	Unit $(\ell_1 + \ell_2)$ -norm ball for balance parameter $\tau = 1/2$, which is similar to the unit $\ell_{1.4}$ -ball. However, while the $\ell_{1.4}$ -ball has no corner, the $(\ell_1 + \ell_2)$ -ball has corners.	276
Fig. 24.9	Constraints in three-dimensional parameter space.	277
Fig. 24.10	Trace norm of a matrix.	278
Fig. 25.1	LS solution for straight-line model $f_\theta(x) = \theta_1 + \theta_2 x$, which is strongly affected by an outlier.	280
Fig. 25.2	ℓ_2 -loss and ℓ_1 -loss. The ℓ_2 -loss magnifies large residuals.	281
Fig. 25.3	Solution of least absolute deviations for straight-line model $f_\theta(x) = \theta_1 + \theta_2 x$ for the same training samples as Fig. 25.1. Least absolute deviations give a much more robust solution than LS.	281
Fig. 25.4	Huber loss, with threshold $\eta = 1$.	282
Fig. 25.5	Quadratic upper bound $\frac{\eta r^2}{2c} + \frac{\eta c}{2} - \frac{\eta^2}{2}$ of Huber loss $\rho_{\text{Huber}}(r)$ for $c > 0$, which touches each other at $r = \pm c$.	284
Fig. 25.6	Weight functions for Huber loss minimization and Tukey loss minimization.	285
Fig. 25.7	Updated solution $\hat{\theta}$ is no worse than current solution $\tilde{\theta}$.	285
Fig. 25.8	Iteratively reweighted LS for Huber loss minimization.	286
Fig. 25.9	MATLAB code of iteratively reweighted LS for Huber loss minimization. Straight-line model $f_\theta(x) = \theta_1 + \theta_2 x$ is used, with threshold $\eta = 1$.	287
Fig. 25.10	Examples of iteratively reweighted LS for Huber loss minimization. Straight-line model $f_\theta(x) = \theta_1 + \theta_2 x$ is used, with threshold $\eta = 1$.	288
Fig. 25.11	Quadratic upper bound $\frac{\theta^2}{2c} + \frac{c}{2}$ of absolute value $ \theta $ for $c > 0$, which touches each other at $\theta = \pm c$.	289
Fig. 25.12	Iteratively reweighted LS for ℓ_1 -regularized Huber loss minimization.	289
Fig. 25.13	MATLAB code of iteratively reweighted LS for ℓ_1 -regularized Huber loss minimization with Gaussian kernel model.	290

Fig. 25.14	Example of ℓ_1 -regularized Huber loss minimization with Gaussian kernel model.	291
Fig. 25.15	Tukey loss, with threshold $\eta = 3$.	291
Fig. 25.16	Example of Tukey loss minimization. Tukey loss minimization gives more robust solutions than Huber loss minimization, but only a local optimal solution can be obtained.	292
Fig. 26.1	Binary classification as function approximation.	296
Fig. 26.2	MATLAB code of classification by ℓ_2 -regularized LS for Gaussian kernel model.	296
Fig. 26.3	Example of classification by ℓ_2 -regularized LS for Gaussian kernel model.	297
Fig. 26.4	0/1-loss and ℓ_2 -loss as functions of margin $m = f_{\theta}(\mathbf{x})y$.	298
Fig. 26.5	Example of ℓ_2 -loss minimization for linear-in-input model. Since the ℓ_2 -loss has a positive slope when $m > 1$, the obtained solution contains some classification error even though all samples can be correctly classified in principle.	299
Fig. 26.6	Popular surrogate loss functions.	300
Fig. 26.7	One-versus-rest reduction of multiclass classification problem.	301
Fig. 26.8	One-versus-one reduction of multiclass classification problem.	301
Fig. 27.1	Linear-in-input binary classifier $f_{\mathbf{w},\gamma}(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + \gamma$. \mathbf{w} and γ are the normal vector and the intercept of the decision boundary, respectively.	304
Fig. 27.2	Decision boundaries that separate all training samples correctly.	304
Fig. 27.3	Decision boundary of hard margin support vector machine. It goes through the center of positive and negative training samples, $\mathbf{w}^T \mathbf{x}_+ + \gamma = +1$ for some positive sample \mathbf{x}_+ and $\mathbf{w}^T \mathbf{x}_- + \gamma = -1$ for some negative sample \mathbf{x}_- .	305
Fig. 27.4	Soft margin support vector machine allows small margin errors.	306
Fig. 27.5	Quadratic programming.	307
Fig. 27.6	Example of linear support vector classification. Among 200 dual parameters $\{\alpha_i\}_{i=1}^n$, 197 parameters take zero and only 3 parameters specified by the square in the plot take nonzero values.	309
Fig. 27.7	KKT optimality conditions.	310
Fig. 27.8	When $\alpha_i = 0$, \mathbf{x}_i is inside the margin and correctly classified. When $0 < \alpha_i < C$, \mathbf{x}_i is on the margin border (the dotted lines) and correctly classified. When $\alpha_i = C$, \mathbf{x}_i is outside the margin, and if $\xi_i > 1$, $m_i < 0$ and thus \mathbf{x}_i is misclassified.	310
Fig. 27.9	Nonlinearization of support vector machine by kernel trick.	311
Fig. 27.10	MATLAB code of support vector classification for Gaussian kernel. <code>quadprog.m</code> included in Optimization Toolbox is required. Free alternatives to <code>quadprog.m</code> are available, e.g. from http://www.mathworks.com/matlabcentral/fileexchange/ .	313
Fig. 27.11	Example of support vector classification for Gaussian kernel.	314
Fig. 27.12	Hinge loss and squared hinge loss.	315
Fig. 27.13	Hinge loss as maximizer of $1 - m$ and 0.	316
Fig. 27.14	Iterative retargeted LS for ℓ_2 -regularized squared hinge loss minimization.	317

Fig. 27.15	MATLAB code of iterative retargeted LS for ℓ_2 -regularized squared hinge loss minimization.	318
Fig. 27.16	Example of ℓ_2 -regularized squared hinge loss minimization.	319
Fig. 27.17	Examples of support vector classification with outliers.	319
Fig. 27.18	Ramp loss and squared ramp loss.	320
Fig. 28.1	Stochastic gradient algorithm for logistic regression.	322
Fig. 28.2	MATLAB code of stochastic gradient ascent for logistic regression.	323
Fig. 28.3	Example of stochastic gradient ascent for logistic regression.	324
Fig. 28.4	Logistic loss.	325
Fig. 28.5	MATLAB code for LS probabilistic classification.	327
Fig. 28.6	Example of LS probabilistic classification for the same data set as Fig. 28.3.	328
Fig. 29.1	Classification of sequence of hand-written digits.	330
Fig. 29.2	Sequence classification.	331
Fig. 29.3	Stochastic gradient algorithm for conditional random field.	333
Fig. 29.4	Dynamic programming, which solves a complex optimization problem by breaking it down into simpler subproblems recursively. When the number of steps to the goal is counted, dynamic programming trace back the steps from the goal. In this case, many subproblems of counting the number of steps from other positions are actually shared and thus dynamic programming can efficiently reuse the solutions to reduce the computation costs.	334
Fig. 30.1	Ensemble learning. Bagging trains weak learners in parallel, while boosting sequentially trains weak learners.	344
Fig. 30.2	Decision stump and decision tree classifiers. A decision stump is a depth-one version of a decision tree.	344
Fig. 30.3	MATLAB code for decision stump classification.	345
Fig. 30.4	Example of decision stump classification.	345
Fig. 30.5	Algorithm of bagging.	346
Fig. 30.6	MATLAB code of bagging for decision stumps.	346
Fig. 30.7	Example of bagging for decision stumps.	347
Fig. 30.8	Algorithm of adaboost.	349
Fig. 30.9	Confidence of classifier in adaboost. The confidence of classifier φ , denoted by θ , is determined based on the weighted misclassification rate R .	350
Fig. 30.10	MATLAB code of adaboost for decision stumps.	351
Fig. 30.11	Example of adaboost for decision stumps.	352
Fig. 30.12	Exponential loss.	353
Fig. 30.13	Loss functions for boosting.	353
Fig. 31.1	Choice of step size. Too large step size overshoots the optimal solution, while too small step size yields slow convergence.	356
Fig. 31.2	Algorithm of passive-aggressive classification.	358
Fig. 31.3	MATLAB code for passive-aggressive classification.	359
Fig. 31.4	Example of passive-aggressive classification.	359
Fig. 31.5	MATLAB code for passive-aggressive regression with the ℓ_2 -loss.	360

Fig. 31.6	Algorithm of AROW classification.	362
Fig. 31.7	MATLAB code for AROW classification.	363
Fig. 31.8	Examples of passive-aggressive and AROW classifications.	363
Fig. 31.9	MATLAB code for AROW regression.	364
Fig. 32.1	MATLAB code for analytic computation of predictive variance.	367
Fig. 32.2	Examples of analytic computation of predictive variance. The shaded area indicates the confidence interval.	368
Fig. 32.3	MATLAB code for bootstrap-based confidence estimation.	369
Fig. 32.4	Examples of bootstrap-based confidence estimation. The shaded area indicates the confidence interval.	370
Fig. 32.5	Problem of time-series prediction.	370
Fig. 32.6	Time-series prediction from previous samples.	370
Fig. 32.7	MATLAB code for time-series prediction by ℓ_2 -regularized LS.	371
Fig. 32.8	Examples of time-series prediction by ℓ_2 -regularized LS. The shaded areas indicate the confidence intervals.	372
Fig. 32.9	Bayesian optimization. The shaded areas indicate the confidence intervals.	373
Fig. 33.1	Semisupervised classification. Samples in the same cluster are assumed to belong to the same class.	376
Fig. 33.2	MATLAB code for Laplacian-regularized LS.	379
Fig. 33.3	Examples of Laplacian-regularized LS compared with ordinary LS. Dots denote unlabeled training samples.	380
Fig. 33.4	Covariate shift in regression. Input distributions change, but the input-output relation is unchanged.	380
Fig. 33.5	MATLAB code for importance weighted LS.	381
Fig. 33.6	Example of LS learning under covariate shift. The dashed lines denote learned functions.	381
Fig. 33.7	Relative importance when $p'(x)$ is the Gaussian density with expectation 0 and variance 1 and $p(x)$ is the Gaussian density with expectation 0.5 and variance 1.	383
Fig. 33.8	Algorithm of importance weighted cross validation.	384
Fig. 33.9	MATLAB code for LS relative density ratio estimation for Gaussian kernel model.	386
Fig. 33.10	Example of LS relative density ratio estimation. \times 's in the right plot show estimated relative importance values at $\{\mathbf{x}_i\}_{i=1}^n$.	387
Fig. 33.11	Class-balance change, which affects the decision boundary.	387
Fig. 33.12	Class-prior estimation by distribution matching.	388
Fig. 33.13	MATLAB code for class-balance weighted LS.	389
Fig. 33.14	Example of class-balance weighted LS. The test class priors are estimated as $\tilde{p}'(y = 1) = 0.18$ and $\tilde{p}'(y = 2) = 0.82$, which are used as weights in class-balance weighted LS.	390
Fig. 34.1	MATLAB code for multitask LS.	394
Fig. 34.2	Examples of multitask LS. The dashed lines denote true decision boundaries and the contour lines denote learned results.	395

Fig. 34.3	Alternate learning of task similarity $\gamma_{t,t'}$ and solution θ .	396
Fig. 34.4	Multidimensional function learning.	396
Fig. 34.5	Continuous Sylvester equation.	398
Fig. 34.6	MATLAB code for multidimensional regression.	399
Fig. 34.7	Examples of multidimensional regression.	399
Fig. 34.8	Proximal gradient method.	401
Fig. 34.9	MATLAB code for multitask learning with trace norm regularization.	402
Fig. 34.10	Examples of multitask LS with trace norm regularization. The data set is the same as Fig. 34.2. The dashed lines denote true decision boundaries and the contour lines denote learned results.	403
Fig. 35.1	Curse of dimensionality.	406
Fig. 35.2	Linear dimensionality reduction. Transformation by a fat matrix T corresponds to projection onto a subspace.	407
Fig. 35.3	Data centering.	407
Fig. 35.4	PCA, which tries to keep the position of original samples when the dimensionality is reduced.	408
Fig. 35.5	MATLAB code for PCA.	409
Fig. 35.6	Example of PCA. The solid line denotes the one-dimensional embedding subspace found by PCA.	409
Fig. 35.7	Locality preserving projection, which tries to keep the cluster structure of original samples when the dimensionality is reduced.	410
Fig. 35.8	Popular choices of similarity measure.	411
Fig. 35.9	MATLAB code for locality preserving projection.	412
Fig. 35.10	Example of locality preserving projection. The solid line denotes the one-dimensional embedding subspace found by locality preserving projection.	413
Fig. 35.11	MATLAB code for Fisher discriminant analysis.	414
Fig. 35.12	Examples of Fisher discriminant analysis. The solid lines denote the found subspaces to which training samples are projected.	415
Fig. 35.13	MATLAB code for local Fisher discriminant analysis.	417
Fig. 35.14	Examples of local Fisher discriminant analysis for the same data sets as Fig. 35.12. The solid lines denote the found subspaces to which training samples are projected.	418
Fig. 35.15	MATLAB code for semisupervised local Fisher discriminant analysis.	420
Fig. 35.16	Examples of semisupervised local Fisher discriminant analysis. Lines denote the found subspaces to which training samples are projected. "LFDA" stands for local Fisher discriminant analysis, "SELF" stands for semisupervised LFDA, and "PCA" stands for principal component analysis.	421
Fig. 35.17	MATLAB code for supervised dimensionality reduction based on QMI.	423
Fig. 35.18	Example of supervised dimensionality reduction based on QMI. The solid line denotes the found subspace to which training samples are projected.	424
Fig. 35.19	MATLAB code for unsupervised dimensionality reduction based on QMI.	425
Fig. 35.20	Example of unsupervised dimensionality reduction based on QMI. The solid line denotes the found subspace to which training samples are projected.	426
Fig. 35.21	MATLAB code for unsupervised matrix imputation.	426

Fig. 35.22	Example of unsupervised matrix imputation. The gray level indicates the value of each entry in $[-5, 5]$.	427
Fig. 36.1	Nonlinear PCA in a feature space. “ \times ” denotes a sample, the solid line denotes the one-dimensional embedding subspace found by PCA, and “ \circ ” denotes a projected sample.	430
Fig. 36.2	Eigenvalue problems for PCA. Appropriately choosing the expression of eigenvalue problem depending on whether matrix Ψ is fat or skinny allows us to reduce the computational costs.	431
Fig. 36.3	MATLAB code for kernel PCA with Gaussian kernels.	433
Fig. 36.4	Examples of kernel PCA with Gaussian kernels. Original two-dimensional samples are transformed to infinite-dimensional feature space by Gaussian kernels with width h , and then PCA is applied to reduce the dimensionality to two.	434
Fig. 36.5	MATLAB code of Laplacian eigenmap for 10-nearest neighbor similarity.	435
Fig. 36.6	Example of Laplacian eigenmap for 10-nearest neighbor similarity.	435
Fig. 36.7	Dimensionality reduction by neural network. The number of hidden nodes is smaller than the number of input (and output) nodes.	436
Fig. 36.8	Autoencoder. Input and output are the same and the number of hidden nodes is smaller than the number of input nodes.	437
Fig. 36.9	Chain rule for autoencoder.	438
Fig. 36.10	MATLAB code for denoising autoencoder. See Section 12.5 for details of hand-written digit data set “ <code>digit.mat</code> .”	439
Fig. 36.11	Example of denoising autoencoder.	440
Fig. 36.12	Restricted Boltzmann machine.	441
Fig. 36.13	Contrastive divergence algorithm for restricted Boltzmann machine. Note that $q(\mathbf{z} \mathbf{x} = \hat{\mathbf{x}}_i)$ and $q(\mathbf{x} \mathbf{z} = \hat{\mathbf{z}}_i)$ can be factorized as Eq. (36.6), which allows efficient computation.	443
Fig. 36.14	MATLAB code for denoising restricted Boltzmann machine. See Section 12.5 for details of hand-written digit data set “ <code>digit.mat</code> .”	443
Fig. 36.15	Example of denoising restricted Boltzmann machine.	444
Fig. 36.16	Construction of deep neural network by stacking.	445
Fig. 37.1	k -means clustering algorithm.	448
Fig. 37.2	MATLAB code for k -means clustering.	449
Fig. 37.3	Example of k -means clustering. A filled square denotes a cluster center.	450
Fig. 37.4	Algorithm of spectral clustering.	451
Fig. 37.5	MATLAB code for spectral clustering.	451
Fig. 37.6	Example of spectral clustering.	452
Fig. 37.7	Clustering can be regarded as compressing d -dimensional vector \mathbf{x} into c -valued scalar y .	453
Fig. 37.8	MATLAB code for LS QMI estimation.	455
Fig. 37.9	Example of LS QMI estimation.	456
Fig. 38.1	MATLAB code for local outlier factor.	459

Fig. 38.2	Example of outlier detection by local outlier factor. The diameter of circles around samples is proportional to the value of local outlier factor.	460
Fig. 38.3	Support vector data description. A hypersphere that contains <i>most</i> of the training samples is found. Samples outside the hypersphere are regarded as outliers.	460
Fig. 38.4	MATLAB code of support vector data description for Gaussian kernel. <code>quadprog.m</code> included in Optimization Toolbox is required. Free alternatives to <code>quadprog.m</code> are available, e.g. from http://www.mathworks.com/matlabcentral/fileexchange/ .	463
Fig. 38.5	Examples of support vector data description for Gaussian kernel. Circled samples are regarded as outliers.	464
Fig. 38.6	Inlier-based outlier detection by density ratio estimation. For inlier density $p'(\mathbf{x})$ and test sample density $p(\mathbf{x})$, the density ratio $w(\mathbf{x}) = p'(\mathbf{x})/p(\mathbf{x})$ is close to one when \mathbf{x} is an inlier and it is close to zero when \mathbf{x} is an outlier.	465
Fig. 38.7	MATLAB code of KL density ratio estimation for Gaussian kernel model with Gaussian bandwidth chosen by cross validation. The bottom function should be saved as “ <code>KLIEP.m</code> .”	466
Fig. 38.8	Example of KL density ratio estimation for Gaussian kernel model.	467
Fig. 39.1	MATLAB code for LS density difference estimation.	473
Fig. 39.2	Example of LS density difference estimation. \times 's in the right plot show estimated density difference values at $\{\mathbf{x}_i\}_{i=1}^n$ and $\{\mathbf{x}'_{i'}\}_{i'=1}^{n'}$.	474
Fig. 39.3	Lower bound of $\text{sign}(t)$ by $-2 \max(0, 1 - t) + 1$.	475
Fig. 39.4	Change detection in time series.	478
Fig. 39.5	MATLAB code for change detection in time series based on the energy distance.	479
Fig. 39.6	Examples of change detection in time series based on the energy distance.	480
Fig. 39.7	Structural change in Gaussian Markov networks.	480
Fig. 39.8	MATLAB code of a gradient-projection algorithm of ℓ_1 -constraint MLE for Gaussian Markov networks. The bottom function should be saved as “ <code>L1BallProjection.m</code> .”	481
Fig. 39.9	MATLAB code of a gradient-projection algorithm of ℓ_1 -constraint KL density ratio estimation for Gaussian Markov networks. “ <code>L1BallProjection.m</code> ” is given in Fig. 39.8.	484

List of Tables

Table 5.1	Example of Contingency Table	53
Table 7.1	Convolution	75
Table 10.1	Type-I Error α (False Positive) and Type-II Error β (False Negative)	102
Table 10.2	Contingency Table for $x \in \{1, \dots, \ell\}$ and $y \in \{1, \dots, m\}$. $c_{x,y}$ Denotes the Frequency of (x,y) , $d_x = \sum_{y=1}^m c_{x,y}$, $e_y = \sum_{x=1}^{\ell} c_{x,y}$, and $n = \sum_{x=1}^{\ell} \sum_{y=1}^m c_{x,y}$	103
Table 10.3	Wilcoxon Rank-Sum Test. In this Example, $r_1 = 3$, $r_2 = 5.5$, $r_3 = 1$, and the Rank-Sum is $r = 9.5$	107
Table 11.1	Example Of Asymmetric Loss	120

