

Emergency Dispatch Priority and Coordination System

Final Project Report

ENSE707 Software Quality Assurance

Leo Cao (23211788), Fateh Bhular (23217987), Shawn Lee (23204035)

Auckland University of Technology

Table of Content

1. Project Completion and Final Implementation.....	4
1.1 Project Overview.....	4
1.2 Final Scope and Changes Since Assessment 1 (What did we change?).....	4
1.3 Final System Architecture and Design.....	6
1.4 Final Implemented Functionality.....	8
1.5 Final Prototype Evidence (Assignment 2 system).....	10
1.6 Remaining Implementation Limitations.....	13
2. Requirements Verification and Traceability.....	14
2.1 Requirements Review and Changes Since Assessment 1.....	14
2.2 Final Requirements Traceability Matrix.....	16
2.3 Partially Implemented, Unverified and Out-of-Scope Requirements.....	19
3. Test Execution and Final Test Results.....	20
3.1 Final testing Approach.....	20
3.2 Final Test Cases.....	20
3.3 Test Execution Results.....	22
3.4 Failed Tests and Corrective Actions.....	22
3.5 Regression Testing.....	24
3.6 Remaining Testing Risks.....	24
4. Test Automation and Quality Engineering.....	25
4.1 Automation Selection.....	25
4.2 Automated Test Implementation.....	25
4.3 Automated Test Results.....	25
4.4 Automation Maintainability.....	25
4.5 Manual and Exploratory Testing.....	25
5. Continuous Integration and DevOps QA.....	26
5.1 Development and Integration Workflow.....	26
5.2 Continuous Integration Pipeline.....	26
5.3 Quality Gates.....	26
5.4 Smoke and Sanity Testing.....	26
5.5 CI Evidence and Limitations.....	26
6. Defect Management and Root Cause Analysis lao.....	27
6.1 Defect Management Approach.....	27
6.2 Severity, Priority and Status Definitions.....	27
6.3 Defect Lifecycle.....	27
6.4 Final Defect Register.....	27
6.5 Root Cause Analysis: Defect One.....	27
6.6 Root Cause Analysis: Defect Two.....	27
6.7 Root Cause Analysis: Defect Three.....	27
6.8 Corrective and Preventive Actions.....	27
7. Quality Testing.....	28
7.1 Risk-Based Selection of Quality Areas.....	28
7.2 Quality Area One: [e.g. Security].....	28
7.3 Quality Area Two: [e.g. Performance].....	28

7.4 Results and Limitations.....	28
7.5 Recommended Improvements.....	28
8. Quality Metrics and Final Release Decision.....	29
8.1 Final Quality Metrics.....	29
8.2 Requirements and Acceptance-Criteria Evaluation.....	29
8.3 Outstanding Defects and Residual Risks.....	29
8.4 Final Release Decision.....	29
9. AI-Assisted Development and Critical Reflection.....	30
9.1 AI-Assisted Activities.....	30
9.2 Representative GitHub Copilot Evidence.....	31
9.3 Human Review and Validation.....	31
9.4 AI-Related Quality Risks.....	31
9.5 Critical Reflection.....	31
10. Quality Improvement and Future Recommendations.....	32
10.1 Key Quality Lessons.....	32
10.2 Improvements to the Development and QA Process.....	32
10.3 Future Testing and Automation Improvements.....	32
10.4 Future Continuous Quality Engineering.....	32
11. Team Contribution and Professional Reflection.....	33

1. Project Completion and Final Implementation

1.1 Project Overview

There is a high volume of calls received by emergency dispatchers every day in New Zealand alone. Sometimes there are too many cases, so even office workers have to go out into the field to keep up with all of them (*1News Reporters, 2026*). This causes stress on the current emergency system, which underlines the need for a new response system that can effectively manage all emergency cases and coordinate response units for these cases. The Emergency Dispatch Priority and Coordination System was developed to improve the management of emergency calls, case handling, prioritisation, department routing, and response-unit coordination. The prototype from phase I allows the dispatcher to create a case and put it through the system, which assigns a priority. The case is then routed to the assigned departments, where they can view the case details on their dashboards with very quick updates. After a unit has finished a case, they can update it on their dashboard, and once all units have signed off, the case closes.




1.2 Final Scope and Changes Since Assessment 1 (*What did we change?*)

The original scope from assignment 1 was to develop an emergency dispatch priority and coordination system prototype that managed emergency cases, case prioritisation, case routing to departments, and response-unit coordination. The scope for the final assignment includes some changes to the features due to new findings, corrections required from the previous scope, as well as new ideas.

Scope Area	Assessment 1 Scope	Assignment 2 Scope	Justification
Case recording	Dispatchers can record caller details, incident type, description, location, severity, and required departments in a form. Submitting this form creates a new case.	No scope change. The required inputs remain validated, and the case number and timestamp are generated automatically during case creation.	Case recording provides the information that is used in prioritisation, routing, unit assignment, and testing. The automatic timestamp and case number improve consistency.
Prioritisation	The system automatically determines the case priority using the department-related rules. The dispatcher's selected severity is used when there are no keyword matches.	Scope changed. An authorised dispatcher can override the calculated priority by giving a mandatory reason, which is stored in the audit log.	Priority override allows a miscalculated priority to be corrected. The original priority, updated priority, user, reason, and the timestamp should all be recorded for accountability,
Routing	Cases are routed to every department selected by the dispatcher. Multi-department cases appear in all of the selected departments' interfaces.	No scope change. Selected departments can view the case on their dashboards. Cases are excluded from unrelated departments' dashboards.	This workflow satisfies the multi-department routing scope from assignment 1. There is no external emergency-service integration in this prototype.
Unit assignment and coordination	The first available unit from each required department will be assigned to the case. If no compatible units are available, the case will be in a queue.	Scope changed. Unit assignment assigns the nearest available unit using its stored location data. If no unit is available, the case remains in the queue.	Nearest-unit selection can reduce travel distance for the selected response unit and the expected time of arrival. This is supported by location data that is measurable, defined rules, and repeatable tests.
Case lifecycle, sign-off, and history	Cases use the following states: Open, In Progress, Closed. Each unit signs off individually, and the case only closes when all units have signed off. Dispatchers can search previous cases by caller name, case number, or date.	No scope change. The case lifecycle, unit sign-off, and case history are kept the same. Case closes after all required response units have signed off. History remains searchable by the inputs mentioned.	The lifecycle prevents cases from being closed too early on multi-department cases, and keeps all states consistent throughout the case lifecycle. The history supports traceability and access to previous cases.
Role-based GUI	There are separate interfaces and restrictions provided for dispatchers, departments, response units, and the prototype admin role. Department and response unit users are restricted to their assigned scope.	No scope change. The role-based interfaces and server-side access controls are kept. The admin is prototype only and is used for testing and demonstration.	Role-specific interfaces reduce the complexity and prevent users from accessing pages they shouldn't be allowed to access. Admin is kept for the prototype for easier testing and demonstration.
Architecture & Technology	This system uses C#, .NET, Razor Pages, HTML/CSS, MSTest, and GitHub with a modular design.	No scope change. The structure, repository abstractions, priority strategy, dependency injection, and central dispatch service are kept.	Keeping the existing technology stack avoids migration and regression risks. Explaining the architecture shows how the prototype supports maintainability, extensibility, and testing.
Security and Persistence	The system uses in-memory repositories and fake accounts in text files. Operational data was lost after restarting the program. Role-based authorisation was implemented, but not permanent storage or encryption.	Scope changed. Includes permanent database storage, password hashing, encryption at rest, and a persistent audit log. The audit log records important actions related to a case, timestamps, and the responsible user.	Persistent storage prevents important data from being lost after the program restarts. Password hashing and encryption reduce the risk of sensitive data being exposed if the database is accessed directly. Audit logging improves accountability, traceability, and security review.

1.3 Final System Architecture and Design

There are six layers used in our system architecture: Domain, Application, Logic, Infrastructure, Web, and Authentication. This separation in the system means that each part can focus on one responsibility, while still contributing a part to the complete dispatch workflow.



The **domain layer** contains the system's main objects, with each of them controlling its own rules, functionality, and state changes in the system. For example, assigning cases, releasing a unit, or closing a case. The main objects are cases, units, departments, priorities, and case states. The **application layer** is the coordinator of the system and tells parts of the system "what needs to happen". DispatchService is an example in the application layer, where it coordinates the case creation, prioritisation, routing, and case-related tasks. The **logic layer** contains the rules about the system objects that are independent of the interface and database. For example, KeywordSeverityPriority.cs implements the priority logic in the system, where its rules can be changed independently. The **infrastructure layer** contains all of the department, case, notification and other repositories. These have direct access to the database and its chosen operations. The **web layer** uses ASP.NET Core Razor Pages to display the interface and pages of the system. This includes the sign-in page, dispatcher dashboard, department dashboard, and all other system pages. Lastly, the **authentication layer** holds files that are responsible for credential checking and making sure users can only access information that is permitted by their role.

Our system implements **two main design patterns: the repository pattern and the strategy pattern**. The repository design pattern gives an abstraction layer between the business logic and data storage. This gives a consistent way of managing data while hiding the implementation details (*GeeksforGeeks, 2026*). `ICaseRepository`, `IDepartmentRepository` and `IDispatchNotifier` all use the repository design pattern to separate the workflow from the storage. The strategy design pattern is a behavioural design pattern where a group of similar algorithms are used in a way that makes them interchangeable. This allows the algorithm to vary depending on what the client requires for their task, and enables these changes during runtime without modifying the existing code (*GeeksforGeeks, 2026*). In our system, the strategy pattern was used for case priority calculation. The `IPriorityStrategy` interface defines the framework to calculate priority, and `KeywordSeverityPriority` provides the implementation of that framework.



We used **dependency injection** to connect the different layers and components of our system architecture. All of the repositories, priority strategy, notification service, and the dispatch service are loaded when the application starts. Rather than every class creating its own dependencies created unnecessary load on the system, the components are provided to those classes instead. This reduces the coupling between components while also making testing easier because the repositories and services can be provided for testing instead of the real implementations.

The `DispatchService` was implemented as the **central service for the main system workflow**. It coordinates the case creation, priority calculation, storage, unit assignment, notifications, unit sign-off, and the reassignment of released units to the cases in queue. The intention of this service was to prevent similar workflows from being implemented in different locations of the system. The pages receive user input and display information, while `DispatchService` coordinates what should happen to the case and units (backend of the application).

Domain-controlled state was used to reduce the possibility of invalid states during runtime. The states of cases and response units are controlled by the domain objects instead of the user interface. The

Case object controls whether the unit can be assigned, when a unit signs off, and whether the case should be Open, Closed, or In Progress. The Unit object controls its availability and the current case assignment. With domain objects controlling their own states, it prevents invalid states. For example, an unavailable unit still being assigned to another case, or a multi-department case closing when not all units have signed off.

All of the design decisions and patterns implemented improve the quality of the system and make it easier to test and maintain. The **layered architecture helps with testing**, due to all the business logic being separated from the web interface. This allows the business logic to be tested without needing to load the interface, allowing for easier automated testing. The **repository design pattern reduces the coupling** between components because the application layer doesn't worry about how the data is stored. Overall, the design decisions make the system more modular and easier to modify without needing to also modify other unrelated layers. The persistent database, password hashing, and audit logging added improve the reliability, security and traceability of the system. This is because it prevents data loss after the program restarts, protected information is secure, and important actions on cases are recorded for accountability.

1.4 Final Implemented Functionality

The following table summarises the core functionality implemented in the final version of the Emergency Dispatch Priority and Coordination System

Requirement	Final implemented functionality
FR-01 & FR-02	An emergency case is recorded, validated, and created based on caller, incident, location, severity, and department information is validated correctly
FR-03	Department users can only view their units and update unit location and their worker count. The unit availability is controlled by assignment and sign-off.
FR-04	The system calculates priority using department rules. An authorised dispatcher can override the priority result with a mandatory reason

FR-05	The cases appear on every selected department's dashboard and are excluded from unrelated department dashboards.
FR-06	The nearest available response unit is selected using its stored location data. If no unit is available, the case remains waiting until a compatible unit is free.
FR-07	Each department dashboard only displays its relevant cases and includes new routed cases automatically. The page refreshes every 5 seconds.
FR-08	The case follows the defined state rules (Open, In Progress, and Closed) in waiting, assignment, partial sign-off, and completion.
FR-09	Units become unavailable when assigned and available again after signing off. Two requests at the same time cannot give one unit two active assignments.
FR-10	Each unit that is assigned receives a notification containing the case number, incident type, and location. If the notification fails, it should not undo successful case creation or assignment.
FR-11	Units sign off individually; if units are still assigned to a multi-department case, its state should be In Progress. The case closes after all assigned cases have signed off.
FR-12	Dispatchers can search by caller name, case number, or date. Cases that match any of the fields are returned.
FR-13	Important actions include case creation, priority override, routing, assignment, sign-off, and closure. These are stored with the case action, user or system actor, and timestamp. Audit records should remain accessible after the program restarts.
NFR-SO2 & NFR-U01	Dispatchers, departments, and response units can access only their allocated pages and scope. Any unauthorised page requests should be denied.
NFR-R03	Cases, units, assignments, notifications, accounts, and audit records should remain accessible after the application has restarted. Stored data should be retrieved without missing or changed fields.
NFR-SO1	Sensitive account data should not be stored as readable plaintext in the local database. Authorised operations can encrypt, store, retrieve, and decrypt the data correctly.
NFR-SO3	Account passwords should be stored using password hashing. Correct passwords should be accepted, while incorrect passwords and direct hash comparison attempts are rejected.
NFR-P01	Cases should be sent to the relevant department dashboards in under 2 seconds.

1.5 Final Prototype Evidence (*Assignment 2 system*)

The screenshot shows the 'Record Emergency' form in the 'Emergency Dispatch' system. The form is divided into three main sections: 'Caller', 'Incident', and 'Response Required'. The 'Caller' section has fields for 'Full name' and 'Phone number'. The 'Incident' section has fields for 'Incident type' (e.g., vehicle collision), 'Incident location' (Street address or clear location), 'Incident description' (Describe the situation, hazards, people involved, and relevant observations), 'Latitude' (-35.0485), 'Longitude' (174.7633), and 'Initial severity assessment' (Medium). The 'Response Required' section has checkboxes for 'Medical' (Ambulance and clinical response), 'Police' (Police response and scene safety), and 'Fire' (Fire and rescue response). At the bottom, there are 'Cancel' and 'Create Case' buttons.

Figure 1.5.1: Dispatcher case-recording form

This is the /Cases/Create page where the caller details, incident details, location, reported severity, and department selection are captured. It provides dispatchers with a simple GUI to enter details rather than the older, confusing page. The location input is sent to the unit-assignment service, where it checks the coordinates of the location and finds the nearest available unit from each selected department. All mandatory information is checked using server-side validation, and the severity is checked using the priority system, which calculates the final priority for the case. The priority can also be overridden with a mandatory explanation of why it is changing. It will then be saved to the audit log, and the case details will be saved on the dispatcher's dashboard (Figure 1.5.2).

The screenshot shows the 'Dispatcher Dashboard' with a green notification bar at the top stating 'CASE-00CB8611 created successfully. Routing and available-unit assignment are complete.' Below the dashboard title, there is a 'Record Emergency' button and a 'Live updates' indicator. The main section is titled 'NEEDS ATTENTION' and 'Waiting for response units', with a note 'No compatible unit is currently available for one or more required responses.' Below this is a table with columns: CASE, INCIDENT AND LOCATION, PRIORITY, REQUIRED RESPONSE, ASSIGNED, and CURRENT STATE.

CASE	INCIDENT AND LOCATION	PRIORITY	REQUIRED RESPONSE	ASSIGNED	CURRENT STATE
CASE-00CB8611 09 Oct, 16:01	House fire 17 Queen street	High Override	Medical, Police, Fire	POL-01, FIR-01	Waiting for Medical

Figure 1.5.2: Case on dispatcher's dashboard




Figure 1.5.3: Department-specific dashboard

Figure 1.5.3 shows the police department's dashboard, where only cases assigned to this department will be displayed. Each dashboard shows the current cases that require police units, the list of all response units along with their availability status, and any notifications from the system. Each of these components is separated for easier viewing, with the goal of users being able to interpret critical information quickly. Dashboards reload every 5 seconds so that any new information is quickly updated, without the user having to manually reload the page, and reduce the chances of missed information.




Figure 1.5.4: Response-unit workspace

Figure 1.5.4 shows the interface of the POLICE-1 unit, where they receive the current assignment and its details. The dispatcher's note is added because it provides important information that helps the unit prepare for the case. After the case is handled, the unit can sign off from the

case, which only closes when all assigned units have signed off.

DISPATCHER RECORDS

Case History

Search previous emergency cases by caller, case ID, or date.

Caller name

Case ID

Recorded date

e.g. Alex Morgan

CASE-1234ABCD

dd / mm / yyyy

A case is returned when any entered field matches.

Search

All cases

2 found

Current and completed emergency records.

CASE	RECORDED	CALLER	INCIDENT AND LOCATION	PRIORITY	STATUS
CASE-D7CEA716 Medical	09 Oct 2026 16:51	Jane Doe 0219876543	Vehicle collision 385 Great South road	Medium	Open
CASE-0DCB8611 Medical, Police, Fire	09 Oct 2026 16:01	John Doe 0211234567	House fire 17 Queen street	High	In Progress

Figure 1.5.5: Case history showing case in queue

When no response units are available, the newly created case goes into a queue, with the status “Open”. Figure 1.5.5 shows the case that was just created with the status in the case history log. In the case history page, the dispatcher can search for cases by caller name, case ID, or the date it was created.

PROTOTYPE ADMINISTRATION

Persistent Audit Log

Important system actions are shown newest first.

TIME	ACTION	USER	CASE	UNIT	CHANGE	REASON
09 Oct 2026 16:51:32	Case created	admin	CASE-D7CEA716	—	— → Priority: Medium; Departments: Medical	Emergency case submitted.
09 Oct 2026 16:01:03	Unit assigned	admin	CASE-0DCB8611	FIR-01	Available → Assigned	Closest available unit selected at 0.00 km.
09 Oct 2026 16:01:03	Unit assigned	admin	CASE-0DCB8611	POL-01	Available → Assigned	Closest available unit selected at 0.00 km.
09 Oct 2026 16:01:03	Case created	admin	CASE-0DCB8611	—	— → Priority: High; Departments: Medical, Police, Fire	Emergency case submitted.

Figure 1.5.6: Audit log of case actions

Figure 1.5.6 shows the audit log of actions taken by different users. Every major action: creation, assignment, override, sign-off, and closure, is saved to this log to track who did what and to help with traceability. If an important event happened and someone had to figure out who performed a certain action, this log helps them find which user did it, making it easier for investigation if it occurs.

CASE REPORT
CASE-D7CEA716
 Recorded 09 October 2020 at 10:37

STATUS OPEN	CURRENT PRIORITY MEDIUM	REQUIRED RESPONSE Medical	COORDINATION Waiting for Medical
-----------------------	-----------------------------------	-------------------------------------	--

Incident details
The information recorded when the case was created.

INCIDENT TYPE
Vehicle collision

REPORTED SEVERITY
Medium

DESCRIPTION
Three vehicles in the crash, two moderately injured

LOCATION
303 Great South road

LATITUDE
-36.848300

LONGITUDE
171.763300

Priority decision
Calculated and final priority values for this case.

CALCULATED PRIORITY
Medium

FINAL PRIORITY
Medium

OVERRIDE
No manual override recorded

Caller details
Private information visible to dispatch and administration only.

CALLER NAME Jane Doe	CALLER PHONE 02/9876543
--------------------------------	-----------------------------------

Response coordination
Assignment, distance, and sign-off evidence for each required department.

No response units have been assigned yet.

Waiting for response: No available Medical unit has been assigned.

1 of 2

Print sidebar: 2 sheets of paper, Destination: Save to PDF, Orientation: Portrait, Pages: All, Colour mode: Colour, More settings, Print using the system dialogue...

Figure 1.5.7: Printable case report

All cases have a “print report” button which generates a report of the case details and its full lifecycle. It shows the incident details, priority decision including the override details if any, caller details, the response coordination, and finally the case activity (displayed like the audit log, but only actions linking to this case).

1.6 Remaining Implementation Limitations

The final prototype implements all of the important requirements of a real-life emergency dispatch system, but it is still a local hosted prototype. These requirements include case recording, department routing, prioritisation, response-unit assignment, and audit logging. The routing is done locally, so it does not communicate with anything outside of this local hosted prototype, like real life emergency services. The distance calculation required coordinates, and adding a coordinate finder was out of the scope. Therefore, the dispatcher has to enter coordinates from a mock coordinate list, and use that for demos.

Dashboards are updated every five seconds using polling. In the future, we would like to add real-time push updates, which would allow departments to receive cases instantaneously, instead of five seconds later. Another limitation is that the SQLite database and locking has only been tested for this prototype, and is not viable for large distributed systems.

As an Emergency Dispatch Priority and Coordination system, the security is not suitable for what it should be for a real life emergency system. Our prototype still lacks secure database management, authentication methods, and firewalls for system protection, so while it is a functioning prototype, it should not be applied to real life emergency scenarios or implemented into systems.

2. Requirements Verification and Traceability

2.1 Requirements Review and Changes Since Assessment 1

The refined functional and non functional requirements that were created in assignment one were revisited during the development and testing of the final prototype. The complete list of all requirements from assignment one is provided in **Appendix 5**.

The changes made in the final prototype showed that the original requirements no longer reflected the intended behaviour of the new prototype. As a result, we had to revisit the original functional requirements; making sure it properly described the intended behaviour, and adding new requirements for functionalities introduced in assignment 2. All these updated functional requirements for assignment two are provided in **Appendix 6**, and the upcoming section only mentions the changes that were made. Minor changes such as rewording or clarity were not included in the table below because they did not change the intended behaviour of the requirement.

The table only identifies requirements where the expected system behaviour or project scope was meaningfully changed, removed, or added during Assessment 2. Only the requirements which have been meaningfully changed in expected system behaviour or project scope are identified in the table.

2.1.1 Functional Requirement Changes

ID	Change from Assessment 1	Reason
FR-01	Added coordinates and reported severity, and clarified the required response departments and timestamp.	To support the updated case recording and priority/assignment requirements.
FR-03	Unit availability is now controlled automatically instead of being manually updated by departments.	To prevent inconsistent unit availability states.
FR-04	Added an authorised dispatcher priority override with a required reason.	To allow incorrect calculated priorities to be corrected with accountability.
FR-06	Changed unit assignment from the first available unit to the nearest available unit.	To make unit selection location-based rather than list based.
FR-08	Removed the unused assigned-unit removal scenario and clarified the three case states.	To match the agreed case lifecycle.
FR-13	new requirement ; added persistent audit logging for important system actions.	To improve traceability and accountability.

2.1.2 Non-Functional Requirement Changes

ID	Assessment 2 change	Reason
NFR-RO3	Expanded persistence to cases, units, assignments, notifications, accounts and audit events across restarts.	To cover all persistent data used by the final system.
NFR-SO1	Added AES-256-GCM encryption for selected sensitive stored data.	To protect sensitive data stored by the system.
NFR-SO2	Added department/unit scope and denial of direct unauthorised requests.	To strengthen access control beyond the interface.
NFR-SO3	New requirement for salted PBKDF2 password hashing.	To prevent passwords from being stored in plaintext.

2.2 Final Requirements Traceability Matrix

The final requirement traceability matrix links every requirement defined in the **Appendix 6** document to its implemented functionality, verification evidence, final result, and related defects where applicable. Section 3 gives more details on the testing procedures and execution results.

2.2.1 Functional Requirements Traceability Matrix:

ID	Final implementation	Verification Evidence	Result	Defect
FR-01	Validated Razor form records caller, incident, location, coordinates, severity and selected departments.	TC-01, TC-02 and HTTP workflow	Passed	D-06
FR-02	Creates one case with a generated identifier and timestamp. Initial status depends on unit availability.	TC-01, TC-03 and HTTP workflow	Passed	–
FR-03	Department users can view and update their units' location, coordinates and personnel count. Availability is controlled by assignment and sign-off.	FR-03 valid/invalid update tests, restart test and role tests	Passed	D-06
FR-04	Department-specific keyword rules calculate priority, with reported severity as the fallback. Authorised overrides require a reason.	TC-04 and PriorityOverrideTests	Passed	D-06
FR-05	Cases are visible to selected departments and excluded from unrelated department dashboards.	TC-03, TC-05, TC-09, role tests and HTTP tests	Passed	–
FR-06	Selects the nearest compatible available unit using Haversine distance. Cases wait when no compatible unit is available.	TC-06–TC-08 and DistanceAssignmentTests	Passed	D-03
FR-07	Department dashboards contain only relevant cases and reload every five seconds.	TC-09 and rendered-page HTTP refresh test	Automated checks passed	D-06

FR-08	Domain rules control Open, In Progress and Closed case states.	TC-03, TC-07, TC-10 and database lifecycle test	Passed	–
FR-09	Assignment makes units unavailable; sign-off releases them; locking prevents duplicate active assignment.	TC-06–TC-10, concurrency test and database lifecycle test	Passed	–
FR-10	Assigned units receive persistent case notifications. Notification failure does not undo a successful dispatch.	TC-03, notification-failure test and notification restart test	Passed	D-04
FR-11	Units sign off individually, and a case closes after the final required response signs off.	TC-10, database lifecycle test and HTTP workflow	Passed	–
FR-12	Dispatcher history supports OR-based search by caller, case number or date.	TC-11 and repository search tests	Passed	–
FR-13	Important case actions are stored persistently with actor, time, case and unit information.	AuditLoggingTests, PriorityOverrideTests and database lifecycle test	Passed	D-01, D-06

2.2.2 Non-Functional Requirements Traceability Matrix:

ID	Final implementation	Verification evidence	Result	Defect
NFR-P01	Database-backed multi-department dispatch must finish within two seconds locally.	TC-05; database-backed performance test	Passed (35 ms)	–
NFR-P02	Support 100 concurrent users with responses within two seconds.	No representative concurrent-user load test	Unverified, out of scope	–
NFR-M01	Layered architecture and repository interfaces separate critical workflows from adapters; notification failure is isolated.	Architecture review; notification failure test	Partially verified	D-04

NFR-M02	Strategy and repository abstractions reduce changes to core workflow, but adding roles or department types still requires configuration and code changes.	Code and architecture review	Partially met	–
NFR-R01	Stored case information remains consistent across selected department projections.	TC-03, TC-05, TC-09; HTTP role tests	Passed	–
NFR-R02	Maintain 99.9% weekly availability.	No deployed monitoring period	Unverified, out of scope	–
NFR-R03	Cases, units, assignments, notifications, accounts and audit events persist across restarts.	SqlitePersistenceTests; multi-restart lifecycle	Passed	D-01
NFR-R04	Continue operating with 100 simultaneously open cases.	No controlled 100-case operational or load test	Unverified	–
NFR-S01	Selected sensitive database fields use AES-GCM; deployed TLS has not been independently verified.	Raw-database encryption and restart test	Partially passed	D-02
NFR-S02	Cookie authentication, middleware, role claims and scope checks restrict access.	TC-12; report access; real HTTP tests	Passed	D-06
NFR-S03	Passwords stored as salted PBKDF2 hashes; incorrect passwords rejected.	SecurityTests; restart authentication test	Passed	D-02
NFR-U01	Dispatcher, department, response-unit and prototype Admin interfaces are role-specific.	TC-12; page-model and HTTP tests	Passed	D-06
NFR-U02	Validation provides user-facing messages without exposing stack traces.	Invalid-input and login tests; manual review still required	Partially verified	D-06
NFR-U03	Users complete core tasks after no more than one hour of training.	No representative timed usability study	Unverified	–

2.3 Partially Implemented, Unverified and Out-of-Scope Requirements

3. Test Execution and Final Test Results

- ☒ ~~Execute the planned tests against the completed system~~
- ☒ ~~Include relevant functional and non functional tests (unit, integration, system, acceptance, regression, usability, security, performance, or accessibility)~~
- ☒ ~~Include positive, negative, boundary, invalid input, and error handling scenarios where applicable~~
- ☒ ~~Provide at least 15 final test cases with execution results~~
- ☒ ~~Summarise the number of planned, executed, passed, failed, blocked, and not run tests~~
- ☐ ~~Explain failed tests, corrective actions, regression testing, and remaining quality risks~~

3.1 Final Testing Approach

In the final prototype we have added multiple changes into the prototype from the previous phase. These include priority override, nearest unit assignment, a database, improved security as well as audit logging. These increased the scope of what the requirement would need to test on thus the testing scope is increased to test these newly added features. The final testing stage as all implementations would need to be verified on the updated functional and non functional requirements in task 2. These testing approaches would include unit, integration, end to end, security and performance.

3.2 Final Test Cases

For the final test case, we have 167 tests which all of the tests pass, the table would consist primarily of core functional and non-functional requirements. These test cases cover different test types (integration, unit, and performance) and conditions (positive, negative, invalid input, boundary and error handling).

Test ID	Test Situation	Test Type	Condition	Status
TC-01	Creating emergency cases using valid incident information.	Integration	Positive	Pass
TC-02	Creating emergency cases using incomplete incident information.	Integration	Invalid Input	Pass
TC-03	Create, prioritize, store and assign cases to relevant departments.	Integration	Positive	Pass
TC-04	Calculate priority using departments specific keywords.	Unit	Positive	Pass
TC-05	Complete in process multi department within 2 seconds.	Performance	Positive	Pass
TC-06	Skip unavailable units and assign to the closest available and compatible unit.	Integration	Negative	Pass
TC-07	Queue the emergency case when there are no response units available and assign it after a unit is "open".	Integration	Negative	Pass
TC-08	Prevent concurrent submission from assigning the same unit to two cases.	Integration	Negative	Pass
TC-09	Display only relevant department cases and include new cases after refreshing,	Integration	Positive	Pass
TC-10	Keep a case In Progress until the final unit assigned to it signs off.	Integration	Positive	Pass
TC-11	Search case history using caller name, case, identifier or date.	Unit	Positive	Pass
TC-13	Reject priority override when dispatcher does not provide a reason.	Integration	Invalid Input	Pass

TC-14	Verify audit logs remain ordered by checking if the newest log appears first.	Integration	Positive	Pass
TC-15	Verify emergency case and unit assignment information is persisted when the database restarts.	Integration	Positive	Pass
TC-16	Verify the password hashing uses different salt and rejects incorrect passwords.	Unit (security)	Positive & Negative	Pass
TC-17	Deny coordinate location outside of the permitted boundaries.	Unit	Boundary & Invalid Input	Pass
TC-18	Check whether notification failure does not interrupt case creation or assignment.	Integration	Error handling	Pass

These 17 test cases are demonstrations of the different testing approaches used throughout all the automated tests rather than the entire test coverage of the system. The detailed specification of these 17 test cases are provided in **Appendix 7**.

3.3 Test Execution Results

The final tests were executed against the completed system, covering 167 automated test executions mentioned in task 3.2. The results are summarised below:

Test Execution Results & Metrics	Number
Planned Test	167
Executed Test	167
Passed Test	167
Failed Test	0

Blocked Test	0
Not-Run Test	0
Pass Rate:	100%

The test pass rate was calculated from the total number of pass executed tests by the total number of executed tests times 100. Therefore giving 100% pass rate. This shows that the current system fully satisfies the expected outcome set for all automated tests. (Figure 3.3.1 shows all 167 had passed in Test Explorer in Visual Studio, tested in MSTest and used SQLite for database related tests).




Figure 3.3.1: All Test Case Pass Evidence

Although all 167 tests made had passed this does not indicate that the system is fully verified of the systems full functionality and quality of the implementation defined by the requirements.

3.4 Failed Tests and Corrective Actions

For the initial automated test result (**This was before task 3.2 Final Test Cases**) , there were 31 failed test cases out of 167 automated tests, resulting in a pass rate of 81.4%.




Figure 3.4.1: System.IO.IOException




Figure 3.4.2: AES-GCM Decryption

After reviewing all failed test cases, all these test cases were mostly caused by the exception, System.IO.IOException. These results occurred when trying to conduct testing while the cleanup process tried to delete the temporary SQLite database and lock up the files due to the connection still being used. These issues occurred throughout the different test cases such as WebApplicationTest, SqlitePersistenceTests, SecurityTests and AuditLoggingTests. Therefore, this is more related to the database connection rather than any failed testing logic implementation. These test cases would need to be fixed in order to verify that all functionalities are working as intended.

The action taken to resolve this issue was to disable pooling for all the tests. Since each time the test requires the SQLite connection to the database, pooling could retain the database connection in the connection pool to be reused, thus preventing cleanup of the temporary database file created during the tests. Applying this change resolves the SystemIO.IOException issue.

After confirming that this update worked, this was then tested on a separate device to ensure that the issue is not related to the local environment. This resulted in 18 test cases failing rather than 31 on the initial device. These issues were related to `System.Security.Cryptography.AuthenticationTagMismatchException`. This occurred when the web application tried to decrypt stored data from the database. Further investigation led to `Program.cs`, where this is not so much an authentication issue, but rather that the database is immediately initialised before the test could replace it with a temporary database. So the initialized database was changed so the database would only be initialized when the service requested it; this is implemented through utilizing factory functions. This allowed the temporary database to be used instead of unnecessarily initializing the original database setup.




Figure 3.4.3: Result after the changes

Applying both changes towards the final testing implementation. All 167 tests passed with 0 failed tests.

3.5 Regression Testing

3.6 Remaining Testing Risks

4. Test Automation and Quality Engineering - fateh

- ☐ *Identify suitable test cases for automation and justify the selection*
- ☐ *Implement automated tests using an appropriate tool or framework where suitable*
- ☐ *Report automated test execution results using logs, screenshots, reports, or repository evidence*
- ☐ *Discuss the benefits, limitations, and maintainability of the automated test suite*
- ☐ *Where automation is not appropriate, justify the use of manual or exploratory testing*

4.1 Automation Selection

- Check project test files

4.2 Automated Test Implementation

- Check project test files

4.3 Automated Test Results

- Check project test files

4.4 Automation Maintainability

4.5 Manual and Exploratory Testing

5. Continuous Integration and DevOps QA - shawn

- ☐ *Describe the development and integration workflow*
- ☐ *Implement a simple CI workflow or equivalent automated quality check where appropriate*
- ☐ *Define quality gates (successful build, passing tests, linting, code review, or coverage threshold)*
- ☐ *Demonstrate smoke or sanity testing where relevant*
- ☐ *If CI/CD is not technically appropriate, justify an alternative quality workflow*

5.1 Development and Integration Workflow

5.2 Continuous Integration Pipeline

5.3 Quality Gates

5.4 Smoke and Sanity Testing

5.5 CI Evidence and Limitations

6. Defect Management and Root Cause Analysis **lao**

- ☐ *Maintain a final defect register covering defects found during development and testing*
- ☐ *Define severity, priority, and defect status categories*
- ☐ *Describe the defect lifecycle used in the project*
- ☐ *Analyse at least 3 significant defects using root cause analysis*
- ☐ *Propose corrective actions and defect-prevention measures*
- ☐ *Explain how defect analysis improved product or process quality*

D-01 = data lost after application restart

D-02 = plaintext/readable credentials and sensitive stored data

D-03 = unit assignment used first-available instead of nearest

D-04 = notification failure could make a successful dispatch appear to fail

D-05 = HTTP tests could accidentally use the developer database

D-06 = earlier tests had weak negative/audit/real-page coverage

6.1 Defect Management Approach

6.2 Severity, Priority and Status Definitions

6.3 Defect Lifecycle

6.4 Final Defect Register

6.5 Root Cause Analysis: Defect One

6.6 Root Cause Analysis: Defect Two

6.7 Root Cause Analysis: Defect Three

6.8 Corrective and Preventive Actions

7. Quality Testing

- ☐ *Conduct quality testing relevant to the project (security, performance, usability, accessibility, compatibility, reliability, or maintainability)*
- ☐ *Address at least 2 quality areas where applicable*
- ☐ *Use risk-based reasoning to justify the selected testing activities*
- ☐ *Document testing evidence, results, limitations, and recommended improvements*

7.1 Risk-Based Selection of Quality Areas

7.2 Quality Area One: [e.g. Security]

7.3 Quality Area Two: [e.g. Performance]

7.4 Results and Limitations

7.5 Recommended Improvements

8. Quality Metrics and Final Release Decision

- ☐ *Present relevant quality metrics (test pass rate, defect severity distribution, requirement coverage, test coverage, automation coverage, code quality indicators, commit activity)*
- ☐ *Evaluate the completed system against requirements, acceptance criteria, and quality attributes*
- ☐ *Summarise testing results, defect status, metrics, limitations, and residual risks*
- ☐ *State whether the system is ready for release, conditionally ready, or not ready for release*
- ☐ *Justify the release decision using evidence*

8.1 Final Quality Metrics

8.2 Requirements and Acceptance-Criteria Evaluation

8.3 Outstanding Defects and Residual Risks

8.4 Final Release Decision

9. AI-Assisted Development and Critical Reflection

- ☐ Explain how GitHub Copilot was used (implementation, testing, debugging, refactoring, or QA activities)
- ☐ Provide representative evidence of AI-assisted development
- ☐ Explain how AI-assisted outputs were reviewed, modified, tested, accepted, or rejected
- ☐ Identify quality risks found in AI-assisted outputs (incorrect logic, insecure code, poor maintainability, unsuitable assumptions)
- ☐ Reflect on how AI-assisted development affected productivity, learning, testing, software quality, and professional practice

9.1 AI-Assisted Activities




Figure 1.2.1: Github Copilot Evaluation

In the previous assignment, the functional requirements and non-functional requirements are defined and the acceptance criteria are created to describe expected behaviour of the core functional requirements. GitHub Copilot has been used to review the requirements that are gaps identified of core functionality with acceptance criteria. FR-02 and FR-07 are flagged as gaps that need to be considered for further changes. FR-01, FR-04, FR-05, FR-06, FR-08, FR-09 and FR-11 are not found as issues and are considered potential issues by GitHub Copilot. It identified that FR-02 acceptance criteria is not fully met, this criteria in FR-02 “Given a case is newly created from a recorded call, when creation completes, then the case status is set to “Open” with no units assigned to it yet”. FR-07 is flagged because GitHub described that the dashboard does not automatically refresh without user action, which doesn’t meet this: “Given a department’s dashboard is open, when the information of a case changes e.g. priority, location, then the dashboard should refresh and show the new changes automatically.” and “Given a department’s dashboard is open, when a case is routed to that department, then the dashboard should display the new case automatically.” When personally

investigating whether the FR-02 implementation meets the acceptance criteria gaps during testing, there isn't an issue because if there is a unit available, then the case would be assigned, thus receiving the status of "InProgress". The acceptance criteria is only met when there are no available units in that relevant department. Therefore, the acceptance criteria would need to be updated that the criteria is only for when there are no available units. For FR-07, after personal testing of the prototype, it has met its expected behaviour since the dashboard is updated without manually refreshing. The suggested GitHub flagged issues because it assumed that automatic updates mean adding a push mechanism (SignalR) to satisfy the stated criteria.

9.2 Representative GitHub Copilot Evidence

9.3 Human Review and Validation

9.4 AI-Related Quality Risks

9.5 Critical Reflection

10. Quality Improvement and Future Recommendations

- ☐ *Identify the main quality lessons learned from the project*
- ☐ *Recommend improvements to the development and QA process*
- ☐ *Propose future improvements to testing, automation, CI/CD, monitoring, security, usability, accessibility, or maintainability*
- ☐ *Explain how the project could evolve toward stronger continuous quality engineering practice*

10.1 Key Quality Lessons

10.2 Improvements to the Development and QA Process

10.3 Future Testing and Automation Improvements

10.4 Future Continuous Quality Engineering

11. Team Contribution and Professional Reflection

- ☐ *Provide a contribution statement for each group member*
- ☐ *Provide evidence from GitHub commits, project artefacts, testing work, documentation, and implementation tasks*
- ☐ *Include a brief individual reflection from each group member*

11.1 Contribution Statement

11.2 GitHub and Project Evidence

11.3 Individual Reflection – Member One

11.4 Individual Reflection – Member Two

11.5 Individual Reflection – Member Three

Delivarables (Notes)

Prepare a 15-slide presentation covering: title/members/problem/stakeholders/scope, key requirements, final prototype and changes since Assessment 1, testing approach/coverage/results, automation/CI/CD, defects and RCA, quality metrics and release decision, Copilot use and limitations, individual contributions and lessons learned

All students participate in the demonstration and show the working prototype

Demo includes key features, important test cases, automated tests/CI results, defect fixes, evidence major requirements are satisfied

Be prepared to answer questions on the project, code, testing, quality artefacts, AI-assisted development, and individual contributions

Deliverables

- Final Project and Software Quality Assurance Report: 6,000–7,000 words
- Source code and GitHub repository link, with evidence from GitHub commits
- Contribution statement for each group member
- Project presentation
- Turnitin Similarity Report

References:

O Aotearoa, R. I. T. R. I. (n.d.). Pressure grew to fix the 111 emergency call system, with the 1958 model still in use. RNZ.

https://www.rnz.co.nz/news/emergencies_local/585202/pressure-grows-to-fix-111-emergency-call-system-with-1958-model-still-in-use

1News Reporters. (2026, August 10). St John bracing for another 111 spike amid record demand. 1News.

<https://www.1news.co.nz/2026/08/10/st-john-bracing-for-another-111-spike-amid-record-demand/>

GeeksforGeeks. (2026, May 13). Repository design pattern. GeeksforGeeks.

<https://www.geeksforgeeks.org/system-design/repository-design-pattern/>

GeeksforGeeks. (2026, May 14). Strategy design pattern. GeeksforGeeks.

<https://www.geeksforgeeks.org/system-design/strategy-pattern-set-1/>