AutoTeaKG-Silver: An Uncertainty-Aware Evidence Graph for Tea Functional Activity Literature

Anonymous Authors

Abstract

Tea, tea extracts, and tea-derived components are widely studied for antioxidant, anti-inflammatory, metabolic, cardiovascular, neuroprotective, and gut-microbiota-related activities. However, the evidence is fragmented across tea types, component definitions, processing conditions, model systems, and endpoint labels, making it difficult to compare claims or identify where evidence is strong. We introduce AutoTeaKG-Silver, an automatically generated, provenance-rich, uncertainty-aware evidence graph for tea functional activity literature. The system retrieves PubMed records, converts title/abstract and open full-text methods sections into structured evidence records, normalizes activity and evidence labels, extracts processing and extraction context, and exports a graph in which every edge retains source provenance and uncertainty attributes. In the current KG v3 release, AutoTeaKG-Silver contains 635 evidence records, 1,989 nodes, and 8,195 edges. The pipeline increases processing-context coverage from 146 to 183 records and extraction-context coverage from 154 to 185 records, while explicitly preserving 303 records whose processing or extraction context remains missing. The resulting resource exposes uneven evidence support across activity classes, identifies processing-context reporting gaps, and provides a microbiome-ready graph substrate for downstream mechanism queries. AutoTeaKG-Silver should therefore be interpreted not as a manually verified gold-standard database, but as a reproducible silver-standard evidence infrastructure for living tea bioactivity synthesis.

1 Introduction

Tea is a chemically complex beverage and botanical material with a large literature on potential health-related functions. Reviews have summarized the biological potential of catechins, theaflavins, theanine, caffeine, polysaccharides, and other tea-derived compounds across antioxidant, inflammatory, metabolic, cardiovascular, and neuroprotective endpoints [1–3]. A parallel literature studies how tea processing and extraction alter chemical profiles and product quality [4–6]. More recently, tea–microbiome interactions have become a prominent mechanistic theme, especially for metabolic and gut-brain-axis phenotypes [7–9]. These bodies of work make tea an attractive domain for structured evidence synthesis.

The central difficulty is that tea functional activity evidence is abundant but poorly aligned. A claim about "green tea", "EGCG", "tea polyphenols", "fermented tea", or "tea polysaccharides" may refer to different materials, processing states, extraction methods, doses, and experimental settings. Evidence strength also varies substantially: animal studies, in vitro experiments, randomized trials, cohort studies, and narrative reviews often appear together in the same prose summary. Narrative reviews are useful for expert interpretation, but they do not provide a machine-readable evidence layer that can answer comparative questions such as which activities have human evidence, which are mostly preclinical, or whether processing information is reported at all.



Figure 1: Graphical overview of AutoTeaKG-Silver. The pipeline converts PubMed tea functional activity literature into structured evidence records, recovers processing and extraction context from abstracts and open PMC methods sections, and exports a provenance-rich uncertainty-aware evidence graph.

Existing tea databases do not solve this functional evidence problem. TeaPVs and TeaNekT provide genomic and transcriptomic resources for tea plant biology [10, 11]. TRSRD is closer to a tea-domain knowledge graph, but it focuses on risky substances rather than functional activity evidence [12]. More general natural-product resources such as NPASS and natural-product drug-interaction knowledge graphs show that natural products can be represented computationally [13, 14], but they do not encode the tea-specific combination of functional activity, processing context, evidence level, and microbiome mechanism.

We argue that the missing contribution is not another static spreadsheet of tea papers, but an automated evidence infrastructure that makes uncertainty explicit. Manual curation can improve record quality, but it does not scale to a living PubMed-updated resource. Conversely, raw large-language-model extraction is not sufficient unless outputs are constrained by domain schemas, provenance, validation flags, and uncertainty classes. The practical goal is therefore to build a silver-standard graph: a resource that is automatically generated, reproducible, inspectable, and useful for evidence mapping, while avoiding the stronger claim that every edge is expert verified.

This paper introduces AutoTeaKG-Silver, an uncertainty-aware evidence graph for tea functional activity literature. The pipeline retrieves PubMed records, generates structured evidence records, extracts tea type, component group, activity category, study type, evidence level, mechanism labels, microbiome features, and host phenotypes, and then enriches records with processing and extraction context from abstracts and open full-text methods sections. The final graph preserves evidence-record nodes so that each relation can be traced back to a paper, raw claim text, evidence level, and uncertainty flag.

The contributions are fourfold. First, we define a graph-ready evidence model for tea functional activity literature that separates activity claims from study design, evidence level, component context, processing context, and uncertainty. Second, we build an automated silver-standard resource with 635 evidence records and 8,195 graph edges, excluding manual annotation as a data-generation dependency. Third, we show that processing and extraction context remain a measurable bottleneck: targeted extraction improves coverage, but many records lack open full-text or report insufficient methods detail. Fourth, we provide figure-ready query tables and graph outputs that support evidence mapping, processing-aware analysis, and microbiome mechanism exploration.

2 Related Work

2.1 Tea bioactivity reviews and evidence synthesis

The tea bioactivity literature is rich in narrative synthesis. Recent reviews summarize the biological potential of tea bioactive compounds across inflammation, oxidation, metabolism, microbiota modulation, and other health-related endpoints [1]. Other reviews focus on specific mechanistic constraints, such as the bioavailability of tea polyphenols and the difficulty of extrapolating in vitro activity to in vivo health effects [2]. Tea polysaccharides have also become a distinct review topic because their chemical characterization, conjugates, and bioactivities differ from those of catechin-centered polyphenol literature [3]. These reviews establish that the domain is active and biologically broad, but their outputs remain prose summaries rather than computable evidence records. AutoTeaKG-Silver differs by representing study type, evidence level, activity category, component context, and uncertainty as queryable fields.

2.2 Processing-aware tea chemistry and microbiome mechanisms

Tea processing and extraction strongly influence chemical composition, product quality, and downstream interpretation. Food engineering reviews describe ultrasound, microwave, pressurized-liquid, supercritical, and other extraction technologies for recovering tea bioactives [4]. Tea processing reviews further show that harvesting, withering, rolling, fermentation or oxidation, drying, and storage can alter phytochemical profiles, especially in black tea and fermented products [5]. Metabolomics studies provide analytical evidence that processing technology changes tea quality and chemical profiles [6]. In parallel, microbiome-focused work links differently processed tea, tea polyphenols, fermented tea, and tea polysaccharides to gut microbiota, microbial metabolites, host barrier function, metabolic outcomes, and cognition-related phenotypes [7–9, 15, 16]. These studies motivate the processing-aware and microbiome-aware dimensions of AutoTeaKG-Silver.

2.3 Tea databases, natural-product resources, and knowledge graphs

Existing tea resources address important but different layers of tea biology. TeaPVs focuses on genomic variation in *Camellia sinensis*, and TeaNekT provides comparative transcriptomic information for tea plant biology [10, 11]. TRSRD uses natural-language processing and knowledge graph techniques for tea risky-substance research, but the target domain is risk and safety rather than functional activity evidence [12]. Broader natural-product resources such as NPASS provide quantitative activity and species-source information, and natural-product drug-interaction knowledge graphs show the feasibility of graph-based representation for natural products [13, 14]. AutoTeaKG-Silver is complementary to these resources: it targets tea functional activity claims, evidence strength, processing/extraction context, microbiome mechanisms, and uncertainty-aware provenance.

3 Materials and Methods

3.1 Corpus construction and retrieval archive

The corpus was constructed from PubMed searches over tea functional activity, component, processing, extraction, microbiome, and human-evidence query blocks. The archived query set covered the publication window from 2022-01-01 to 2026-03-31 and included broad review retrieval, functional activity primary studies, microbiome-focused studies, processing-aware studies, and human

Table 1: Reproducible construction stages for AutoTeaKG-Silver v1 and KG v3. Counts refer to the current manuscript data release.

Stage	Main script or artifact	Primary output	Count or result
PubMed retrieval archive	search archive	query logs and batch summaries	5 query blocks
Auto-only ideation and profiling	auto-only ideation script	auto-only data profile	596 GLM5 records
Silver KG construction	silver-build script	base silver KG directory	635 records
Abstract-level context extraction	targeted context extractor	abstract-patch directory	365 patches
Vocabulary normalization	vocabulary normalizer	normalized context directory	0 unmapped labels
PMC methods retrieval	PMC methods retriever	methods-section cache	151 records with methods text
Methods-level extraction	methods batch runner	methods-patch directory	151 patches
Final KG v3 figures	query-table and figure script	query tables and figures	1,989 nodes; 8,195 edges

evidence searches. Across the larger retrieval batches, records were deduplicated by PMID and normalized into paper-level metadata tables. The manuscript uses the locked auto-only evidence graph derived from these retrievals rather than manually adjudicated mini-gold records.

3.2 Evidence-record schema

Each evidence record represents a structured claim anchored to a source paper. Core fields include the source paper identifier, tea type, material form, component group, activity category, endpoint label, study type, evidence level, model system, dose or exposure text, effect direction, mechanism label, microbiota taxon, microbial metabolite, host phenotype, raw claim text, confidence score, and provenance metadata. Activity categories include antioxidant, anti-inflammatory, metabolic improvement, anti-obesity, gut microbiota modulation, neuroprotection, cardiovascular protection, and other. Evidence levels distinguish preclinical in vivo evidence, human observational evidence, human interventional evidence, evidence synthesis, non-quantitative evidence synthesis, and low-preclinical evidence.

3.3 Auto-only extraction pipeline

AutoTeaKG-Silver was designed as an auto-only pipeline. The construction path used PubMed metadata, title/abstract text, candidate-record heuristics, GLM5 title/abstract extraction, schema validation, post-processing, duplicate consolidation, and graph export. Manual audit worksheets, mini-gold annotations, and adjudication logs were excluded from the data-generation path. This design choice is deliberate: the goal is to create a scalable silver-standard evidence layer whose uncertainty is visible, rather than to claim expert-level verification for each relation.

3.4 Processing and extraction context recovery

Processing and extraction context were recovered in three stages. The first stage used conservative rule-based matching over titles, abstracts, and claim text. The second stage targeted records flagged as missing processing or extraction context and prompted GLM5 to extract only tea-material

processing, extraction, and component context from title/abstract text. The third stage queried NCBI E-utilities to map PMIDs to open PMC full text, extracted methods-like sections, and ran a targeted methods-section extractor on records with available full-text context. All targeted extraction steps were patch-first: the model generated a patch table, and patched copies of the silver dataset and KG were regenerated rather than overwriting the base resource.

3.5 Vocabulary normalization

LLM surface labels were normalized into a controlled processing and extraction vocabulary. For example, black tea manufacturing and black tea formation were mapped to black tea processing; brick-like form and brick tea processing were mapped to compressed/brick tea processing; cold brewing and hot brewing were mapped to brewing/infusion; and isolation, isolated, and purification were mapped to isolation/purification. Raw LLM labels were retained in mapping tables so that normalization decisions remain auditable.

3.6 Uncertainty assignment

Each record was assigned uncertainty flags and an uncertainty class. Flags captured low LLM confidence, missing processing or extraction context, generic mechanism labels, missing named microbiota, taxonomy expansion needs, preclinical-only evidence, review-summary records, uncertain effect direction, and schema validation problems. The uncertainty class summarized these signals into low, moderate, or high uncertainty. This design keeps uncertainty in the graph rather than hiding it during filtering.

3.7 Graph construction and query tables

The graph preserves papers and evidence records as explicit nodes. Evidence records are linked to tea type, material form, component group, processing step, extraction method, activity category, study type, evidence level, effect direction, mechanisms, microbiota features, metabolites, host phenotypes, and uncertainty flags. Graph edges retain paper identifier, record identifier, evidence level, study type, effect direction, confidence score, and uncertainty class. Query tables were generated from the final KG v3 to support evidence mapping, activity-by-evidence heatmaps, uncertainty summaries, processing and extraction label distributions, microbiome mechanism subsets, and node/edge composition summaries.

3.8 Reproducibility package

The current manuscript release is organized so that each result can be traced to a script and output directory (Table 1). The final graph used for all Results figures is stored at `reports/methods_processing_vocab_normalized`. Its record table is `autoteakg_silver_records.csv`; graph files are `kg_v3/nodes.csv` and `kg_v3/edges.csv`. Figure-ready query tables are stored in `reports/kg_v3_query_tables`. Publication figures are regenerated by `scripts/generate_kg_v3_query_tables_and_figures.py` and exported as PDF, PNG, and SVG under `figures/kg_v3`. The paper draft project copies the figure PDFs and query tables into `writing_outputs/20260412_autoteakg_silver_paper`.



Figure 2: Node and edge type composition of KG v3. The graph preserves evidence-record provenance while linking papers, activity categories, evidence levels, tea/component context, processing/extraction context, mechanisms, microbiota features, metabolites, phenotypes, and uncertainty flags.

4 Results

4.1 AutoTeaKG-Silver constructs a provenance-rich tea functional activity graph

The final KG v3 contains 635 silver evidence records, 1,989 nodes, and 8,195 edges (Figure 2). The graph includes paper nodes, evidence-record nodes, activity-category nodes, study-type nodes, evidence-level nodes, tea and component context nodes, processing and extraction context nodes, mechanism nodes, microbiota-feature nodes, microbial-metabolite nodes, host-phenotype nodes, and uncertainty-flag nodes. The explicit EvidenceRecord layer is important because it prevents mechanistic and activity relations from becoming detached from their source papers.

4.2 Evidence-level normalization exposes uneven support across activity classes

The activity-by-evidence heatmap shows that tea functional activity claims are not evenly supported across evidence levels (Figure 3). Several activity categories are dominated by preclinical in vivo records and non-quantitative evidence syntheses, while human observational and interventional evidence is concentrated in fewer categories. This pattern supports the central motivation for evidence grading: without evidence-level normalization, review-derived, animal, cohort, and randomized-trial claims are easily mixed into a single apparent evidence base.

4.3 Targeted extraction improves but does not eliminate missing processing context

Processing and extraction context increased across extraction stages (Figure 4). Rule-based extraction identified processing context in 146 records and extraction context in 154 records. Abstract-



Figure 3: Heatmap of normalized activity categories stratified by evidence level in KG v3. The distribution shows that animal evidence and non-quantitative evidence syntheses dominate several activity categories, while human interventional and observational evidence is concentrated in fewer endpoints.

level targeted GLM5 extraction increased coverage, and PMC methods-section extraction further raised processing-context coverage to 183 records and extraction-context coverage to 185 records. The improvement is measurable but modest, indicating that processing context is not uniformly available from abstracts alone.

The full-text retrieval analysis clarified why context remains missing. Of 329 records still flagged after abstract-level extraction, 151 records had PMC methods-like sections, while 178 lacked open PMC full text (Figure 5). Methods-section extraction generated patches for all 151 available records and recovered details such as crushing and sieving, cleaning–drying–powdering, steaming and fixation, ultrasonic ethanol extraction, methanol sonication, microwave-assisted extraction, brewing, and isolation/purification.

4.4 Vocabulary normalization reduces processing and extraction label fragmentation

Processing and extraction labels generated by LLM extraction required normalization before graph use. The final vocabulary-normalized KG reduced surface-form fragmentation while retaining raw labels for provenance. Fermentation/oxidation was the dominant processing context, followed by storage/aging, enzymatic treatment, roasting, black tea processing, processing category contrast, drying, steaming/fixation, and crushing/grinding/sieving. Extraction labels were concentrated in other extraction, aqueous extraction, isolation/purification, analytical characterization, brewing/infusion, solvent extraction, ultrasound-assisted extraction, and commercial preparation (Figure 6).



Figure 4: Context recovery across automated extraction stages. Rule-based extraction established the initial context layer, abstract-level targeted GLM5 extraction added additional context, and PMC methods-section extraction further improved recovery of processing and extraction variables.

4.5 Uncertainty classes make silver-standard status explicit

The final KG contains 100 low-uncertainty records, 470 moderate-uncertainty records, and 65 high-uncertainty records. The activity-level uncertainty composition (Figure 7) shows that moderate uncertainty dominates the resource. This result is not a defect of the resource; it is the intended operating mode of a silver-standard evidence graph. Instead of filtering uncertainty away, AutoTeaKG-Silver stores uncertainty as a queryable property that downstream users can use to restrict analyses.

4.6 The graph supports microbiome-mechanism queries

KG v3 contains 190 microbiome-relevant records. These records connect tea types and component groups to gut microbiota modulation, microbial metabolites, host phenotypes, and mechanism labels. The microbiome subset provides a graph-native substrate for querying component–microbiota–metabolite–phenotype paths rather than treating microbiome mentions as isolated keywords. This design is motivated by recent work linking tea polyphenols, oolong tea polyphenols, and tea polysaccharides to microbiota-mediated metabolic, inflammatory, and neuroprotective programs [7–9, 15, 16].

5 Discussion

AutoTeaKG-Silver reframes tea functional activity synthesis as an automated evidence-graph construction problem. The main contribution is not that the system replaces expert review. Rather, the system creates a reproducible and updateable substrate that makes evidence level, provenance, missing context, and uncertainty visible. This framing is important because tea bioactivity claims often differ in study design, material identity, processing state, and mechanism specificity.

The results show that evidence grading changes interpretation. Tea functional activity cate-



Figure 5: Full-text methods availability funnel for records that remained missing context after abstract-level extraction. Of 329 remaining records, PMC methods-like sections were available for 151 records, while 178 records lacked open PMC full text.

gories contain a mixture of animal studies, human studies, meta-analyses, randomized trials, and reviews. Treating these records as equivalent would inflate confidence in claims that remain mostly preclinical. By encoding evidence level and study type as first-class graph attributes, AutoTeaKG-Silver allows users to query the evidence base under stricter assumptions.

The processing-context experiments reveal a second challenge. Processing and extraction variables are essential for interpreting tea chemistry and activity, yet many abstracts omit these details. Targeted LLM extraction and PMC methods retrieval improve coverage, but 303 records remain flagged for missing processing or extraction context. This result suggests that future improvements should focus on full-text access and methods-section extraction rather than repeatedly prompting abstracts.

The uncertainty layer is a practical compromise between scale and reliability. A manually curated gold-standard resource would be smaller and slower to update. A raw LLM graph would be larger but difficult to trust. AutoTeaKG-Silver occupies the middle ground: it keeps all records provenance-rich, marks uncertainty explicitly, and provides query tables and figures that can be regenerated from the graph.

6 Limitations

This work has four important limitations. First, AutoTeaKG-Silver is a silver-standard resource, not a manually verified gold-standard database. The graph should be used with uncertainty filters when precise biological conclusions are required. Second, the current system relies on PubMed abstracts and open PMC full text; records without PMC full text remain difficult to refine. Third, processing and extraction labels are normalized by rules after LLM extraction, but some labels still represent broad process categories rather than complete experimental protocols. Fourth, the microbiome subgraph includes grouped taxa and generic mechanism labels, so causal interpretation requires additional normalization and full-text validation.



Figure 6: Top normalized processing and extraction labels after abstract-level and methods-section extraction. Vocabulary normalization reduces LLM label fragmentation by mapping surface forms such as black tea manufacturing, matcha production, brewing, isolation, and chromatographic analysis into controlled context labels.

7 Conclusion

AutoTeaKG-Silver demonstrates that tea functional activity literature can be converted into an automated, provenance-rich, uncertainty-aware evidence graph. The current KG v3 release contains 635 evidence records, 1,989 nodes, and 8,195 edges, and provides figure-ready query tables for evidence mapping, processing-aware analysis, uncertainty assessment, and microbiome mechanism exploration. The results support a practical conclusion: automated evidence graphs can accelerate tea bioactivity synthesis, provided that uncertainty, provenance, and missing context are treated as first-class data rather than hidden errors.

References

[1] Qiaoxian Luo, Longbiao Luo, Jinmin Zhao, Yitao Wang, and Hua Luo. Biological potential and mechanisms of tea's bioactive compounds: An updated review. *Journal of Advanced Research*, 65:345–363, 2024. doi: 10.1016/j.jare.2023.12.004.

[2] Mingchuan Yang, Xiangchun Zhang, and Chung S. Yang. Bioavailability of tea polyphenols: A key factor in understanding their mechanisms of action in vivo and health effects. *Journal of Agricultural and Food Chemistry*, 73(7):3816–3825, 2025. doi: 10.1021/acs.jafc.4c09205.

[3] Ahmed K. Rashwan, Riham A. El-Shiekh, Abdelkader Bassiony, Asem M. Abdelshafy, Ahmed I. Osman, Hala A. Younis, Fanrui Zhou, Youssuf A. Gherbawy, Hesham R. El-Seedi, Jiang Shi, and Wei Chen. Recent advances in chemical characterization, emerging applications, and biological activities of tea polysaccharides and their conjugates from leaves and



Figure 7: Uncertainty composition by activity category. Each record was assigned an uncertainty class based on LLM confidence, schema validity, mechanism specificity, context completeness, evidence level, and taxonomy status.

flowers: A review. *International Journal of Biological Macromolecules*, 328:147540, 2025. doi: 10.1016/j.ijbiomac.2025.147540.

[4] Sonali Raghunath, Sravanthi Budaraju, Seyed Mohammad Taghi Gharibzahedi, Mohamed Koubaa, Shahin Roohinejad, and Kumar Mallikarjunan. Processing technologies for the extraction of value-added bioactive compounds from tea. *Food Engineering Reviews*, 15(2): 276–308, 2023. doi: 10.1007/s12393-023-09338-2.

[5] Muhammad Aaqil, Chunxiu Peng, Ayesha Kamal, Taufiq Nawaz, Fei Zhang, and Jiashun Gong. Tea harvesting and processing techniques and its effect on phytochemical profile and final quality of black tea: A review. *Foods*, 12(24):4467, 2023. doi: 10.3390/foods12244467.

[6] Jie Wang and Zhen Li. Effects of processing technology on tea quality analyzed using high-resolution mass spectrometry-based metabolomics. *Food Chemistry*, 443:138548, 2024. doi: 10.1016/j.foodchem.2024.138548.

[7] Zimo Zhao, Ruofan Chen, and Ken Ng. Effects of differently processed tea on the gut microbiota. *Molecules*, 29(17):4020, 2024. doi: 10.3390/molecules29174020.

[8] Zheyi Song, Chi-Tang Ho, and Xin Zhang. Gut microbiota mediate the neuroprotective effect of oolong tea polyphenols in cognitive impairment induced by circadian rhythm disorder. *Journal of Agricultural and Food Chemistry*, 72(21):12184–12197, 2024. doi: 10.1021/acs.jafc.4c01922.

[9] Baoming Tian, Pinjiao Huang, Yizhu Pan, Hong Gu, Kai Yang, Zhengxun Wei, and Xiangchun Zhang. Tea polyphenols reduced obesity by modulating gut microbiota-scfas-barrier

and inflammation in high-fat diet-induced mice. *Molecular Nutrition & Food Research*, 68(24): e2400685, 2024. doi: 10.1002/mnfr.202400685.

[10] Yanlin An, Xiaoqin Zhang, Sixia Jiang, Jingjing Zhao, and Feng Zhang. Teapvs: a comprehensive genomic variation database for tea plant (camellia sinensis). *BMC Plant Biology*, 22 (1):513, 2022. doi: 10.1186/s12870-022-03901-5.

[11] Xinghai Zheng, Zahin Mohd Ali, Peng Ken Lim, Marek Mutwil, and Yuefei Wang. Comparative transcriptome database for camellia sinensis reveals genes related to the cold sensitivity and albino mechanism of 'anji baicha'. *Physiologia Plantarum*, 176(4):e14474, 2024. doi: 10.1111/ppl.14474.

[12] Yongmei Wang, Peng Wang, Yongheng Zhang, Siyi Yao, Zhipeng Xu, and Youhua Zhang. Trsrd: a database for research on risky substances in tea using natural language processing and knowledge graph-based techniques. *Database*, 2023:baad031, 2023. doi: 10.1093/database/baad031.

[13] Hui Zhao, Yuan Yang, Shuaiqi Wang, Xue Yang, Kaicheng Zhou, Caili Xu, Xuyao Zhang, Jiajun Fan, Dongyue Hou, Xingxiu Li, Ying Tan, Shanshan Wang, Xin-Yi Chu, Dongzhi Zhuoma, Fengying Zhang, Dianwen Ju, Xian Zeng, and Yu Zong Chen. Npass database update 2023: quantitative natural product activity and species source database for biomedical research. *Nucleic Acids Research*, 51(D1):D621–D628, 2023. doi: 10.1093/nar/gkac1069.

[14] Sanya B. Taneja, Tiffany J. Callahan, Mary F. Paine, Sandra L. Kane-Gill, Halil Kilicoglu, Marcin P. Joachimiak, and Richard D. Boyce. Developing a knowledge graph for pharmacokinetic natural product-drug interactions. *Journal of Biomedical Informatics*, 140:104341, 2023. doi: 10.1016/j.jbi.2023.104341.

[15] Ruyi Zhang, Qiling Li, Yuxuan Gu, and Wenli Liao. Harnessing the power of fermented tea to improve gut microbiota and combat obesity epidemic. *Biology*, 13(10):779, 2024. doi: 10.3390/biology13100779.

[16] Beatriz Arce-López, Guadalupe X. Bazan, Susana Molina, Maria Carmen Crespo, María García-Beccaria, Silvia Cruz-Gil, Cristina M. Fernández-Díaz, Ana Ramírez de Molina, Ricardo Ramos-Ruiz, and Maria Isabel Espinosa-Salinas. Effect of fiber-modified kombucha tea on gut microbiota in healthy population: A randomized controlled trial (rct). *Current Research in Food Science*, 11:101130, 2025. doi: 10.1016/j.crfs.2025.101130.