Benchmarking Natural Polysaccharide Function Prediction with a Sparse Anchor and Core Structural Features

[Author names and affiliations to be inserted for submission]

Abstract

Natural polysaccharides are increasingly studied for antioxidant, immunomodulatory, antitumor, and metabolic regulatory activities, yet machine learning for polysaccharide structure-function prediction remains underdeveloped. A major reason is that existing carbohydrate machine learning tools are largely glycan-centric, whereas natural polysaccharides are typically described by incomplete but heterogeneous structural evidence such as monosaccharide composition, linkage patterns, branching information, and molecular-weight ranges. We therefore build a practical benchmark for multi-label function prediction from public polysaccharide resources and examine which structural signals are actually useful under current public-data conditions. Starting from public-site DoLPHiN ingestion and a filtered benchmark of 4,121 records with 18 function labels, we reproduce classical, sequence, and graph baselines and establish a tuned logistic baseline as a strong sparse anchor. We then test a family of structure-aware extensions and find that the most stable conclusion is not that a new model decisively wins, but that a small set of structured features consistently carries the useful signal. Under a fixed random split, a compact polysaccharide-specific core representation that encodes molecular-weight buckets, branching availability, and residue-set composition improves macro-F1 from 0.2610 to 0.2678. However, under a stricter DOI-grouped split, the tuned logistic anchor remains stronger, indicating that the apparent gain is split-sensitive rather than robustly general. Paired bootstrap analysis further shows that the random-split gain is not statistically decisive. Controlled ablations nevertheless give a clear mechanistic result: molecular-weight and residue features are the dominant contributors, branching provides a smaller positive effect, and several superficially plausible features are neutral or harmful. These results establish a reproducible benchmark, identify a strong sparse baseline, and clarify which structural signals are currently most useful for natural polysaccharide prediction.

Scientific Contribution. This study introduces a reproducible benchmark for multi-label structure-function prediction of natural polysaccharides from public resources. It shows that a tuned sparse logistic baseline is a strong anchor under current public-data conditions and that the apparent benefit of structured augmentation is modest and split-sensitive. Controlled ablations identify molecular-weight, residue-set, and branching features as the main usable structural signals in the current benchmark.

Keywords: natural polysaccharides; benchmark; multi-label prediction; cheminformatics; glycobioinformatics; interpretable machine learning

1 Introduction

Natural polysaccharides are multifunctional macromolecules associated with antioxidant, immunomodulatory, antitumor, anti-inflammatory, and metabolic regulation activities. The recent release of domain resources such as DoLPHiN makes it feasible to aggregate structural descriptors and reported health functions for thousands of natural polysaccharides, creating a realistic opportunity for data-driven prediction rather than purely narrative structure–function analysis. However, this opportunity is still technically immature. In contrast to proteins or small molecules, polysaccharides are rarely represented by a single clean sequence or graph. Instead, available descriptions are often heterogeneous and partially incomplete, combining monosaccharide composition, glycosidic linkages, branching descriptions, modifications, organism source, and approximate molecular-weight ranges.

This representation mismatch creates a practical challenge for machine learning. Existing carbohydrate machine learning has made real progress on glycans, including graph-based modeling and reusable software ecosystems, but these tools are largely built around glycan settings where sequence or graph structure is the primary object of analysis. Natural polysaccharide records are structurally broader and noisier. A direct transfer of glycan-centric representations therefore risks missing the signals that are most accessible in current polysaccharide databases. At the same time, claiming a large end-to-end foundation-model solution at this stage would be premature because benchmark construction, reproducible baselines, and component-level signal validation are still incomplete.

A second complication is semantic rather than architectural. In public resources such as DoLPHiN, function labels are inherited from what has been reported in the literature. The absence of a label therefore does not necessarily mean the polysaccharide truly lacks that function; it may simply be untested or unreported. The present task should therefore be read as weakly supervised multi-label prediction with positive-and-unlabeled characteristics, not as a fully observed true-negative classification problem.

This paper takes a narrower and more defensible position. We first construct a practical supervised benchmark from public polysaccharide resources, starting with full public-site ingestion of DoLPHiN and using CSDB only as an engineering stress-test source rather than as an equal supervised source. We then reproduce a set of classical, sequence, and graph baselines under fixed evaluation protocols, and identify a tuned logistic model as a strong and stable baseline. Our central insight is not that a new architecture clearly solves the task, but that the first reliable progress comes from understanding what the benchmark actually

supports: a strong sparse anchor, a modest random-split gain from structured feature augmentation, and clear ablation evidence about which polysaccharide-specific signals matter.

Our contributions are summarized as follows:

- We build a reproducible benchmark construction and baseline pipeline for multi-label polysaccharide structure–function prediction from public resources.
- We show that a tuned sparse logistic baseline is a strong anchor on this benchmark, and that a compact polysaccharide-specific feature augmentation yields only a modest, split-sensitive gain rather than a uniformly robust improvement.
- We use controlled ablations to show that molecular-weight and residue-set features are the dominant contributors, branching provides a smaller positive effect, and several plausible feature families are weak or harmful.

We deliberately limit our claim scope to current single-source supervised prediction and do not overclaim cross-source biological generalization, because the currently ingested CSDB slice is not label-aligned with the main task.

2 Related Work

Polysaccharide data resources. DoLPHiN provides a database centered on structural and functional properties of natural polysaccharides with reported health benefits, making it a natural starting point for supervised polysaccharide prediction [9]. CSDB, by contrast, is a broader curated carbohydrate structure resource with deeper structural coverage for bacterial, fungal, and plant glycans [8]. At the broader glycoinformatics infrastructure level, GlyTouCan has played an important role as an interoperable glycan repository and accessioning system for heterogeneous glycan records [7, 3]. These resources are complementary, but they are not interchangeable for supervised function prediction. Our work builds operationally on both DoLPHiN and CSDB while explicitly recognizing that only the DoLPHiN-derived subset is currently suitable as the main supervision source for the present task.

Glycan machine learning. Recent glycan machine learning work has shown that carbohydrate-specific inductive biases matter. SweetNet demonstrated that graph convolutional neural networks are well matched to glycans because they directly model branching and nonlinear structure [2]. Related work has also expanded glycan-focused machine learning into interaction prediction and broader deep-learning workflows, as exemplified by LectinOracle and other glycobiology-oriented computational resources [5, 1]. This line of work motivates our general emphasis on structure-aware representation. However, our setting differs from

glycan-focused prediction because natural polysaccharide records are often only partially graph-ready and are frequently reported through mixed textual and tabular evidence.

Practical glycobioinformatics tooling. Toolkits such as glycowork have lowered the barrier to glycan data analysis, representation engineering, and machine learning [6]. At the representation-conversion layer, systems such as GlyLES further highlight the practical importance of standardizing carbohydrate encodings before downstream modeling [4]. We build on the broader lesson of this literature, namely that generic sequence or bag-of-words treatment is often insufficient for carbohydrate data. Our contribution is narrower than proposing a universal carbohydrate architecture. Instead, we identify which structured signals are already reliable enough to improve multi-label function prediction for natural polysaccharides under current public-data conditions.

3 Method

Given a natural polysaccharide record with structural descriptors and metadata, our goal is to predict a set of functional labels from a fixed label vocabulary. Each record is represented by a canonical textual description together with fields such as monomer composition, linkage, branching, modification, molecular weight or molecular-weight range, and organism source. The target is a multi-label set over 18 retained biological function categories. Figure 3 summarizes the pipeline from raw public ingestion to the final `poly-core v1` method.

3.1 Benchmark Construction

We construct the benchmark from public-site ingestion of DoLPHiN followed by schema normalization and label normalization. To obtain a stable supervised task, we remove `unknown` labels, retain only DoLPHiN as the supervision source, and keep only labels with global frequency of at least 20. The resulting benchmark contains 4,121 records and 18 function labels.

We intentionally separate benchmark construction from engineering stress testing. A second ingestion path from CSDB is useful for future cross-source work, but the currently available CSDB slice is structurally rich and label-poor relative to the supervised task. For that reason, CSDB is excluded from the main supervised benchmark and is not used to support the core empirical claim of this paper.

For the main benchmark split, we use a precomputed fixed partition with 2,472 training records, 824 validation records, and 825 test records. All results reported in the main paper use the test partition only. The validation partition is kept for protocol completeness and future model-selection work, but our Stage

2–4 comparisons intentionally reuse the same fixed train/test view so that later-stage improvements can be attributed to controlled representation or configuration changes rather than split regeneration.

Table 1 summarizes the main benchmark statistics. The filtered benchmark is label-sparse and field-imbalanced: records contain 1.56 labels on average, linkage is missing for most records, modification is effectively absent after filtering, and all retained records have `evidence_type = unknown`. These properties reinforce that the task is best interpreted as structured weak supervision over heterogeneous literature-derived records rather than as a clean fully supervised molecular benchmark.

3.2 Tuned Sparse Baseline

Our baseline starts from a simple but strong sparse representation. For each record, we concatenate the canonical representation, monomer composition, linkage, branching, modification, molecular-weight field, source database, and organism source into a lightweight feature string. This string is vectorized with a count-based vocabulary and fed into a one-vs-rest logistic regression classifier. In the revised evaluation protocol, this tuned sparse model is treated as the main anchor rather than as a disposable baseline to be surpassed at all costs.

Stage 2 tuning shows that this baseline is deterministic on the fixed split and benefits materially from reduced regularization and balanced class weighting. The strongest tuned configuration uses `C = 16.0` and `class_weight = balanced`, and serves as the main comparison anchor for the rest of the paper.

3.3 Polysaccharide-Specific Structural Representation

A remaining challenge is that the tuned sparse baseline treats many polysaccharide-specific cues as raw text rather than as normalized signals. Natural polysaccharide records repeatedly expose three high-value cues that are only weakly standardized in the raw text: coarse molecular-weight scale, whether branching information is available, and which residue families are present. These cues are common enough to be extracted reliably, but structured enough to be diluted when left entirely to generic tokenization.

To address this mismatch, we derive a compact token set from the existing structured fields. First, we parse molecular-weight fields into coarse buckets. Second, we encode whether branching information is available. Third, we derive residue-family tokens from monomer composition, linkage, branching, and canonical structural strings, producing markers such as glucose-, galactose-, arabinose-, mannose-, rhamnose-, xylose-, and uronic-acid-related residue presence, together with a residue-diversity signal. These tokens are appended to the tuned baseline feature text and processed by the same logistic classifier.

This design is intentionally modest. It does not attempt to reconstruct a complete carbohydrate graph

from partially specified text, and it does not assume explicit evidence-level annotations that the current benchmark does not contain. Instead, it encodes the most reliable structural regularities that recur in public polysaccharide records and that can be defended by controlled ablation.

3.4 From Poly-feature-only to Poly-core v1

Our first Stage 3 representation was intentionally broader and included evidence-proxy features, sample weighting by structural completeness, source-kingdom tokens, modification tokens, and composition-count tokens. This broader version produced a small gain over the tuned logistic baseline, but Stage 4 ablation revealed that the useful signal was concentrated in a smaller subset of components.

The final method, `poly-core v1`, therefore keeps only the three ablation-supported families: molecular-weight buckets, branching tokens, and residue-set tokens. It removes weak evidence-proxy features, sample weighting, source-kingdom context, modification features, and composition-count tokens. This simplification improves the final result and keeps the method aligned with the evidence actually supported by the experiments.

A full artifact checklist, benchmark-statistics note, split summary, and token-level reproducibility note are prepared separately as supplementary material so that the main paper can stay focused on the benchmark and method claim.

4 Results and Discussion

4.1 Experimental Setup

The main supervised benchmark is `dataset_publishable_supervised_v1`, which contains 4,121 DoLPHiN-derived records and 18 canonical function labels. We evaluate under a fixed random split protocol and report macro-F1 as the primary metric because the label distribution is highly imbalanced. We also report exact match ratio as a stricter secondary metric. Because the label space is weakly supervised and positive-unlabeled in character, these metrics should be interpreted as comparative ranking tools under a fixed protocol rather than as direct estimates of absolute biological truth. In particular, exact match is highly sensitive to over- and under-predicting the full label set for each record, whereas macro-F1 better reflects whether rare labels are recovered at all; the two metrics therefore need not rank sparse baselines in the same order.

We compare trivial, classical, sequence, graph, and additional simple sparse baselines, including a majority predictor, untuned logistic regression, random forest, TF-IDF logistic regression, linear SVM, a lightweight

Table 1: Main benchmark statistics for the filtered DoLPHiN-derived supervised dataset. Missing-rate values are computed after filtering into the 4,121-record benchmark.

Statistic	Value
Records	4,121
Labels retained	18
Average labels per record	1.56
Median labels per record	1
Canonical representation missing rate	0.0%
Monomer composition missing rate	2.4%
Linkage missing rate	80.9%
Branching missing rate	0.0%
Modification missing rate	100.0%
MW/range missing rate	26.6%
Organism-source missing rate	0.0%
DOI missing rate	0.1%
Retained evidence type	unknown only

sequence n-gram model, a lightweight transformer baseline implemented with native PyTorch modules, and a graph GCN baseline. After Stage 2 tuning, logistic regression with `C = 16.0` and balanced class weighting becomes the main anchor. All Stage 2–4 runs are evaluated on the same fixed split, and the reported multi-seed runs are deterministic in this setting, so the final comparison reflects controlled representation differences rather than optimization variance.

The benchmark split contains 2,472 training records, 824 validation records, and 825 test records. The benchmark is generated by retaining only DoLPHiN-derived supervision, removing `unknown` labels, and keeping labels with global frequency of at least 20. This fixed split is intentionally reused across Stage 2, Stage 3, and Stage 4 so that each later-stage comparison isolates representation or configuration changes rather than split-induced variance.

Implementation details. The tuned logistic anchor uses count-vectorized feature text with a token pattern that preserves alphanumeric, equality, and hyphen-delimited tokens, `min_df = 1`, no vocabulary cap, `C = 16.0`, `class_weight = balanced`, and one-vs-rest logistic regression with the `liblinear` solver. On the fixed training split, this yields a vocabulary of 6,255 tokens. The final `poly-core v1` method keeps the same classifier and augments the input text with only three structured token families: molecular-weight buckets (`<10 kDa`, `10--100 kDa`, `100 kDa--1 MDa`, $\geq$`1 MDa`, or unknown), branching-presence tokens, and residue-set tokens derived from the canonical structure, monomer composition, linkage, and branching fields. It does not use evidence-proxy features, sample weighting, source-kingdom features, modification tokens, or coarse composition-count tokens. This design choice follows directly from the Stage 3 and Stage 4 ablation results.

4.2 Main Results

Table 2 and Figure 1 report the random-split comparison. To avoid an unfair reading of the table, we separate it conceptually into two parts: reproduced baseline families and the tuned logistic anchor plus proposed methods. We did not run a full Stage 2 hyperparameter search for every baseline family, so the tuned logistic result should be interpreted as the strongest stable anchor rather than as proof that all other model families are fully optimized. The reproduced baselines should therefore be read as breadth-of-family references, whereas the tuned logistic row is the paper's explicit optimization anchor. Based on these results, we make four observations:

- **The benchmark is nontrivial.** The majority baseline reaches only 0.0397 macro-F1, while untuned logistic regression improves to 0.1580. This shows that the label space is not solved by prior frequency alone, but that even a sparse textual view of structure already contains predictive signal.
- **Tuning matters more than early architectural novelty.** Stage 2 increases the logistic anchor from 0.1580 to 0.2610 macro-F1, largely through weaker regularization and balanced class weighting. This justifies using tuned logistic regression as the main anchor for method development.
- **Additional sparse baselines matter, but they change the ranking by metric.** TF-IDF logistic regression and linear SVM do not beat the tuned count-based logistic anchor on macro-F1, but they achieve the strongest exact-match scores among the nontrivial sparse baselines. This confirms that the benchmark supports multiple competitive sparse references and that metric choice materially changes which simple model looks strongest.
- **The final representation gives only a modest random-split gain.** `poly-core v1` improves macro-F1 to **0.2678**, exceeding the tuned logistic anchor at 0.2610. However, this gain is small, its paired bootstrap confidence interval crosses zero, and it does not persist under the stricter grouped-split setting introduced below. We therefore treat it as a promising but split-sensitive result rather than as a decisive model win. Its exact match is not the best value in the table, which reinforces that our claim is specifically about balanced multi-label recovery under macro-F1 rather than about optimizing the strictest all-label metric.

4.3 Grouped-Split and Bootstrap Reassessment

To address the risk that a fixed random split overestimates generalization, we added a deterministic DOI-grouped split in which all records sharing the same DOI are kept in the same partition. This split removes a major source of near-duplicate leakage through paper-specific phrasing and reporting patterns. We also evaluate the tuned logistic anchor and `poly-core v1` under a development protocol that uses validation for

Table 2: Main comparison on `publishable_supervised_v1`. Upper block: reproduced baseline families under a shared fixed protocol without exhaustive family-specific tuning. Lower block: the explicitly tuned logistic anchor and the proposed method variants. Note that macro-F1 and exact match emphasize different failure modes in this weakly supervised multi-label setting, so the strongest model need not be the same under both metrics. **Red**: best, blue: second best.

Method	Macro-F1 ↑	Exact Match ↑
Majority	0.0397	0.2776
Logistic (untuned)	0.1580	0.2848
Random Forest	0.1752	**0.3127**
TF-IDF + Logistic	0.2514	0.2897
Linear SVM	0.2521	0.2921
Sequence n-gram	0.2035	0.2824
Sequence Transformer	0.0397	0.2776
Graph GCN	0.1941	0.1721
Logistic (tuned)	0.2610	0.2606
Poly-feature-only v1	0.2654	0.2582
Poly-core v1	**0.2678**	0.2570

method selection and reports test only once for the final frozen comparison.

Table 3 summarizes the revised picture. Under the random split, `poly-core v1` still shows a small positive delta over the tuned logistic anchor on the test partition. However, paired bootstrap analysis yields a 95% confidence interval of $[-0.0115, 0.0260]$, so the random-split gain is not statistically decisive. Under the DOI-grouped split, the direction reverses: tuned logistic reaches 0.1250 macro-F1 on the grouped test partition, whereas `poly-core v1` reaches 0.1140. The corresponding bootstrap interval for the difference is $[-0.0254, 0.0020]$. In other words, the current feature augmentation is informative for ablation and representation analysis, but not yet robust enough to support a strong grouped-generalization claim.

Per-label analysis reinforces the same conclusion. On the random split, the aggregate macro-F1 gain is concentrated in a small subset of labels such as *antimicrobial*, *neuroprotective*, and *organ-protective* prediction rather than being broadly uniform. Under the DOI-grouped split, some labels degrade sharply, most notably *antiaging*. We therefore treat the feature augmentation as a label-sensitive and split-sensitive modification, not as a universally stronger classifier. The additional TF-IDF and SVM baselines point in the same direction: simple sparse alternatives can improve exact match without improving macro-F1, so metric trade-offs must be read explicitly rather than collapsed into a single notion of "best".

Qualitative case studies show the same pattern at the record level: `poly-core v1` can recover missing labels or prune false positives on selected examples, but it also introduces grouped-split failures where the tuned logistic anchor remains correct. This makes the method more useful as a probe for feature relevance than as a settled replacement for the sparse anchor.



Figure 1: Main comparison on the `publishable_supervised_v1` benchmark. The strongest untuned baseline is the sequence n-gram model, the strongest tuned anchor is logistic regression, and the final `poly-core v1` method gives the best macro-F1 under the fixed random-split protocol.

Table 3: Revised robustness summary for the tuned logistic anchor and `poly-core v1`. Validation is used for development; test is used once for final reporting. Reported confidence intervals are paired bootstrap intervals for the macro-F1 difference `poly-core v1` minus tuned logistic on the test partition.

Split	Logistic val	Poly-core val	Logistic test	Poly-core test
Random	0.3143	0.3152	0.2610	0.2678
DOI-grouped	0.1189	0.1218	**0.1250**	0.1140

Test comparison	Δ Macro-F1	95% CI
Random split	+0.0068	[-0.0115, 0.0260]
DOI-grouped split	-0.0110	[-0.0254, 0.0020]

4.4 Stage-wise Method Development

The experiment pipeline clarifies how the final result emerged. Stage 1 established executable baselines across classical, sequence, and graph families. Stage 2 showed that tuned logistic regression was the strongest stable anchor. Stage 3 then tested whether a broad evidence-aware extension could improve over that anchor. It could not. The full evidence-aware variant underperformed the tuned logistic baseline, and its sub-variants revealed that weak evidence proxies and broad token augmentation were not the source of gain.

This negative result is informative and should be read as a scoped failure case rather than as a discarded implementation detail. The current supervised benchmark does not contain meaningful variation in explicit evidence-level annotation; all retained records carry `evidence_type = unknown`. Therefore, a strong evidence-aware claim would be technically weak. The effective gain instead comes from a core structural

Table 4: Stage 3 method evolution under the same tuned logistic backbone. This table makes the failure-to-success trajectory explicit rather than leaving it implicit in the text.

Configuration	Macro-F1 ↑
Tuned logistic anchor	0.2610
Evidence-aware v1 (full)	0.2579
Weight-only variant	0.2595
Feature-only variant (poly + evidence tokens)	0.2582
Poly-feature-only v1	0.2654
Poly-core v1	**0.2678**

Table 5: Ablation study around `poly-feature-only v1` (reference macro-F1 = 0.2654). Positive deltas indicate improvement after removing a component.

Ablation	Macro-F1 ↑	Δ vs. Reference
Remove MW	0.2461	-0.0193
Remove branching	0.2598	-0.0056
Remove modification	0.2619	-0.0035
Remove residue	0.2533	-0.0121
Remove source kingdom	0.2621	-0.0033
Remove composition terms	0.2669	**+0.0015**
Poly-core v1	**0.2678**	+0.0024

representation that better matches the reporting style of natural polysaccharides, although the grouped-split reassessment shows that this gain is not yet robust enough to displace the tuned sparse anchor as the strongest overall conclusion.

4.5 Ablation Study

Table 5 and Figure 2 summarize the key ablations around the initial Stage 3 winner `poly-feature-only v1`. Based on these results, we make three observations:

- **Molecular-weight buckets are the strongest component.** Removing MW tokens reduces macro-F1 from 0.2654 to 0.2461, the largest drop among all ablations.
- **Residue-set tokens are also critical.** Removing residue tokens reduces macro-F1 to 0.2533, confirming that coarse residue-family composition provides important function-related signal.
- **Not every engineered feature helps.** Branching remains a supported positive component, but modification and source-kingdom tokens are weak. Removing composition-count tokens actually improves performance, which allows us to simplify the method into the final `poly-core v1` configuration.



Figure 2: Component ablation around `poly-feature-only v1`. Molecular-weight and residue features are the strongest positive contributors, while the coarse composition-count feature family is slightly harmful and is removed in the final method.

4.6 Stress-test and Scope Boundary

We also built a merged `DoLPHiN + CSDB` pipeline and ran leave-one-source-out experiments as an engineering stress test. This pipeline is executable and useful for future work, but it should not be overinterpreted in the current paper. The present CSDB slice is structurally valuable but not label-aligned with the main supervised task, and training on it does not provide a fair biological test of function prediction generalization.

We therefore treat cross-source evaluation as a forward-looking stress-test result rather than as the main scientific evidence. This scope boundary keeps the paper centered on a benchmark claim that is genuinely supported by the available data.

5 Conclusions

We presented a reproducible benchmark and modeling pipeline for multi-label structure–function prediction of natural polysaccharides. Starting from public DoLPHiN ingestion and a filtered supervised benchmark, we reproduced a range of baseline families and established a tuned logistic regression anchor that is stronger than a naive reading of the problem might suggest. We then showed that a compact polysaccharide-specific structural representation can produce a modest random-split gain, while controlled ablations demonstrate that molecular-weight, residue-set, and branching features drive that gain.

The main scientific insight is narrower than our original Stage 3 hypothesis. On the current benchmark, the decisive contribution is not a universally stronger model, but a clearer understanding of what the bench-

mark supports: a strong sparse anchor, a split-sensitive structured augmentation, and a set of feature-level findings that remain interpretable under ablation. This narrower claim is also the more credible one: it identifies which signals are useful now, and avoids claiming more than the present data can support.

Limitation. Our benchmark is intentionally conservative and single-source in its main supervised setting. Although we implemented a merged `DoLPHiN + CSDB` pipeline, the currently ingested CSDB slice is not label-aligned enough to support a strong cross-source supervised claim. In addition, explicit evidence-level annotations are largely unavailable in the retained supervised data, which limits the strength of any current evidence-aware modeling result. More fundamentally, the benchmark labels are literature-derived positives with unknown negatives, so the task is closer to weakly supervised or positive-unlabeled multi-label prediction than to fully observed classification. The revised DOI-grouped split also shows that the current feature augmentation does not yet deliver robust grouped generalization, even though it remains informative in random-split ablations. Future work should therefore focus on better evidence annotation, stronger source alignment, more chemically faithful cross-database structural normalization, PU-aware evaluation and learning protocols, and grouped generalization tests rather than on scaling model size alone.

6 Declarations

Availability of data and materials. The benchmark construction scripts, split definitions, baseline implementations, and supplementary benchmark statistics used in this study are available in the project repository and associated submission package. The main manuscript results are based on the DoLPHiN-derived filtered benchmark artifact `dataset_publishable_supervised_v1` together with the fixed random and DOI-grouped split files described in the supplementary reproducibility materials. Replace this paragraph with the final repository URL and persistent identifiers at submission time.

Competing interests. The authors declare that they have no competing interests.

Funding. [Insert funding information here. If none: Not applicable.]

Authors' contributions. [AA] designed the study. [AA] and [BB] implemented the benchmark and experiments. [AA], [BB], and [CC] analyzed the results. [AA] drafted the manuscript. All authors revised the manuscript and approved the final version.

Acknowledgements. [Insert acknowledgements here. If none: Not applicable.]



Figure 3: Overview of the proposed benchmark construction and `poly-core v1` pipeline.

Authors' information. [Optional author-information paragraph, or Not applicable.]

Reproducibility note. To reduce ambiguity between the benchmark claim and the engineering scaffold, we provide a supplementary reproducibility package that lists the exact benchmark artifact names, split statistics, tuned-anchor configuration, and final token-family definition used for `poly-core v1`.

References

[1] Daniel Bojar, Rani K. Powers, Diogo M. Camacho, and James J. Collins. Deep-learning resources for studying glycan-mediated host-microbe interactions. *Cell Host & Microbe*, 29(1):132–144.e3, 2021.

[2] Rebekka Burkholz, John Quackenbush, and Daniel Bojar. Using graph convolutional neural networks to learn a representation for glycans. *Cell Reports*, 35(11):109251, 2021.

[3] Akihiro Fujita, Nobuyuki P. Aoki, Daisuke Shinmachi, Masaaki Matsubara, Shinichiro Tsuchiya, Masaaki Shiota, Tamiko Ono, Issaku Yamada, and Kiyoko F. Aoki-Kinoshita. The international glycan repository glytoucan version 3.0. *Nucleic Acids Research*, 49(D1):D1529–D1533, 2021.

[4] Roman Joeres, Daniel Bojar, and Olga V. Kalinina. Glyles: Grammar-based parsing of glycans from iupac-condensed to smiles. *Journal of Cheminformatics*, 15:37, 2023.

[5] Jon Lundstrøm, Emma Korhonen, Frédérique Lisacek, and Daniel Bojar. Lectinoracle: A generalizable deep learning model for lectin–glycan binding prediction. *Advanced Science*, 9(1):e2103807, 2022.

[6] Luc Thomès, Rebekka Burkholz, and Daniel Bojar. Glycowork: A python package for glycan data science and machine learning. *Glycobiology*, 31(10):1240–1244, 2021.

[7] Michael Tiemeyer, Kazuhiro Aoki, James Paulson, Richard D. Cummings, William S. York, Niclas G. Karlsson, Frederique Lisacek, Nicolle H. Packer, Matthew P. Campbell, Nobuyuki P. Aoki, et al. Glytoucan: An accessible glycan structure repository. *Glycobiology*, 27(10):915–919, 2017.

[8] Philip V. Toukach and Ksenia S. Egorova. Source files of the carbohydrate structure database: The way to sophisticated analysis of natural glycans. *Scientific Data*, 9:131, 2022.

[9] Yefu Xin, Yongling Cao, Shuheng Yang, Junhao Hu, Miao Tian, Jian Dai, Jing Shi, Bingcong Yu, Nike Gu, Xiangxu Hu, Rui Zhu, Qianni Duan, Yu Tian, and Hualin Wang. Dolphin: A proposed architecture and technical implementation of a database of structural and functional properties of natural polysaccharides with health benefits. *Food Chemistry*, 495:146534, 2025.