# **Jakarta EE**

**ENTERPRISE JAVA** 

Hany ahmed



Set of servers on the Internet that support HTTP

Resources are identified by URLs and usually accessed through hyper linked documents called HTML

HTTP Protocol is being used by a web client (Usually a web browser) to request documents from a web server

#### HTML

```
<!DOCTYPE html>
<html>
     <head>
          <meta http-equiv="Content-Type" content="text/html; charset=utf-8"/>
          <title>Hello to my page</title>
          <link href="styles.css" rel="stylesheet" type="text/css">
          <script src="script.js" type="application/javascript" />
     </head>
     <body>
          <h1>Hello!</h1>
          <img src="home.gif" alt="Home" />
          <!-- Need to add more content here -->
          Welcome to my site
          <a href="https://www.google.org">Search on google</a>
     </body>
</html>
```

#### **HTML forms**

```
<form action="registerAction" method="POST">
             <input type="text" name="name"><br>
    name
    Password <input type="password" name="pass">
    Gender
        <input type="radio" name="gender" value="male">Male
        <input type="radio" name="gender" value="female">Female
    Languages
        <input type="checkbox" name="language" value="ar">Arabic
        <input type="checkbox" name="language" value="en">English
    City
        <select name="city">
             <option value="1">Cairo</option>
             <option value="2">Giza</option>
        </select>
    <textarea name="details"></textarea><br />
    <input type="submit" value="Register">
 </form>
```

# Coding an enterprise application

Listening for incoming requests

Request routing


Request/Response processing

Multithreading


State management

Resource pooling

#### **EE Model**



# **EE Components**



# **Workshop: Running the server**


Download tomcat

Start it using bin/startup.sh

Stopping it using bin/shutdown.sh

View logs: logs/catalina.out

#### Servlet




# **HttpServlet Example**

```
doGet(HttpServletRequest request, HttpServletResponse response){
    response.setContentType("text/html");
   PrintWriter out = response.getWriter();
   out.println("<html>");
   out.println("<head>");
   out.println("<title>Hello</title>");
   out.println("</head>");
   out.println("<body>");
   out.println("<h1>Hello world</h1>");
   out.println("</body>");
   out.println("</html>");
```

# Workshop: Servlet

```
Create new maven project
Add dependency for jakartaee-api
          <dependency>
               <groupId>jakarta.platform</groupId>
               <artifactId>jakarta.jakartaee-api</artifactId>
               <version>8.0.0
               <scope>provided</scope>
          </dependency>
Create your first Servlet
package the project into war
Deploy it to tomcat
```

# Web directory structure



### Handle request data

```
URL guery parameters or form data
action?name=ali&interest=reading&interest=football
Get parameter value
String name = request.getParameter("name");
String[] arr = request.getParameterValues("interest");
Get all parameters
Map<String, String[]> map = request.getParameterMap();
Enumeration<String> en = request.getParameterNames();
```

### **Request Dispatcher**

```
From request
// absolute
request.getRequestDispatcher("/welcome");
// relative
request.getRequestDispatcher("welcome");
```

forward: to forward the request to another servlet and discard the current

include: to pass request and include response from another servlet

#### Request attributes

```
Data held by HttpServletRequest object
// set
request.setAttribute("user", "ahmed");
// get
String user = (String)
request.getAttribute("user");
// remove
request.removeAttribute("user");
// get all attribute names
Enumeration<String> en =
request.getAttributeNames();
```

#### **Cookies**

```
// add cookie
Cookie cookie = new Cookie ("user", "ahmed");
cookie.setMaxAge(60*60*24*30);
response.addCookie(cookie);
// Get cookie
Cookie[] cookies = request.getCookies();
   if (cookies != null)
      for (int i = 0; i < cookies.length; i++)</pre>
         Cookie cookie = cookies[i];
         if(cookieName.equals(cookie.getName()))
```

#### **Cookies notes**


All cookies are sent by default by the browser at every request

Sending a cookie with the same name with a new value would override the old cookie.

Updating a cookie doesn't take any effect until It's sent with the headers.

Setting the maximum age to zero or negative would result in invalidating the cookie.

### Session




# **Scopes**

request

session

application (ServletContext)

#### **Filter**



#### **Documents**

under/webapp

- static content (html, js, cs, jpg ...)
- dynamic content (jsp)

#### **JSP**

Document files like HTML

Accepts dynamic parts like scriplets, expressions

```
Today's date: <%= new java.util.Date()%> with access to implicit objects like: request, response, session, application, out
```

Accepts placeholders with custom expressions (EL)

```
${param.name} ${param["name"]}
${header.Host} ${requestScope.attr}
${sessionScope.attr} ${applicationScope.attr}
```

#### JSP vs Servlet

```
<html>
                                                             out.write("<html>\r\n ");
<head><title>First JSP</title></head>
                                                             double num = Math.random():
<body>
                                                             if (num > 0.95) {
<%
                                                              out.write("<h2>You will have a luck day!");
 double num = Math.random():
                                                              out.write("</h2>(");
 if (num > 0.95) {
                                                              out.print( num );
%>
                                                              out.write(")\r\n");
  <h2>You'll have a luck day!</h2>(<%= num %>)
                                                             } else {
 <%
                                                              out.write("\r\n "):
 } else {
                                                              out.write("<h2>Well, life goes on ... ");
%>
                                                              out.write("</h2>(");
  <h2>Well, life goes on ... </h2>(<%= num %>)
                                                              out.print( num );
<%
                                                              out.write(")\r\n ");
%>
                                                             out.write("<a href=\"");
<a href="<%= request.getRequestURI() %>"><h3>Try
                                                             out.print( request.getRequestURI() );
Again</h3></a>
                                                             out.write("\">"):
</body>
                                                             out.write("<h3>Try Again</h3></a>\r\n");
</html>
                                                             out.write("</html>\r\n");
```

# MVC

