HW/SW Co-Design - Project Report

Shay Midginski 206391724
Nitzan Behar 209825066

Benchmark: go

Part I - Overview:

Description of the benchmark:

1. This benchmark measures the performance of running Monte Carlo Tree Search (MCTS) with the UCT (Upper Confidence bounds applied to Trees) selection policy.
2. Monte Carlo tree search (MCTS) is a heuristic tree search algorithm for decision processes. It is used in multiple board games like Chess, Checkers, Backgammon and Go.
3. At its core, MCTS solves one problem: given a huge decision tree that's too large to search exhaustively, decide which move maximizes long-run win probability, using only random simulation as a way to estimate the value of positions.
4. The general MCTS algorithm loops over four stage:
   (a) **Selection:** descend the existing tree from the root, picking a child at each level according to the UCT formula, until you reach a node with unexplored moves or no children.
   (b) **Expansion:** add one new child node for an unvisited move.
   (c) **Simulation:** play the rest of the game out with uniformly random legal moves.
   (d) **Backpropagation (Rollout):** propagate the simulated game's win/loss result back up the path taken, updating each node's statistics.

   We can see those stages in this drawing (taken from Wikipedia). Circles indicate states and squares indicate actions:




Figure 1: The four stages of the Monte Carlo tree search algorithm

5. In the current benchmark, the MCTS algorithm is implemented on a game of Go, played on a 9×9 board (versus the traditional 19×19). Because Go has no known closed-form evaluation function and an enormous branching factor, its engines are commonly built around MCTS.



Figure 2: Go game board

6. Go is a good workload for measuring performance because it's algorithmically dense rather than I/O or library-bound. It stresses object attribute access, function-call overhead, list/set manipulation, and recursion, all core CPython interpreter costs.

Libraries:

1. The two libraries used in the benchmark are **math** and **random**.

2. **random** is a Python standard library that is used for all randomness in the benchmark.
3. **math** is also a Python standard library that is used only in the UTC formula (log and sqrt).
4. Everything else is written in plain Python using only builtin types.

Data structures:

1. Five data structures define the game, each solving a specific performance problem:
   (a) **Board:** The board grid. that holds **Board.squares**, a flat Python list of SIZE*SIZE = 81 **Square** objects. Each Square pre-computes and caches its neighbours list once at board construction, so adjacency lookups during search are O(1) list access, never recomputed.
   (b) **Stone groups:** union-find with path compression. Instead of maintaining explicit group objects, each **Square** doubles as a union-find node where *self.reference* is the parent pointer, *find()* is the $O\big(log^*(n)\big)$ find function with path compression that recursively follows reference until it hits a self-referencing root, and rewrites *self.reference* to point directly at that root on the way back and *ledges* as liberty count that is stored only on the root of each group (payload). *move()* performs the union step when placing a stone next to a friendly group and merges liberty counts.
   (c) **Empty positions:** swap-to-end array with reverse index. **EmptySet** needs fast random sampling and fast removal of arbitrary elements so it uses two parallel arrays - *empties* (a list of empty positions at any order) and *empty_ pos* (reverse index: empty_pos[pos] = that position's index within empties). *remove(pos)* swaps the target element with the last element and pops in O(1) instead of O(n).
   (d) **ZobristHash:** Position repetition detection set that keeps a single running integer hash updated incrementally on every stone placement/removal rather than rehashing the whole board. A Python set (hash_set) stores every board-hash ever seen in the game, so duplicate-position detection is an O(1) average-case hash in hash_set check.
   (e) **UCTNode:** The search tree. UCTNode represents the MCTS tree with the following properties:
      i. No explicit list of children. Instead, *pos_ child* is a fixed-size array of length, initialized to *None*, where *pos_ child[pos]* is the child node reached by playing at board position pos. This gives O(1) lookup/insertion of a child by move at the cost of allocating an 81-slot array per node (acceptable since the board is small and fixed-size).
      ii. Parent pointers, not child lists, drive backpropagation. Each node stores parent, and *update_ path()* walks a path list, built during *play()*'s descent, to backprop so the path is a plain Python list acting as a stack of visited nodes for that single simulation.
      iii. Unexplored moves as a mutable list, consumed via swap-pop. *unexplored* is a list of valid but not yet tried positions. *select()* picks a random index and removes it with the same swap and pop trick like **EmptySet** that gives O(1) removal.
      iv. A cached best child pointer instead of recomputing on read. *bestchild* holds the current UCT-argmax child, refreshed after every backprop step that touches that subtree, so *select()*'s exploitation branch is an O(1) pointer follow instead of an O(children) scan through *pos_ child* every time a node is visited during selection. The O(children) scan (*best_ child()*) only runs once per backprop, not once per selection descent.

   The tree is a sparse, lazily-grown structure. The root starts with zero children and gains exactly one new node per simulation (the expansion step), so after 200 simulations there are at most 200 nodes total, each an 81-slot array mostly full of None. The whole tree is discarded and rebuilt from scratch on every call to *computer_ move()* with no persistence across moves.

Algorithm:

bm_go executes 2 well-known algorithms: Monte Carlo Tree Search (MCTS) and Upper Confidence bounds (UCT).

Instead of thoroughly analyzing every possible future state, MCTS treats decision-making as a recursive "multi-armed bandit" problem. It builds an asymmetric search tree, guided entirely by statistics gathered from random game simulations, balancing the exploration of new moves with the exploitation of known successful strategies (using

the UCT policy) to estimate long-term win probabilities.

In this bm_go (a 9×9 Go game), the algorithm evaluates choices by running a budget of 200 iterations per turn. A single iteration is managed by UCTNode.play(), which cycles through four specific phases:

1. Selection: The algorithm navigates from the root down the existing tree using select(). If there are unexplored moves - it expands the tree, otherwise - it follows the cached bestchild (regarding UCT policy).
2. Expansion: Handled inside play(), when select() returns a move, a new UCTNode child is created and linked into the pos_child list. This tree growth happens at most once per iteration.
3. Simulation (Playout): Starting from the newly added node, random_playout() plays the rest of the game to completion using uniformly random legal moves via board.random_move() until it reaches a terminal state or hits the hard limit of MAXMOVES = 243.
4. Backpropagation: Update_path() walks the path list gathered during selection. It flips the color at each step (since each tree level alternates the player to move), updates the wins and losses statistics for every node involved, and refreshes the parent's cached bestchild.

Once all 200 iterations are complete, the engine finalizes its decision via best_visited(). It selects the root's child node with the highest total visit count, relying on visits rather than pure win rate as the most statistically stable indicator of the best move.

UCT is the specific decision-making policy used during the selection phase of the MCTS algorithm. Its primary purpose is to determine which child node the search should descend into next. It does it by mathematically balancing the need to capitalize on known good moves with the need to investigate unexplored ones - UCT ensures that, given enough time (simulations), the algorithm will always converge on the optimal move without requiring any pre-programmed knowledge of the game.

The algorithm evaluates each potential child node using a specific formula implemented in score() and its optimized twin best_child(). It weighs two competing factors:

1. Exploitation (Wins/Visits): This term represents the empirical win rate of a move. It naturally steers the algorithm toward paths that have already proven successful in previous simulations.
2. Exploration $\left(C \cdot \sqrt{\frac{ln(parent_visits)}{visits}}\right)$: This term ensures that lesser-played moves are not abandoned due to early bad luck. It artificially inflates the score of a child node if it hasn't been visited recently, pulling the search back to it periodically. The exploration score grows slowly as the parent is visited, but shrinks as the specific child gets more visits.

The veriable C is a balancing constant that dictates the engine's behavior. A lower C makes the AI trust its current win rates more (favoring exploitation), while a higher C forces it to test a wider variety of moves (favoring exploration).

Part II - Initial Analysis:

Basic benchmark test run:

```
pyperformance run -b go -o go_basic_results.json
```

1. This command executed 20 independent measurement processes of go benchmark (and one calibration run).
2. The results were consistent, with a mean runtime of 213 ms, a median of 212 ms, and a standard deviation of only 7.6 ms seconds.
3. This low variance indicates a stable testing environment.
4. This measurment will act as our base in the optimization process.

Performance analysis:

1. We have ran perf record on the entire pyperformance run using:

```
sudo perf record -F 99 -g --call-graph dwarf -e cpu-clock -- python3.12-dbg -m
pyperformance run --bench go
sudo perf report --stdio --no-inline > go_perf_report_312.txt
```

2. Let's sort the results by %self using:

```
grep "^    [0-9]" go_perf_report_312.txt | sort -k2 -rn
```

3. The results show us 4 dominant function:

```
96.23%    48.94%    python    python3.12d    [.] _PyEval_EvalFrameDefault
15.69%     1.42%    python    python3.12d    [.] _Py_Dealloc
34.33%     0.43%    python    python3.12d    [.] binary_op1
18.50%     0.37%    python    python3.12d    [.]
_PyObject_VectorcallTstate.lto_priv.2
```

   (a) The first column is %children and the second column is %self.
   (b) Besides the fisrt line, every other function has %self $\leqslant$ 0.2%.

4. **_PyEval_EvalFrameDefault** is CPython's core bytecode interpreter. Every Python operation run through this function. This is why its %Children = 96.23%. This interpreter loop cost is a fixed overhead for almost every Python run, so we don't see a reason to dig into that optimization path.
5. The other 3 calls here are really insignificant compared to the CPython interpreter loop.
6. **_Py_Dealloc** is called when an object's reference count hits zero. It runs the type's deallocator to free the object's memory. Heavy time here means the workload is creating and destroying a lot of short-lived objects like temporary ints, floats, tuples from arithmetic/loops.
7. **binary_op1** is CPython's dispatcher for binary operators (+, -, *) in the bytecode interpreter. High time here means the code spends a lot of time doing arithmetic between Python objects and each operation pays type-dispatch overhead rather than being a raw machine op like it would be in C.
8. **_PyObject_VectorcallTstate** is a wrapper around the vectorcall mechanism used for the general object-call path (functions, bound methods, callables, etc.).
9. Overall, this top-level report tells us that the cost is intrinsic to the interpreter loop, not external. Almost none of the runtime is lost to something outside the interpreter (I/O, a slow C library, syscalls).
10. Therefore, we will run another perf record against a single invocation of bm_go instead of the full pyperformance run wrapper. We will enable actual Python function resolution using CPython 3.12 added built-in perf support, PYTHONPERFSUPPORT=1, that injects per-call trampoline frames so perf can resolve and display real Python function names:

```
export PYTHONPERFSUPPORT=1
```

```
sudo -E perf record -F 99 -g --call-graph dwarf -e cpu-clock -o perf_single.data -
- python3.12-dbg /usr/local/lib/python3.12/dist-packages/pyperformance/data-
files/benchmarks/bm_go/run_benchmark.py --worker -l1 -w1 -n3
sudo perf report -g -i perf_single.data --no-inline > go_perf_report_312_single.txt
```

11. We sort the results by %self using:

```
grep "^    [0-9]" go_perf_report_312_single.txt | sort -k2 -rn
```

12. Here we can see that the **Vectorcall** function family are much dominant than before, and higher than the deallocation or binary operations:

```
97.36%    54.13%    python3.12-dbg    python3.12d    [.] _PyEval_EvalFrameDefault
17.16%     1.98%    python3.12-dbg    python3.12d    [.]
_PyObject_VectorcallTstate.lto_priv.2
18.15%     1.65%    python3.12-dbg   python3.12d     [.] PyObject_Vectorcall
11.22%     1.65%    python3.12-dbg   python3.12d     [.] _PyFunction_Vectorcall
```

13. That points the investigation at "what makes each call/attribute-access expensive" not at arithmetic operations.
14. We will also sort the Python symbols by %children, to see which Python function is invoking most of the work, using:

```
grep "py::" go_perf_report_312_single.txt | sort -k1 -rn
```

15. The results here show us who is the function the drives most of the work:

```
24.75%     0.33%     python3.12-dbg     [JIT] tid 2158     [.]
py::Square.find:/usr/local/lib/python3.12/dist-packages/pyperformance/data-
files/benchmarks/bm_go/run_benchmark.py
18.81%     0.00%     python3.12-dbg     [JIT] tid 2158     [.]
py::Board.useful:/usr/local/lib/python3.12/dist-packages/pyperformance/data-
files/benchmarks/bm_go/run_benchmark.py
 7.59%     0.00%     python3.12-dbg     [JIT] tid 2158     [.]
py::Square.move:/usr/local/lib/python3.12/dist-packages/pyperformance/data-
files/benchmarks/bm_go/run_benchmark.py
 7.26%     0.00%     python3.12-dbg     [JIT] tid 2158     [.]
py::EmptySet.random_choice:/usr/local/lib/python3.12/dist-
packages/pyperformance/data-files/benchmarks/bm_go/run_benchmark.py
 4.95%     0.00%     python3.12-dbg     [JIT] tid 2158     [.]
py::Square.remove:/usr/local/lib/python3.12/dist-packages/pyperformance/data-
files/benchmarks/bm_go/run_benchmark.py
 4.29%     0.00%     python3.12-dbg     [JIT] tid 2158     [.]
py::ZobristHash.update:/usr/local/lib/python3.12/dist-packages/pyperformance/data-
files/benchmarks/bm_go/run_benchmark.py
```

16. Those resutls show that **Square.find** + **Board.useful** alone are reponsible for 43.56% of total children time, nearly half the entire run is spent inside these two methods and their callees. This tells us that the **Vectorcall** overhead is probably concentrated in those specific methods.
17. If we look inside **Square.find** calls we can see:




Figure 3: Screenshot from go_perf_report_312.txt

18. That is the evidence for the attribute resolution cost inside this function specifically. And the if we look at the code we see why: *find()* is a classic union-find root walk: each Square points at a reference (its parent in the group), and *find()* keeps calling *find()* again on that reference until it reaches a square that references itself (*reference.pos* == *self.pos*, the group's root). So a single call to *find()* can fan out into a chain of nested recursive *find()* calls.
19. The same picture is seen in **Board.useful** but for different reason:




Figure 4: Screenshot from go_perf_report_312.txt

useful() is calling several genuinely different methods in sequence so a single call to *useful()* dispatches to *useful_fast()*, *zobrist.update()*, and *find()* on each of up to 4 neighboring squares

20. The only function that shows us something different is **ZobristHash.update** - the graph shows arithmetic/allocation cost, not attribute lookup, but that is a function that only runs 4.29% of the time:




Figure 5: Screenshot from go_perf_report_312.txt

21. We see the above functions use repeated *self.attr* access. That part of the investigation tells us that indeed, the **Vectorcall** overhead we saw in originated to **Square.find** and **Board.useful**.

Flame graphs:

We have genereated a flame graph for the single process run of the benchmark using:

```
sudo perf script -i perf_single.data --no-inline > go_single.perf
~/FlameGraph/stackcollapse-perf.pl go_single.perf > go_single.folded
~/FlameGraph/flamegraph.pl go_single.folded > go_312_single_flamegraph.svg
```




Figure 6: go_single flame graph

1. The dominant components in this flame graph match the functions already flagged as the bottleneck in the perf output, but give us a different angle:
   (a) **Square.find** is the widest component in the graph. Although we can see in the graph that most of the work in it is done by actual Python code (**_PyEval_EvalFrameDefault**), we can also see the recursion we described earlier.
   (b) We see similar thing for **Board.useful**, large part is actual Python work and we also see a rise in the

call stack.

2. We can see that the Python work done is those functions is the actual logic of the MCTS algorithm.
3. That, in addition to our prior data, narrows our optimization path: we assume that improving the attributes resolution can cause a significant performance improvement.

Profiling data:

1. In this benchmark there's no single dominant CPython function. the hot path is the MCTS random-playout loop (*UCTNode.random_playout* → *Board.move* → *Board.useful* → *Square.find*), which runs thousands of times per game. Square.find (24.75%) and Board.useful (18.81%) alone account for 43.56% of total runtime. Everything outside this loop is negligible by comparison.
2. Looking at those results, we understand that every little improvement to the algorithm will be hard, require correctness proof and will probably not cause significant improvement. On the other hand, customizing the attribute resolution to less-general approch that gives us better performance for that usecase may cause the improvement we are look for.
3. These are the areas we think we can improve performance:
   (a) **Dict-based attribute access on hot instance classes:** *Square.find()* and *Board.useful()* run O(playouts × moves × neighbors) times, and each call reads/writes *self.reference*, *self.pos*, *self.timestamp*, etc.
   Python's default is using **__dict__** which uses string hash + dict probe on every attribute touch. We shall look at ways to remove this hashing cost and the per-instance dict allocation entirely.
   (b) **UCTNode instantiation during tree growth:** every newly explored board position allocates a fresh *UCTNode()* (*node.pos_child[pos]* = *UCTNode()*). Across thousands of playouts this repeats constantly, and each new node also allocated its own **__dict__**, matching the **_Py_Dealloc** frames that we saw in the first perf report.

Part III - Optimizations:

Description of improvements made:

1. We shall improve the three points mentioned in part II:
2. **Dict-based attribute access on hot instance classes:**
   (a) **__dict__** is the regular Python dictionary where an object's instance attributes actually live. When we write *self.board = board*, Python actually does *self.__dict__['board'] = board*. Every instance carries its own dict, created automatically the first time we assign an attribute to it or at construction. This default methis is what gives Python classes their dynamic flexibility. We can add a brand-new attribute to an instance at any time from anywhere, even if we didn't declared it in *__init__*. The cost of that flexibility is that every attribute read/write goes through the same machinery: hash the attribute name string, probe the hash table, follow any collision chain. That's the exact mechanism we saw nested under *Square.find()*. In addition, each instance carries a full dict object with its own hash table and resize logic alongside the actual data, which is typically more overhead than the attributes themselves would need if they were just fixed fields from memory perspective.
   (b) On the other hand, **__slots__** is the opt-out from that default. This tells CPython to allocate a fixed set of slots (attributes) directly in the instance's memory layout. The **__dict__** is not created at all. That way, attribute access becomes a fixed-offset read instead of a hash-table probe. We also lose the ability to add attributes not listed in **__slots__** but we gain faster attribute access, less memory per instance and faster instance creation/deletion. For our usecase, we know in advances all the attributes we need and we can allocate them upfront.

Before: each class didn't had **__slots__**.

After:

```
class Square:
    __slots__ = ('board', 'pos', 'timestamp', 'removestamp', 'zobrist_strings',
                 'neighbours', 'color', 'reference', 'ledges', 'used',
                 'temp_ledges')
    ...

class EmptySet:
    __slots__ = ('board', 'empties', 'empty_pos')
    ...

class ZobristHash:
    __slots__ = ('board', 'hash_set', 'hash')
    ...

class Board:
    __slots__ = ('squares', 'emptyset', 'zobrist', 'color', 'finished',
                 'lastmove', 'history', 'white_dead', 'black_dead')
    ...

class UCTNode:
    __slots__ = ('bestchild', 'pos', 'wins', 'losses', 'pos_child', 'parent',
                 'unexplored')
    ...
```

Why this is faster:

Without **__slots__**, *self.reference* and *self.pos* (read repeatedly inside *find()*, called 24.75% of total

runtime) resolve through *self.__dict__['reference']* that hash the string "reference", probe the table, follow any collision chain. With **__slots__**, each name gets a fixed C-level offset in the instance's memory layout, so *self.reference* becomes a direct offset read, no hashing and no dict machinery.

3. **UCTNode instantiation during tree growth:**
   This is not an individual fix, but a good side effect from our previous fix.
   node.pos_child[pos] = UCTNode() fires on every newly explored board position across thousands of MCTS playouts which is being called far more than *Square/Board* (which are built once and mutated in place). Each construction without **__slots__** pays for two allocations (the object + its **__dict__**). With **__slots__**, only the object itself is allocated, at a fixed, smaller size.
   Cost removed:
   Cuts the malloc/free pair per node down from two allocations to one, directly reducing the **_Py_Dealloc** / **PyObject_Malloc** / **_PyMem_DebugMalloc** overhead visible in the profile. This is a partial fix because the number of UCTNode instances created is unchanged (no pooling/reuse), so the call frequency is the same, but our cost per-instantiation went down.

Part IV - Performance Comperison:

1. We ran perf record on the optimized mdp code using:

```
pyperformance run --manifest MANIFEST -b gooptimized -o go_optimized_results.json
```

   The results were consistent, with a mean runtime of 172 ms, a median of 172 ms, and a standard deviation of only 1.17 ms.

2. Now we will compare the optimized results to the basic run:

```
pyperformance compare go_basic_results.json go_optimized_results.json
```

   The results:

```
### go ###
Mean +- std dev: 213 ms +- 8 ms -> 172 ms +- 1 ms: 1.24x faster
Significant (t=41.09)
```

3. This is clear improvement that achived 19.2% reduction in runtime. That confirms that our bottleneck analysis was correct.

4. We ran another perf record run on the optimized data, using:

```
sudo perf record -F 99 -g --call-graph dwarf -e cpu-clock -- python3.12-dbg -m
pyperformance run --manifest MANIFEST -b gooptimized
sudo perf report --stdio --no-inline > go_perf_report_312_opt.txt
grep "^    [0-9]" go_perf_report_312_opt.txt | sort -k2 -rn
```

   If we sort the results by %self we see:

```
81.25%    12.50%  python3.12-dbg  python3.12d    [.] _PyEval_EvalFrameDefault
10.42%     2.08%  python3.12-dbg  python3.12d    [.] type_new_impl
10.42%     2.08%  python3.12-dbg  python3.12d    [.] r_object
10.42%     2.08%  python3.12-dbg  python3.12d    [.] _PyMem_DebugRawAlloc
10.42%     2.08%  python3.12-dbg  python3.12d    [.] PyObject_Malloc
81.25%     0.00%  python3.12-dbg  python3.12d    [.]
cfunction_vectorcall_FASTCALL_KEYWORDS
81.25%     0.00%  python3.12-dbg  python3.12d    [.]
_PyObject_VectorcallTstate.lto_priv.2
81.25%     0.00%  python3.12-dbg  python3.12d    [.] _PyFunction_Vectorcall
81.25%     0.00%  python3.12-dbg  python3.12d    [.] _PyEval_Vector
79.17%     0.00%  python3.12-dbg  python3.12d    [.] builtin_exec_impl.lto_priv.0
79.17%     0.00%  python3.12-dbg  python3.12d    [.] builtin_exec.lto_priv.0
79.17%     0.00%  python3.12-dbg  python3.12d    [.] _PyVectorcall_Call
```

   We can see the whole **Vectorcall** functions family went down to 0%, and that the %self of **_PyEval_EvalFrameDefault** went down to 12.5%.

Part V - Hardware Acceleration Proposal:

We chose to implement a hardware acceleration on the other benchmark.

Part VI - Conclusion:

In conclusion, the optimizations applied to the bm_go benchmark successfully addressed the overhead of Python's dynamic attribute access and redundant evaluations. By combining targeted algorithmic adjustments such as decoupled path compression and optimized child-node scoring, and with data-structure improvements like __slots__ and localized standard library bindings, the benchmark achieved a 19.3% reduction in overall runtime, improving from 213ms to 172ms, and several of the functions were made negligible.