



CSCI 232

232 Algorithms & Data Structures

LECTURE: 7

J. L. Pach

OUTLINE:

- ✂ Stack
- ✂ Queue
- ✂ Structs Are Value Types
- ✂ Structs as Function Arguments
- ✂ Naming Convention Ptr Suffix
- ✂ The Double Pointer Rule
- ✂ Core operations

STACK

(LIFO – Last In, First Out)

STACK (LIFO – LAST IN, FIRST OUT)

- ✂ Last element pushed is the first to be popped.
- ✂ Operations:
 - ✂ `push(x)` → add to the top
 - ✂ `pop()` → remove from the top

Stack (LIFO):

```
+-----+
| D | <- Top (newest element)
+-----+
| C |
+-----+
| B |
+-----+
| A | <- Bottom (oldest element)
+-----+
```

`push(E)` => E goes on top

`pop()` => removes D from the top

Stack — Example

```

push(E)      pop()
|            |
v            v
+-----+    +-----+
| E | <- Top | D | <- removed
+-----+    +-----+
| D |        | C |
+-----+    +-----+
| C |        | B |
+-----+    +-----+
| B |        | A | <- Bottom
+-----+
| A | <- Bottom
+-----+

```

The element added **last** is removed **first**.

QUEUE

(FIFO – First In, First Out)

QUEUE (FIFO – FIRST IN, FIRST OUT)

- ✂ First element enqueued is the first to be dequeued.
- ✂ Operations:
 - ✂ enqueue(x) → add to the rear
 - ✂ dequeue() → remove from the front

Queue (FIFO):

```
Front -> +-----+ +-----+ +-----+ +-----+ <- Rear
         | A | --> | B | --> | C | --> | D |
         +-----+ +-----+ +-----+ +-----+
```

enqueue(E) => E goes to the rear

dequeue() => removes A from the front

Queue — Example

```
enqueue(E):
```

```
Front -> [ A ] -> [ B ] -> [ C ] -> [ D ] -> [ E ] <- Rear
```

```
dequeue():
```

```
    [ A ] removed
```

```
Front -> [ B ] -> [ C ] -> [ D ] -> [ E ] <- Rear
```

The element added **first** is removed **first**.

STACK & QUEUE

The difference between a stack and a queue is not in the underlying structure—they both work on linked lists—but in the way elements are added and removed.

- ✂ In a stack, elements are inserted at the front and also removed from the front (LIFO).
- ✂ In a queue, elements are inserted at the rear but removed from the front (FIFO).

Structure	Insert	Remove	Rule
Stack	Top	Top	Last In, First Out
Queue	Rear	Front	First In, First Out

STRUCTS ARE

Value Types

STRUCTS ARE VALUE TYPES

In C, a struct is a **value type** — just like `int` or `double`. When you assign a struct to another variable, the **entire content is copied**. Both variables are independent — changing one does not affect the other.

```
typedef struct {  
    int value;  
} Node;  
  
Node a;  
a.value = 10;  
  
Node b = a;    /* full copy — b gets its own value field */  
b.value = 99;  
  
printf("%d\n", a.value); // 10 — unchanged  
printf("%d\n", b.value); // 99
```



`b` is a completely independent copy of `a`. There is no shared memory between them.

STRUCTS AS FUNCTION ARGUMENTS 1/2

The same rule applies when passing a struct to a function. The function receives a **full copy** — it cannot modify the original.

```
void setZero(Node n)
{
    n.value = 0; // modifies the LOCAL copy only
}

int main(void)
{
    Node nodeA;
    nodeA.value = 42;
    setZero(nodeA);
    printf("%d\n", nodeA.value); // still 42 — original unchanged
}
```



STRUCTS AS FUNCTION ARGUMENTS 2/2

```
void setZero(Node n)
{
    n.value = 0;
    // modifies the LOCAL copy only
}

int main(void)
{
    Node nodeA;
    nodeA.value = 42;
    setZero(nodeA);
    printf("%d\n", nodeA.value);
    // still 42 — original unchanged
}
```



```
void setZero(Node *nodePtr)
{
    nodePtr->value = 0; // modifies the original
}
```



To modify a struct inside a function
— pass a **pointer** to it.

NAMING CONVENTION

Ptr Suffix

NAMING CONVENTION — PTR SUFFIX

Every variable that is a pointer gets the suffix `Ptr` in its name.

This makes the type visible directly in the name — no need to check the declaration.

```
Node *headPtr    // pointer to Node
Node **headPtr2Ptr // pointer to pointer to Node
Node *currentPtr // pointer used for traversal
Node *newNodePtr // pointer to a new node
Node *tempPtr    // temporary pointer
```



If you see `Ptr` at the end — it is a pointer.

If you see `Ptr2Ptr` at the end — it is a pointer to a pointer.

No guessing. No checking declarations.

WHY THIS MATTERS AT THE CALL SITE

```
// headPtr → pass directly  
printList(headPtr);  
  
// headPtr2Ptr → pass address of pointer  
addFirst(&headPtr, &nodes[0]);
```



When you call a function and see `&headPtr` — you immediately know:
the function receives a `headPtr2Ptr` and **can modify** your `headPtr`.

When you call a function and see just `headPtr` — the function
reads the list but **cannot change** where `headPtr` points.

NODE STRUCTURE

& typedef

STRUCT WITHOUT TYPEDEF

```
struct Node
{
    int value;
    struct Node *next; // must write "struct Node" — typedef not yet complete
};

struct Node nodeA;      // must write "struct Node" everywhere
struct Node *headPtr = NULL;
```



Every declaration requires the full `struct Node`.
Verbose but explicit — you always know it is a struct.

STRUCT WITH TYPEDEF

```
typedef struct Node
{
    int value;
    struct Node *next; // still "struct Node" here — typedef not complete yet
} Node;
```

```
Node nodeA; // now "Node" alone is enough
Node *headPtr = NULL;
```



`typedef` creates an alias.

Inside the struct body the alias is not yet defined — `struct Node *next` is still required there.

Everywhere else — `Node` alone works.

STRUCT WITH TYPEDEF + FORWARD DECLARATION

```
typedef struct Node Node; // tell the compiler "Node" will exist
```

```
struct Node  
{  
    int value;  
    Node *next;    // alias already known — works here too  
};
```

```
Node nodeA;  
Node *headPtr = NULL;
```



Cleanest form.

Forward declaration lets you use `Node` even inside the struct body.

We use this form for the rest of the course.

STACK MEMORY

No malloc

STACK MEMORY — NO MALLOC

Memory comes from two places:

- ✂ **Stack** — local variables, managed automatically by the compiler
- ✂ **Heap** — `malloc()` / `free()`, managed manually by the programmer

In this lecture we work exclusively on the stack.

No `malloc()`. No `free()`. No memory leaks.

The pointer logic is **identical** to heap-based lists.

Once this is solid, switching to `malloc()` is a small step.

Nodes Live in an Array in main()



```
int main(void)
{
    Node nodes[4];    /* all nodes live here — on the stack */
    Node *headPtr = NULL; /* headPtr starts empty */
    for (int i = 0; i < 4; i++)
    {
        nodes[i].value = (i + 1) * 10;
        nodes[i].next = NULL;
    }
    /* pass addresses of stack nodes to list functions */
    addFirst(&headPtr, &nodes[0]); // headPtr → nodes[0]
    addFirst(&headPtr, &nodes[1]); // headPtr → nodes[1] → nodes[0]

    printList(headPtr);
    return 0;
}
```

Nodes live in `nodes[]` for the entire lifetime of `main()`.

WHY NOT CREATE NODES INSIDE FUNCTIONS?

```
Node *createNode_BROKEN(int value) /* DANGEROUS — do not do this */
{
    Node newNode;      /* lives only inside this function */
    newNode.value = value;
    newNode.next = NULL;
    return &newNode;    /* dangling pointer — node is gone after return */
}

void initNode(Node *nodePtr, int value) /* SAFE — node lives in main(), function only initializes it */
{
    nodePtr->value = value;
    nodePtr->next = NULL;
}
```



A function can **modify** a node through a pointer.

A function cannot **create** a node on the stack and return its address.

THE DOUBLE

Pointer Rule

THE PROBLEM — SINGLE POINTER

```
void addFirst_BROKEN(Node *headPtr, Node *newNodePtr)
{
    newNodePtr->next = headPtr;
    headPtr = newNodePtr; // changes the LOCAL copy only
} // caller's headPtr is unchanged

int main(void)
{
    Node nodes[1];
    Node *headPtr = NULL;
    initNode(&nodes[0], 10);
    addFirst_BROKEN(headPtr, &nodes[0]);
    // headPtr is still NULL here
}
```



The function received a **copy** of `headPtr`. Changing the copy does not change the original.

THE RULE 1/2

Every function that modifies the list receives `Node **headPtr2Ptr`.

Pass the address of `headPtr` using `&`:

```
addFirst(&headPtr, &nodes[0]); // &headPtr gives the function direct access
```



Inside the function:

- ✂ `headPtr2Ptr` holds the **address** of `headPtr` in `main()`
- ✂ `*headPtr2Ptr` IS `headPtr` in `main()` — not a copy
- ✂ `(*headPtr2Ptr)->value` accesses the first node's field

THE RULE 2/2

Read-only functions receive `Node *headPtr` — no modification needed.

```
/* modifying — always double pointer */  
int addFirst (Node **headPtr2Ptr, Node *newNodePtr);  
int addLast  (Node **headPtr2Ptr, Node *newNodePtr);  
int removeFirst(Node **headPtr2Ptr);  
int deleteValue(Node **headPtr2Ptr, int value);  
  
/* read-only — single pointer is sufficient */  
int printList (Node *headPtr);
```



DOUBLE POINTER — MEMORY PICTURE

main():

headPtr [● —————▶ [10 | NULL]]

&headPtr = address of headPtr variable

Inside addFirst(Node **headPtr2Ptr, Node *newNodePtr):

headPtr2Ptr ———▶ headPtr in main()

*headPtr2Ptr = headPtr in main() ← we write here directly

After *headPtr2Ptr = newNodePtr:

headPtr [● —▶ [20 | ● —▶ [10 | NULL]]]

*headPtr2Ptr = newNodePtr changes main() 's headPtr directly.

No copy. No return value needed.

CORE

Operations

INITNODE

```
void initNode(Node *nodePtr, int value)
{
    nodePtr->value = value;
    nodePtr->next = NULL;
}
```



- ✂ Receives a pointer to an **existing** node — allocated by the caller.
- ✂ Sets `value` and clears `next`.
- ✂ Does not allocate memory — the caller owns the node.

```
Node nodes[3];
initNode(&nodes[0], 10);
initNode(&nodes[1], 20);
initNode(&nodes[2], 30);
```



PRINTLIST 1/2

```
int printList(Node *headPtr)
{
    if (headPtr == NULL)
    {
        printf("List is empty.\n");
        return -1;
    }
    Node *currentPtr = headPtr;
    while (currentPtr != NULL)
    {
        printf("%d\n", currentPtr->value);
        currentPtr = currentPtr->next;
    }
    return 0;
}
```



PRINTLIST 2/2

- ⌘ Read-only → single pointer is sufficient.
- ⌘ `currentPtr` is a local traversal variable — moving it does not affect the caller's `headPtr`.
- ⌘ Loop ends when `currentPtr` reaches `NULL`.

ADDFIRST — BEFORE & AFTER

BEFORE addFirst(&headPtr, &nodes[2]):

headPtr —▶ [10 | —▶ [20 | NULL]]

newNodePtr —▶ [30 | NULL]

AFTER:

headPtr —▶ [30 | —▶ [10 | —▶ [20 | NULL]]]

New node is placed at the **front**.

`headPtr` now points to the new node.

Works for both empty and non-empty lists.

ADDFIRST

```
int addFirst(Node **headPtr2Ptr, Node *newNodePtr)
{
    if (headPtr2Ptr == NULL)
    {
        printf("Error: headPtr2Ptr is NULL.\n");
        return -1;
    }
    if (newNodePtr == NULL)
    {
        printf("Error: newNodePtr is NULL.\n");
        return -1;
    }
    newNodePtr->next = *headPtr2Ptr; // new node points to current first
    *headPtr2Ptr = newNodePtr; // headPtr now points to new node
    return 0;
}
```



ADDLAST — BEFORE & AFTER

BEFORE addLast(&headPtr, &nodes[2]):

headPtr —▶ [10 | —▶ [20 | NULL]]

newNodePtr —▶ [30 | NULL]

AFTER:

headPtr —▶ [10 | —▶ [20 | —▶ [30 | NULL]]]

New node is placed at the **rear**.

`headPtr` does not change — unless the list was empty.

Walk to the last node, then attach.

ADDLAST

```
// ha ha ;)
```



End-to-End Example

```
int main(void)
{
    Node nodes[4];
    Node *headPtr = NULL;
    initNode(&nodes[0], 10);
    initNode(&nodes[1], 20);
    initNode(&nodes[2], 30);
    initNode(&nodes[3], 40);
    addLast(&headPtr, &nodes[0]); // 10
    addLast(&headPtr, &nodes[1]); // 10 -> 20
    addLast(&headPtr, &nodes[2]); // 10 -> 20 -> 30
    addFirst(&headPtr, &nodes[3]); // 40 -> 10 -> 20 -> 30
    printList(headPtr);
    // 40
    // 10
    // 20
    // 30
    return 0;
}
```



BEST PRACTICES

HEAD AND TAIL ARE JUST REFERENCES

`headPtr` , `tailPtr` , `currentPtr` — these are all just pointers.

They point to nodes, but they **do not own** them.

Nodes live in the `nodes[]` array in `main()` .

```
Node *headPtr = &nodes[0];
```

```
Node *tailPtr = &nodes[2];
```

```
// headPtr and tailPtr point to the same memory as nodes[0] and nodes[2]
```

```
// there is no duplication — just two pointers to existing nodes
```



Changing `headPtr = headPtr->next` does not destroy any node.

It only changes what `headPtr` points to.

The node in `nodes[0]` still exists unchanged.

USE PARENTHESES FOR CLARITY

When chaining pointer operations, add parentheses to make the intent explicit. This is especially helpful while you are learning pointer traversal.

```
// harder to follow — which -> binds first?  
current->next->next  
// intent is clear — step by step  
(current->next)->next
```



```
// harder to follow  
(*headPtr2Ptr)->value  
// reads naturally — dereference first, then access field  
(*headPtr2Ptr)->value // already clear with the parentheses
```



Once pointer traversal becomes intuitive, parentheses are optional. Until then — use them.

NEVER DEREFERENCE NULL

```
// WRONG — crash if headPtr is NULL
```

```
printf("%d\n", headPtr->value);
```

```
// CORRECT — guard before every dereference
```

```
if (headPtr != NULL)
```

```
{
```

```
    printf("%d\n", headPtr->value);
```

```
}
```



Every pointer access must be guarded.

`headPtr == NULL` means the list is empty — that is valid state, not a bug.

Dereferencing `NULL` is always a bug.

COPYING A POINTER COPIES THE ADDRESS

```
Node *aPtr = headPtr;  
Node *bPtr = aPtr;    // both point to the same node
```



```
headPtr —▶  
aPtr   —▶ [ 10 | —▶ [ 20 | NULL ] ]  
bPtr   —▶
```

Three pointers, one node in memory.

Changing `bPtr->value` changes what `aPtr` and `headPtr` also see.

There is no copy of the data — only a copy of the address.

DRAW BEFORE YOU CODE

Before writing any function that modifies a list — draw the state **before** and **after** on paper.

addFirst — before:

headPtr —► [10 | —► [20 | NULL]]

newNodePtr —► [5 | NULL]

addFirst — after:

headPtr —► [5 | —► [10 | —► [20 | NULL]]]

If you cannot draw it — you cannot code it.

Paper is faster than the debugger at this stage.

SUMMARY

Rule	Why
<code>Ptr</code> suffix for every pointer	type visible in the name
<code>headPtr2Ptr</code> for modifying functions	makes <code>**</code> explicit at declaration
Single <code>headPtr</code> for read-only functions	no <code>**</code> needed when not modifying
Nodes live in <code>main()</code>	no dangling pointers, no malloc
Guard every dereference	<code>NULL</code> is valid state, not a bug

THANK

You