



ESOF 322

Software Engineering

LECTURE: 7

J. L. Pach

OUTLINE:

🔧 Agile Software Development

AGILE

Software Development

WHY AGILE METHODS EXIST — THE MOTIVATION 1/3

1. Business Context

- ✂ Businesses operate in **rapidly changing global environments** — new markets, economic shifts, competing products
- ✂ Software must be delivered **quickly** to exploit opportunities and respond to competition
- ✂ Companies may **sacrifice quality or compromise on requirements** if they can deploy software fast

2. The Problem with Plan-Driven Approaches

3. Why Requirements Always Change

WHY AGILE METHODS EXIST — THE MOTIVATION 2/3

1. Business Context

2. The Problem with Plan-Driven Approaches

- ✘ Traditional waterfall/specification-based processes require **complete, stable requirements upfront** — which is practically impossible in dynamic environments
- ✘ When requirements change (and they always do), the design and implementation must be **reworked and retested**, making the process lengthy
- ✘ By the time software is finally delivered, **the original business need may no longer exist**
- ✘ Exception: **safety-critical systems** (e.g., aerospace, medical devices) genuinely require plan-driven approaches due to the need for exhaustive analysis

WHY AGILE METHODS EXIST — THE MOTIVATION 3/3

1. Business Context
2. The Problem with Plan-Driven Approaches
3. Why Requirements Always Change
 - ✂ Customers cannot predict how a system will affect working practices
 - ✂ They cannot foresee how it will interact with other systems
 - ✂ Real requirements often only become clear **after** users gain experience with a delivered system
 - ✂ External factors continuously drive requirement changes

WHAT AGILE METHODS ARE

Core Definition

Agile methods are **incremental development approaches** that:

- ⌘ Produce software in **small, frequent increments** (typically every 2–3 weeks)
- ⌘ **Interleave** specification, design, and implementation — no separate phases
- ⌘ **Minimize documentation** — informal communication over formal written documents
- ⌘ **Involve customers continuously** for rapid feedback on changing requirements
- ⌘ Use **extensive tool support** (automated testing, CI tools, UI generation)

KEY HISTORICAL CONTEXT

- ✂ Agile emerged in the **late 1990s** as a reaction to heavyweight plan-driven methods
- ✂ Major agile methods:
 - ✂ **Extreme Programming (XP)** (1999), **Scrum** (2001), **DSDM** (2003)
- ✂ In the 1980s—early 1990s, the dominant view was: better software = careful planning + formalized QA + rigorous processes
- ✂ That approach was designed for large, geographically dispersed teams on long-lived government/aerospace systems — justified when:
 - ✂ Multiple teams must be coordinated; System is safety-critical; Many people will maintain software over its lifetime
- ✂ When applied to **small/medium business systems**, the overhead became disproportionate: more time spent on *how* to develop than on actual development.

THE AGILE MANIFESTO

Published at agilemanifesto.org:

Value (More Important)	Over (Less Important but Still Valued)
Individuals and interactions	Processes and tools
Working software	Comprehensive documentation
Customer collaboration	Contract negotiation
Responding to change	Following a plan

Critical nuance: The manifesto does NOT say the right column has no value — it says the **left column is valued MORE**

FIVE CORE PRINCIPLES OF AGILE METHODS

Principle	Description
Customer involvement	Customers closely involved throughout; provide/prioritize requirements; evaluate iterations
Embrace change	Design to accommodate changing requirements as a natural expectation, not an exception
Incremental delivery	Software developed in increments; customer specifies requirements per increment
Maintain simplicity	Actively eliminate complexity from both software and process
People, not process	Exploit team skills; let team develop their own working methods without prescriptive processes

PLAN-DRIVEN VS. AGILE — THE FUNDAMENTAL DIFFERENCE

Plan-Driven:

Requirements → [Requirements Spec Document] → Design & Implementation

(Iteration happens WITHIN activities; formal documents communicate BETWEEN stages)

Agile:

Requirements Engineering ↔ Design & Implementation (continuously)

(Iteration happens ACROSS activities; requirements and design evolve TOGETHER)



Important nuance: In practice, the boundary is not absolute. Plan-driven processes often incorporate agile practices, and agile methods may include some planned activities. A pure agile process is not inevitably code-only — it may produce design documentation and models when the team decides an iteration should focus on that.

WHERE AGILE WORKS BEST

Two primary domains:

1. **Software product development** — small/medium products for sale (virtually all software products and apps are now developed with agile)
2. **Custom system development within an organization** — where:
 - ✖ Clear customer commitment to involvement exists
 - ✖ Few external stakeholders and regulations
 - ✖ System is standalone (not tightly integrated with parallel development streams)
 - ✖ Small/medium team can be co-located, enabling informal communication

AGILE VS PLAN-BASEN DEVELOPMENT



EXTREME PROGRAMMING (XP)

THE FOUNDATIONAL AGILE METHOD

WHAT XP IS:

- ⚡ Developed by **Kent Beck** — the name reflects pushing recognized good practices to "*extreme*" levels
- ⚡ Most significant contribution: the **set of agile development practices** it introduced, even if XP itself is rarely used in its pure form today

THE XP RELEASE CYCLE

Select user stories → Plan release → Break down to tasks → Develop/integrate/test software → Release software
→ Evaluate system

XP'S 10 KEY PRACTICES

Practice	Description
Collective ownership	All developers work on all code; anyone can change anything; no "islands of expertise"
Continuous integration	Completed tasks integrated into whole system immediately; all unit tests must pass after every integration
Incremental planning	Requirements recorded on "story cards"; stories broken into "tasks"
On-site customer	Customer representative available full-time as part of the development team
Pair programming	Developers work in pairs at one computer, checking each other's work
Refactoring	Continuous code improvement whenever opportunities found — keeps code simple and maintainable
Simple design	Only enough design to meet current requirements — no more
Small releases	Minimal useful functionality first; frequent incremental releases
Sustainable pace	No excessive overtime — it reduces code quality and medium-term productivity
Test-first development	Tests written <i>before</i> code; automated unit test frameworks used

AGILE DEVELOPMENT - USER STORIES 1/4

- ✂ What they are :
 - ✂ Scenarios of use that a system user might experience
 - ✂ Written collaboratively by customer and development team on "**story cards**"
 - ✂ Brief, narrative, scenario-based descriptions of system needs
- ✂ How they're used
- ✂ Advantages
- ✂ Disadvantages

AGILE DEVELOPMENT - USER STORIES 2/4



What they are



How they're used :



Team breaks stories into **task cards** (e.g.,



"Change dose"



"Formulary selection"



"Dose checking")



Estimates effort per task; customer **prioritizes** stories



Aim: implement functionality deliverable in ~**2 weeks** per release

AGILE DEVELOPMENT - USER STORIES 3/4



What they are



How they're used



Advantages :

- ✖ Much easier for users to relate to than formal requirements documents or use cases
- ✖ Useful for involving users in requirements elicitation
- ✖ Flexible — unimplemented stories can be changed or discarded as requirements evolve

AGILE DEVELOPMENT - USER STORIES 4/4

✂ What they are

✂ How they're used

✂ Advantages

✂ Disadvantages

✂ **Completeness problem:** Hard to judge if enough stories cover all essential requirements

✂ A single story may not give a true picture of an activity

✂ Experienced users often omit things they take for granted

REFACTORING

Traditional approach: Design for change — anticipate future changes upfront

XP's rejection of this: Designing for anticipated change is often **wasted effort** — anticipated changes frequently never materialize, and actual changes requested are completely different

What refactoring is:

Why it's necessary:

Practical limitations:

REFACTORING 1/4

✂ Traditional approach:

- ✂ Design for change — anticipate future changes upfront

✂ XP's rejection of this:

- ✂ Designing for anticipated change is often **wasted effort** — anticipated changes frequently never materialize, and actual changes requested are completely different

- ✂ What refactoring is

- ✂ Why it's necessary

- ✂ Practical limitations

REFACTORING 2/4

✂ What refactoring is :

- ✂ Continuously looking for and implementing improvements to existing code
- ✂ Making improvements **even when there's no immediate need** for them
- ✂ Examples: reorganizing class hierarchies to remove duplicate code, renaming attributes/methods for clarity, replacing similar code sections with library method calls

✂ Why it's necessary

✂ Practical limitations

REFACTORING 3/4

- ✂ What refactoring is
- ✂ Why it's necessary :
 - ✂ Incremental development naturally causes **local changes to degrade software structure**
 - ✂ Without refactoring: code duplication, inappropriate reuse, structural degradation, workarounds
 - ✂ Refactoring maintains **readability and understandability** over time
- ✂ Practical limitations

REFACTORING 4/4

- ✂ What refactoring is
- ✂ Why it's necessary
- ✂ Practical limitations :
 - ✂ Development pressure causes refactoring to be **delayed** in favor of new features
 - ✂ Some changes require **architectural** modification — not addressable by code-level refactoring
 - ✂ Development environments include refactoring tools that simplify finding dependencies and making global modifications

TEST-FIRST / TEST-DRIVEN DEVELOPMENT (TFD/TDD) 1/5

- ✂ The core innovation :
 - ✂ Write tests **before** you write the code — the opposite of traditional "code then test"
 - ✂ Tests can be run during coding, discovering problems **during development** not after
- ✂ Key features of XP testing
- ✂ Why test-first works
- ✂ The link to user stories
- ✂ Test automation requirements
- ✂ Problems with test-first development

TEST-FIRST / TEST-DRIVEN DEVELOPMENT (TFD/TDD) 2/5

- ✂ The core innovation
- ✂ Key features of XP testing :
 - ✂ Test-first development
 - ✂ Incremental test development from scenarios
 - ✂ User involvement in test development and validation
 - ✂ Automated testing frameworks (e.g., **JUnit** for Java)
- ✂ Why test-first works
- ✂ The link to user stories
- ✂ Test automation requirements
- ✂ Problems with test-first development

TEST-FIRST / TEST-DRIVEN DEVELOPMENT (TFD/TDD) 3/5

- ✂ The core innovation
- ✂ Key features of XP testing
- ✂ Why test-first works :
 - ✂ Writing tests implicitly defines **both an interface AND a specification of behavior**
 - ✂ Reduces requirements/interface misunderstandings
 - ✂ Forces task implementers to **thoroughly understand the specification** before coding
 - ✂ Clarifies ambiguities and omissions before implementation
 - ✂ Prevents "**test-lag**" — where implementation gets ahead of testing and tests get skipped

TEST-FIRST / TEST-DRIVEN DEVELOPMENT (TFD/TDD) 4/5

- ✂ The core innovation
- ✂ Key features of XP testing
- ✂ Why test-first works
- ✂ The link to user stories
- ✂ Test automation requirements :
 - ✂ Story cards → Task cards → One or more unit tests per task → Implementation
- ✂ Problems with test-first development

TEST-FIRST / TEST-DRIVEN DEVELOPMENT (TFD/TDD) 5/5

- ⌘ Problems with test-first development :
 - ⌘ Programmers prefer programming to testing → they write **incomplete tests**, skip edge cases
 - ⌘ Some tests are very hard to write incrementally (e.g., complex UI display logic and screen workflows)
 - ⌘ **Coverage completeness** cannot be guaranteed — large test suite ≠ complete coverage
 - ⌘ Crucial system parts may remain untested despite the appearance of thoroughness
 - ⌘ Without test review and additional post-development tests, bugs can ship

PAIR PROGRAMMING 1/3

- ✂ The practice :
 - ✂ Two programmers sit at **one computer** to develop software
 - ✂ Pairs are **dynamic** — they rotate so all team members work with each other
- ✂ Three key advantages
- ✂ Productivity question (nuanced)

PAIR PROGRAMMING 2/3



The practice



Three key advantages :

- ✖ **Collective ownership** — reflects "egoless programming" (1971): software owned by team, not individuals; team collectively resolves problems
- ✖ **Informal code review** — every line of code seen by at least two people; cheaper than formal inspections though probably finds fewer errors
- ✖ **Encourages refactoring** — when one developer refactors, the pair benefits immediately, so there's social support for it

PAIR PROGRAMMING 3/3

⌘ Productivity question (nuanced) :

- ⌘ Intuitive concern: two people at one computer = half the output
- ⌘ productivity comparable to two working independently — because pairs discuss before coding (fewer false starts) and informal inspection reduces debugging time
- ⌘ significant productivity **loss** vs. two individuals; quality benefits don't fully compensate
- ⌘ reduces project risk when team members leave; implicit knowledge is distributed, not siloed

THANK YOU!